FCC Test Report

Report No.	:	**1812C60051812502**
Applicant	:	**Shenzhen Qianyan Technology LTD**
Address	:	**No. 3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China**
Product Name	:	**Govee TV Light Bar**
Report Date	:	**2026-04-10**

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Contents

1. General Information 6
1.1. Client Information 6
1.2. Description of Device (EUT) 6
1.3. Auxiliary Equipment Used During Test 7
1.4. Operation channel list 7
1.5. Description of Test Modes 7
1.6. Measurement Uncertainty 7
1.7. Additional Instructions 8
1.8. Test Summary 8
1.9. Description of Test Facility 9
1.10. Disclaimer 9
1.11. Test Equipment List 10
2. Antenna requirement 12
2.1. Conclusion 12
3. Conducted Emission at AC power line 13
3.1. EUT Operation 13
3.2. Test Setup 13
3.3. Test Data 14
4. 6dB Bandwidth 16
4.1. EUT Operation 16
4.2. Test Setup 16
4.3. Test Data 17
5. Maximum Conducted Output Power 18
5.1. EUT Operation 18
5.2. Test Setup 18
5.3. Test Data 18
6. Power Spectral Density 19
6.1. EUT Operation 19
6.2. Test Setup 19
6.3. Test Data 19
7. Emissions in non-restricted frequency bands 20
7.1. EUT Operation 20
7.2. Test Setup 20
7.3. Test Data 20
8. Band edge emissions (Radiated) 21
8.1. EUT Operation 21
8.2. Test Setup 21
8.3. Test Data 22
9. Emissions in restricted frequency bands (below 1GHz) 25
9.1. EUT Operation 25
9.2. Test Setup 26

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

9.3. Test Data 27
10. Emissions in restricted frequency bands (above 1GHz).....29
10.1. EUT Operation 29
10.2. Test Setup 30
10.3. Test Data 31
APPENDIX I -- TEST SETUP PHOTOGRAPH 34
APPENDIX II -- EXTERNAL PHOTOGRAPH 34
APPENDIX III -- INTERNAL PHOTOGRAPH.....34

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

TEST REPORT

Applicant	:	Shenzhen Qianyan Technology LTD
Manufacturer	:	Shenzhen Qianyan Technology LTD
Product Name	:	Govee TV Light Bar
Model No.	:	H6046
Trade Mark	:	Govee
Rating(s)	:	Input: 24V⎓1A
Test Standard(s)	:	**47 CFR Part 15.247** **KDB 558074 D01 15.247 Meas Guidance v05r02** **ANSI C63.10-20200+Cor.1-2023**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with above listed standard(s) requirements.
This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt: 2026-01-19

Date of Test: 2026-01-19 to 2026-03-10

Prepared By: Yuki Long

(Yuki Long)

Approved & Authorized Signer: Hugo Chen

(Hugo Chen)

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	2026-04-10

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

1. General Information

1.1. Client Information

Applicant	:	Shenzhen Qianyan Technology LTD
Address	:	No. 3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China
Manufacturer	:	Shenzhen Qianyan Technology LTD
Address	:	No. 3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China

1.2. Description of Device (EUT)

Product Name	:	Govee TV Light Bar
Model No.	:	H6046
Trade Mark	:	Govee
Test Power Supply	:	DC 24V from adapter input AC 120V/60Hz
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	Manufacturer: Dong Guan Royal Intelligent Co., Ltd Model: BI24GL-240100-AdU Input: 100-240V~, 50/60Hz 0.8A Output: 24.0V⎓1.0A
RF Specification		
Operation Frequency	:	802.11b/g/n(HT20): 2412MHz to 2462MHz;
Number of Channel	:	802.11b/g/n(HT20): 11 Channels;
Modulation Type	:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	:	PCB Antenna
Antenna Gain(Peak)	:	3.98dBi
Remark: (1) All of the RF specification are provided by customer. (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
/	/	/	/

1.4. Operation channel list

Operation Band:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

1.5. Description of Test Modes

Pretest Modes	Descriptions
TM1	Keep the EUT in 802.11b transmitting mode.
TM2	Keep the EUT in 802.11g transmitting mode.
TM3	Keep the EUT in 802.11n(HT20) transmitting mode.

1.6. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	2.8dB
Occupied Bandwidth	552Hz
Conducted Output Power	0.84dB
Power Spectral Density	0.84dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.64dB; 6G-18GHz: 4.82dB 18G-40GHz: 5.62dB
Radiated emissions (Below 30MHz)	3.14dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.94dB; Vertical: 4.34dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

1.7. Additional Instructions

Power level setup in software: EspRFTestTool
Operation Band:

Mode	Channel(MHz)	Power level	Transmitting type
802.11b	2412	default	data pack TX
802.11b	2437	default	data pack TX
802.11b	2462	default	data pack TX
802.11g	2412	default	data pack TX
802.11g	2437	default	data pack TX
802.11g	2462	default	data pack TX
802.11n(HT20)	2412	default	data pack TX
802.11n(HT20)	2437	default	data pack TX
802.11n(HT20)	2462	default	data pack TX

1.8. Test Summary

Test Items	Test Modes	Status
Conducted Emission at AC power line	Mode1,2,3	P
6dB Bandwidth	Mode1,2,3	P
Maximum Conducted Output Power	Mode1,2,3	P
Power Spectral Density	Mode1,2,3	P
Emissions in non-restricted frequency bands	Mode1,2,3	P
Band edge emissions (Radiated)	Mode1,2,3	P
Emissions in restricted frequency bands (below 1GHz)	Mode1,2,3	P
Emissions in restricted frequency bands (above 1GHz)	Mode1,2,3	P
Note: P: Pass N: N/A, not applicable		

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.:279531
Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

Test Location
Shenzhen Anbotek Compliance Laboratory Limited.
Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.10. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

1.11. Test Equipment List

Conducted Emission at AC power line					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	2025-09-05	2026-09-04
2	Software Name EZ-EMC	Farad Technology	ANB-03A	/	/
3	EMI Test Receiver(CE2#)	Rohde & Schwarz	ESCI	2025-12-29	2026-12-28
4	Three Phase V-type Artificial Power Network LISN 200A	EMtrace	PWL-50-3200A	2025-12-29	2026-12-28
5	10dB Attenuator	Emtrace	10dB100W	2025-12-29	2026-12-28
6	Pulse limiter	EMtrace	PL00903-2#	2025-12-30	2026-12-29

6dB Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	2025-10-10	2026-10-09
2	DC Power Supply	IVYTECH	IV3605	2025-09-05	2026-09-04
3	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	2025-12-29	2026-12-28
4	MXA Spectrum Analysis	KEYSIGHT	N9020A	2025-12-29	2026-12-28
5	Oscilloscope	Tektronix	MDO3012	2025-09-30	2026-09-29
6	MXG RF Vector Signal Generator	Agilent	N5182A	2025-12-29	2026-12-28
7	RF Test software	Toscend	JS1120-3	/	/

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver(RE2/3#)	Rohde & Schwarz	ESR26	2025-12-30	2026-12-29
2	EMI Preamplifier	SKET Electronic	LNPA-0118G-45	2025-12-30	2026-12-29
3	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	2025-10-27	2028-10-26
4	EMI Test Software EZ-EMC	SHURPLE	N/A	/	/
5	Horn Antenna	A-INFO	LB-180400-KF	2024-01-22	2027-01-21
6	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	2025-12-29	2026-12-28
7	Amplifier	Talent Microwave	TLLA18G40G-53-30	2026-01-05	2027-01-04

Emissions in frequency bands (below 1GHz)					
Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver(RE2/3#)	Rohde & Schwarz	ESR26	2025-12-30	2026-12-29
2	Pre-amplifier	SONOMA	310N	2025-12-30	2026-12-29
3	Bilog Broadband Antenna	Schwarzbeck	VULB9163	2025-10-26	2028-10-25
4	Loop Antenna (9K-30M)	Schwarzbeck	FMZB1519B	2025-09-05	2026-09-04
5	EMI Test Software EZ-EMC	SHURPLE	N/A	/	/

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

2. Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1. Conclusion

The antenna is a **PCB antenna** which permanently attached, and the best case gain of the antenna is **3.98 dBi**. It complies with the standard requirement.

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

3. Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b)and (c)of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).
Test Limit:	

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Test Method:	ANSI C63.10-2020+Cor.1-2023 section 6.2
Procedure:	Refer to ANSI C63.10-2020+Cor.1-2023 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices

3.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.

3.2. Test Setup



Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

3.3. Test Data

Temperature:	22.9 °C	Humidity:	53 %	Atmospheric Pressure:	101 kPa

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Power Supply: DC 24V from adapter input AC 120V/60Hz



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	36.21	17.92	54.13	65.99	-11.86	QP	
2	0.1500	29.91	17.92	47.83	55.99	-8.16	AVG	
3	0.1860	31.88	18.02	49.90	64.21	-14.31	QP	
4	0.1860	23.28	18.02	41.30	54.21	-12.91	AVG	
5	0.2140	29.71	18.08	47.79	63.04	-15.25	QP	
6	0.2140	20.56	18.08	38.64	53.04	-14.40	AVG	
7	0.2460	26.92	18.09	45.01	61.89	-16.88	QP	
8	0.2740	19.69	18.10	37.79	50.99	-13.20	AVG	
9	0.4860	20.88	18.10	38.98	56.24	-17.26	QP	
10	0.4860	16.30	18.10	34.40	46.24	-11.84	AVG	
11	0.8580	27.10	18.10	45.20	56.00	-10.80	QP	
12	0.8580	19.04	18.10	37.14	46.00	-8.86	AVG	

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Temperature:	22.9 °C	Humidity:	53 %	Atmospheric Pressure:	101 kPa

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Power Supply: DC 24V from adapter input AC 120V/60Hz



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	35.33	17.92	53.25	65.99	-12.74	QP	
2	0.1500	28.45	17.92	46.37	55.99	-9.62	AVG	
3	0.1860	30.30	18.02	48.32	64.21	-15.89	QP	
4	0.1860	21.80	18.02	39.82	54.21	-14.39	AVG	
5	0.2140	29.01	18.08	47.09	63.04	-15.95	QP	
6	0.2140	19.83	18.08	37.91	53.04	-15.13	AVG	
7	0.2460	26.02	18.09	44.11	61.89	-17.78	QP	
8	0.4900	14.71	18.11	32.82	46.17	-13.35	AVG	
9	0.8580	27.10	18.10	45.20	56.00	-10.80	QP	
10	0.8580	16.95	18.10	35.05	46.00	-10.95	AVG	
11	1.7140	20.83	18.07	38.90	56.00	-17.10	QP	
12	1.7140	11.60	18.07	29.67	46.00	-16.33	AVG	

Note:
1. Only record the worst data in the report.
2. Result(dBμV)=Reading(dBμV)+Factor(dB);
OverLimit(dB)=Result(dBμV)-Limit(dBμV)

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

4. 6dB Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW ≥ [3 × RBW]. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “−6 dB down amplitude”. If a marker is below this “−6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

4.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.

4.2. Test Setup



Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

4.3. Test Data

Temperature:	22.1 °C	Humidity:	61 %	Atmospheric Pressure:	101 kPa

Please Refer to Appendix for Details.

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

5. Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.9.2 Maximum conducted (average) output power

5.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.

5.2. Test Setup



5.3. Test Data

Temperature:	22.1 °C	Humidity:	61 %	Atmospheric Pressure:	101 kPa

Please Refer to Appendix for Details.

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

6. Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.10, Maximum power spectral density level in the fundamental emission

6.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.

6.2. Test Setup



6.3. Test Data

Temperature:	22.1 °C	Humidity:	61 %	Atmospheric Pressure:	101 kPa

Please Refer to Appendix for Details.

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

7. Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023 Section 11.11.1, Section 11.11.2, Section 11.11.3

7.1. EUT Operation

Operating Environment:	
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.

7.2. Test Setup



7.3. Test Data

Temperature:	22.1 °C	Humidity:	61 %	Atmospheric Pressure:	101 kPa

Please Refer to Appendix for Details.

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

8. Band edge emissions (Radiated)

<table>
<tr><td>Test Requirement:</td><td>Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).</td></tr>
<tr><td>Test Limit:</td><td>
<table>
<tr><td>Frequency (MHz)</td><td>Field strength (microvolts/meter)</td><td>Measurement distance (meters)</td></tr>
<tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr>
<tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr>
<tr><td>1.705-30.0</td><td>30</td><td>30</td></tr>
<tr><td>30-88</td><td>100 **</td><td>3</td></tr>
<tr><td>88-216</td><td>150 **</td><td>3</td></tr>
<tr><td>216-960</td><td>200 **</td><td>3</td></tr>
<tr><td>Above 960</td><td>500</td><td>3</td></tr>
</table>
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10-2020+Cor 1-2023 section 6.10
KDB 558074 D01 15.247 Meas Guidance v05r02</td></tr>
<tr><td>Procedure:</td><td>ANSI C63.10-2020+Cor 1-2023 section 6.10.5.2</td></tr>
</table>

8.1. EUT Operation

<table>
<tr><td colspan="2">Operating Environment:</td></tr>
<tr><td>Test mode:</td><td>1: 802.11b mode: Keep the EUT in 802.11b transmitting mode.
2: 802.11g mode: Keep the EUT in 802.11g transmitting mode.
3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.</td></tr>
</table>

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

8.2. Test Setup



Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

8.3. Test Data

Temperature:	22.1 °C	Humidity:	61 %	Atmospheric Pressure:	101 kPa

TM1 / CH: L						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	38.77	9.58	48.35	74.00	-25.65	Horizontal
2390.00	40.91	9.73	50.64	74.00	-23.36	Horizontal
2310.00	40.16	9.58	49.74	74.00	-24.26	Vertical
2390.00	46.60	9.73	56.33	74.00	-17.67	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.43	9.58	39.01	54.00	-14.99	Horizontal
2390.00	36.68	9.73	46.41	54.00	-7.59	Horizontal
2310.00	30.51	9.58	40.09	54.00	-13.91	Vertical
2390.00	39.04	9.73	48.77	54.00	-5.23	Vertical

TM1 / CH: H						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.60	9.91	56.51	74.00	-17.49	Horizontal
2500.00	40.88	9.94	50.82	74.00	-23.18	Horizontal
2483.50	46.96	9.91	56.87	74.00	-17.13	Vertical
2500.00	40.58	9.94	50.52	74.00	-23.48	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.98	9.91	47.89	54.00	-6.11	Horizontal
2500.00	29.94	9.94	39.88	54.00	-14.12	Horizontal
2483.50	39.73	9.91	49.64	54.00	-4.36	Vertical
2500.00	30.20	9.94	40.14	54.00	-13.86	Vertical

Remark: 1. Result=Reading + Factor

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

TM2 / CH: L						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	37.41	9.58	46.99	74.00	-27.01	Horizontal
2390.00	41.30	9.73	51.03	74.00	-22.97	Horizontal
2310.00	39.90	9.58	49.48	74.00	-24.52	Vertical
2390.00	43.77	9.73	53.50	74.00	-20.50	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	30.13	9.58	39.71	54.00	-14.29	Horizontal
2390.00	36.77	9.73	46.50	54.00	-7.50	Horizontal
2310.00	30.83	9.58	40.41	54.00	-13.59	Vertical
2390.00	36.37	9.73	46.10	54.00	-7.90	Vertical

TM2 / CH: H						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.64	9.91	56.55	74.00	-17.45	Horizontal
2500.00	40.94	9.94	50.88	74.00	-23.12	Horizontal
2483.50	46.78	9.91	56.69	74.00	-17.31	Vertical
2500.00	40.53	9.94	50.47	74.00	-23.53	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.15	9.91	46.06	54.00	-7.94	Horizontal
2500.00	29.04	9.94	38.98	54.00	-15.02	Horizontal
2483.50	38.68	9.91	48.59	54.00	-5.41	Vertical
2500.00	29.73	9.94	39.67	54.00	-14.33	Vertical

Remark: 1. Result=Reading + Factor

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

TM3 / CH: L						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	35.41	9.58	44.99	74.00	-29.01	Horizontal
2390.00	39.30	9.73	49.03	74.00	-24.97	Horizontal
2310.00	38.90	9.58	48.48	74.00	-25.52	Vertical
2390.00	41.77	9.73	51.50	74.00	-22.50	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	28.81	9.58	38.39	54.00	-15.61	Horizontal
2390.00	34.23	9.73	43.96	54.00	-10.04	Horizontal
2310.00	28.44	9.58	38.02	54.00	-15.98	Vertical
2390.00	34.37	9.73	44.10	54.00	-9.90	Vertical

TM3 / CH: H						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.37	9.91	54.28	74.00	-19.72	Horizontal
2500.00	38.88	9.94	48.82	74.00	-25.18	Horizontal
2483.50	45.96	9.91	55.87	74.00	-18.13	Vertical
2500.00	40.58	9.94	50.52	74.00	-23.48	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	34.13	9.91	44.04	54.00	-9.96	Horizontal
2500.00	29.19	9.94	39.13	54.00	-14.87	Horizontal
2483.50	35.50	9.91	45.41	54.00	-8.59	Vertical
2500.00	29.87	9.94	39.81	54.00	-14.19	Vertical

Remark: 1. Result=Reading + Factor

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

9. Emissions in restricted frequency bands (below 1GHz)

<table>
<tr><td>Test Requirement:</td><td>Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).</td></tr>
<tr><td>Test Limit:</td><td>
<table>
<tr><td>Frequency (MHz)</td><td>Field strength (microvolts/meter)</td><td>Measurement distance (meters)</td></tr>
<tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr>
<tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr>
<tr><td>1.705-30.0</td><td>30</td><td>30</td></tr>
<tr><td>30-88</td><td>100 **</td><td>3</td></tr>
<tr><td>88-216</td><td>150 **</td><td>3</td></tr>
<tr><td>216-960</td><td>200 **</td><td>3</td></tr>
<tr><td>Above 960</td><td>500</td><td>3</td></tr>
</table>
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10-2020+Cor 1-2023 section 6.6.4
KDB 558074 D01 15.247 Meas Guidance v05r02</td></tr>
<tr><td>Procedure:</td><td>ANSI C63.10-2020+Cor 1-2023 section 6.6.4</td></tr>
</table>

9.1. EUT Operation

<table>
<tr><td colspan="2">Operating Environment:</td></tr>
<tr><td>Test mode:</td><td>1: 802.11b mode: Keep the EUT in 802.11b transmitting mode.
2: 802.11g mode: Keep the EUT in 802.11g transmitting mode.
3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.</td></tr>
</table>

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

9.2. Test Setup



Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

9.3. Test Data

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Temperature:	22.5 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Power Supply: DC 24V from adapter input AC 120V/60Hz



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	47.346	38.84	-23.46	15.38	40.00	-24.62	QP	
2	68.782	40.64	-27.49	13.15	40.00	-26.85	QP	
3	106.199	37.56	-22.22	15.34	43.50	-28.16	QP	
4	129.809	47.46	-26.11	21.35	43.50	-22.15	QP	
5	211.063	45.30	-24.07	21.23	43.50	-22.27	QP	
6	336.035	39.75	-20.14	19.61	46.00	-26.39	QP	

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

Temperature:	22.5 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

Test Power Supply: DC 24V from adapter input AC 120V/60Hz



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	37.188	47.68	-25.45	22.23	40.00	-17.77	QP	
2	51.888	44.42	-23.63	20.79	40.00	-19.21	QP	
3	68.993	49.86	-27.56	22.30	40.00	-17.70	QP	
4	105.734	44.87	-22.21	22.66	43.50	-20.84	QP	
5	128.225	56.64	-25.83	30.81	43.50	-12.69	QP	
6	211.249	49.54	-24.51	25.03	43.50	-18.47	QP	

Note:
1. Only record the worst data in the report.
2. Result(dBμV/m) = Reading(dBμV) + Factor(dB/m);
   Over Limit(dB) = Result(dBμV/m) - Limit(dBμV/m)

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

10. Emissions in restricted frequency bands (above 1GHz)

<table>
<tr><td>Test Requirement:</td><td>Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).</td></tr>
<tr><td>Test Limit:</td><td>
<table>
<tr><td>Frequency (MHz)</td><td>Field strength (microvolts/meter)</td><td>Measurement distance (meters)</td></tr>
<tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr>
<tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr>
<tr><td>1.705-30.0</td><td>30</td><td>30</td></tr>
<tr><td>30-88</td><td>100 **</td><td>3</td></tr>
<tr><td>88-216</td><td>150 **</td><td>3</td></tr>
<tr><td>216-960</td><td>200 **</td><td>3</td></tr>
<tr><td>Above 960</td><td>500</td><td>3</td></tr>
</table>
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10-2020+Cor 1-2023 section 6.6.4
KDB 558074 D01 15.247 Meas Guidance v05r02</td></tr>
<tr><td>Procedure:</td><td>ANSI C63.10-2020+Cor 1-2023 section 6.6.4</td></tr>
</table>

10.1. EUT Operation

<table>
<tr><td colspan="2">Operating Environment:</td></tr>
<tr><td>Test mode:</td><td>1: 802.11b mode: Keep the EUT in 802.11b transmitting mode.
2: 802.11g mode: Keep the EUT in 802.11g transmitting mode.
3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode.</td></tr>
</table>

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

10.2. Test Setup



Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

10.3. Test Data

Temperature:	24.2 °C	Humidity:	54.3 %	Atmospheric Pressure:	101 kPa

TM1 / CH: L						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4824.00	29.09	15.31	44.40	74.00	-29.60	Vertical
7236.00	30.50	18.06	48.56	74.00	-25.44	Vertical
9648.00	30.68	23.77	54.45	74.00	-19.55	Vertical
12060.00	*			74.00		Vertical
14472.00	*			74.00		Vertical
4824.00	28.46	15.31	43.77	74.00	-30.23	Horizontal
7236.00	31.01	18.06	49.07	74.00	-24.93	Horizontal
9648.00	28.47	23.77	52.24	74.00	-21.76	Horizontal
12060.00	*			74.00		Horizontal
14472.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4824.00	21.11	15.31	36.42	54.00	-17.58	Vertical
7236.00	22.28	18.06	40.34	54.00	-13.66	Vertical
9648.00	22.58	23.77	46.35	54.00	-7.65	Vertical
12060.00	*			54.00		Vertical
14472.00	*			54.00		Vertical
4824.00	20.97	15.31	36.28	54.00	-17.72	Horizontal
7236.00	23.58	18.06	41.64	54.00	-12.36	Horizontal
9648.00	20.21	23.77	43.98	54.00	-10.02	Horizontal
12060.00	*			54.00		Horizontal
14472.00	*			54.00		Horizontal

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

TM1 / CH: M						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.04	15.41	44.45	74.00	-29.55	Vertical
7311.00	28.85	18.01	46.86	74.00	-27.14	Vertical
9748.00	30.62	23.79	54.41	74.00	-19.59	Vertical
12185.00	*			74.00		Vertical
14622.00	*			74.00		Vertical
4874.00	28.26	15.41	43.67	74.00	-30.33	Horizontal
7311.00	29.93	18.01	47.94	74.00	-26.06	Horizontal
9748.00	28.77	23.79	52.56	74.00	-21.44	Horizontal
12185.00	*			74.00		Horizontal
14622.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4874.00	19.86	15.41	35.27	54.00	-18.73	Vertical
7311.00	19.75	18.01	37.76	54.00	-16.24	Vertical
9748.00	20.87	23.79	44.66	54.00	-9.34	Vertical
12185.00	*			54.00		Vertical
14622.00	*			54.00		Vertical
4874.00	19.36	15.41	34.77	54.00	-19.23	Horizontal
7311.00	20.01	18.01	38.02	54.00	-15.98	Horizontal
9748.00	19.48	23.79	43.27	54.00	-10.73	Horizontal
12185.00	*			54.00		Horizontal
14622.00	*			54.00		Horizontal

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com

TM1 / CH: H						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4924.00	28.90	15.51	44.41	74.00	-29.59	Vertical
7386.00	28.79	17.97	46.76	74.00	-27.24	Vertical
9848.00	30.06	23.82	53.88	74.00	-20.12	Vertical
12310.00	*			74.00		Vertical
14772.00	*			74.00		Vertical
4924.00	28.92	15.51	44.43	74.00	-29.57	Horizontal
7386.00	30.28	17.97	48.25	74.00	-25.75	Horizontal
9848.00	29.27	23.82	53.09	74.00	-20.91	Horizontal
12310.00	*			74.00		Horizontal
14772.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4924.00	19.69	15.51	35.20	54.00	-18.80	Vertical
7386.00	19.19	17.97	37.16	54.00	-16.84	Vertical
9848.00	21.31	23.82	45.13	54.00	-8.87	Vertical
12310.00	*			54.00		Vertical
14772.00	*			54.00		Vertical
4924.00	19.17	15.51	34.68	54.00	-19.32	Horizontal
7386.00	20.39	17.97	38.36	54.00	-15.64	Horizontal
9848.00	19.71	23.82	43.53	54.00	-10.47	Horizontal
12310.00	*			54.00		Horizontal
14772.00	*			54.00		Horizontal

Remark:
1. Result =Reading + Factor

2. Test frequency are from 1GHz to 25GHz, “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

3. Only the worst case is recorded in the report.

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

---------- End of Report ----------

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.
Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com