


ANNEX E TEST DATA

For

Project No.:	8337EU011928W
Client:	Shenzhen Qianyan Technology LTD
Product Name:	Govee Permanent Outdoor Lights Elite
Model No.:	H805D
FCC ID:	2A7VD-H805CB
Technology:	WiFi 2.4G
Test Engineer:	<i>Mikoy zhu</i>
Test Date:	2026-01-05

Test Summary

Item	Result
Duty Cycle	Pass
Bandwidth	Pass
Maximum Conducted Output Power	Pass
Maximum Power Spectral Density	Pass
Unwanted Emissions In Non-restricted Frequency Bands	Pass



1. Duty Cycle


1.1 Test Result


1.1.1 Ant1


Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	12.417	12.547	98.96	0.05	0.03
		2437	12.416	12.546	98.96	0.05	0.03
		2462	12.417	12.547	98.96	0.05	0.03
802.11g	SISO	2412	2.065	2.194	94.12	0.26	0.03
		2437	2.064	2.194	94.07	0.27	0.03
		2462	2.065	2.194	94.12	0.26	0.03
802.11n (HT20)	SISO	2412	1.921	2.050	93.71	0.28	0.03
		2437	1.920	2.050	93.66	0.28	0.04
		2462	1.921	2.051	93.66	0.28	0.04


1.2 Test Graph


1.2.1 Ant1











2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	14.140	/	Pass
		2437	1	14.139	/	Pass
		2462	1	14.139	/	Pass
802.11g	SISO	2412	1	18.036	/	Pass
		2437	1	17.685	/	Pass
		2462	1	17.799	/	Pass
802.11n (HT20)	SISO	2412	1	18.879	/	Pass
		2437	1	18.811	/	Pass
		2462	1	18.849	/	Pass


2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	9.261	≥ 0.5	Pass
		2437	1	9.265	≥ 0.5	Pass
		2462	1	9.263	≥ 0.5	Pass
802.11g	SISO	2412	1	16.678	≥ 0.5	Pass
		2437	1	16.552	≥ 0.5	Pass
		2462	1	16.653	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	1	17.791	≥ 0.5	Pass
		2437	1	17.859	≥ 0.5	Pass
		2462	1	17.948	≥ 0.5	Pass


2.2 Test Graph


2.2.1 OBW
















2.2.2 6dB BW











3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	12.32	<=30	Pass
		2437	12.59	<=30	Pass
		2462	12.78	<=30	Pass
802.11g	SISO	2412	13.79	<=30	Pass
		2437	14.11	<=30	Pass
		2462	14.29	<=30	Pass
802.11n (HT20)	SISO	2412	13.85	<=30	Pass
		2437	14.08	<=30	Pass
		2462	14.31	<=30	Pass

Note1: Antenna Gain: Ant1: 3.98dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD


Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	1.00	≤ 8	Pass
		2437	1.11	≤ 8	Pass
		2462	1.83	≤ 8	Pass
802.11g	SISO	2412	-4.89	≤ 8	Pass
		2437	-4.62	≤ 8	Pass
		2462	-4.37	≤ 8	Pass
802.11n (HT20)	SISO	2412	-5.21	≤ 8	Pass
		2437	-4.68	≤ 8	Pass
		2462	-4.39	≤ 8	Pass


Note1: Antenna Gain: Ant1: 3.98dBi;


4.2 Test Graph


4.2.1 PSD











5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	1.22
		2437	1	1.63
		2462	1	1.63
802.11g	SISO	2412	1	-4.88
		2437	1	-4.79
		2462	1	-4.36
802.11n (HT20)	SISO	2412	1	-5.45
		2437	1	-4.53
		2462	1	-4.36

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020+Cor 1-2023, the channel contains the maximum PSD level was used to establish the reference level.


5.1.2 CSE


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	1	1.22	-18.78	Pass
		2437	1	1.63	-18.37	Pass
		2462	1	1.63	-18.37	Pass
802.11g	SISO	2412	1	-4.88	-24.88	Pass
		2437	1	-4.79	-24.79	Pass
		2462	1	-4.36	-24.36	Pass
802.11n (HT20)	SISO	2412	1	-5.45	-25.45	Pass
		2437	1	-4.53	-24.53	Pass
		2462	1	-4.36	-24.36	Pass


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020+Cor 1-2023, the channel contains the maximum PSD level was used to establish the reference level.


5.2 Test Graph


5.2.1 Ref
















5.2.2 CSE



























































----- End of Report -----