

Test Report

Report No. : CQASZ20220901542E-01
Applicant: Guangdong Lilin Intelligent Technology Co., Ltd.
Address of Applicant: Room 601, Building 8, No.31 Duimianling Street, Dalingshan Town, Dongguan City, Guangdong Province, China
Equipment Under Test (EUT):
Product: Robot Vacuum Cleaner
Model No.: R200, R201, R202, R203, R2001, R2002, R2003, R2004, Redkey Q10, R200A, R200A1, R200A2, R200A3, R200B, R200B1, R200B2, R200B3, R200C, R200C1, R200C2, R200C3, R200D1, R200D2, R200D3, R200D4, R200E1, R200E2, R200E3, R200A4, R200B4, R200C4, R200F1, R200F2, R200F1, R200F2, R200F3, R200F4, R200Z1, R200Z2, R200Z3, R200Z4
Test Model No.: R200
Brand Name: N/A
FCC ID: 2A7XF-R200
Standards: 47 CFR Part 15, Subpart C
Date of Receipt: 2022-09-09
Date of Test: 2022-09-09 to 2022-11-10
Date of Issue: 2022-12-26
Test Result : PASS*

*In the configuration tested, the EUT complied with the standards specified above.

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220901542E-01	Rev.01	Initial report	2022-12-26

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 ADDITIONAL INSTRUCTIONS	8
4.4 TEST ENVIRONMENT	9
4.5 DESCRIPTION OF SUPPORT UNITS	9
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	10
4.7 TEST LOCATION	11
4.8 TEST FACILITY	11
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	11
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	11
4.11 EQUIPMENT LIST	12
5 TEST RESULTS AND MEASUREMENT DATA	13
5.1 ANTENNA REQUIREMENT	13
5.2 CONDUCTED EMISSIONS	14
5.3 CONDUCTED PEAK OUTPUT POWER	28
5.4 20dB OCCUPY BANDWIDTH	33
5.5 CARRIER FREQUENCIES SEPARATION	37
5.6 HOPPING CHANNEL NUMBER	40
5.7 DWELL TIME	42
5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	50
5.9 SPURIOUS RF CONDUCTED EMISSIONS	56
5.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	66
5.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	68
5.11.1 Radiated Emission below 1GHz	71
5.11.2 Transmitter Emission above 1GHz	83
6 PHOTOGRAPHS - EUT TEST SETUP	85
6.1 RADIATED EMISSION	85
6.2 CONDUCTED EMISSION	86
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	88

4 General Information

4.1 Client Information

Applicant:	Guangdong Lilin Intelligent Technology Co., Ltd.
Address of Applicant:	Room 601, Building 8, No.31 Duimianling Street, Dalingshan Town, Dongguan City, Guangdong Province, China
Manufacturer:	Guangdong Lilin Intelligent Technology Co., Ltd.
Address of Manufacturer:	Room 601, Building 8, No.31 Duimianling Street, Dalingshan Town, Dongguan City, Guangdong Province, China
Factory:	Guangdong Lilin Intelligent Technology Co., Ltd.
Address of Factory:	Room 601, Building 8, No.31 Duimianling Street, Dalingshan Town, Dongguan City, Guangdong Province, China

4.2 General Description of EUT

Product Name:	Robot Vacuum Cleaner
Model No.:	R200, R201, R202, R203, R2001, R2002, R2003, R2004, Redkey Q10, R200A, R200A1, R200A2, R200A3, R200B, R200B1, R200B2, R200B3, R200C, R200C1, R200C2, R200C3, R200D1, R200D2, R200D3, D200D4, R200E1, R200E2, R200E3, R200A4, R200B4, R200C4, R200F1, R200F2, R200F1, R200F2, R200F3, R200F4, R200Z1, R200Z2, R200Z3, R200Z4
Test Model No.:	R200
Trade Mark:	N/A
Software Version:	V2.4.6
Hardware Version:	V1.1.29
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☒ Mobile ☐ Portable
Test Software of EUT:	rtworiv_V2
Antenna Type:	FPC antenna
Antenna Gain:	3.84 dBi
Power Supply:	1# Li-ion battery: DC 14.4V 5000mAh, Charge by DC 24V for Charging Base 2# Li-ion battery: DC 14.4V 2500mAh, Charge by DC 24V for Charging Base 3# Li-ion battery: DC 16.8V 5200mAh, Charge by DC 24V for Charging Base 4# Li-ion battery: DC 14.4V 5000mAh, Charge by DC 24V for Charging Base 5# Li-ion battery: DC 14.4V 5000mAh, Charge by DC 24V for Charging Base 6# Li-ion battery: DC 14.4V 5000mAh, Charge by DC 24V for Charging Base

	Charging Base:Output:19V 1A
	Dust collecting bucket:Power AC 120V~ 60Hz
	Model:AD-0191900100US
	Input:100-240V~50/60Hz 0.8A
	Output:19V 1A

Note:

The only difference between # 2 and # 1 battery is the battery capacity.

The only difference between # 3 and # 1 is battery capacity and output voltage.

The only difference between # 4 and # 1 is that the power supply mode is changed from dust collecting bucket to charging base.

The only difference between # 5 and # 1 is that the power plate of the dust collecting bucket is different.

The only difference between # 6 and # 1 is that the wheel motor suppliers are different.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

4.3 Additional Instructions

EUT Test Software Settings:		
Mode:	☒ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: *##3646633##*	
EUT Power level:	Class2 (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480

Run Software:



4.4 Test Environment

Operating Environment:	
Temperature:	25 °C
Humidity:	54% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty
1	Radiated Emission (Below 1GHz)	5.12dB
2	Radiated Emission (Above 1GHz)	4.60dB
3	Conducted Disturbance (0.15~30MHz)	3.34dB
4	Radio Frequency	3×10^{-8}
5	Duty cycle	0.6 %
6	Occupied Bandwidth	1.1%
7	RF conducted power	0.86dB
8	RF power density	0.74
9	Conducted Spurious emissions	0.86dB
10	Temperature test	0.8℃
11	Humidity test	2.0%
12	Supply voltages	0.5 %
13	Frequency Error	5.5 Hz

4.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 22984-1

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2022/9/9	2023/9/8
Spectrum analyzer	R&S	FSU26	CQA-038	2022/9/9	2023/9/8
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2022/9/9	2023/9/8
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2022/9/9	2023/9/8
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2021/9/16	2024/9/15
Bilog Antenna	R&S	HL562	CQA-011	2021/9/16	2024/9/15
Horn Antenna	R&S	HF906	CQA-012	2021/9/16	2024/9/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/9/16	2024/9/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2022/9/9	2023/9/8
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2022/9/9	2023/9/8
Antenna Connector	CQA	RFC-01	CQA-080	2022/9/9	2023/9/8
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2022/9/9	2023/9/8
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2022/9/9	2023/9/8
EMI Test Receiver	R&S	ESPI3	CQA-013	2022/9/9	2023/9/8
LISN	R&S	ENV216	CQA-003	2022/9/9	2023/9/8
Coaxial cable	CQA	N/A	CQA-C009	2022/9/9	2023/9/8

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	 The antenna is FPC antenna. The best case gain of the antenna is 3.84 dBi.

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1—Excess I/O cables shall be bundled in the center. If bundling is not possible, then the cables shall be arranged in serpentine fashion. Bundling shall not exceed 40 cm in length . 2—Excess power cords shall be bundled in the center or shortened to an appropriate length. 3—EUT and all cables shall be insulated, if required, from the ground plane by up to 12 mm of insulating material . 4—EUT connected to one LISN. LISN may be placed on top of, or immediately beneath, the ground plane. i All other equipment powered from a second LISN or additional LISN(s). ii A multiple-outlet strip may be used for multiple power cords of non-EUT equipment. 5—Horizontal projection from the closest point of EUT to the nearest point of the LISN. For radiated emission testing, the LISNs shall be removed. 6—Ground reference plane.		
Test Setup:			


Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.

Test Voltage:	AC 120V/60Hz
Test Results:	Pass

1#

Measurement Data

Live line:




	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.16	26.11	9.39	35.60	55.73	-20.13	Average	Line
2	0.16	37.44	9.39	46.93	65.73	-18.80	QP	Line
3	0.17	25.27	9.39	34.76	55.21	-20.45	Average	Line
4	0.17	36.25	9.39	45.74	65.21	-19.47	QP	Line
5	0.19	25.14	9.39	34.63	54.04	-19.41	Average	Line
6	0.19	35.33	9.39	44.82	64.04	-19.22	QP	Line
7	0.25	24.93	9.39	34.42	51.92	-17.50	Average	Line
8	0.25	31.55	9.39	41.04	61.92	-20.88	QP	Line
9	0.43	19.31	9.41	28.82	47.35	-18.53	Average	Line
10	0.43	24.27	9.41	33.78	57.35	-23.57	QP	Line
11	0.59	19.67	9.49	29.35	46.00	-16.65	Average	Line
12	0.59	25.46	9.49	35.14	56.00	-20.86	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq.	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.17	23.98	9.57	33.65	55.21	-21.56	Average	Neutral
2	0.17	33.44	9.57	43.11	65.21	-22.10	QP	Neutral
3	0.19	23.47	9.53	33.10	54.26	-21.16	Average	Neutral
4	0.19	32.10	9.53	41.73	64.26	-22.53	QP	Neutral
5	0.23	22.51	9.46	32.07	52.45	-20.38	Average	Neutral
6	0.23	29.60	9.46	39.16	62.45	-23.29	QP	Neutral
7	0.28	21.49	9.41	31.00	50.97	-19.97	Average	Neutral
8	0.28	28.18	9.41	37.69	60.97	-23.28	QP	Neutral
9	0.48	19.60	9.58	29.28	46.34	-17.06	Average	Neutral
10	0.48	25.02	9.58	34.70	56.34	-21.64	QP	Neutral
11	1.19	19.91	9.60	29.62	46.00	-16.38	Average	Neutral
12	1.19	24.86	9.60	34.57	56.00	-21.43	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

2#

Measurement Data

Live line:




	Freq.	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.18	22.16	9.55	31.81	54.72	-22.91	Average	Line
2	0.18	27.05	9.55	36.70	64.72	-28.02	QP	Line
3	0.31	20.52	9.40	30.02	49.97	-19.95	Average	Line
4	0.31	25.28	9.40	34.78	59.97	-25.19	QP	Line
5	0.59	18.42	9.60	28.21	46.00	-17.79	Average	Line
6	0.59	23.58	9.60	33.37	56.00	-22.63	QP	Line
7	0.75	18.82	9.60	28.69	46.00	-17.31	Average	Line
8	0.75	23.81	9.60	33.68	56.00	-22.32	QP	Line
9	1.09	19.44	9.84	29.38	46.00	-16.62	Average	Line
10	1.09	24.34	9.84	34.28	56.00	-21.72	QP	Line
11	1.33	20.25	10.38	30.75	46.00	-15.25	Average	Line
12	1.33	25.12	10.38	35.62	56.00	-20.38	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
		Level			Line	Limit		
		dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.16	22.15	9.59	31.84	55.73	-23.89	Average	Neutral
2	0.16	27.17	9.59	36.86	65.73	-28.87	QP	Neutral
3	0.27	20.84	9.41	30.35	51.12	-20.77	Average	Neutral
4	0.27	25.83	9.41	35.34	61.12	-25.78	QP	Neutral
5	0.35	19.42	9.44	28.96	49.08	-20.12	Average	Neutral
6	0.35	24.79	9.44	34.33	59.08	-24.75	QP	Neutral
7	0.62	18.74	9.60	28.56	46.00	-17.44	Average	Neutral
8	0.62	23.53	9.60	33.35	56.00	-22.65	QP	Neutral
9	0.96	19.22	9.60	28.95	46.00	-17.05	Average	Neutral
10	0.96	24.13	9.60	33.86	56.00	-22.14	QP	Neutral
11	1.15	19.69	9.60	29.40	46.00	-16.60	Average	Neutral
12	1.15	24.71	9.60	34.42	56.00	-21.58	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

3#

Measurement Data

Live line:




	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.24	20.99	9.46	30.55	52.27	-21.72	Average	Line
2	0.24	26.04	9.46	35.60	62.27	-26.67	QP	Line
3	0.36	19.26	9.46	28.82	48.84	-20.02	Average	Line
4	0.36	24.15	9.46	33.71	58.84	-25.13	QP	Line
5	0.67	18.42	9.60	28.29	46.00	-17.71	Average	Line
6	0.67	23.27	9.60	33.14	56.00	-22.86	QP	Line
7	0.77	18.12	9.60	27.98	46.00	-18.02	Average	Line
8	0.77	23.30	9.60	33.16	56.00	-22.84	QP	Line
9	1.20	19.80	10.09	30.00	46.00	-16.00	Average	Line
10	1.20	24.48	10.09	34.68	56.00	-21.32	QP	Line
11	1.63	17.16	10.93	28.22	46.00	-17.78	Average	Line
12	1.63	22.54	10.93	33.60	56.00	-22.40	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
		Level			Line	Limit		
		dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.24	20.75	9.46	30.31	52.27	-21.96	Average	Neutral
2	0.24	25.74	9.46	35.30	62.27	-26.97	QP	Neutral
3	0.33	19.40	9.42	28.92	49.45	-20.53	Average	Neutral
4	0.33	24.62	9.42	34.14	59.45	-25.31	QP	Neutral
5	0.46	18.47	9.56	28.13	46.78	-18.65	Average	Neutral
6	0.46	23.46	9.56	33.12	56.78	-23.66	QP	Neutral
7	0.76	18.42	9.60	28.28	46.00	-17.72	Average	Neutral
8	0.76	23.41	9.60	33.27	56.00	-22.73	QP	Neutral
9	1.21	19.68	9.60	29.39	46.00	-16.61	Average	Neutral
10	1.21	24.79	9.60	34.50	56.00	-21.50	QP	Neutral
11	1.40	18.30	9.60	28.02	46.00	-17.98	Average	Neutral
12	1.40	23.28	9.60	33.00	56.00	-23.00	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

4#

Measurement Data

Live line:




	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.22	21.33	9.49	30.92	53.01	-22.09	Average	Line
2	0.22	26.10	9.49	35.69	63.01	-27.32	QP	Line
3	0.38	19.10	9.48	28.68	48.39	-19.71	Average	Line
4	0.38	24.04	9.48	33.62	58.39	-24.77	QP	Line
5	0.57	18.36	9.60	28.13	46.00	-17.87	Average	Line
6	0.57	23.28	9.60	33.05	56.00	-22.95	QP	Line
7	0.84	18.44	9.60	28.25	46.00	-17.75	Average	Line
8	0.84	23.39	9.60	33.20	56.00	-22.80	QP	Line
9	1.14	19.46	9.95	29.52	46.00	-16.48	Average	Line
10	1.14	24.49	9.95	34.55	56.00	-21.45	QP	Line
11	1.36	18.55	10.44	29.11	46.00	-16.89	Average	Line
12	1.36	23.24	10.44	33.80	56.00	-22.20	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.18	21.29	9.55	30.94	54.72	-23.78	Average	Neutral
2	0.18	26.46	9.55	36.11	64.72	-28.61	QP	Neutral
3	0.38	19.11	9.48	28.69	48.28	-19.59	Average	Neutral
4	0.38	23.96	9.48	33.54	58.28	-24.74	QP	Neutral
5	0.46	18.67	9.56	28.33	46.69	-18.36	Average	Neutral
6	0.46	23.29	9.56	32.95	56.69	-23.74	QP	Neutral
7	0.68	18.34	9.60	28.22	46.00	-17.78	Average	Neutral
8	0.68	23.25	9.60	33.13	56.00	-22.87	QP	Neutral
9	0.99	19.09	9.60	28.80	46.00	-17.20	Average	Neutral
10	0.99	23.78	9.60	33.49	56.00	-22.51	QP	Neutral
11	1.25	20.01	9.60	29.72	46.00	-16.28	Average	Neutral
12	1.25	24.63	9.60	34.34	56.00	-21.66	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5#

Measurement Data

Live line:




	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.28	20.36	9.42	29.88	50.97	-21.09	Average	Line
2	0.28	25.32	9.42	34.84	60.97	-26.13	QP	Line
3	0.44	18.70	9.55	28.35	47.06	-18.71	Average	Line
4	0.44	23.66	9.55	33.31	57.06	-23.75	QP	Line
5	0.75	18.67	9.60	28.54	46.00	-17.46	Average	Line
6	0.75	23.24	9.60	33.11	56.00	-22.89	QP	Line
7	1.16	19.46	10.01	29.58	46.00	-16.42	Average	Line
8	1.16	24.56	10.01	34.68	56.00	-21.32	QP	Line
9	1.39	18.35	10.49	28.96	46.00	-17.04	Average	Line
10	1.39	23.08	10.49	33.69	56.00	-22.31	QP	Line
11	1.68	16.78	11.01	27.92	46.00	-18.08	Average	Line
12	1.68	21.29	11.01	32.43	56.00	-23.57	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.17	21.54	9.56	31.20	54.96	-23.76	Average	Neutral
2	0.17	26.41	9.56	36.07	64.96	-28.89	QP	Neutral
3	0.27	20.41	9.41	29.92	51.12	-21.20	Average	Neutral
4	0.27	25.49	9.41	35.00	61.12	-26.12	QP	Neutral
5	0.50	23.31	9.60	33.01	46.08	-13.07	Average	Neutral
6	0.50	27.00	9.60	36.70	56.08	-19.38	QP	Neutral
7	0.61	18.47	9.60	28.28	46.00	-17.72	Average	Neutral
8	0.61	23.16	9.60	32.97	56.00	-23.03	QP	Neutral
9	0.97	18.67	9.60	28.39	46.00	-17.61	Average	Neutral
10	0.97	23.88	9.60	33.60	56.00	-22.40	QP	Neutral
11	1.26	19.72	9.60	29.43	46.00	-16.57	Average	Neutral
12	1.26	24.77	9.60	34.48	56.00	-21.52	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

6#

Measurement Data

Live line:




	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.23	20.95	9.48	30.53	52.63	-22.10	Average	Line
2	0.23	25.90	9.48	35.48	62.63	-27.15	QP	Line
3	0.32	19.81	9.41	29.32	49.84	-20.52	Average	Line
4	0.32	24.60	9.41	34.11	59.84	-25.73	QP	Line
5	0.43	18.50	9.53	28.13	47.35	-19.22	Average	Line
6	0.43	26.58	9.53	36.21	57.35	-21.14	QP	Line
7	0.71	18.26	9.60	28.15	46.00	-17.85	Average	Line
8	0.71	23.38	9.60	33.27	56.00	-22.73	QP	Line
9	0.92	18.74	9.60	28.49	46.00	-17.51	Average	Line
10	0.92	23.77	9.60	33.52	56.00	-22.48	QP	Line
11	1.36	18.57	10.44	29.13	46.00	-16.87	Average	Line
12	1.36	23.27	10.44	33.83	56.00	-22.17	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




	Freq.	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	dBuV	dBuV	dBuV	dBuV	dBuV	dBuV		
1	0.21	21.16	9.49	30.75	53.21	-22.46	Average	Neutral
2	0.21	26.07	9.49	35.66	63.21	-27.55	QP	Neutral
3	0.32	19.60	9.41	29.11	49.71	-20.60	Average	Neutral
4	0.32	24.66	9.41	34.17	59.71	-25.54	QP	Neutral
5	0.47	18.59	9.57	28.26	46.60	-18.34	Average	Neutral
6	0.47	23.43	9.57	33.10	56.60	-23.50	QP	Neutral
7	0.77	18.34	9.60	28.20	46.00	-17.80	Average	Neutral
8	0.77	23.46	9.60	33.32	56.00	-22.68	QP	Neutral
9	1.06	19.11	9.60	28.81	46.00	-17.19	Average	Neutral
10	1.06	24.31	9.60	34.01	56.00	-21.99	QP	Neutral
11	1.43	18.21	9.60	27.93	46.00	-18.07	Average	Neutral
12	1.43	23.06	9.60	32.78	56.00	-23.22	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	-1.59	≤21	PASS
		2441	0.19	≤21	PASS
		2480	0.54	≤21	PASS
2DH5	Ant1	2402	-0.87	≤21	PASS
		2441	0.65	≤21	PASS
		2480	1.15	≤21	PASS


Test plot as follows:




DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441



2DH5_Ant1_2480



5.4 20dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.936	2401.532	2402.468	---	PASS
		2441	0.933	2440.532	2441.465	---	PASS
		2480	0.939	2479.532	2480.471	---	PASS
2DH5	Ant1	2402	1.257	2401.361	2402.618	---	PASS
		2441	1.326	2440.328	2441.654	---	PASS
		2480	1.311	2479.334	2480.645	---	PASS


Test plot as follows:




DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441



2DH5_Ant1_2480




5.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	1	≥ 0.626	PASS
2DH5	Ant1	Hop	1.003	≥ 0.884	PASS

Test plot as follows:




5.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS

Test plot as follows:



5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass


Measurement Data


TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.38	330	0.125	≤0.4	PASS
DH3	Ant1	Hop	1.63	190	0.309	≤0.4	PASS
DH5	Ant1	Hop	2.87	100	0.287	≤0.4	PASS
2DH1	Ant1	Hop	0.39	330	0.128	≤0.4	PASS
2DH3	Ant1	Hop	1.63	150	0.245	≤0.4	PASS
2DH5	Ant1	Hop	2.87	80	0.23	≤0.4	PASS


Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$


Test plot as follows:
















5.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	-2.26	-41.95	≤ -22.26	PASS
		High	2480	0.24	-48.85	≤ -19.76	PASS
		Low	Hop_2402	-1.78	-49.93	≤ -21.78	PASS
		High	Hop_2480	-0.26	-49.82	≤ -20.26	PASS
2DH5	Ant1	Low	2402	-1.67	-42.27	≤ -21.67	PASS
		High	2480	0.37	-48.78	≤ -19.63	PASS
		Low	Hop_2402	-6.19	-50.39	≤ -26.19	PASS
		High	Hop_2480	-0.18	-49.2	≤ -20.18	PASS

Test plot as follows:




DH5_Ant1_Low_Hop_2402




DH5_Ant1_High_Hop_2480




2DH5_Ant1_Low_2402



2DH5_Ant1_High_2480




2DH5_Ant1_Low_Hop_2402




2DH5_Ant1_High_Hop_2480




5.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=cable loss+ attenuation factor.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type.
Test Results:	Pass


DH5_Ant1_2402_0~Reference




DH5_Ant1_2402_30~1000




DH5_Ant1_2402_1000~26500




DH5_Ant1_2441_0~Reference



DH5_Ant1_2441_30~1000



DH5_Ant1_2441_1000~26500



DH5_Ant1_2480_0~Reference



DH5_Ant1_2480_30~1000

