



18/88 Merrindale Drive Croydon South, Victoria, 3136, Australia
Telephone: +61 3 9761 5888
Facsimile: +61 3 8761 6547
Email: sales@emcbayswater.com.au
ABN: 49 112 221 333

RF Radiation Exposure Evaluation

In accordance with:

CFR47 FCC Part 2, Subpart J, 2.1093

FCC KDB 447498 D01 v06

Sealite Pty Ltd

PCA-2201

2.4GHz Radio Module

FCC ID: 2A7Y2AV-RFM-01

REPORT: E2206-1543-2

DATE: September, 2022



RF Radiation Exposure Evaluation Report

EMC Bayswater Test Report: E2206-1543-2
Issue Date: September, 2022

Product: 2.4GHz Radio Module
Model No: PCA-2201
Serial No: None stated
FCC ID: 2A7Y2AV-RFM-01

Client Details: Mr. Jens Ohle
Sealite Pty Ltd
11 Industrial Drive
Somerville
Victoria 3192
Australia

Phone No: +61 3 5977 6128
e-mail: jens.ohle@spx.com

Standard(s): CFR47 FCC Part 2, Subpart J, 2.1093
Radiofrequency radiation exposure evaluation: portable devices.

FCC KDB 447498 D01 v06
RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES
FOR MOBILE AND PORTABLE DEVICES

Results Summary: RF Radiation exposure requirements **Complied**

Test Date(s): 23rd of June, 2022

Test House (Issued By): EMC Bayswater Pty Ltd
18/88 Merrindale Drive
Croydon South
Victoria, 3136
Australia

FCC Accredited Test Firm Registration number: 527798
FCC Accredited Test Firm Designation number: AU0004

Phone No: +61 3 9761 5888 Email: sales@emcbayswater.com.au
Fax: +61 3 8761 6547 Web: www.emcbayswater.com.au

The Sealite Pty Ltd, PCA-2201, 2.4GHz Radio Module, measured maximum power is below the SAR exception threshold (60mm distance) and the calculated power density level at a distance of 20cm are below the maximum levels allowed by regulations therefore complied with the requirements of CFR47 FCC Part 2, Subpart J, 2.1093.

This is to certify that the necessary evaluations were made by EMC Bayswater Pty Ltd, and that the Sealite Pty Ltd, PCA-2201, 2.4GHz Radio Module, has been tested in accordance with requirements contained in the appropriate commission regulations.

Prepared by:

Approved by:



12/09/2022 12:47

Adnan Zaman
(EMC Test Engineer)

Neville Liyanapatabendige
(Manager)

Date

RF Radiation Exposure Evaluation *for* Sealite Pty Ltd

Contents

1. Introduction	4
2. Test Report Revision History.....	4
3. Report Information	4
4. Product Details	5
4.1. Product Sample Details	5
4.2. Product description	5
5. SAR and RF Exposure exception evaluation.....	6
5.1. SAR exception evaluation.....	6
5.2. RF Exposure Evaluation (MPE)	7
6. Conclusion.....	7

1. Introduction

RF Radiation Exposure evaluation was performed on a Sealite Pty Ltd, PCA-2201, 2.4GHz Radio Module in accordance with CFR47 FCC Part 2, Subpart J, 2.1093.

2. Test Report Revision History

None

3. Report Information

EMC Bayswater Pty Ltd reports apply only to the specific samples tested under the stated test conditions. All samples tested were in good operating condition throughout the entire test program unless otherwise stated. EMC Bayswater Pty Ltd does not in any way guarantees the later performance of the product/equipment. It is the manufacturer's responsibility to ensure that additional production units of the tested model are manufactured with identical electrical and mechanical components. EMC Bayswater Pty Ltd shall have no liability for any deductions, inference or generalisations drawn by the clients or others from EMC Bayswater Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Bayswater Pty Ltd. This report shall not be reproduced except in full, without the written approval of EMC Bayswater Pty Ltd. This document may be altered or revised by EMC Bayswater Pty Ltd personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by EMC Bayswater Pty Ltd will nullify the document.

4. Product Details

4.1. Product Sample Details

The device, as supplied by the client, is described as follows:

Product:	2.4GHz Radio Module	
Model No:	PCA-2201	
Serial No:	None stated	
Firmware:	Not supplied	
Software:	N/A	
Power Specifications:	3.3VDC	
Dimensions:	28.25mm x 27.50mm x 7.5mm (Length x Width x Height)	
Weight:	4 gm	
EUT Type:	Tested as table-top	
Transmitter details:	Description:	nRF52833
	Type:	Bluetooth ® 5.1, IEEE 802.15.4-2006, 2.4 GHz transceiver
	Max power:	<+20dBm
	Antenna:	Part number: TE Connectivity 2118059-1 Frequency Range (MHz): 2300 – 3800 MHz Peak Gain +4dBi

(Customer supplied product information)

4.2. Product description

The device has been described by the customer as follows:

“2.4GHz Radio Module to be embedded in aviation lanterns for communication using proprietary protocol 802.15.4.”

(Customer supplied product description information)

5. SAR and RF Exposure exception evaluation

5.1. SAR exception evaluation

As per Appendix A of KDB 447498 D01 General RF Exposure Guidance v06

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	mW
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465	
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462	

SAR test exclusion threshold for 2410MHz transmitter is 196.9mW for 60mm distance.

- The measured maximum peak conducted power at antenna connector is 100mW (Worst-case, Without Duty Cycle correction factor).

The measurement uncertainty was calculated at $\pm 4.83\text{dB}$. The reported uncertainty is an expanded uncertainty calculated using a coverage factor of approximately $k=2$ which gives a level of confidence of approximately 95%.

The measured peak conducted power is below the SAR exception threshold for 60mm distance.

5.2. RF Exposure Evaluation (MPE)

As per section 1.1310 of CFR 47 following Maximum Permissible Exposure (MPE) limits are applicable.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

Limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields for 2402 to 2480MHz as per Table 1 of Section 15.1310 is 1 mW/cm² (General Population/Un-controlled).

Prediction Worst case:

Using equation

$$S = PG / 4\pi R^2$$

where: S = Power density

P = Power input to the antenna

G = Antenna gain

R = Distance to the center of radiation of the antenna

Band	Maximum Conducted Power @ Antenna (dBm)*	Antenna Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Distance (cm)	Calculated Power Density at 20cm (mW/cm ²)	Power Density Limit** (mW/cm ²)
2.4GHz	20	+4.0	24.0	251	20	0.0499	1

*Worst-case, Without Duty Cycle correction factor

** MPE limit for General Population/Un-controlled exposure

Table 1: Results for MPE Evaluation

6. Conclusion

The measured EIRP is below the SAR exception threshold (60mm distance) and the calculated power density level at a distance of 20cm are below the maximum levels allowed by regulations.