

Test Report

Report No.: MTi230505009-05E1

Date of issue: 2023-06-02

Applicant: Ningbo Fulman Communication Technology Co., Ltd

Product: True Wireless Bluetooth Earbuds

Model(s): NBJ, NBJB0, NBJW0, NBJG0, NBJL0, NBJP0,
NBJY0, NBJM0

FCC ID: 2A7Z4-NBJ

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Test conditions	7
1.4	Description of support units	7
2	Measurement uncertainty	8
3	Summary of Test Result.....	9
4	Test Laboratory.....	10
5	Equipment List	11
6	Test Result	12
6.1	Antenna requirement	12
6.2	AC power line conducted emissions.....	13
6.3	Radiated spurious emission	14
6.4	20dB emission bandwidth	28
6.5	Maximum conducted output power	29
6.6	Carrier frequency separation	30
6.7	Time of occupancy.....	31
6.8	Number of hopping channels	32
6.9	Band edge (Conducted)	33
6.10	Conducted spurious emissions	34
	Appendix A: 20dB Emission Bandwidth	35
	Appendix B: Maximum conducted output power	40
	Appendix C: Carrier frequency separation	45
	Appendix D: Time of occupancy	48
	Appendix E: Number of hopping channels	57
	Appendix F: Band edge measurements	60
	Appendix G: Conducted Spurious Emission	66
	Photographs of the Test Setup.....	79
	Photographs of the EUT	80


Test Result Certification	
Applicant:	Ningbo Fulman Communication Technology Co., Ltd
Address:	No.98 Yuanzhong Road, Xiangshan Economic Development Zone, Ningbo, Zhejiang Province, China
Manufacturer:	Ningbo Fulman Communication Technology Co., Ltd
Address:	No.98 Yuanzhong Road, Xiangshan Economic Development Zone, Ningbo, Zhejiang Province, China
Product description	
Product name:	True Wireless Bluetooth Earbuds
Trademark:	VENTION
Model name:	NBJ
Series Model:	NBJB0, NBJW0, NBJG0, NBJL0, NBJP0, NBJY0, NBJM0
Standards:	FCC 47 CFR Part 15 Subpart C
Test method:	ANSI C63.10-2013
Date of Test	
Date of test:	2023-05-26 ~ 2023-06-02
Test result:	Pass

Test Engineer :



(Maleah Deng)

Reviewed By :



(Leon Chen)

Approved By :



(Tom Xue)

1 General Description

1.1 Description of the EUT

Product name:	True Wireless Bluetooth Earbuds
Model name:	NBJ
Series Model:	NBJB0, NBJW0, NBJG0, NBJL0, NBJP0, NBJY0, NBJM0
Model difference:	All the models are the same circuit and module, except the model name and color and Earphone left and right ear pcb layout.
Product color:	The product comes in multiple colors: black, white, green, blue, pink, yellow, gray.
Electrical rating:	Input: Earphone: DC 5V/50mA Charging case: DC 5V/220mA Battery: Earphone: DC 3.6V 50mAh 0.18Wh Charging box: DC 3.7V 320mAh 1.184Wh
Hardware version:	V1.1
Software version:	V1.2
Accessories:	Cable: USB-A to Type-C cable (0.3m)
Test sample(s) number:	MTi230505009-05S1001
RF specification:	
Bluetooth version:	V5.3
Operation frequency:	2402MHz - 2480MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK
Antenna(s) information:	Antenna type: FPC antenna Antenna gain: Left: 0.00 dBi; Right: 0.10 dBi
Maximum conducted output power:	2.17 dBm

1.2 Description of test modes

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	-	-

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Mode	Test Software	FCC Assist 1.0.2.2		
	Channel	2402MHz	2441MHz	2480MHz
GFSK	Power setting	10	10	10
$\pi/4$ -DQPSK		10	10	10

Ant1: Right, Ant2: Left

The test software:



1.3 Test conditions

Environment of test site:

Temperature:	15°C~35°C
Humidity:	20 % RH ~ 75 % RH

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
/	/	/	/
Support cable list			
Description	Length (m)	From	To
/	/	/	/

2 Measurement uncertainty

Parameter	Measurement uncertainty
AC power line conducted emission (9 kHz~30 MHz)	± 2.5 dB
Occupied Bandwidth	± 3 %
Conducted RF output power	± 0.16 dB
Conducted spurious emissions	± 0.21 dB
Radiated emission (9 kHz ~ 30 MHz)	± 4.0 dB
Radiated emission (30 MHz~1 GHz)	± 4.2 dB
Radiated emission (above 1 GHz)	± 4.3 dB

Note: the measurement uncertainty is calculated and correspond to a factor $k = 2$ (which provide confidence levels of 95.45 %)

3 Summary of Test Result

No.	FCC reference	Description of test	Result
1	§ 15.203	Antenna requirement	Pass
2	§ 15.207	AC power line conducted emissions	N/A
3	§ 15.247(d), 15.209, 15.205	Radiated spurious emissions	Pass
4	§ 15.247(a)(1)	20dB emission bandwidth	Pass
5	§ 15.247(b)(1)	Maximum conducted output power	Pass
6	§ 15.247(a)(1)	Carrier Frequencies Separation	Pass
7	§ 15.247(a)(1)	Time of occupancy	Pass
8	§ 15.247(a)(1)	Number of hopping channels	Pass
9	§ 15.247(d)	Band edge (Conducted)	Pass
10	§ 15.247(d)	Conducted spurious emissions	Pass

Notes:

N/A means not applicable.

Since the EUT cannot be operating while charging, therefore AC power line conducted emissions test is not required.

4 Test Laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

5 Equipment List

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTi-E002	EMI Test Receiver	R&S	ESCI3	101368	2023/04/26	2024/04/25
MTi-E023	Artificial power network	Schwarzbeck	NSLK8127	NSLK8127#841	2023/05/05	2024/05/04
MTi-E025	Artificial power network	Schwarzbeck	NSLK8127	8127183	2023/05/05	2024/05/04
MTi-E043	EMI test receiver	R&S	ESCI7	101166	2023/04/26	2024/04/25
MTi-E046	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00044	2021/05/30	2024/05/29
MTi-E044	Broadband antenna	Schwarzbeck	VULB9163	9163-1338	2021/05/30	2024/05/29
MTi-E045	Horn antenna	Schwarzbeck	BBHA9120D	9120D-2278	2021/05/30	2024/05/29
MTi-E047	Pre-amplifier	Hewlett-Packard	8447F	3113A06184	2023/04/26	2024/04/25
MTi-E048	Pre-amplifier	Agilent	8449B	3008A01120	2023/05/05	2024/05/04
MTi-E120	Broadband antenna	Schwarzbeck	VULB9163	9163-1419	2021/05/30	2024/05/29
MTi-E121	Pre-amplifier	Hewlett-Packard	8447D	2944A09365	2023/05/05	2024/05/04
MTi-E123	Pre-amplifier	Agilent	8449B	3008A04723	2023/05/05	2024/05/04
MTi-E135	Horn antenna	Schwarzbeck	BBHA 9170	00987	2021/05/30	2024/05/29
MTi-E136	Pre-amplifier	Space-Dtronics	EWLAN1840G-G45	210405001	2023/05/05	2024/05/04
MTi-E062	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2023/04/26	2024/04/25
MTi-E067	RF Control Unit	Tonscend	JS0806-1	19D8060152	2023/04/26	2024/04/25
MTi-E068	RF Control Unit	Tonscend	JS0806-2	19D8060153	2023/04/26	2024/04/25
MTi-E069	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2023/05/05	2024/05/04
MTi-E010S	EMI Measurement Software	Farad	EZ-EMC Ver. EMEC-3A1	/	/	/
MTi-E014S	RF Test System	Tonscend	TS@JS1120 V2.6.88.0330	/	/	/

Note: the calibration interval of the test equipment is 12 or 24 months and the calibrations are traceable to international system unit(SI)

6 Test Result

6.1 Antenna requirement

§ 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Description of the antenna of EUT

The antenna of the EUT is permanently attached.

There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of § 15.203.

6.2 AC power line conducted emissions

6.2.1 Limits


Frequency (MHz)	Detector type / Bandwidth	Limit-Quasi-peak dB μ V	Limit-Average dB μ V
0.15 -0.5	Average / 9 kHz	66 to 56	56 to 46
0.5 -5		56	46
5 -30		60	50

Note 1: the limit decreases with the logarithm of the frequency in the range of 0.15 MHz to 0.5 MHz.

6.2.2 Test Procedures

- Test method: ANSI C63.10-2013 Section 6.2.
- The EUT is connected to the main power through a line impedance stabilization network (LISN). All support equipment is powered from additional LISN(s).
- Emissions were measured on each current carrying line of the EUT using an EMI test receiver connected to the LISN powering the EUT.
- The test receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes described in Item 1.2.
- The test data of the worst-case condition(s) was recorded.

6.2.3 Test setup



For the actual test configuration, please refer to the related item – Photographs of the test setup.

6.2.4 Test Result

Notes:

Since the EUT cannot be operating while charging, therefore AC power line conducted emissions test is not required.

6.3 Radiated spurious emission

6.3.1 Limits

§ 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

§ 15.209 Radiated emission limits; general requirements.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note 1: the tighter limit applies at the band edges.

Note 2: the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector

§ 15.35 (b) requirements:

When average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, e.g., see §§ 15.250, 15.252, 15.253(d), 15.255, 15.256, and 15.509 through 15.519, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

According to ANSI C63.10-2013, the tests shall be performed in the frequency range shown in the following table:

Frequency range of measurements for unlicensed wireless device


Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

Frequency range of measurements for unlicensed wireless device with digital device


Highest frequency generated or used in the device or on which the device operates or tunes	Upper frequency range of measurement
Below 1.705 MHz	30 MHz
1.705 MHz to 108 MHz	1000 MHz
108 MHz to 500 MHz	2000 MHz
500 MHz to 1000 MHz	5000 MHz
Above 1000 MHz	5th harmonic of the highest frequency or 40 GHz, whichever is lower

6.3.2 Test setup


Below 30MHz



30MHz~1GHz



Above 1GHz



For the actual test configuration, please refer to the related item – Photographs of the test setup.

6.3.3 Test procedure

- a) Test method: ANSI C63.10-2013 Section 6.3, 6.4, 6.5, 6.6, 6.10.
- b) The EUT is placed on an on-conducting table 0.8 meters above the ground plane for measurement below 1GHz, 1.5 meters above the ground plane for measurement above 1GHz.
- c) Emission below 18 GHz were measured at a 3 meters test distance, above 18 GHz were measured at 1-meter test distance with the application of a distance correction factor
- d) The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

KDB 558074 D01 15.247 Meas Guidance v05r02

The use of a duty cycle correction factor (DCCF) is permitted for calculating average radiated field strength emission levels for an FHSS device in 15.247. This DCCF can be applied when the unwanted emission limit is subject to an average field strength limit (e.g., within a Government Restricted band) and the conditions specified in Section 15.35(c) can be satisfied. The average radiated field strength is calculated by subtracting the DCCF from the maximum radiated field strength level as determined through measurement. The maximum radiated field strength level represents the worst-case (maximum amplitude) RMS measurement of the emission(s) during continuous transmission (i.e., not including any time intervals during which the transmitter is off or is transmitting at a reduced power level). It is also acceptable to apply the DCCF to a measurement performed with a peak detector instead of the specified RMS power averaging detector. Note that Section 15.35(c) specifies that the DCCF shall represent the worst-case (greatest duty cycle) over any 100 msec transmission period.

Test instrument setup

Frequency	Test receiver / Spectrum analyzer setting
9 kHz ~ 150 kHz	Quasi Peak / RBW: 200 Hz
150 kHz ~ 30 MHz	Quasi Peak / RBW: 9 kHz
30 MHz ~ 1 GHz	Quasi Peak / RBW: 120 kHz
Above 1 GHz	Peak / RBW: 1 MHz, VBW: 3MHz, Peak detector AVG / RBW: 1 MHz, VBW: 1/T, Peak detector

6.3.4 Test results

Notes:

The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.

All modes of operation of the EUT were investigated, and only the worst-case results are reported.

There were no emissions found below 30MHz within 20dB of the limit.


Calculation formula:

Measurement (dB μ V/m) = Reading Level (dB μ V) + Correct Factor (dB/m)

Over (dB) = Measurement (dB μ V/m) – Limit (dB μ V/m)

ANT 2: Left
Radiated emissions between 30MHz – 1GHz


Test mode:	TX 2DH5-2480	Polarization:	Horizontal
Power supply:	DC 3.7V	Test site:	RE chamber 2



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		51.8430	35.84	-5.02	30.82	40.00	-9.18	QP
2		119.0179	43.79	-10.08	33.71	43.50	-9.79	QP
3	*	143.8295	47.63	-10.71	36.92	43.50	-6.58	QP
4		167.8242	45.51	-9.77	35.74	43.50	-7.76	QP
5		264.7457	41.44	-5.98	35.46	46.00	-10.54	QP
6		420.5803	37.56	-3.77	33.79	46.00	-12.21	QP

Radiated emissions between 30MHz – 1GHz

Test mode:	TX 2DH5-2480	Polarization:	Vertical
Power supply:	DC 3.7V	Test site:	RE chamber 2



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		32.7486	35.19	-7.93	27.26	40.00	-12.74	QP
2	*	51.3005	38.61	-4.91	33.70	40.00	-6.30	QP
3		62.8708	34.55	-7.58	26.97	40.00	-13.03	QP
4		143.8295	40.68	-10.71	29.97	43.50	-13.53	QP
5		252.0627	35.21	-6.08	29.13	46.00	-16.87	QP
6		432.5457	33.95	-3.90	30.05	46.00	-15.95	QP

Radiated emissions 1 GHz ~ 25 GHz

Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
π/4-DQPSK - 2402 MHz TX mode							
4804	38.49	0.74	39.23	74.00	-34.77	Peak	V
4804	33.12	0.74	33.86	54.00	-20.14	AVG	V
7206	41.56	6.02	47.58	74.00	-26.42	Peak	V
7206	35.24	6.02	41.26	54.00	-12.74	AVG	V
9608	41.85	5.88	47.73	74.00	-26.27	Peak	V
9608	35.68	5.88	41.56	54.00	-12.44	AVG	V
4804	38.61	0.74	39.35	74.00	-34.65	Peak	H
4804	32.82	0.74	33.56	54.00	-20.44	AVG	H
7206	41.58	6.02	47.60	74.00	-26.40	Peak	H
7206	35.12	6.02	41.14	54.00	-12.86	AVG	H
9608	40.90	5.88	46.78	74.00	-27.22	Peak	H
9608	34.24	5.88	40.12	54.00	-13.88	AVG	H
π/4-DQPSK - 2441 MHz TX mode							
4882	40.21	1.05	41.26	74.00	-32.74	Peak	V
4882	34.93	1.05	35.98	54.00	-18.02	AVG	V
7323	40.47	5.94	46.41	74.00	-27.59	Peak	V
7323	34.27	5.94	40.21	54.00	-13.79	AVG	V
9764	41.01	6.55	47.56	74.00	-26.44	Peak	V
9764	35.03	6.55	41.58	54.00	-12.42	AVG	V
4882	40.08	1.05	41.13	74.00	-32.87	Peak	H
4882	34.59	1.05	35.64	54.00	-18.36	AVG	H
7323	40.44	5.94	46.38	74.00	-27.62	Peak	H
7323	34.18	5.94	40.12	54.00	-13.88	AVG	H
9764	40.68	6.55	47.23	74.00	-26.77	Peak	H
9764	34.70	6.55	41.25	54.00	-12.75	AVG	H


Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
π/4-DQPSK - 2480 MHz TX mode							
4960	41.44	1.50	42.94	74.00	-31.06	Peak	V
4960	35.04	1.50	36.54	54.00	-17.46	AVG	V
7440	39.60	5.61	45.21	74.00	-28.79	Peak	V
7440	34.60	5.61	40.21	54.00	-13.79	AVG	V
9920	40.64	6.10	46.74	74.00	-27.26	Peak	V
9920	35.11	6.10	41.21	54.00	-12.79	AVG	V
4960	43.44	1.50	44.94	74.00	-29.06	Peak	H
4960	36.96	1.50	38.46	54.00	-15.54	AVG	H
7440	40.55	5.61	46.16	74.00	-27.84	Peak	H
7440	34.67	5.61	40.28	54.00	-13.72	AVG	H
9920	41.10	6.10	47.20	74.00	-26.80	Peak	H
9920	35.88	6.10	41.98	54.00	-12.02	AVG	H

Radiated emissions at band edge

Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
π/4-DQPSK – Low band-edge							
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
2310	46.42	-8.08	38.34	74.00	-35.66	Peak	V
2310	37.32	-8.08	29.24	54.00	-24.76	AVG	V
2390	46.81	-7.71	39.10	74.00	-34.90	Peak	V
2390	37.63	-7.71	29.92	54.00	-24.08	AVG	V
2310	46.89	-8.08	38.81	74.00	-35.19	Peak	H
2310	37.52	-8.08	29.44	54.00	-24.56	AVG	H
2390	47.61	-7.71	39.90	74.00	-34.10	Peak	H
2390	37.60	-7.71	29.89	54.00	-24.11	AVG	H
π/4-DQPSK – High band-edge							
2483.5	48.46	-7.24	41.22	74.00	-32.78	Peak	V
2483.5	37.76	-7.24	30.52	54.00	-23.48	AVG	V
2500	47.61	-7.17	40.44	74.00	-33.56	Peak	V
2500	37.97	-7.17	30.80	54.00	-23.20	AVG	V
2483.5	46.85	-7.24	39.61	74.00	-34.39	Peak	H
2483.5	38.22	-7.24	30.98	54.00	-23.02	AVG	H
2500	48.01	-7.17	40.84	74.00	-33.16	Peak	H
2500	37.98	-7.17	30.81	54.00	-23.19	AVG	H

ANT 1: Right
Radiated emissions between 30MHz – 1GHz


Test mode:	TX 2DH5-2480	Polarization:	Horizontal
Power supply:	DC 3.7V	Test site:	RE chamber 2



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		53.1313	31.52	-5.29	26.23	40.00	-13.77	QP
2		124.5690	44.10	-10.50	33.60	43.50	-9.90	QP
3	*	143.8295	45.41	-10.71	34.70	43.50	-8.80	QP
4		199.2855	42.68	-8.30	34.38	43.50	-9.12	QP
5		287.9904	38.94	-6.07	32.87	46.00	-13.13	QP
6		408.9460	34.17	-3.77	30.40	46.00	-15.60	QP

Radiated emissions between 30MHz – 1GHz

Test mode:	TX 2DH5-2480	Polarization:	Vertical
Power supply:	DC 3.7V	Test site:	RE chamber 2



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	51.3005	35.92	-4.90	31.02	40.00	-8.98	QP
2		62.4314	34.04	-7.45	26.59	40.00	-13.41	QP
3		72.0843	35.54	-10.08	25.46	40.00	-14.54	QP
4		119.8556	36.15	-10.20	25.95	43.50	-17.55	QP
5		143.8295	39.15	-10.71	28.44	43.50	-15.06	QP
6		242.5253	32.10	-6.42	25.68	46.00	-20.32	QP

Radiated emissions 1 GHz ~ 25 GHz

Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
π/4-DQPSK - 2402 MHz TX mode							
4804	40.84	0.74	41.58	74.00	-32.42	Peak	V
4804	34.90	0.74	35.64	54.00	-18.36	AVG	V
7206	40.97	6.02	46.99	74.00	-27.01	Peak	V
7206	34.10	6.02	40.12	54.00	-13.88	AVG	V
9608	41.23	5.88	47.11	74.00	-26.89	Peak	V
9608	35.96	5.88	41.84	54.00	-12.16	AVG	V
4804	41.87	0.74	42.61	74.00	-31.39	Peak	H
4804	35.80	0.74	36.54	54.00	-17.46	AVG	H
7206	40.17	6.02	46.19	74.00	-27.81	Peak	H
7206	35.00	6.02	41.02	54.00	-12.98	AVG	H
9608	40.71	5.88	46.59	74.00	-27.41	Peak	H
9608	34.33	5.88	40.21	54.00	-13.79	AVG	H
π/4-DQPSK - 2441 MHz TX mode							
4882	40.82	1.05	41.87	74.00	-32.13	Peak	V
4882	34.63	1.05	35.68	54.00	-18.32	AVG	V
7323	40.70	5.94	46.64	74.00	-27.36	Peak	V
7323	34.18	5.94	40.12	54.00	-13.88	AVG	V
9764	41.21	6.55	47.76	74.00	-26.24	Peak	V
9764	34.43	6.55	40.98	54.00	-13.02	AVG	V
4882	40.76	1.05	41.81	74.00	-32.19	Peak	H
4882	35.49	1.05	36.54	54.00	-17.46	AVG	H
7323	40.55	5.94	46.49	74.00	-27.51	Peak	H
7323	34.27	5.94	40.21	54.00	-13.79	AVG	H
9764	40.19	6.55	46.74	74.00	-27.26	Peak	H
9764	33.56	6.55	40.11	54.00	-13.89	AVG	H

Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	Peak/AVG	H/V
π/4-DQPSK - 2480 MHz TX mode							
4960	43.40	1.50	44.90	74.00	-29.10	Peak	V
4960	37.44	1.50	38.94	54.00	-15.06	AVG	V
7440	39.52	5.61	45.13	74.00	-28.87	Peak	V
7440	33.93	5.61	39.54	54.00	-14.46	AVG	V
9920	40.88	6.10	46.98	74.00	-27.02	Peak	V
9920	33.74	6.10	39.84	54.00	-14.16	AVG	V
4960	40.35	1.50	41.85	74.00	-32.15	Peak	H
4960	33.71	1.50	35.21	54.00	-18.79	AVG	H
7440	39.59	5.61	45.20	74.00	-28.80	Peak	H
7440	34.07	5.61	39.68	54.00	-14.32	AVG	H
9920	41.15	6.10	47.25	74.00	-26.75	Peak	H
9920	35.88	6.10	41.98	54.00	-12.02	AVG	H

Radiated emissions at band edge


Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector	Polarization
(MHz)	(dB μ V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)	Peak/AVG	H/V
$\pi/4$-DQPSK – Low band-edge							
(MHz)	(dB μ V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)	Peak/AVG	H/V
2310	46.97	-8.08	38.89	74.00	-35.11	Peak	V
2310	37.38	-8.08	29.30	54.00	-24.70	AVG	V
2390	48.58	-7.71	40.87	74.00	-33.13	Peak	V
2390	37.86	-7.71	30.15	54.00	-23.85	AVG	V
2310	46.79	-8.08	38.71	74.00	-35.29	Peak	H
2310	37.33	-8.08	29.25	54.00	-24.75	AVG	H
2390	47.78	-7.71	40.07	74.00	-33.93	Peak	H
2390	38.46	-7.71	30.75	54.00	-23.25	AVG	H
$\pi/4$-DQPSK – High band-edge							
2483.5	49.25	-7.24	42.01	74.00	-31.99	Peak	V
2483.5	39.84	-7.24	32.60	54.00	-21.40	AVG	V
2500	48.08	-7.17	40.91	74.00	-33.09	Peak	V
2500	38.08	-7.17	30.91	54.00	-23.09	AVG	V
2483.5	48.39	-7.24	41.15	74.00	-32.85	Peak	H
2483.5	38.95	-7.24	31.71	54.00	-22.29	AVG	H
2500	47.67	-7.17	40.50	74.00	-33.50	Peak	H
2500	38.64	-7.17	31.47	54.00	-22.53	AVG	H

6.4 20dB emission bandwidth

6.4.1 Limits

None, for reporting purposes only.

6.4.2 Test setup



6.4.3 Test procedures

Test method: ANSI C63.10-2013 Section 6.9.2

6.4.4 Test results


Note: See the Appendix A

6.5 Maximum conducted output power

6.5.1 Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

6.5.2 Test setup



6.5.3 Test procedure

Test method: ANSI C63.10-2013 Section 7.8.5

6.5.4 Test results

Note: see the Appendix B


6.6 Carrier frequency separation

6.6.1 Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater

6.6.2 Test setup



6.6.3 Test procedure

Test method: ANSI C63.10-2013 Section 7.8.2

6.6.4 Test results


Note: see the Appendix C

6.7 Time of occupancy

6.7.1 Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

6.7.2 Test setup



6.7.3 Test procedure

Test method: ANSI C63.10-2013 Section 7.8.4

6.7.4 Test results


Note: see the Appendix D

6.8 Number of hopping channels

6.8.1 Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

6.8.2 Test setup



6.8.3 Test procedure

Test method: ANSI C63.10-2013 Section 7.8.3

6.8.4 Test results


Note: see the Appendix E

6.9 Band edge (Conducted)

6.9.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.9.2 Test setup



6.9.3 Test procedure

Test method: ANSI C63.10-2013 Section 6.10.4

6.9.4 Test results


Note: see the Appendix F

6.10 Conducted spurious emissions

6.10.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.10.2 Test setup



6.10.3 Test procedure

Test method: ANSI C63.10-2013 Section 7.8.8

6.10.4 Test results

Note: See the Appendix G

APPENDIX A: 20DB EMISSION BANDWIDTH

Test Result

Test Mode	Antenna	Frequency [MHz]	20db EBW [MHz]
DH5	Ant1	2402	1.011
	Ant2	2402	1.026
	Ant1	2441	1.023
	Ant2	2441	0.999
	Ant1	2480	1.035
	Ant2	2480	0.999
2DH5	Ant1	2402	1.296
	Ant2	2402	1.341
	Ant1	2441	1.338
	Ant2	2441	1.284
	Ant1	2480	1.293
	Ant2	2480	1.287

Test Graphs

DH5_Ant1_2402



DH5_Ant2_2402



DH5_Ant1_2441



DH5_Ant2_2441



DH5_Ant1_2480



DH5_Ant2_2480



2DH5_Ant1_2402



2DH5_Ant2_2402



2DH5_Ant1_2441



2DH5_Ant2_2441



2DH5_Ant1_2480



2DH5_Ant2_2480



APPENDIX B: MAXIMUM CONDUCTED OUTPUT POWER

Test Result Peak

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	1.39	≤20.97	PASS
	Ant2	2402	0.8	≤20.97	PASS
	Ant1	2441	0.67	≤20.97	PASS
	Ant2	2441	0.19	≤20.97	PASS
	Ant1	2480	0.54	≤20.97	PASS
	Ant2	2480	0.23	≤20.97	PASS
2DH5	Ant1	2402	2.17	≤20.97	PASS
	Ant2	2402	1.6	≤20.97	PASS
	Ant1	2441	1.42	≤20.97	PASS
	Ant2	2441	0.92	≤20.97	PASS
	Ant1	2480	1.29	≤20.97	PASS
	Ant2	2480	1.03	≤20.97	PASS

Test Graphs

DH5_Ant1_2402



DH5_Ant2_2402




DH5_Ant1_2441



DH5_Ant2_2441



DH5_Ant1_2480




DH5_Ant2_2480



2DH5_Ant1_2402



2DH5_Ant2_2402




2DH5_Ant1_2441



2DH5_Ant2_2441



2DH5_Ant1_2480



2DH5_Ant2_2480



APPENDIX C: CARRIER FREQUENCY SEPARATION

Test Result

Test Mode	Antenna	Frequency [MHz]	Result [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	1.002	≥ 0.690	PASS
	Ant2	Hop	0.998	≥ 0.690	PASS
2DH5	Ant1	Hop	1.002	≥ 0.892	PASS
	Ant2	Hop	1	≥ 0.892	PASS

Test Graphs

DH5_Ant1_Hop



DH5_Ant2_Hop



2DH5_Ant1_Hop



2DH5_Ant2_Hop



APPENDIX D: TIME OF OCCUPANCY

Test Result



Test Mode	Antenna	Frequency [MHz]	BurstWidth [ms]	Hops in 31.6s [Num]	Result [s]	Limit [s]	Verdict
DH1	Ant1	Hop	0.383	316	0.121	≤0.4	PASS
	Ant2	Hop	0.381	317	0.121	≤0.4	PASS
DH3	Ant1	Hop	1.638	166	0.272	≤0.4	PASS
	Ant2	Hop	1.638	159	0.26	≤0.4	PASS
DH5	Ant1	Hop	2.885	114	0.329	≤0.4	PASS
	Ant2	Hop	2.885	108	0.312	≤0.4	PASS
2DH1	Ant1	Hop	0.391	315	0.123	≤0.4	PASS
	Ant2	Hop	0.391	319	0.125	≤0.4	PASS
2DH3	Ant1	Hop	1.643	153	0.251	≤0.4	PASS
	Ant2	Hop	1.643	158	0.26	≤0.4	PASS
2DH5	Ant1	Hop	2.891	110	0.318	≤0.4	PASS
	Ant2	Hop	2.891	100	0.289	≤0.4	PASS

Notes:


1. Period time = $0.4s * 79 = 31.6s$
2. Result (Time of occupancy) = $BurstWidth[ms] * Hops\ in\ 31.6s\ [Num]$


Test Graphs

DH1_Ant1_Hop




DH1_Ant2_Hop






DH3_Ant1_Hop




DH3_Ant2_Hop




DH5_Ant1_Hop







DH5_Ant2_Hop




2DH1_Ant1_Hop





2DH1_Ant2_Hop








2DH3_Ant1_Hop




2DH3_Ant2_Hop



2DH5 Ant1_Hop






APPENDIX E: NUMBER OF HOPPING CHANNELS

Test Result


Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
	Ant2	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS
	Ant2	Hop	79	≥ 15	PASS

Test Graphs

DH5_Ant1_Hop




DH5_Ant2_Hop



2DH5_Ant1_Hop



2DH5_Ant2_Hop



APPENDIX F: BAND EDGE MEASUREMENTS

Test Graphs

