



FCC TEST REPORT

FCC ID: 2A7ZC-FC2

On Behalf of

GEOMATE POSITIONING PTE. LTD.

Handheld GNSS Data Collector

Model No.: FC2

Prepared for : GEOMATE POSITIONING PTE. LTD.
Address : 808 FRENCH ROAD #04-167 KITCHENER COMPLEX SINGAPORE
(200808)

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2312102-C01-R01
Date of Receipt : December 25, 2023
Date of Test : December 25, 2023 - June 20, 2024
Date of Report : June 20, 2024
Version Number : V0
Test Result : Pass

TABLE OF CONTENTS

Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	6
1.1. Description of Standards and Results	6
2. GENERAL INFORMATION	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List	10
3. MAXIMUM PEAK OUTPUT POWER	11
3.1. Limit	11
3.2. Test Procedure	11
3.3. Test Setup	11
3.4. Test Result	11
4. BANDWIDTH	12
4.1. Limit	12
4.2. Test Procedure	12
4.3. Test Result	12
5. CARRIER FREQUENCY SEPARATION	23
5.1. Limit	23
5.2. Test Procedure	23
5.3. Test Result	23
6. NUMBER OF HOPPING CHANNEL	25
6.1. Limit	25
6.2. Test Procedure	25
6.3. Test Result	25
7. DWELL TIME	27
7.1. Test limit	27
7.2. Test Procedure	27
7.3. Test Result	27
8. RADIATED EMISSIONS	37
8.1. Limit	37
8.2. Block Diagram of Test setup	38
8.3. Test Procedure	39
8.4. Test Result	39
9. BAND EDGE COMPLIANCE	54
9.1. Block Diagram of Test Setup	54
9.2. Limit	54
9.3. Test Procedure	54
9.4. Test Result	54
10. POWER LINE CONDUCTED EMISSIONS	70
10.1. Block Diagram of Test Setup	70
10.2. Limit	70
10.3. Test Procedure	70

10.4. Test Result-----	70
11. ANTENNA REQUIREMENTS-----	73
11.1. Limit-----	73
11.2. Result -----	73
12. TEST SETUP PHOTO-----	74
12.1. Photo of Radiated Emission test-----	74
12.2. Photo of Conducted Emission test -----	75

TEST REPORT DECLARATION

Applicant : GEOMATE POSITIONING PTE. LTD.
Address : 808 FRENCH ROAD #04-167 KITCHENER COMPLEX SINGAPORE (200808)
Manufacturer : GEOMATE POSITIONING PTE. LTD.
Address : 808 FRENCH ROAD #04-167 KITCHENER COMPLEX SINGAPORE (200808)
EUT Description : Handheld GNSS Data Collector
(A) Model No. FC2
(B) Trademark 

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Yannis Wen
Project Engineer



Approved by (name + signature).....: Jack Xu
Project Manager



Date of issue.....: June 20, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	June 20, 2024	Initial released Issue	Yannis Wen

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	P
Antenna requirement	FCC Part 15: 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.		

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description : Handheld GNSS Data Collector

Model Number : FC2

Diff : N/A

Power supply : DC 5V from adapter, DC 3.8V from battery.

Radio Technology : Bluetooth EDR

Operation frequency : 2402-2480MHz

Channel No. : 79 Channels

Channel spacing : 1MHz

Modulation type : GFSK, $\pi/4$ DQPSK, 8DPSK

Antenna Type : Internal Antenna, max gain -4.64dBi
(Antenna information is provided by applicant.)

Coaxial cable loss : Max. coaxial cable loss:0.5dB
(Cable lossvalue is provided by applicant.)

Software version : V1.0

Hardware version : V1.0

Intend use : Residential, commercial and light industrial environment
environment


2.2. Accessories of Device (EUT)

Accessories : AC Adapter
 Manufacturer : EDAC POWER Electronics Co., Ltd
 Model : EA1012AVRU-050
 Ratings : Input: 100-240Vac~50/60Hz 1.0A
 Output: 5.0V=2.4A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
1.	Notebook PC	Lenovo	ThinkPad E14	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Tested mode, channel information		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
$\pi/4$ DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
8DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	24℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

September 15, 2019 Certificated by IC

Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2℃
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2023.08.16	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2023.08.16	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-10 2082-Wa	2023.08.16	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2023.08.16	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2023.08.28	1Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2023.08.19	1Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00128	2023.08.19	1Year
RF Cable	Resenberger	Cable 1	/	RE1	2023.08.16	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2023.08.16	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2023.08.16	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2023.08.16	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2023.08.16	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2023.08.16	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2023.08.16	1Year
Horn Antenna	SCHWARZBECK	BBHA 9170	/	00946	2023.08.19	1Year
Preamplifier	SKET	LNPA_1840 -50	/	SK2018101801	2023.08.16	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2023.08.16	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2023.08.16	1 Year
Temp. & Humid. Chamber	Teelong	TL-HW408S	/	TL-20191205-01	2023.07.25	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2023.08.16	1 Year
Adjustable attenuator	MWRFTest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	Farad	Alpha-3A1
CE	EZ-EMC	Farad	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit


Please refer section 15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Mode	Freq(MHz)	Conducted Power (dBm)	Limit(dBm)	Result
GFSK	2402	3.782	30	Pass
	2441	-0.07	30	Pass
	2480	-1.784	30	Pass
$\pi/4$ DQPSK	2402	3.003	21	Pass
	2441	-1.007	21	Pass
	2480	-2.735	21	Pass
8DPSK	2402	2.952	21	Pass
	2441	-0.749	21	Pass
	2480	-2.538	21	Pass

4. BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure


The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

-20dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)
NVNT	1-DH1	2402	Ant1	0.764
NVNT	1-DH1	2441	Ant1	0.752
NVNT	1-DH1	2480	Ant1	0.828
NVNT	2-DH1	2402	Ant1	1.210
NVNT	2-DH1	2441	Ant1	1.222
NVNT	2-DH1	2480	Ant1	1.230
NVNT	3-DH1	2402	Ant1	1.212
NVNT	3-DH1	2441	Ant1	1.214
NVNT	3-DH1	2480	Ant1	1.214

-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1




Date: 12.MAR.2024 17:12:41

-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1




Date: 12.MAR.2024 17:19:45

-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1




Date: 12.MAR.2024 17:23:16

-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1




Date: 12.MAR.2024 18:38:32

-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1




Date: 12.MAR.2024 18:40:22

-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1




Date: 12.MAR.2024 18:41:45

-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1




Date: 12.MAR.2024 18:55:38

-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1



Date: 12.MAR.2024 18:57:51

-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1




Date: 12.MAR.2024 18:59:29

Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.719
NVNT	1-DH1	2441	Ant1	0.729
NVNT	1-DH1	2480	Ant1	0.723
NVNT	2-DH1	2402	Ant1	1.141
NVNT	2-DH1	2441	Ant1	1.095
NVNT	2-DH1	2480	Ant1	1.117
NVNT	3-DH1	2402	Ant1	1.121
NVNT	3-DH1	2441	Ant1	1.123
NVNT	3-DH1	2480	Ant1	1.121

OBW NVNT 1-DH1 2402MHz Ant1




Date: 12.MAR.2024 17:12:33

OBW NVNT 1-DH1 2441MHz Ant1




Date: 12.MAR.2024 17:19:36

OBW NVNT 1-DH1 2480MHz Ant1




Date: 12.MAR.2024 17:23:07

OBW NVNT 2-DH1 2402MHz Ant1




Date: 12.MAR.2024 18:38:20

OBW NVNT 2-DH1 2441MHz Ant1




Date: 12.MAR.2024 18:40:10

OBW NVNT 2-DH1 2480MHz Ant1




Date: 12.MAR.2024 18:41:33

OBW NVNT 3-DH1 2402MHz Ant1




Date: 12.MAR.2024 18:55:24

OBW NVNT 3-DH1 2441MHz Ant1



Date: 12.MAR.2024 18:57:37

OBW NVNT 3-DH1 2480MHz Ant1



Date: 12.MAR.2024 18:59:15

5. CARRIER FREQUENCY SEPARATION

5.1. Limit


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure


The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2440.832	2441.832	1	0.752	Pass
NVNT	2-DH1	Ant1	2440.832	2441.83	0.998	0.807	Pass
NVNT	3-DH1	Ant1	2440.83	2441.832	1.002	0.808	Pass




CFS NVNT 2-DH1 2441MHz Ant1



Date: 12.MAR.2024 17:58:23

CFS NVNT 3-DH1 2441MHz Ant1



Date: 12.MAR.2024 18:51:46

6. NUMBER OF HOPPING CHANNEL

6.1. Limit


Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW.


6.3. Test Result

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH1	Ant1	79	15	Pass
NVNT	2-DH1	Ant1	79	15	Pass
NVNT	3-DH1	Ant1	79	15	Pass




Date: 12.MAR.2024 17:44:35

Hopping No. NVNT 2-DH1 2441MHz Ant1



Date: 12.MAR.2024 18:01:53

Hopping No. NVNT 3-DH1 2441MHz Ant1



Date: 12.MAR.2024 18:52:36

7. DWELL TIME

7.1. Test limit

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz.

The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span = 0Hz, Sweep = auto.


7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.378	120.204	318	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.632	257.856	158	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.881	299.624	104	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.384	120.192	313	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.635	258.33	158	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.884	291.284	101	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.385	122.045	317	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.635	258.33	158	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.887	288.7	100	31600	400	Pass


Note: Total Dwell Time= Pulse Time* Burst Count

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Date: 12.MAR.2024 17:44:45

Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 17:45:19

Dwell NVNT 1-DH3 2441MHz Ant1 One Burst




Date: 12.MAR.2024 17:52:10

Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 17:52:45

Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Date: 12.MAR.2024 17:53:44

Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 17:54:18

Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Date: 12.MAR.2024 18:02:04

Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 18:02:39

Dwell NVNT 2-DH3 2441MHz Ant1 One Burst




Date: 12.MAR.2024 18:46:16

Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 18:46:51

Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Date: 12.MAR.2024 18:45:07

Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 18:45:42

Dwell NVNT 3-DH1 2441MHz Ant1 One Burst




Date: 12.MAR.2024 18:52:50

Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 18:53:26

Dwell NVNT 3-DH3 2441MHz Ant1 One Burst




Date: 12.MAR.2024 19:01:40

Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated




Date: 12.MAR.2024 19:02:14

Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Date: 12.MAR.2024 19:02:47

Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



Date: 12.MAR.2024 19:03:21

8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

8.2. Block Diagram of Test setup


8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result


We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS


Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		34.1281	16.53	13.70	30.23	40.00	-9.77	peak
2		57.1380	16.72	13.41	30.13	40.00	-9.87	peak
3	*	137.1795	20.88	14.11	34.99	43.50	-8.51	peak
4		144.8078	20.32	14.67	34.99	43.50	-8.51	peak
5		204.9551	19.68	10.98	30.66	43.50	-12.84	peak
6		241.0557	18.46	12.57	31.03	46.00	-14.97	peak

Note: 1. *: Maximum data; x: Over limit; !: over margin.

2. Measurement = Reading Level + Correct Factor; Correct Factor = Antenna Factor + Cable Loss.

Horizontal:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		57.5065	12.09	13.41	25.50	40.00	-14.50	peak
2		145.0790	13.97	14.69	28.66	43.50	-14.84	peak
3	*	205.6751	21.92	11.00	32.92	43.50	-10.58	peak
4		249.9796	17.52	12.77	30.29	46.00	-15.71	peak
5		452.7197	12.58	17.59	30.17	46.00	-15.83	peak
6		674.3404	11.59	21.38	32.97	46.00	-13.03	peak

Note: 1. *: Maximum data; x: Over limit; !: over margin.

2. Measurement = Reading Level + Correct Factor; Correct Factor = Antenna Factor + Cable Loss.

Remark: 1. All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz was listed in this report.

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	47.47	V	33.95	10.18	34.26	57.34	74	-16.66	PK
4804	35.56	V	33.95	10.18	34.26	45.43	54	-8.57	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	44.84	H	33.95	10.18	34.26	54.71	74	-19.29	PK
4804	35.09	H	33.95	10.18	34.26	44.96	54	-9.04	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	44.03	V	33.93	10.2	34.29	53.87	74	-20.13	PK
4882	33.26	V	33.93	10.2	34.29	43.10	54	-10.90	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	43.22	H	33.93	10.2	34.29	53.06	74	-20.94	PK
4882	33.77	H	33.93	10.2	34.29	43.61	54	-10.39	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	43.90	V	33.93	10.2	34.29	53.74	74	-20.26	PK
4960	36.48	V	33.93	10.2	34.29	46.32	54	-7.68	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	45.08	H	33.93	10.2	34.29	54.92	74	-19.08	PK
4960	33.62	H	33.93	10.2	34.29	43.46	54	-10.54	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


Conducted RF Spurious Emission

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref




Date: 12.MAR.2024 17:13:04

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission




Date: 12.MAR.2024 17:14:52

Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref




Date: 12.MAR.2024 17:19:55

Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission




Date: 12.MAR.2024 17:20:09

Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref




Date: 12.MAR.2024 17:23:42

Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission




Date: 12.MAR.2024 17:23:55

Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref




Date: 12.MAR.2024 18:39:01

Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission




Date: 12.MAR.2024 18:39:15

Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref




Date: 12.MAR.2024 18:40:36

Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission




Date: 12.MAR.2024 18:40:50

Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref




Date: 12.MAR.2024 18:42:15

Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission




Date: 12.MAR.2024 18:42:29

Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Ref



Date: 12.MAR.2024 18:56:12

Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission



Date: 12.MAR.2024 18:56:25