

RF Test Data for Bluetooth LE (Conducted Measurements)



General Description of EUT	
Product Name:	Allegro X8
Test Model:	Allegro X8
Sample ID:	202206-0362-06#
Environmental Conditions	
Temperature:	25°C
Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ
Test Engineer:	Huang jian ping
Note: For a more detailed features description, please refer to the report TBR-C-202206-0362-121	


Contents

1. Duty Cycle.....	3
2. Maximum Conducted Output Power	6
3. -6dB Bandwidth	9
4. Occupied Channel Bandwidth	12
5. Maximum Power Spectral Density Level.....	15
6. Band Edge	18
7. Conducted RF Spurious Emission	21
8. Restrict Band	25

1. Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1Mbps	2402	Ant1	86.8	0.61	0.46
NVNT	BLE 1Mbps	2440	Ant1	86.89	0.61	0.46
NVNT	BLE 1Mbps	2480	Ant1	87.2	0.59	0.46






2. Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	1.351	30	Pass
NVNT	BLE 1Mbps	2440	Ant1	1.022	30	Pass
NVNT	BLE 1Mbps	2480	Ant1	0.172	30	Pass


Test Graphs

Power NVNT BLE 1Mbps 2402MHz Ant1



Power NVNT BLE 1Mbps 2440MHz Ant1






3. -6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	0.66	0.5	Pass
NVNT	BLE 1Mbps	2440	Ant1	0.65	0.5	Pass
NVNT	BLE 1Mbps	2480	Ant1	0.65	0.5	Pass


Test Graphs

-6dB Bandwidth NVNT BLE 1Mbps 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1Mbps 2440MHz Ant1






4. Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1Mbps	2402	Ant1	1.03
NVNT	BLE 1Mbps	2440	Ant1	1.029
NVNT	BLE 1Mbps	2480	Ant1	1.028


Test Graphs

OBW NVNT BLE 1Mbps 2402MHz Ant1





OBW NVNT BLE 1Mbps 2440MHz Ant1






5. Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-14.709	8	Pass
NVNT	BLE 1Mbps	2440	Ant1	-15.009	8	Pass
NVNT	BLE 1Mbps	2480	Ant1	-15.924	8	Pass






6. Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-54.13	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-52.43	-20	Pass



Test Graphs

Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Ref



Band Edge NVNT BLE 1Mbps 2402MHz Ant1 Emission









7. Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	-39.75	-20	Pass
NVNT	BLE 1Mbps	2440	Ant1	-39.63	-20	Pass
NVNT	BLE 1Mbps	2480	Ant1	-40.5	-20	Pass









8. Restrict Band

Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1Mbps	2402	Ant1	2310	-46.78	2.3	50.78	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2310	-56.77	2.3	40.79	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2378.256	-43.26	2.3	54.3	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2377.968	-52.13	2.3	45.43	Average	54	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-46.45	2.3	51.11	Peak	74	Pass
NVNT	BLE 1Mbps	2402	Ant1	2390	-56.35	2.3	41.21	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-46.3	2.3	51.26	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2483.5	-55.92	2.3	41.64	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2485.48	-42.52	2.3	55.04	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2489.896	-52.63	2.3	44.93	Average	54	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-46.1	2.3	51.46	Peak	74	Pass
NVNT	BLE 1Mbps	2480	Ant1	2500	-56.17	2.3	41.39	Average	54	Pass



Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Peak



Restrict Band NVNT BLE 1Mbps 2480MHz Ant1 Average

