



■ Report No.: DDT-RE23070410-1E03

■ Issued Date: Oct. 27, 2023

FCC RF EXPOSURE REPORT

Applicant	:	JBU GLOBAL LLC
Address of Applicant	:	19416 NE 26th AVE, 114B, Miami, Florida 33180, United States
Manufacturer	:	SHENZHEN GXTSONIC TECHNOLOGY CO., LTD
Address of Manufacturer	:	1F, Building 3, Tianxin Shuichan Industrial Park, Gushu Village, Xixiang Town, Bao'an District, Shenzhen, CHINA
Equipment under Test	:	Animato S1
Model No.	:	Animato S1, CS-K15
Trade Mark	:	N/A
FCC ID	:	2A7ZM-ANIMATOS1
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE23070410-1E05
Issue Date	:	2023/10/27
Issue By	:	Gongdong Dongdian Testing Service Co., Ltd.
Address of Laboratory	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory.....	5
2.	RF Exposure evaluation for FCC.....	6

Test Report Declare

Applicant	:	JBU GLOBAL LLC
Address	:	19416 NE 26th AVE, 114B, Miami, Florida 33180, United States
Equipment under Test	:	Animato S1
Model No.	:	Animato S1, CS-K15
Trade Mark	:	N/A
Manufacturer	:	SHENZHEN GXTSONIC TECHNOLOGY CO., LTD
Address	:	1F,Building 3,Tianxin Shuichan Industrial Park,Gushu Village,Xixiang Town,Bao'an District,Shenzhen,CHINA

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Gongdong Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Gongdong Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-RE23070410-1E03		
Date of Receipt:	Aug. 16, 2023	Date of Test:	Aug. 16, 2023 ~ Oct. 27, 2023

Prepared By:

Tiger Mo

Tiger Mo/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Gongdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Oct. 27, 2023	

1. General Information

1.1. Description of equipment

EUT Name	: Animato S1
Model Number	: Animato S1, CS-K15
Difference of models	: Above models are identical in schematic and structure, only the Model Number is different for all the models, therefore the test performed on the model CS-K15.
EUT function description	: Please reference user manual of this device
Power Supply	: DC 5V - 1A (USB-C input) Rechargeable Lithium, 3000mAh for speaker
Operation frequency	: 2402 MHz - 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK
Antenna Type	: PCB antenna , maximum PK gain: -0.58 dBi Chip antenna , maximum PK gain: 2.7dBi
Sample Number	: S23070410-03

1.2. Assess laboratory

Gongdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Manufacturing Tolerance

BT Ant1:

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-3.82	-3.28	-2.32
Tolerance $\pm$ (dB)	2	2	2
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-3.13	-2.61	-1.69
Tolerance $\pm$ (dB)	2	2	2

Estimation Result

Worse case is as below: [2480 MHz, 0.31 dBm, (1.07 mW) output power]

$(1.07/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.34 < 3.0$ for 1-g SAR

BT Ant2:

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-7.06	-9.46	-5.29
Tolerance $\pm$ (dB)	2	2	2
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-6.70	-6.16	-5.47
Tolerance $\pm$ (dB)	2	2	2

Estimation Result

Worse case is as below: [2480 MHz, -3.29 dBm, (0.469 mW) output power]

$(0.469/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.15 < 3.0$ for 1-g SAR

BT Ant3:

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-7.14	-8.20	-5.74
Tolerance ±(dB)	2	2	2
π/4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-6.64	-7.67	-5.29
Tolerance ±(dB)	2	2	2

Estimtion Result

Worse case is as below: [2480 MHz, 3.29 dBm, (0.469 mW) output power]

$(0.469/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.15 < 3.0$ for 1-g SAR

The EUT support Ant1, Ant2, Ant3 simultaneous emission.

$0.34/3 + 0.15/3 + 0.15/3 = 0.21 < 1$

Then SAR evaluation is not required.

END OF REPORT