

# RF Exposure Evaluation Report

## 1 RF EXPOSURE

Product Name: Bendable wearable  
 Model No.: C6814  
 FCC ID: 2A833-C6814

## 2. RF Exposure Evaluation

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

### 2.1 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

### 2.2 EUT RF EXPOSURE EVALUATION

| Worst Mode:   |                       |                         |                       |       |                  |       |
|---------------|-----------------------|-------------------------|-----------------------|-------|------------------|-------|
| Channel (MHz) | Conducted Power (dBm) | Tune up Tolerance (dBm) | Maximum tune-up Power |       | Calculated value | Limit |
|               |                       |                         | (dBm)                 | (mW)  |                  |       |
| 433.92MHz     | -9.14                 | -9 $\pm$ 1              | -8.0                  | 0.158 | 0.021            | 3.0   |

dBm=dBuV/m -95.2, Fundamental field strength max is 86.06dBuV/m, so power is -9.14dBm

Calculated value is 0.155< 3.0, So there is no require SAR test.