

Testing Report

Customer Name: EC-LINK Automation (Shenzhen) Co. Ltd.


Product Name: Planar RFID antenna

Sample Model: Ha-VIS RF-ANT-LR20

Reference Standard: *GB/T 9410-2008; ANSI/IEEE Std 149-1979*

Issue Date: 2022.10.12

Engineer: Jackson	Date: 2022.10.12
Auditor: Eason	Date: 2022.10.12
Approver: Janson	Date: 2022.10.12



Version

Version No.	Date	Description	Formulate	Approval
A0	2022.10.12	For the first time, formulate	Jackson	Eason

Contents


1.General Information	3
1.1 General information of testing institutions	3
1.2 Testing principle	3
1.3 Test equipment	4
1.4 Test environment	4
1.5 Statement	4
2.Sample Information	5
2.1 Client information	5
2.2 Description of EUT(S)	5
2.3 Antenna size photo	6
2.4 DUT setup photo of free space OTA testing	6
3.Test Results	7
3.1 Test standard	7
3.2 Test uncertainty	7
3.3 Test data	8
3.3.1 Typical free space gain	8
3.3.2 Typical free space radiation pattern	8
(The following is blank)	9

1.General Information

1.1 General information of testing institutions

Name	Shenzhen RFI-LAB Communication Technology Co., Ltd.
Address	10/F A, Lingyun Bld, Liufang Road, Baoan District, Shenzhen
Tel	13631623357
E-mail	liss@tech-now.com
Equipment	All the equipment used in the report is fixed in Zone B, West Side of 1/F, Building 1, Tingwei Industrial Park, No.6 Liufang Road, Bao 'an District, Shenzhen

1.2 Testing principle



1.3 Test equipment

Equipment	Model No.	Serial No.	Manufacturer	Calibration date	Next calibration date
OTA Test System	RayZone-5000	RFI-LAB-RF-D00	GTS	2021.3.15	2023.3.14
Network Analyzer	E5071C	RFI-LAB-RF-D01	KEYSIGHT	2022.5.13	2023.5.12

1.4 Test environment

Temperature	24.2℃
Humidity	59%RH
Pressure	100.13kPa

1.5 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen RFI-LAB Communication Technology Co., Ltd. have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

2.Sample Information


2.1 Client information

Name	EC-LINK Automation (Shenzhen) Co. Ltd.
Address	Room 2206, Block B, Shixia Xintian Century Business Center, Futian District, Shenzhen City
Contacts	/
Tel	/
E-mail	/

2.2 Description of EUT(S)


Product Name	Planar RFID antenna
Sample Model	Ha-VIS RF-ANT-LR20
Size	/
Serial No.	/
Test Item	Gain; Radiation pattern
Frequency Range	840MHz-960MHz
Received Date	2022.10.12
Test Date	2022.10.12
Remark	/

2.3 Antenna size photo




2.4 DUT setup photo of free space OTA testing

Planform



Front view



3. Test Results

3.1 Test standard

Name	Parameter	Method	Standard no.
Mobile communication antenna	Antenna gain	Generic specification for antennas used in the mobile communications	GB/T 9410-2008
	Radiation pattern		
Antenna	Gain and directivity	IEEE Standard Test Procedures for Antennas	ANSI/IEEE Std 149-1979

3.2 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of $K=2$ and the 95% confidence level to express the extended uncertainty.

Item	Uncertainty
Antenna gain	$\pm 0.72\text{dB}$


3.3 Test data

3.3.1 Typical free space gain


Frequency/MHz	840	850	860	870	880	890	900	910	920	930	940	950	960
Peak Gain/dBi	-25.67	-26.11	-26.17	-26.01	-25.62	-25.02	-24.47	-24.17	-23.74	-22.69	-21.95	-23.89	-24.41

3.3.2 Typical free space radiation pattern


(1) X-Z Plane:




(2) Y-Z Plane:



(3) X-Y Plane:



(4) Typical Free Space 3D Radiation Pattern at 900MHz:



End

(The following is blank)