



RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{GHz}}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

f_{GHz} is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

For BT Left

Max EIRP Power(dBm)	Max EIRP Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
2.56	1.803	2480	5	0.567873	3.0

For BT Right

Max EIRP Power(dBm)	Max EIRP Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
2.79	1.901	2480	5	0.598740	3.0

So a SAR test is not required