

TEST REPORT

Applicant Name: Shenzhen Saiku Electronic Co., Ltd.
Address: 3F, Building C14, Fuyuan Industrial City, Jiuwei Community,
Hangcheng Street, Shenzhen, China
Report Number: 2501Y29066E-RF-00
FCC ID: 2A8DG-B2

Test Standard (s)

FCC Part 2.1091

Sample Description

Product Type: Pet Barrier Transmitter
Model No.: B2
Multiple Model(s) No.: N/A
Trade Mark: N/A
Date Received: 2025/11/21
Issue Date: 2025/12/05

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Bruce Lin

Bruce Lin
RF Engineer

Approved By:

Jimmy Xiao

Jimmy Xiao
EMC Manager

Note: The information marked * is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.
This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
LOCAL SUPPORT EQUIPMENT	6
EXTERNAL I/O CABLE.....	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	9
APPLICABLE STANDARD	9
BLOCK DIAGRAM OF TEST SETUP	9
TEST PROCEDURES.....	10
TEST DATA.....	10
EUT PHOTOGRAPHS	11
TEST SETUP PHOTOGRAPHS	12

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501Y29066E-RF-00	Original Report	2025/12/05

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Pet Barrier Transmitter
Tested Model	B2
Multiple Model(s)	N/A
Frequency Range	125kHz
Input Voltage	DC 3.7V from battery or DC 5V from USB
Sample serial number	3DA0-1 (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

Objective

This test report is in accordance with Part 2, Subpart J Section 2.1091 of the Federal Communications Commission's rules and KDB680106 D01 Wireless Power Transfer v04.

Test Methodology

All tests and measurements indicated in this document were performed in accordance KDB 680106 D01 Wireless Power Transfer v04

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter	Uncertainty
Electric Field	1.14dB
Magnetic Field	0.74dB
Temperature	±1 °C
Humidity	±1%
Supply voltages	±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

Each test item follows test standards and with no deviation.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode.

EUT Exercise Software

No software used in test.

Local Support Equipment

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§1.1310 & §2.1091	Maximum Permissible Exposure(MPE)	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
SPEAG	Probe	MAGPy-8H3D-E3D	3106	2025/04/29	2026/04/28
SPEAG	Data Acquisition System	MAPGPY-DAS	3089	2025/04/29	2026/04/28

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE)


(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According with 680106 D01 Wireless Power Transfer v04 clause 3.2

Accordingly, for § 2.1091-Mobile devices, the MPE limits between 100 kHz to 300 kHz are to be considered the same as those at 300 kHz in Table 1 of § 1.1310, that is, 614 V/m and 1.63 A/m, for the electric field and magnetic field, respectively. For § 2.1093-Portable devices below 4 MHz and down to 100 kHz, the MPE limits in § 1.1310 (with the 300 kHz limit applicable all the way down to 100 kHz) can be used for the purpose of equipment authorization in lieu of SAR evaluations.

Block Diagram of Test Setup



Test Procedures

- 1) Perform H-field and E-field measurements for each all sides of the EUT at 20cm, along all the principal axes defined with respect to the orientation of the transmitting element (e.g., coil or antenna).
- 2) The highest emission level was recorded and compared with limit.
- 3) The EUT was measured according to 680106 D01 Wireless Power Transfer v04.

Test Data

Environmental Conditions

Temperature:	25.8 °C
Relative Humidity:	45 %
ATM Pressure:	100.9 kPa

The testing was performed by Rainbow Zhu on 2025-12-01.

Test mode: Transmitting

H-Field Strength

Test Frequency (kHz)	Position A (A/m)	Position B (A/m)	Position C (A/m)	Position D (A/m)	Position E (A/m)	Position F (A/m)	Limit (A/m)
125	0.28	0.18	0.40	0.37	0.29	0.30	1.63

Note: Test with 20cm distance from the center of the probe(s) to the edge of the device.

E-Field Strength

Test Frequency (kHz)	Position A (V/m)	Position B (V/m)	Position C (V/m)	Position D (V/m)	Position E (V/m)	Position F (V/m)	Limit (V/m)
125	1.19	1.23	1.58	1.14	1.69	1.99	614

Note: Test with 20cm distance from the center of the probe(s) to the edge of the device.

EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2504Y29066E-RF EUT External photos and Attachment No.2 2504Y29066E-RF EUT Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2501Y29066E-RF-TSP Test Setup photo.

******* END OF REPORT *******