

# FCC TEST REPORT

FOR

Workwell Technologies, Inc.

Workwell cloud time clock

Test Model: JL2500

Additional Model No.: Please Refer to Page 6


Prepared for : Workwell Technologies, Inc.  
Address : 2777 Loker Avenue West, Suite A Carlsbad, California 92010, USA

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,  
Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 31, 2022  
Number of tested samples : 2  
Sample number : A051922154-1, A051922154-2  
Sample number : Prototype  
Date of Test : May 31, 2022 ~ June 15, 2022  
Date of Report : June 16, 2022



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity

**FCC TEST REPORT**  
**FCC CFR 47 PART 15 C****Report Reference No.** ..... : **LCSA051922154EB****Date of Issue**..... : June 16, 2022**Testing Laboratory Name**..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.****Address**..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China**Testing Location/ Procedure**..... : Full application of Harmonised standards ■  
Partial application of Harmonised standards □  
Other standard testing method □**Applicant's Name**..... : **Workwell Technologies, Inc.****Address**..... : 2777 Loker Avenue West, Suite A Carlsbad, California 92010, USA**Test Specification****Standard**..... : FCC CFR 47 PART 15 C / ANSI C63.10: 2013**Test Report Form No.**..... : LCSEMC-1.0**TRF Originator**..... : Shenzhen LCS Compliance Testing Laboratory Ltd.**Master TRF**..... : Dated 2011-03**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description**..... : Workwell cloud time clock**Trade Mark**..... : N/A**Test Model**..... : JL2500Input: 5V $\overline{\text{---}}$ 1A**Ratings**..... : For Adapter Input: 100-240V~, 50/60Hz, 0.3A MaxFor Adapter Output: 5V $\overline{\text{---}}$ 1A**Result** ..... : Positive**Compiled by:**

Rory Huang/ Administrator

**Supervised by:**

Jin Wang/ Technique principal

**Approved by:**

Gavin Liang/ Manager




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**FCC -- TEST REPORT**

|                          |                        |                                       |
|--------------------------|------------------------|---------------------------------------|
| <b>Test Report No. :</b> | <b>LCSA051922154EB</b> | <u>June 16, 2022</u><br>Date of issue |
|--------------------------|------------------------|---------------------------------------|

|                          |                                                                                                          |
|--------------------------|----------------------------------------------------------------------------------------------------------|
| Test Model.....          | : JL2500                                                                                                 |
| EUT.....                 | : Workwell cloud time clock                                                                              |
| <b>Applicant.....</b>    | <b>: Workwell Technologies, Inc.</b>                                                                     |
| Address.....             | : 2777 Loker Avenue West, Suite A Carlsbad, California 92010, USA                                        |
| Telephone.....           | : /                                                                                                      |
| Fax.....                 | : /                                                                                                      |
| <b>Manufacturer.....</b> | <b>: SHENZHEN WANGLINFA TECHNOLOGY CORPORATION</b>                                                       |
| Address.....             | : 2/F Block P, Shang Xia Wei Industrial Area, Sha 3, Shajing, Bao-an District, ShenZhen GuangDong, China |
| Telephone.....           | : /                                                                                                      |
| Fax.....                 | : /                                                                                                      |
| <b>Factory.....</b>      | <b>: SHENZHEN WANGLINFA TECHNOLOGY CORPORATION</b>                                                       |
| Address.....             | : 2/F Block P, Shang Xia Wei Industrial Area, Sha 3, Shajing, Bao-an District, ShenZhen GuangDong, China |
| Telephone.....           | : /                                                                                                      |
| Fax.....                 | : /                                                                                                      |


|                    |                 |
|--------------------|-----------------|
| <b>Test Result</b> | <b>Positive</b> |
|--------------------|-----------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.




Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity

**Revision History**

| Report Version | Issue Date    | Revision Content | Revised By |
|----------------|---------------|------------------|------------|
| 000            | June 16, 2022 | Initial Issue    | --         |
|                |               |                  |            |
|                |               |                  |            |






## TABLE OF CONTENTS

|                                                       |           |
|-------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION .....</b>                   | <b>6</b>  |
| 1.1. Description of Device (EUT) .....                | 6         |
| 1.2. Host System Configuration List and Details ..... | 7         |
| 1.3. External I/O .....                               | 7         |
| 1.4. Description of Test Facility .....               | 7         |
| 1.5. Statement of the Measurement Uncertainty .....   | 7         |
| 1.6. Measurement Uncertainty .....                    | 7         |
| 1.7. Description of Test Modes .....                  | 8         |
| <b>2. TEST METHODOLOGY .....</b>                      | <b>9</b>  |
| 2.1. EUT Configuration .....                          | 9         |
| 2.2. EUT Exercise .....                               | 9         |
| 2.3. General Test Procedures .....                    | 9         |
| <b>3. SYSTEM TEST CONFIGURATION .....</b>             | <b>10</b> |
| 3.1. Justification .....                              | 10        |
| 3.2. EUT Exercise Software .....                      | 10        |
| 3.3. Special Accessories .....                        | 10        |
| 3.4. Block Diagram/Schematics .....                   | 10        |
| 3.5. Equipment Modifications .....                    | 10        |
| 3.6. Test Setup .....                                 | 10        |
| <b>4. SUMMARY OF TEST RESULTS .....</b>               | <b>11</b> |
| <b>5. POWER LINE CONDUCTED EMISSIONS .....</b>        | <b>12</b> |
| 5.1 Standard Applicable .....                         | 12        |
| 5.2 Block Diagram of Test Setup .....                 | 12        |
| 5.3 Test Results .....                                | 12        |
| <b>6. RADIATED EMISSION MEASUREMENT .....</b>         | <b>15</b> |
| 6.1. Standard Applicable .....                        | 15        |
| 6.2. Instruments Setting .....                        | 15        |
| 6.3. Test Procedure .....                             | 16        |
| 6.4. Block Diagram of Test Setup .....                | 18        |
| 6.5. Test Results .....                               | 18        |
| <b>7. 99% AND 20DB BANDWIDTH MEASUREMENT .....</b>    | <b>23</b> |
| 7.1. Standard Applicable .....                        | 23        |
| 7.2. Block Diagram of Test Setup .....                | 23        |
| 7.3. Test Procedure .....                             | 23        |
| 7.4. Test Results .....                               | 24        |
| <b>8. ANTENNA REQUIREMENTS .....</b>                  | <b>25</b> |
| 8.1 Standard Applicable .....                         | 25        |
| 8.2 Antenna Connected Construction .....              | 25        |
| 8.3. Results: Compliance. ....                        | 25        |
| <b>9. LIST OF MEASURING EQUIPMENTS .....</b>          | <b>26</b> |
| <b>10. TEST SETUP PHOTOGRAPHS OF EUT .....</b>        | <b>27</b> |
| <b>11. EXTERIOR PHOTOGRAPHS OF THE EUT .....</b>      | <b>27</b> |
| <b>12. INTERIOR PHOTOGRAPHS OF THE EUT .....</b>      | <b>27</b> |





## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

|                      |                                                                                                                              |
|----------------------|------------------------------------------------------------------------------------------------------------------------------|
| EUT                  | : Workwell cloud time clock                                                                                                  |
| Test Model           | : JL2500                                                                                                                     |
| Additional Model No. | : BN6000, BN6100, BN6200, BN6300, BN6400, BN6500, BN6600, BN6700                                                             |
| Model Declaration    | : PCB board, structure and internal of these model(s) are the same, So no additional models were tested                      |
| Power Supply         | : Input: 5V $\overline{=}$ 1A<br>For Adapter Input: 100-240V~, 50/60Hz, 0.3A Max<br>For Adapter Output: 5V $\overline{=}$ 1A |
| Hardware Version     | : V2.0                                                                                                                       |
| Software Version     | : V0.05                                                                                                                      |


#### 2.4G WLAN

|                     |                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Range     | : 2412 – 2462 MHz                                                                                                                          |
| Channel Number      | : 11 Channels for 20MHz bandwidth (2412~2462MHz)<br>7 Channels for 40MHz bandwidth (2422~2452MHz)                                          |
| Channel Spacing     | : 5MHz                                                                                                                                     |
| Modulation Type     | : IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)<br>IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : Internal Antenna, 2.0dBi(Max.)                                                                                                           |

#### 125KHz

|                     |                |
|---------------------|----------------|
| Operating Frequency | : 125KHz       |
| Channel Number      | : 1 channel    |
| Channel Spacing     | : N/A          |
| Modulation Type     | : OOK          |
| Antenna Description | : Coil Antenna |





## 1.2. Host System Configuration List and Details

| Manufacturer                     | Description | Model             | Serial Number | Certificate |
|----------------------------------|-------------|-------------------|---------------|-------------|
| SHENZHEN FUJIA APPLIANCE CO.,LTD | ADAPTER     | FJ-SW1160501000DU | --            | FCC         |

## 1.3. External I/O

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| Power Port           | 1        | N/A   |
| USB Port             | 1        | N/A   |

## 1.4. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 1.5. Statement of the Measurement Uncertainty


The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.6. Measurement Uncertainty

| Test Item              | Frequency Range | Uncertainty | Note |
|------------------------|-----------------|-------------|------|
| Radiation Uncertainty  | 9KHz~30MHz      | ±3.10dB     | (1)  |
|                        | 30MHz~200MHz    | ±2.96dB     | (1)  |
|                        | 200MHz~1000MHz  | ±3.10dB     | (1)  |
|                        | 1GHz~26.5GHz    | ±3.80dB     | (1)  |
|                        | 26.5GHz~40GHz   | ±3.90dB     | (1)  |
| Conduction Uncertainty | 150kHz~30MHz    | ±1.63dB     | (1)  |
| Power disturbance      | 30MHz~300MHz    | ±1.60dB     | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.





### 1.7. Description of Test Modes

The EUT operates at 125 KHz. The following operating modes were applied for the related test items.

All test modes were tested, only the result of the worst case was recorded in the report.

It was pre-tested on the positioned of each 3 axis. The worst case was found positioned on X-plane.


| Mode of Operations     | Transmitting Frequency (KHz) |
|------------------------|------------------------------|
| OOK                    | 125                          |
| For Conducted Emission |                              |
| Test Mode              | TX Mode                      |
| For Radiated Emission  |                              |
| Test Mode              | TX Mode                      |

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power.

Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worst case.

\*\*\*Note: Using a temporary antenna connector for the EUT when the conducted measurements are performed.





## 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.201 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures


#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.





### 3. SYSTEM TEST CONFIGURATION

#### 3.1. Justification

The system was configured for testing in a continuous transmits condition.

#### 3.2. EUT Exercise Software

Powered on the EUT then the EUT will transmit at 125 KHz signal.

#### 3.3. Special Accessories

N/A

#### 3.4. Block Diagram/Schematics

Please refer to the related document


#### 3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6. Test Setup

Please refer to the test setup photo.





#### 4. SUMMARY OF TEST RESULTS


| Applied Standard: FCC Part 15 Subpart C        |                                |           |        |
|------------------------------------------------|--------------------------------|-----------|--------|
| FCC Rules                                      | Description of Test            | Result    | Remark |
| §15.203                                        | Antenna Requirements           | Compliant | Note 1 |
| §15.207(a)                                     | AC Conducted Emissions         | Compliant | Note 1 |
| §15.201(a), §15.205(a), §15.209(a), §15.215(a) | Radiated Emissions Measurement | Compliant | Note 1 |
| §2.1049                                        | 99% and 20dB Bandwidth         | Compliant | Note 1 |
| §2.1091                                        | RF Exposure                    | Compliant | Note 2 |

Remark:

1. Note 1 – Test results inside test report;
2. Note 2 – Test results in other test report (RF Exposure Evaluation Report);



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity




## 5. Power Line Conducted Emissions

### 5.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dBμV) |          |
|-----------------------|---------------|----------|
|                       | Quasi-peak    | Average  |
| 0.15 to 0.50          | 66 to 56      | 56 to 46 |
| 0.50 to 5             | 56            | 46       |
| 5 to 30               | 60            | 50       |

### 5.2 Block Diagram of Test Setup




### 5.3 Test Results

**PASS.**


The test data please refer to following page.

|               |          |                |          |
|---------------|----------|----------------|----------|
| Temperature   | 22.5°C   | Humidity       | 53.5%    |
| Test Engineer | Joker Hu | Configurations | Transmit |



**AC Conducted Emission @ AC 120V/60Hz(worst case)**

Line



| No. | Mk. | Freq.   | Reading | Correct | Measure- | Limit | Margin |          |         |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|---------|
|     |     | MHz     | dBuV    | Factor  | ment     |       |        | Detector | Comment |
| 1   | *   | 0.1500  | 32.47   | 19.63   | 52.10    | 66.00 | -13.90 | QP       |         |
| 2   |     | 0.1500  | 13.80   | 19.63   | 33.43    | 56.00 | -22.57 | AVG      |         |
| 3   |     | 0.4606  | 20.78   | 19.64   | 40.42    | 56.68 | -16.26 | QP       |         |
| 4   |     | 0.4661  | 6.14    | 19.64   | 25.78    | 46.58 | -20.80 | AVG      |         |
| 5   |     | 1.0456  | 9.93    | 19.65   | 29.58    | 56.00 | -26.42 | QP       |         |
| 6   |     | 1.0591  | -2.09   | 19.65   | 17.56    | 46.00 | -28.44 | AVG      |         |
| 7   |     | 2.3685  | 11.14   | 19.70   | 30.84    | 56.00 | -25.16 | QP       |         |
| 8   |     | 2.4136  | -3.21   | 19.70   | 16.49    | 46.00 | -29.51 | AVG      |         |
| 9   |     | 5.1855  | 11.90   | 19.80   | 31.70    | 60.00 | -28.30 | QP       |         |
| 10  |     | 5.3115  | -3.90   | 19.80   | 15.90    | 50.00 | -34.10 | AVG      |         |
| 11  |     | 23.0505 | 5.79    | 20.07   | 25.86    | 60.00 | -34.14 | QP       |         |
| 12  |     | 24.0946 | -7.53   | 20.05   | 12.52    | 50.00 | -37.48 | AVG      |         |




Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Neutral




| No. | Mk. | Freq.   | Reading | Correct | Measure- | Limit | Margin |          |         |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|---------|
|     |     | MHz     | Level   | Factor  | ment     |       |        | Detector | Comment |
|     |     |         | dBuV    | dB      | dBuV     | dBuV  | dB     |          |         |
| 1   |     | 0.1546  | 28.92   | 19.63   | 48.55    | 65.75 | -17.20 | QP       |         |
| 2   |     | 0.1636  | 11.35   | 19.63   | 30.98    | 55.28 | -24.30 | AVG      |         |
| 3   | *   | 0.4561  | 24.09   | 19.64   | 43.73    | 56.76 | -13.03 | QP       |         |
| 4   |     | 0.4606  | 11.74   | 19.64   | 31.38    | 46.68 | -15.30 | AVG      |         |
| 5   |     | 1.7746  | 15.16   | 19.67   | 34.83    | 56.00 | -21.17 | QP       |         |
| 6   |     | 1.7926  | 0.76    | 19.67   | 20.43    | 46.00 | -25.57 | AVG      |         |
| 7   |     | 4.4160  | 14.64   | 19.70   | 34.34    | 56.00 | -21.66 | QP       |         |
| 8   |     | 4.6411  | 1.13    | 19.70   | 20.83    | 46.00 | -25.17 | AVG      |         |
| 9   |     | 7.6651  | 8.48    | 19.75   | 28.23    | 60.00 | -31.77 | QP       |         |
| 10  |     | 8.1871  | -4.22   | 19.78   | 15.56    | 50.00 | -34.44 | AVG      |         |
| 11  |     | 26.9476 | 12.55   | 20.04   | 32.59    | 60.00 | -27.41 | QP       |         |
| 12  |     | 28.6801 | -3.85   | 20.08   | 16.23    | 50.00 | -33.77 | AVG      |         |

\*\*\*Note:

- 1). Pre-scan all modes and recorded the worst case results in this report.
- 2).  $\text{Measurement} = \text{Reading} + \text{Correct}$ ,  $\text{Margin} = \text{Measurement} - \text{Limit}$ .  
 $\text{Correct Factor} = \text{Lisn Factor} + \text{Cable Factor}$





## 6. RADIATED EMISSION MEASUREMENT

### 6.1. Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation. 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) and 15.215 limit in the table below has to be followed.

| Fundamental Frequency | Field Strength of fundamental<br>(millivolts/meter) | Field Strength of harmonics<br>(microvolts/meter) |
|-----------------------|-----------------------------------------------------|---------------------------------------------------|
| 902-928MHz            | 50                                                  | 500                                               |
| 2400-2483.5MHz        | 50                                                  | 500                                               |
| 5725-5875MHz          | 50                                                  | 500                                               |
| 24.0-24.25GHz         | 250                                                 | 2500                                              |

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |


### 6.2. Instruments Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting                                           |
|-------------------------------------------|---------------------------------------------------|
| Attenuation                               | Auto                                              |
| Start Frequency                           | 1000 MHz                                          |
| Stop Frequency                            | 10 <sup>th</sup> carrier harmonic                 |
| RB / VB (Emission in restricted band)     | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |

| Receiver Parameter     | Setting                                    |
|------------------------|--------------------------------------------|
| Attenuation            | Auto                                       |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG  |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP   |





### 6.3. Test Procedure

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.


##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.





## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.


### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.



### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.





#### 6.4. Block Diagram of Test Setup




#### 6.5. Test Results

##### Results of Radiated Emissions (9 kHz~30MHz)


|               |          |                |          |
|---------------|----------|----------------|----------|
| Temperature   | 23.8℃    | Humidity       | 52.5%    |
| Test Engineer | Joker Hu | Configurations | Transmit |






0 degree

130.0 dBuV/m




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 0.1246          | 92.52          | -9.47         | 83.05          | 105.66         | -22.61      | peak     |
| 2   | 0.1723          | 64.77          | -9.50         | 55.27          | 102.85         | -47.58      | peak     |
| 3   | 0.2584          | 61.84          | -8.98         | 52.86          | 99.34          | -46.48      | peak     |
| 4   | 0.3845          | 60.45          | -8.76         | 51.69          | 95.90          | -44.21      | peak     |
| 5   | 0.5151          | 59.26          | -8.48         | 50.78          | 73.37          | -22.59      | peak     |
| 6   | 1.0438          | 53.60          | -7.17         | 46.43          | 67.23          | -20.80      | peak     |





90 degree



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 0.1226          | 94.06          | -9.46         | 84.60          | 105.80         | -21.20      | peak     |
| 2   | 0.2565          | 60.36          | -8.98         | 51.38          | 99.41          | -48.03      | peak     |
| 3   | 0.3845          | 58.09          | -8.76         | 49.33          | 95.90          | -46.57      | peak     |
| 4   | 0.5151          | 55.02          | -8.48         | 46.54          | 73.37          | -26.83      | peak     |
| 5   | 0.7669          | 51.62          | -7.84         | 43.78          | 69.91          | -26.13      | peak     |
| 6   | 1.0262          | 50.83          | -7.19         | 43.64          | 67.38          | -23.74      | peak     |

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

Measured at both 90 degree and 0 degree, recorded worst case at 0 degree.






## Results of Radiated Emissions (30MHz~1GHz)

|               |          |                |          |
|---------------|----------|----------------|----------|
| Temperature   | 23.5℃    | Humidity       | 52.2%    |
| Test Engineer | Joker Hu | Configurations | Transmit |

Horizontal

70.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 75.7112         | 39.34          | -19.71        | 19.63          | 40.00          | -20.37      | QP       |
| 2   | 150.0107        | 54.67          | -19.82        | 34.85          | 43.50          | -8.65       | QP       |
| 3   | 300.3672        | 54.30          | -15.60        | 38.70          | 46.00          | -7.30       | QP       |
| 4   | 350.4766        | 51.58          | -14.87        | 36.71          | 46.00          | -9.29       | QP       |
| 5   | 480.5276        | 50.84          | -14.18        | 36.66          | 46.00          | -9.34       | QP       |
| 6   | 696.8567        | 49.00          | -10.94        | 38.06          | 46.00          | -7.94       | QP       |





Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 49.8813         | 38.84          | -17.04        | 21.80          | 40.00          | -18.20      | QP       |
| 2   | 99.8777         | 44.17          | -18.19        | 25.98          | 43.50          | -17.52      | QP       |
| 3   | 150.0107        | 53.98          | -19.82        | 34.16          | 43.50          | -9.34       | QP       |
| 4   | 300.3672        | 53.49          | -15.60        | 37.89          | 46.00          | -8.11       | QP       |
| 5   | 350.4766        | 54.30          | -14.87        | 39.43          | 46.00          | -6.57       | QP       |
| 6   | 576.6443        | 50.89          | -10.83        | 40.06          | 46.00          | -5.94       | QP       |

Note:

- 1). Pre-scan all modes and recorded the worst case results in this report.
- 2). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3). Corrected Reading: Antenna Factor + Cable Loss + Read Level = Level.






## 7. 99% and 20dB Bandwidth Measurement

### 7.1. Standard Applicable

According to §15.215, device must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 7.2. Block Diagram of Test Setup



### 7.3. Test Procedure

Use the following spectrum analyzer settings:

Span = 1 KHz

RBW = 100 Hz

VBW = 300 Hz


Sweep = auto

Detector function = peak

Trace = max hold


The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).






## 7.4. Test Results

| 99% and 20dB Bandwidth Measurement |                              |                     |             |
|------------------------------------|------------------------------|---------------------|-------------|
| Test Frequency (KHz)               | 99% Occupied Bandwidth (KHz) | 20dB Bandwidth (Hz) | Limit (KHz) |
| 125                                | 0.218                        | 0.252               | No Limit    |





## 8. Antenna Requirements

### 8.1 Standard Applicable

According to antenna requirement of §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

### 8.2 Antenna Connected Construction

#### 8.2.1. Standard Applicable


According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 8.2.2. Antenna Connector Construction

The antenna used for transmitting is permanently attached and no consideration of replacement. Please see EUT photo for details.

### 8.3. Results: Compliance.






## 9. LIST OF MEASURING EQUIPMENTS

| Item | Equipment                | Manufacturer   | Model No.   | Serial No.      | Cal Date   | Due Date   |
|------|--------------------------|----------------|-------------|-----------------|------------|------------|
| 1    | MXA Signal Analyzer      | Agilent        | N9020A      | MY49100040      | 2021-06-21 | 2022-06-20 |
| 2    | SPECTRUM ANALYZER        | R&S            | FSP40       | 100503          | 2021-11-16 | 2022-11-15 |
| 3    | 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M      | 03CH03-HY       | 2021-06-21 | 2022-06-20 |
| 4    | Positioning Controller   | MF             | MF7082      | MF78020803      | 2021-06-21 | 2022-06-20 |
| 5    | EMI Test Software        | AUDIX          | E3          | /               | N/A        | N/A        |
| 6    | EMI Test Receiver        | R&S            | ESR 7       | 101181          | 2021-06-21 | 2022-06-20 |
| 7    | Active Loop Antenna      | SCHWARZBECK    | FMZB 1519B  | 00005           | 2021-07-25 | 2024-07-24 |
| 8    | By-log Antenna           | SCHWARZBECK    | VULB9163    | 9163-470        | 2021-07-25 | 2024-07-24 |
| 9    | Horn Antenna             | SCHWARZBECK    | BBHA 9120D  | 9120D-1925      | 2021-07-01 | 2024-06-30 |
| 10   | EMI Test Receiver        | R&S            | ESPI        | 101840          | 2021-06-21 | 2022-06-20 |
| 11   | Artificial Mains         | R&S            | ENV216      | 101288          | 2021-06-21 | 2022-06-20 |
| 12   | 10dB Attenuator          | SCHWARZBECK    | MTS-IMP-136 | 261115-001-0032 | 2021-06-21 | 2022-06-20 |
| 13   | Broadband Preamplifier   | SCHWARZBECK    | BBV9745     | 9719-025        | 2021-06-21 | 2022-06-20 |
| 14   | EMI Test Software        | Farad          | EZ          | /               | N/A        | N/A        |





## 10. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

## 11. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

## 12. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF TEST REPORT-----

