

TEST REPORT

FCC ID..... :	2A8GGSW30	
Test Report No..... :	TCT221124E062	
Date of issue..... :	Jan. 05, 2023	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	SHENZHEN SAGAMOBILE CO., LTD.	
Address..... :	RM.12A Benyuan Building, No.6015, Shennan Rd., Futian district, Shenzhen, China	
Manufacturer's name ... :	SHENZHEN SAGAMOBILE CO., LTD.	
Address..... :	RM.12A Benyuan Building, No.6015, Shennan Rd., Futian district, Shenzhen, China	
Standard(s)	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name..... :	Portable Projector	
Trade Mark	SUREWHEEL	
Model/Type reference..... :	SW30	
Rating(s)..... :	AC 120V	
Date of receipt of test item	Nov. 24, 2022	
Date (s) of performance of test..... :	Nov. 24, 2022 ~ Jan. 05, 2023	
Tested by (+signature) ... :	Brews XU	
Check by (+signature).... :	Beryl ZHAO	
Approved by (+signature):	Tomsin	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Test Frequency	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode.....	6
3.2. Description of Support Units	7
4. Facilities and Accreditations	8
4.1. Facilities	8
4.2. Location	8
4.3. Measurement Uncertainty.....	8
5. Test Results and Measurement Data	9
5.1. Antenna requirement	9
5.2. Conducted Emission.....	10
5.3. Maximum Conducted Output Power	14
5.4. 6dB Emission Bandwidth.....	16
5.5. 26dB Bandwidth and 99% Occupied Bandwidth	17
5.6. Power Spectral Density.....	18
5.7. Band edge	19
5.8. Unwanted Emissions	30
5.9. Frequency Stability Measurement	42
Appendix A: Test Result of Conducted Test	
Appendix B: Photographs of Test Setup	
Appendix C: Photographs of EUT	

1. General Product Information

1.1. EUT description

Product Name.....:	Portable Projector
Model/Type reference.....:	SW30
Sample Number.....:	TCT221124E007-0101
Operation Frequency	Band 1: 5180 MHz ~ 5240 MHz Band 3: 5745 MHz ~ 5825 MHz
Channel Bandwidth.....:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz
Modulation Technology	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type.....:	FPC Antenna
Antenna Gain.....:	5dBi
Rating(s).....:	AC 120V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

1.3. Test Frequency

Band 1

20MHz		40MHz	
Channel	Frequency	Channel	Frequency
36	5180	38	5190
40	5200	46	5230
48	5240		

Band 3

20MHz		40MHz	
Channel	Frequency	Channel	Frequency
149	5745	151	5755
157	5785	159	5795
165	5825		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth& 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.
5. For the band 5.15-5.25GHz, EUT meet the requirements of 15.407(a)(ii).

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Software:	
Software Information:	SecureCRT_6.70
Power Level:	Default
Test Mode:	
Engineer mode:	Keep the EUT in continuous transmitting by select channel and modulations with max. duty cycle.
The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	6.5 Mbps
802.11n(HT40)	13.5 Mbps
802.11ac(VHT20)	6.5 Mbps
802.11ac(VHT40)	13.5 Mbps

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339


4.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB


5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT antenna is FPC antenna which permanently attached, and the best case gain of the antenna is 5dBi.	
	

5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane  Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Transmitting Mode														
Test Procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jul. 03, 2023
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Feb. 24, 2023
Line-5	TCT	CE-05	/	Jul. 03, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: L1

Temperature: 25.3 (°C)

Humidity: 56 %

Limit: FCC Part 15C Conduction(QP)

Power: AC 120 V/60 Hz

No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1		0.1819	39.47	10.51	49.98	64.40	-14.42	QP	
2		0.1819	24.07	10.51	34.58	54.40	-19.82	AVG	
3		0.3020	34.04	10.24	44.28	60.19	-15.91	QP	
4	*	0.3020	29.08	10.24	39.32	50.19	-10.87	AVG	
5		0.8940	23.18	10.11	33.29	56.00	-22.71	QP	
6		0.8940	17.30	10.11	27.41	46.00	-18.59	AVG	
7		0.8940	14.39	10.11	24.50	46.00	-21.50	AVG	
8		1.6740	21.90	10.04	31.94	56.00	-24.06	QP	
9		2.3380	25.69	10.03	35.72	56.00	-20.28	QP	
10		2.3380	16.17	10.03	26.20	46.00	-19.80	AVG	
11		3.3740	26.13	10.03	36.16	56.00	-19.84	QP	
12		3.3740	14.21	10.03	24.24	46.00	-21.76	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: *N*

Temperature: 25.3 (°C)

Humidity: 56 %

Limit: FCC Part 15C Conduction(QP)

Power: AC 120 V/60 Hz

No. Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1	0.1900	40.74	10.48	51.22	64.04	-12.82	QP	
2	0.1900	21.91	10.48	32.39	54.04	-21.65	AVG	
3	0.3019	35.87	10.24	46.11	60.19	-14.08	QP	
4 *	0.3019	29.36	10.24	39.60	50.19	-10.59	AVG	
5	1.0060	23.51	10.11	33.62	56.00	-22.38	QP	
6	1.0060	17.38	10.11	27.49	46.00	-18.51	AVG	
7	1.5740	22.78	10.11	32.89	56.00	-23.11	QP	
8	1.5740	13.44	10.11	23.55	46.00	-22.45	AVG	
9	2.3179	26.99	10.13	37.12	56.00	-18.88	QP	
10	2.3179	16.38	10.13	26.51	46.00	-19.49	AVG	
11	3.0300	26.66	10.13	36.79	56.00	-19.21	QP	
12	3.0300	14.64	10.13	24.77	46.00	-21.23	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. = Quasi-Peak


AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40) and the worst case Mode (Lowest channel and 802.11a) was submitted only.

5.3. Maximum Conducted Output Power

5.3.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046										
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E										
Limit:	<table border="1"> <thead> <tr> <th>Frequency Band (MHz)</th><th>Limit</th></tr> </thead> <tbody> <tr> <td>5180 - 5240</td><td>24dBm(250mW) for client device</td></tr> <tr> <td>5260 - 5320</td><td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td></tr> <tr> <td>5470 - 5725</td><td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td></tr> <tr> <td>5745 - 5825</td><td>30dBm(1W)</td></tr> </tbody> </table>	Frequency Band (MHz)	Limit	5180 - 5240	24dBm(250mW) for client device	5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5745 - 5825	30dBm(1W)
Frequency Band (MHz)	Limit										
5180 - 5240	24dBm(250mW) for client device										
5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5745 - 5825	30dBm(1W)										
Test Setup:	 Power meter EUT										
Test Mode:	Transmitting mode with modulation										
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 5. Measure the conducted output power and record the results in the test report.										
Test Result:	PASS										
Remark:	Conducted output power= measurement power +10log(1/x) X is duty cycle=1, so 10log(1/1)=0 Conducted output power= measurement power										

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Power Meter	Agilent	E4418B	MY45100357	Jul. 04, 2023
Power Sensor	Agilent	8481A	MY41091497	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.4. 6dB Emission Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. 26dB Bandwidth and 99% Occupied Bandwidth

5.5.1. Test Specification


Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Power Spectral Density

5.6.1. Test Specification


Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	$\leq 11.00\text{dBm/MHz}$ for Band 1 5150MHz-5250MHz(client device) $\leq 11.00\text{dBm/MHz}$ for Band 2A&2C 5250-5350&5470-5725 $\leq 30.00\text{dBm/500KHz}$ for Band 3 5725MHz-5850MHz The e.i.r.p spectral density for Band 1 5150MHz – 5250 MHz should not exceed 10dBm/MHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW $\geq 3 \times$ RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.7. Band edge

5.7.1. Test Specification

Test Requirement:	FCC CFR47 Part 15E Section 15.407			
Test Method:	ANSI C63.10 2013			
Limit:	In un-restricted band: For Band 1&2A&2C: -27dBm/MHz For Band 3:			
	Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)
	< 5650	-27	5850~5855	27~15.6
	5650~5700	-27~10	5855~5875	15.6~10
	5700~5720	10~15.6	5875~5925	10~-27
	5720~5725	15.6~27	> 5925	-27
E[dBμV/m] = EIRP[dBm] + 95.2 @3m In restricted band:				
Detector		Limit@3m		
Peak		74dBμV/m		
AVG		54dBμV/m		
Test Setup:				
Test Mode:	Transmitting mode with modulation			
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold			


	Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESIB7	100197	Jul. 03, 2023
Spectrum Analyzer	R&S	FSQ40	200061	Jul. 03, 2023
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Feb. 24, 2023
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Feb. 24, 2023
Pre-amplifier	HP	8447D	2727A05017	Jul. 03, 2023
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 11, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 05, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 05, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Apr. 10, 2023
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
Antenna Mast	Keleto	CC-A-4M	/	/
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.7.3. Test Data

AC20-5180



Site: #3 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 21.3(°C)

Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	55.96	-9.85	46.11	74.00	-27.89	peak	P	



Site: #3 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 21.3(°C)


Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	48.30	-9.85	38.45	74.00	-35.55	peak	P	

AC20-5240




Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 21.3(°C) Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	50.24	-9.43	40.81	74.00	-33.19	peak	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 21.3(°C) Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	47.89	-9.43	38.46	74.00	-35.54	peak	P	

AC40-5190




Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 21.3(°C) Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	62.12	-9.85	52.27	74.00	-21.73	peak	P	




Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 21.3(°C) Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	53.27	-9.85	43.42	74.00	-30.58	peak	P	

AC40-5230




Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 21.3(°C) Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	49.48	-9.43	40.05	74.00	-33.95	peak	P	





Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 21.3(°C) Humidity: 50 %

Limit: FCC part 15.407 band edge (PK)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	47.30	-9.43	37.87	74.00	-36.13	peak	P	

AC20-5745




AC20-5825



Site: #3 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 21.3(°C) Humidity: 50 %

Limit: FCC part 15.407 band edge B3 (PK) Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5928.400	50.79	-7.95	42.84	68.20	-25.36	peak	P	





Site: #3 3m Anechoic Chamber Polarization: **Vertical** Temperature: 21.3(°C) Humidity: 50 %


Limit: FCC part 15.407 band edge B3 (PK) Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5941.700	49.20	-7.96	41.24	68.20	-26.96	peak	P	

AC40-5755




AC40-5795




Note: All modulation (802.11a, 802.11n, 802.11ac) have been tested, only the worst case in 802.11ac be reported.


5.8. Unwanted Emissions

5.8.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205				
Test Method:	KDB 789033 D02 v02r01				
Frequency Range:	9kHz to 40GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Transmitting mode with modulation				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit:	Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table, In restricted bands:				
	Frequency		Detector		Limit@3m
	Above 1G		Peak		74dBµV/m
			AVG		54dBµV/m
	Frequency		Field Strength (microvolts/meter)	Measurement Distance (meters)	
	0.009-0.490		2400/F(KHz)	300	
	0.490-1.705		24000/F(KHz)	3	
	1.705-30		30	30	
	30-88		100	3	
	88-216		150	3	
216-960		200	3		
Above 960		500	3		
Test setup:	In un-restricted bands: 68.2dBuV/m				
	For radiated emissions below 30MHz				
Test setup:					
	30MHz to 1GHz				



Above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test results:

PASS

5.8.2. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



Site: #1 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 25.3(C) Humidity: 50 %

Limit: FCC Part 15C RE_3m

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 !	52.3911	23.35	13.16	36.51	40.00	-3.49	QP	P	
2	132.2204	13.61	12.24	25.85	43.50	-17.65	QP	P	
3	191.7450	22.26	10.68	32.94	43.50	-10.56	QP	P	
4 !	222.9501	30.79	11.08	41.87	46.00	-4.13	QP	P	
5 *	269.4282	29.84	12.69	42.53	46.00	-3.47	QP	P	
6 !	774.1584	17.57	23.09	40.66	46.00	-5.34	QP	P	

Vertical:



Site: #1 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 25.3(C) Humidity: 50 %

Limit: FCC Part 15C RE_3m

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 !	39.5756	22.12	13.69	35.81	40.00	-4.19	QP	P	
2 *	51.4806	23.27	13.27	36.54	40.00	-3.46	QP	P	
3	118.1861	20.51	11.45	31.96	43.50	-11.54	QP	P	
4	267.5453	18.91	12.62	31.53	46.00	-14.47	QP	P	
5	374.6225	17.47	15.41	32.88	46.00	-13.12	QP	P	
6	472.1759	14.43	17.82	32.25	46.00	-13.75	QP	P	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40) and the worst case Mode (Lowest channel and 802.11a) was submitted only.

3. Measurement (dBμV) = Reading level + Correction Factor , correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.26	---	8.02	46.28	---	68.2	---	-21.92
15540	H	38.67	---	9.87	48.54	---	74	54	-5.46
---	H	---	---	---	---	---	---	---	---
10360	V	38.12	---	8.02	46.14	---	68.2	---	-22.06
15540	V	38.39	---	9.87	48.26	---	74	54	-5.74
---	V	---	---	---	---	---	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.57	---	7.97	47.54	---	68.2	---	-20.66
15600	H	38.65	---	9.83	48.48	---	74	54	-5.52
---	H	---	---	---	---	---	---	---	---
10400	V	40.96	---	7.97	48.93	---	68.2	---	-19.27
15600	V	38.19	---	9.83	48.02	---	74	54	-5.98
---	V	---	---	---	---	---	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	38.43	---	7.97	46.4	---	68.2	---	-21.8
15720	H	37.11	---	9.83	46.94	---	74	54	-7.06
---	H	---	---	---	---	---	---	---	---
10480	V	38.88	---	7.97	46.85	---	68.2	---	-21.35
15720	V	36.02	---	9.83	45.85	---	74	54	-8.15
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	41.17	---	8.02	49.19	---	68.2	---	-19.01
15540	H	37.88	---	9.87	47.75	---	74	54	-6.25
---	H	---	---	---	---	---	---	---	---
10360	V	42.04	---	8.02	50.06	---	68.2	---	-18.14
15540	V	37.62	---	9.87	47.49	---	74	54	-6.51
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH40: 5200MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.19	---	7.97	48.16	---	68.2	---	-20.04
15600	H	38.46	---	9.83	48.29	---	74	54	-5.71
---	H	---	---	---	---	---	---	---	---
10400	V	40.31	---	7.97	48.28	---	68.2	---	-19.92
15600	V	37.53	---	9.83	47.36	---	74	54	-6.64
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH48: 5240MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.33	---	7.97	49.3	---	68.2	---	-18.9
15720	H	39.85	---	9.83	49.68	---	74	54	-4.32
---	H	---	---	---	---	---	---	---	---
10480	V	40.46	---	7.97	48.43	---	68.2	---	-19.77
15720	V	39.68	---	9.83	49.51	---	74	54	-4.49
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH38: 5190MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.09	---	7.75	46.84	---	68.2	---	-21.36
15570	H	37.24	---	9.87	47.11	---	74	54	-6.89
---	H	---	---	---	---	---	---	---	---
10380	V	40.51	---	7.75	48.26	---	68.2	---	-19.94
15570	V	37.96	---	9.87	47.83	---	74	54	-6.17
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH46: 5230MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.08	---	7.97	49.05	---	68.2	---	-19.15
15690	H	38.77	---	9.83	48.6	---	74	54	-5.4
---	H	---	---	---	---	---	---	---	---
10460	V	41.43	---	7.97	49.4	---	68.2	---	-18.8
15690	V	38.56	---	9.83	48.39	---	74	54	-5.61
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	40.87	---	8.02	48.89	---	68.2	---	-19.31
15540	H	37.04	---	9.87	46.91	---	74	54	-7.09
---	H	---	---	---	---	---	---	---	---
10360	V	38.25	---	8.02	46.27	---	68.2	---	-21.93
15540	V	39.62	---	9.87	49.49	---	74	54	-4.51
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.11	---	7.97	47.08	---	68.2	---	-21.12
15600	H	38.8	---	9.83	48.63	---	74	54	-5.37
---	H	---	---	---	---	---	---	---	---
10400	V	39.65	---	7.97	47.62	---	68.2	---	-20.58
15600	V	38.04	---	9.83	47.87	---	74	54	-6.13
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.86	---	7.97	45.83	---	68.2	---	-22.37
15720	H	37.53	---	9.83	47.36	---	74	54	-6.64
---	H	---	---	---	---	---	---	---	---
10480	V	38.97	---	7.97	46.94	---	68.2	---	-21.26
15720	V	38.21	---	9.83	48.04	---	74	54	-5.96
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.35	---	7.75	48.1	---	68.2	---	-20.1
15570	H	39.89	---	9.87	49.76	---	74	54	-4.24
---	H	---	---	---	---	---	---	---	---
10380	V	38.95	---	7.75	46.7	---	68.2	---	-21.5
15570	V	38.42	---	9.87	48.29	---	74	54	-5.71
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.31	---	7.97	46.28	---	68.2	---	-21.92
15690	H	38.76	---	9.83	48.59	---	74	54	-5.41
---	H	---	---	---	---	---	---	---	---
10460	V	39.99	---	7.97	47.96	---	68.2	---	-20.24
15690	V	37.17	---	9.83	47	---	74	54	-7
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

Modulation Type: Band 3									
11a CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	37.46	---	8.09	45.55	---	74	54	-8.45
17235	H	37.03	---	9.67	46.7	---	68.2	---	-21.5
---	H	---	---	---	---	---	---	---	---
11490	V	40.94	---	8.09	49.03	---	74	54	-4.97
17235	V	38.79	---	9.67	48.46	---	68.2	---	-19.74
---	V	---	---	---	---	---	---	---	---
11a CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	39.69	---	8.10	47.79	---	74	54	-6.21
17355	H	38.55	---	9.65	48.2	---	68.2	---	-20
---	H	---	---	---	---	---	---	---	---
11570	V	38.45	---	8.10	46.55	---	74	54	-7.45
17355	V	39.81	---	9.65	49.46	---	68.2	---	-18.74
---	V	---	---	---	---	---	---	---	---
11a CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	37.07	---	8.12	45.19	---	74	54	-8.81
17475	H	36.58	---	9.62	46.2	---	68.2	---	-22
---	H	---	---	---	---	---	---	---	---
11650	V	38.92	---	8.12	47.04	---	74	54	-6.96
17475	V	38.1	---	9.62	47.72	---	68.2	---	-20.48
---	V	---	---	---	---	---	---	---	---
					(dBμV/m)	(dBμV/m)			
11490	H	38.38	---	8.09	46.47	---	74	54	-7.53
17235	H	38.29	---	9.67	47.96	---	68.2	---	-20.24
---	H	---	---	---	---	---	---	---	---
11490	V	39.55	---	8.09	47.64	---	74	54	-6.36
17235	V	37.81	---	9.67	47.48	---	68.2	---	-20.72
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH157: 5785MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.36	---	8.10	46.46	---	74	54	-7.54
17355	H	39.05	---	9.65	48.7	---	68.2	---	-19.5
---	H	---	---	---	---	---	---	---	---
11570	V	38.91	---	8.10	47.01	---	74	54	-6.99
17355	V	39.15	---	9.65	48.8	---	68.2	---	-19.4
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH165: 5825MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	38.63	---	8.12	46.75	---	74	54	-7.25
17475	H	37.06	---	9.62	46.68	---	68.2	---	-21.52
---	H	---	---	---	---	---	---	---	---
11650	V	38.27	---	8.12	46.39	---	74	54	-7.61
17475	V	39.42	---	9.62	49.04	---	68.2	---	-19.16
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH151: 5755MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	40.62	---	8.09	48.71	---	74	54	-5.29
17265	H	37.18	---	9.67	46.85	---	68.2	---	-21.35
---	H	---	---	---	---	---	---	---	---
11510	V	41.97	---	8.09	50.06	---	74	54	-3.94
17265	V	38.22	---	9.67	47.89	---	68.2	---	-20.31
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH159: 5795MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	38.86	---	8.10	46.96	---	74	54	-7.04
17385	H	38.49	---	9.65	48.14	---	68.2	---	-20.06
---	H	---	---	---	---	---	---	---	---
11590	V	38.44	---	8.10	46.54	---	74	54	-7.46
17385	V	37.51	---	9.65	47.16	---	68.2	---	-21.04
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH149: 5745MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	40.62	---	8.09	48.71	---	74	54	-5.29
17235	H	37.75	---	9.67	47.42	---	68.2	---	-20.78
---	H	---	---	---	---	---	---	---	---
11490	V	40.11	---	8.09	48.2	---	74	54	-5.8
17235	V	38.76	---	9.67	48.43	---	68.2	---	-19.77
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH157: 5785MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.03	---	8.10	46.13	---	74	54	-7.87
17355	H	36.22	---	9.65	45.87	---	68.2	---	-22.33
---	H	---	---	---	---	---	---	---	---
11570	V	37.97	---	8.10	46.07	---	74	54	-7.93
17355	V	38.69	---	9.65	48.34	---	68.2	---	-19.86
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH165: 5825MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	40.44	---	8.12	48.56	---	74	54	-5.44
17475	H	38.05	---	9.62	47.67	---	68.2	---	-20.53
---	H	---	---	---	---	---	---	---	---
11650	V	38.86	---	8.12	46.98	---	74	54	-7.02
17475	V	40.22	---	9.62	49.84	---	68.2	---	-18.36
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH151: 5755MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	39.18	---	8.09	47.27	---	74	54	-6.73
17265	H	37.97	---	9.67	47.64	---	68.2	---	-20.56
---	H	---	---	---	---	---	---	---	---
11510	V	40.63	---	8.09	48.72	---	74	54	-5.28
17265	V	36.04	---	9.67	45.71	---	68.2	---	-22.49
---	V	---	---	---	---	---	---	---	---


11ac(VHT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	40.48	---	8.10	48.58	---	74	54	-5.42
17385	H	37.86	---	9.65	47.51	---	68.2	---	-20.69
---	H	---	---	---	---	---	---	---	---
11590	V	39.69	---	8.10	47.79	---	74	54	-6.21
17385	V	38.32	---	9.65	47.97	---	68.2	---	-20.23
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5.9. Frequency Stability Measurement

5.9.1. Test Specification

Test Requirement:	FCC Part15 Section 15.407(g) &Part2 J Section 2.1055
Test Method:	ANSI C63.10: 2013
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Setup:	 <pre> graph LR SA[Spectrum Analyzer] --- EUT[EUT] subgraph TC [Temperature Chamber] EUT end EUT --- P[AC/DC Power supply] </pre>
Test Procedure:	The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test Result:	PASS
Remark:	Pre-scan was performed at all models(11a,11n,11ac), the worst case (11ac) was found and test data was shown in this report.

Test plots as follows:

Test mode:		802.11ac(HT20)	Frequency(MHz):	5180
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5179.98	-20000	PASS
35		5179.98	-20000	PASS
25		5179.98	-20000	PASS
15		5179.98	-20000	PASS
5		5179.96	-40000	PASS
0		5179.98	-20000	PASS
25	100V	5179.98	-20000	PASS
	120V	5179.98	-20000	PASS
	120V	5179.98	-20000	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5200
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5200	0	PASS
35		5199.98	-20000	PASS
25		5199.98	-20000	PASS
15		5199.98	-20000	PASS
5		5200	0	PASS
0		5199.98	-20000	PASS
25	100V	5199.98	-20000	PASS
	120V	5199.98	-20000	PASS
	120V	5200	0	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5240
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5239.98	-20000	PASS
35		5239.96	-40000	PASS
25		5239.98	-20000	PASS
15		5239.98	-20000	PASS
5		5239.98	-20000	PASS
0		5239.98	-20000	PASS
25	100V	5240	0	PASS
	120V	5240	0	PASS
	120V	5239.98	-20000	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5745
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5744.96	-40000	PASS
35		5744.98	-20000	PASS
25		5744.96	-40000	PASS
15		5744.96	-40000	PASS
5		5744.98	-20000	PASS
0		5744.98	-20000	PASS
25	100V	5744.98	-20000	PASS
	120V	5744.96	-40000	PASS
	120V	5744.98	-20000	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5785
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5784.96	-40000	PASS
35		5784.96	-40000	PASS
25		5784.98	-20000	PASS
15		5785	0	PASS
5		5784.98	-20000	PASS
0		5784.98	-20000	PASS
25	100V	5784.96	-40000	PASS
	120V	5784.98	-20000	PASS
	120V	5784.96	-40000	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5825
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5824.98	-20000	PASS
35		5824.98	-20000	PASS
25		5824.96	-40000	PASS
15		5824.96	-40000	PASS
5		5824.96	-40000	PASS
0		5824.96	-40000	PASS
25	100V	5824.98	-20000	PASS
	120V	5824.98	-20000	PASS
	120V	5824.98	-20000	PASS

Test mode:		802.11ac(HT40)	Frequency(MHz):	5190
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5189.96	-40000	PASS
35		5189.96	-40000	PASS
25		5189.96	-40000	PASS
15		5189.96	-40000	PASS
5		5190	0	PASS
0		5189.96	-40000	PASS
25	100V	5190	0	PASS
	120V	5190	0	PASS
	120V	5190	0	PASS

Test mode:		802.11ac(HT40)	Frequency(MHz):	5230
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5230	0	PASS
35		5230	0	PASS
25		5229.96	-40000	PASS
15		5229.96	-40000	PASS
5		5229.96	-40000	PASS
0		5229.96	-40000	PASS
25	100V	5229.96	-40000	PASS
	120V	5229.96	-40000	PASS
	120V	5229.96	-40000	PASS


Test mode:		802.11ac(HT40)	Frequency(MHz):	5755
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5754.96	-40000	PASS
35		5755	0	PASS
25		5754.96	-40000	PASS
15		5754.96	-40000	PASS
5		5754.96	-40000	PASS
0		5754.96	-40000	PASS
25	100V	5754.96	-40000	PASS
	120V	5755	0	PASS
	120V	5754.96	-40000	PASS



Test mode:		802.11ac(HT40)	Frequency(MHz):	5795
Temperature (°C)	Voltage(VAC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	120V	5795	0	PASS
35		5795	0	PASS
25		5794.96	-40000	PASS
15		5794.96	-40000	PASS
5		5794.96	-40000	PASS
0		5794.96	-40000	PASS
25	100V	5795	0	PASS
	120V	5795	0	PASS
	120V	5794.96	-40000	PASS



Appendix A: Test Result of Conducted Test



Duty Cycle



Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
NVNT	a	5180	96.46	0.16
NVNT	a	5200	96.86	0.14
NVNT	a	5240	97.11	0.13
NVNT	n20	5180	98.02	0
NVNT	n20	5200	98.27	0
NVNT	n20	5240	98.52	0
NVNT	n40	5190	98.62	0
NVNT	n40	5230	98.95	0
NVNT	ac20	5180	98.26	0
NVNT	ac20	5200	98.36	0
NVNT	ac20	5240	98.22	0
NVNT	ac40	5190	98.22	0
NVNT	ac40	5230	98.77	0
NVNT	a	5745	96.21	0.17
NVNT	a	5785	96.54	0.15
NVNT	a	5825	97.06	0.13
NVNT	n20	5745	98.10	0
NVNT	n20	5785	98.10	0
NVNT	n20	5825	98.10	0
NVNT	n40	5755	98.05	0
NVNT	n40	5795	98.03	0
NVNT	ac20	5745	98.15	0
NVNT	ac20	5785	98.40	0
NVNT	ac20	5825	98.03	0
NVNT	ac40	5755	98.29	0
NVNT	ac40	5795	98.15	0




























Duty Cycle NVNT a 5785MHz

























Maximum Conducted Output Power



Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	12.54	0.16	12.70	24	Pass
NVNT	a	5200	12.09	0.14	12.23	24	Pass
NVNT	a	5240	12.56	0.13	12.69	24	Pass
NVNT	n20	5180	11.89	0	11.89	24	Pass
NVNT	n20	5200	12.37	0	12.37	24	Pass
NVNT	n20	5240	12.60	0	12.60	24	Pass
NVNT	n40	5190	11.16	0	11.16	24	Pass
NVNT	n40	5230	11.17	0	11.17	24	Pass
NVNT	ac20	5180	12.06	0	12.06	24	Pass
NVNT	ac20	5200	12.50	0	12.50	24	Pass
NVNT	ac20	5240	12.68	0	12.68	24	Pass
NVNT	ac40	5190	11.41	0	11.41	24	Pass
NVNT	ac40	5230	11.81	0	11.81	24	Pass
NVNT	a	5745	8.46	0.17	8.63	30	Pass
NVNT	a	5785	8.02	0.15	8.17	30	Pass
NVNT	a	5825	7.28	0.13	7.41	30	Pass
NVNT	n20	5745	8.81	0	8.81	30	Pass
NVNT	n20	5785	8.23	0	8.23	30	Pass
NVNT	n20	5825	7.91	0	7.91	30	Pass
NVNT	n40	5755	8.90	0	8.90	30	Pass
NVNT	n40	5795	8.29	0	8.29	30	Pass
NVNT	ac20	5745	9.02	0	9.02	30	Pass
NVNT	ac20	5785	8.68	0	8.68	30	Pass
NVNT	ac20	5825	7.52	0	7.52	30	Pass
NVNT	ac40	5755	9.06	0	9.06	30	Pass
NVNT	ac40	5795	8.32	0	8.32	30	Pass




















































-26dB Bandwidth



Condition	Mode	Frequency (MHz)	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	25.507	Pass
NVNT	a	5200	24.916	Pass
NVNT	a	5240	25.943	Pass
NVNT	n20	5180	28.292	Pass
NVNT	n20	5200	27.779	Pass
NVNT	n20	5240	28.005	Pass
NVNT	n40	5190	51.146	Pass
NVNT	n40	5230	49.687	Pass
NVNT	ac20	5180	27.657	Pass
NVNT	ac20	5200	27.026	Pass
NVNT	ac20	5240	26.776	Pass
NVNT	ac40	5190	50.432	Pass
NVNT	ac40	5230	50.506	Pass

























-6dB Bandwidth



Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	a	5745	16.401	0.5	Pass
NVNT	a	5785	16.401	0.5	Pass
NVNT	a	5825	16.422	0.5	Pass
NVNT	n20	5745	17.552	0.5	Pass
NVNT	n20	5785	17.595	0.5	Pass
NVNT	n20	5825	17.699	0.5	Pass
NVNT	n40	5755	36.359	0.5	Pass
NVNT	n40	5795	36.345	0.5	Pass
NVNT	ac20	5745	17.559	0.5	Pass
NVNT	ac20	5785	17.738	0.5	Pass
NVNT	ac20	5825	17.615	0.5	Pass
NVNT	ac40	5755	36.364	0.5	Pass
NVNT	ac40	5795	36.357	0.5	Pass

























Maximum Power Spectral Density Level



Condition	Mode	Frequency (MHz)	Conducted PSD (dBm)	Duty Factor (dB)	Total PSD (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	-2.19	0.16	-2.03	11	Pass
NVNT	a	5200	-1.78	0.14	-1.64	11	Pass
NVNT	a	5240	-1.43	0.13	-1.30	11	Pass
NVNT	n20	5180	-1.92	0	-1.92	11	Pass
NVNT	n20	5200	-1.52	0	-1.52	11	Pass
NVNT	n20	5240	-0.92	0	-0.92	11	Pass
NVNT	n40	5190	-6.12	0	-6.12	11	Pass
NVNT	n40	5230	-5.95	0	-5.95	11	Pass
NVNT	ac20	5180	-2.08	0	-2.08	11	Pass
NVNT	ac20	5200	-1.55	0	-1.55	11	Pass
NVNT	ac20	5240	-1.38	0	-1.38	11	Pass
NVNT	ac40	5190	-5.91	0	-5.91	11	Pass
NVNT	ac40	5230	-5.33	0	-5.33	11	Pass
NVNT	a	5745	-8.36	0.17	-8.19	30	Pass
NVNT	a	5785	-8.53	0.15	-8.38	30	Pass
NVNT	a	5825	-9.34	0.13	-9.21	30	Pass
NVNT	n20	5745	-8.01	0	-8.01	30	Pass
NVNT	n20	5785	-8.64	0	-8.64	30	Pass
NVNT	n20	5825	-8.89	0	-8.89	30	Pass
NVNT	n40	5755	-11.36	0	-11.36	30	Pass
NVNT	n40	5795	-11.33	0	-11.33	30	Pass
NVNT	ac20	5745	-7.68	0	-7.68	30	Pass
NVNT	ac20	5785	-7.99	0	-7.99	30	Pass
NVNT	ac20	5825	-9.13	0	-9.13	30	Pass
NVNT	ac40	5755	-10.87	0	-10.87	30	Pass
NVNT	ac40	5795	-11.89	0	-11.89	30	Pass














































Appendix B: Photographs of Test Setup

Refer to the test report No. TCT221124E007

Appendix C: Photographs of EUT

Refer to the test report No. TCT221124E007

*******END OF REPORT*******