

FCC 22H 24E 27L, §2.1091 – RF Exposure

FCC ID: 2A8J6-100

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenn a (mW)	Antenn a Gain (numer ic)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
WCDMA BAND 5	21.5±1	22.5	177.83	0.9333 (-0.3dBi)	0.033035	0.5509	Pass
FDD-LTE BAND 5	22±1	23	199.53	0.9333 (-0.3dBi)	0.037066	0.5515	Pass
FDD-LTE BAND 41	22±1	23	199.53	0.5715 (-2.43dBi)	0.022697	1	Pass
ANT1 2.4GWIFI	16±1	17	50.1187	2.466 (3.92dBi)	0.0246	1	Pass
ANT2 2.4GWIFI	16±1	17	50.1187	2.3174 (3.65dBi)	0.02312	1	Pass

Technology	Tune up Produce power(dBm)		Maximum Tune-up (dBm)		Antenna Gain(ANT 1/ANT 2) (numeric)	Power Density (S) (mW/ cm2)		MPE Limit (mW/ cm2)	Σ MPE Ratio	Σ MPE Ratio Limit	Result
	ANT 1	ANT 2	ANT 1	ANT 2		ANT 1	ANT 2				
2.4G WIFI MIMO	16 $\pm$ 1	16 $\pm$ 1	17	17	ANT1:2.466 (3.92dBi) ANT2:2.3174 (3.65dBi)	0.0246	0.02312	1	0.0477	1	Pass

$S=0.037066/0.5515+0.0477/1=0.114909<1$ Pass