



MPE ESTIMATION

FCC ID: 2A8KM-STD2M

1,Per FCC Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices, the limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
2.4G WIFI	2462	18.95	18±1(19)	79.43	1.5	1.41	0.02228
5.8G WIFI	5745	12.72	12±1(13)	19.95	5	3.16	0.01254

$$Pd = \frac{P_{out} * G}{4\pi r^2};$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2304141444-1E/2E**, antenna gain=1.5dBi(2.4G WIFI), 5dBi(PCB Antenna)

2.4G WIFI and 5G WIFI do not support the same transmission

The certified sample is portable device, when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion.

The test exclusion threshold is 0.02228 mW/cm² which is< 1.0mW/cm², RF Exposure testing is not required.

-----The End-----