

TEST REPORT

Product Name : Talkie Buds
Brand Mark : MoerLab
Model No. : AH185
Report Number : BLA-EMC-202309-A2002
FCC ID : 2A8MI-AH185
Date of Sample Receipt : 2023/9/7
Date of Test : 2023/9/8 to 2023/9/18
Date of Issue : 2023/9/18
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

Jiang Su Yisin Tech Co., Ltd
Rm. 103, Bldg. 1, No. 10, Wenzhou Rd., ETDZ, Shuyang County, Suqian,
Jiangsu, CN

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:

Jozu

Review by:

Sueels

Approved by:

Blue Zheng

Date:

2023/9/18



REPORT REVISE RECORD

Version No.	Date	Description
00	2023/9/18	Original

TABLE OF CONTENTS

1	TEST SUMMARY	5
2	GENERAL INFORMATION	6
3	GENERAL DESCRIPTION OF E.U.T.	6
4	TEST ENVIRONMENT	8
5	TEST MODE	8
6	MEASUREMENT UNCERTAINTY	8
7	DESCRIPTION OF SUPPORT UNIT	9
8	LABORATORY LOCATION	9
9	TEST INSTRUMENTS LIST	10
10	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	12
10.1	LIMITS	12
10.2	BLOCK DIAGRAM OF TEST SETUP	12
10.3	PROCEDURE	12
10.4	TEST DATA	14
11	CONDUCTED BAND EDGES MEASUREMENT	17
11.1	LIMITS	17
11.2	BLOCK DIAGRAM OF TEST SETUP	17
11.3	TEST DATA	18
12	RADIATED SPURIOUS EMISSIONS	19
12.1	LIMITS	19
12.2	BLOCK DIAGRAM OF TEST SETUP	20
12.3	PROCEDURE	20
12.4	TEST DATA	22
13	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	31
13.1	LIMITS	31
13.2	BLOCK DIAGRAM OF TEST SETUP	32
13.3	PROCEDURE	32
13.4	TEST DATA	34
14	CONDUCTED SPURIOUS EMISSIONS	39
14.1	LIMITS	39

14.2	BLOCK DIAGRAM OF TEST SETUP	39
14.3	TEST DATA	40
15	POWER SPECTRUM DENSITY	41
15.1	LIMITS	41
15.2	BLOCK DIAGRAM OF TEST SETUP	41
15.3	TEST DATA	41
16	CONDUCTED PEAK OUTPUT POWER	42
16.1	LIMITS	42
16.2	BLOCK DIAGRAM OF TEST SETUP	42
16.3	TEST DATA	43
17	MINIMUM 6DB BANDWIDTH	44
17.1	LIMITS	44
17.2	BLOCK DIAGRAM OF TEST SETUP	44
17.3	TEST DATA	44
18	ANTENNA REQUIREMENT	45
18.1	CONCLUSION	45
19	APPENDIX	46
APPENDIX A: PHOTOGRAPHS OF TEST SETUP		61
APPENDIX B: PHOTOGRAPHS OF EUT		63

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

2 GENERAL INFORMATION

Applicant	Jiang Su Yisin Tech Co., Ltd
Address	Rm. 103, Bldg. 1, No. 10, Wenzhou Rd., ETDZ, Shuyang County, Suqian, Jiangsu, CN
Manufacturer	Jiang Su Yisin Tech Co., Ltd
Address	Rm. 103, Bldg. 1, No. 10, Wenzhou Rd., ETDZ, Shuyang County, Suqian, Jiangsu, CN
Factory	Shenzhen Asia Universal Technology Co., Ltd.
Address	Room 05, 22nd Floor, Yishang Center, No. 22, Jiaan South Road, Baoan District, Shenzhen, China
Product Name	Talkie Buds
Test Model No.	AH185

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	N/A
Software Version	N/A
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Rate data:	1Mbps
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Internal Antenna
Antenna Gain:	-0.35dBi (Provided by the applicant)

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The Highest channel	2480MHz

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	3.7Vdc

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation.

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

9 TEST INSTRUMENTS LIST

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber 1	SKET	966	N/A	2020/11/10	2023/11/9
Chamber 2	SKET	966	N/A	2021/07/20	2024/07/19
Spectrum	R&S	FSP40	100817	2022/09/15	2024/09/14
Receiver	R&S	ESR7	101199	2022/09/15	2024/09/14
Receiver	R&S	ESPI7	101477	2023/07/14	2024/07/13
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2022/09/15	2024/09/14
Horn Antenna	Schwarzbeck	BBHA9120D	01892 P:00331	2022/09/13	2025/09/12
Amplifier	SKET	LNPA_30M01G-30	SK2021060801	2023/07/14	2024/07/13
Amplifier	SKET	PA-000318G-45	N/A	2023/09/12	2024/09/11
Amplifier	SKET	LNPA_18G40G-50	SK2022071301	2023/07/14	2024/07/13
Filter group	SKET	2.4G/5G Filter group r	N/A	2023/07/14	2024/07/13
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2022/9/14	2025/9/13
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2022/09/14	2024/09/13
LISN	R&S	ENV216	3560.6550.15	2022/09/14	2024/09/13
LISN	AT	AT166-2	AKK1806000003	2022/09/14	2024/09/13
ISN	TESEQ	ISNT8-cat6	53580	2022/09/14	2024/09/13
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01045	2023/08/16	2024/08/15
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01075	2023/08/16	2024/08/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of RF Conducted Test

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2022/09/15	2024/09/14
Spectrum	Agilent	N9020A	MY49100060	2023/09/07	2024/09/06
Spectrum	KEYSIGHT	N9030A	MY52350152	2023/06/30	2024/06/29
Spectrum	KEYSIGHT	N9010A	MY54330814	2023/06/30	2024/06/29
Signal Generator	Agilent	N5182A	MY47420955	2023/09/07	2024/09/06
Signal Generator	Agilent	E8257D	MY44320250	2023/06/30	2024/06/29
Signal Generator	Agilent	N5181A	MY46240904	2023/08/02	2024/08/01
Signal Generator	R&S	CMW500	132429	2023/09/07	2024/09/06
BluetoothTester	Anritsu	MT8852B	06262047872	2023/09/07	2024/09/06
Power probe	DARE	RPR3006W	14I00889SN042	2023/09/07	2024/09/06
DCPowersupply	zhaoxin	KXN-305D	20K305D1221363	2022/09/14	2024/09/13
DCPowersupply	zhaoxin	RXN-1505D	19R1505D050168	2022/09/14	2024/09/13
2.4GHz/5GHz RF Test software	MTS	MTS 8310	Version 2.0.0.0	N/A	N/A
Audio Analyzer	Audioprecision	N/A	ATSI-41094	2023/06/30	2024/06/29

10 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

10.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

10.2 BLOCK DIAGRAM OF TEST SETUP



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

10.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as

the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,


4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $\text{LISN} = \text{Read Level} + \text{Cable Loss} + \text{LISN Factor}$

10.4 TEST DATA

[TestMode: Transmitting mode]; [Line: Line] ;[Power:AC120V/60Hz]



Test Result: Pass

[TestMode: Transmitting mode]; [Line: Neutral] ;[Power:AC120V/60Hz]


Conducted Emission Measurement

Project No.: CE

Data :#6

2023/9/12

80.0 dBuV



Site

Limit: FCC Class B Conduction(QP)

EUT: Talkie Buds

M/N: AH185

Mode: BLE TX mode

Note:

Phase:

N

Power:

Distance:

RBW: 9 KHz

VBW: 30 KHz

Temperature: (C)

Humidity: %RH

Sweep Time: 10 ms

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	cm	degree	Comment
1		0.2980	16.80	10.07	26.87	60.30	-33.43	QP		
2		0.2980	11.53	10.07	21.60	50.30	-28.70	AVG		
3		0.7340	23.42	10.03	33.45	56.00	-22.55	QP		
4	*	0.7340	20.79	10.03	30.82	46.00	-15.18	AVG		
5		1.1980	18.29	10.03	28.32	56.00	-27.68	QP		
6		1.1980	12.87	10.03	22.90	46.00	-23.10	AVG		
7		3.4620	12.62	9.96	22.58	56.00	-33.42	QP		
8		3.4620	8.85	9.96	18.81	46.00	-27.19	AVG		
9		11.1220	19.04	9.96	29.00	60.00	-31.00	QP		
10		11.1220	10.29	9.96	20.25	50.00	-29.75	AVG		
11		13.4180	22.54	10.01	32.55	60.00	-27.45	QP		
12		13.4180	12.76	10.01	22.77	50.00	-27.23	AVG		

*:Maximum data x:Over limit !:over margin

<Reference Only

Receiver: ESPI_1

Spectrum Analyzer: ESPI

L.I.S.N:

Engineer Signature:

Test Result: Pass

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

BlueAsia


11 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

12 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

12.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

12.2 BLOCK DIAGRAM OF TEST SETUP



12.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

12.4 TEST DATA


[TestMode: TX below 1G]; [Polarity: Horizontal]



*:Maximum data x:Over limit !:over margin

Test Result: Pass

[TestMode: TX below 1G]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin

Test Result: Pass

Above 1GHz:

[TestMode: TX low channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Talkie Buds
M/N: AH185
Mode: BLE TX-L
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	41.25	4.05	45.30	74.00	-28.70	peak	
2		5606.000	41.08	6.70	47.78	74.00	-26.22	peak	
3		7206.000	39.67	7.93	47.60	74.00	-26.40	peak	
4		8026.500	41.14	8.91	50.05	74.00	-23.95	peak	
5		9608.000	38.43	10.90	49.33	74.00	-24.67	peak	
6	*	11246.00	38.01	13.56	51.57	74.00	-22.43	peak	


*:Maximum data x:Over limit !:over margin (Reference Only)

Receiver: ESR_1 Spectrum Analyzer: FSP40

Antenna: EZ 9120D 1G-18G Engineer Signature:

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin (Reference Only)

Receiver: ESR_1 Spectrum Analyzer: FSP40
Antenna: EZ 9120D 1G-18G Engineer Signature:

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Talkie Buds
M/N: AH185
Mode: BLE TX-M
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3420.500	46.78	-1.64	45.14	74.00	-28.86	peak	
2		4877.500	43.17	4.35	47.52	74.00	-26.48	peak	
3		7326.000	38.94	8.21	47.15	74.00	-26.85	peak	
4		7862.000	40.68	8.82	49.50	74.00	-24.50	peak	
5		9768.000	37.94	11.31	49.25	74.00	-24.75	peak	
6	*	10940.50	38.46	13.36	51.82	74.00	-22.18	peak	


*:Maximum data x:Over limit !:over margin (Reference Only)

Receiver: ESR_1 Spectrum Analyzer: FSP40

Antenna: EZ 9120D 1G-18G Engineer Signature:

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Vertical]




*:Maximum data x:Over limit !:over margin (Reference Only)

Receiver: ESR_1 Spectrum Analyzer: FSP40
Antenna: EZ 9120D 1G-18G Engineer Signature:

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Talkie Buds
M/N: AH185
Mode: BLE TX-H
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3491.000	46.57	-1.21	45.36	74.00	-28.64	peak	
2		4948.000	43.41	5.22	48.63	74.00	-25.37	peak	
3		7440.000	39.13	8.48	47.61	74.00	-26.39	peak	
4		8214.500	40.48	9.00	49.48	74.00	-24.52	peak	
5		9920.000	36.71	11.69	48.40	74.00	-25.60	peak	
6	*	10776.00	38.48	13.11	51.59	74.00	-22.41	peak	


*:Maximum data x:Over limit !:over margin (Reference Only)

Receiver: ESR_1 Spectrum Analyzer: FSP40

Antenna: EZ 9120D 1G-18G Engineer Signature:

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Talkie Buds
M/N: AH185
Mode: BLE TX-H
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	39.84	5.42	45.26	74.00	-28.74	peak	
2		5653.000	40.95	6.76	47.71	74.00	-26.29	peak	
3		7440.000	39.67	8.48	48.15	74.00	-25.85	peak	
4		8449.500	40.06	9.10	49.16	74.00	-24.84	peak	
5		9920.000	37.39	11.69	49.08	74.00	-24.92	peak	
6	*	11128.50	38.29	13.50	51.79	74.00	-22.21	peak	

*:Maximum data x:Over limit !:over margin (Reference Only)

Receiver: ESR_1 Spectrum Analyzer: FSP40

Antenna: EZ 9120D 1G-18G Engineer Signature:

Test Result: Pass

Remark:

1. Final Level = Receiver Read level + Correct factor
2. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

BlueAsia