FCC RF Test Report

APPLICANT	:	Quectel Wireless Solutions Co., Ltd.
EQUIPMENT	:	Smart Module
BRAND NAME	:	Quectel
MODEL NAME	:	SC668S-NA
FCC ID	:	XMR2022SC668SNA
STANDARD	:	47 CFR Part 2, 90(R)
CLASSIFICATION	:	PCS Licensed Transmitter (PCB)
TEST DATE(S)	:	Feb. 07, 2023 ~ Feb. 08, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Maximum Conducted Power and Emission Designator 6
1.5 Testing Site 6
1.6 Test Software 6
1.7 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 9
2.5 Frequency List of Low/Middle/High Channels 10

3 CONDUCTED TEST ITEMS **11**

3.1 Measuring Instruments 11
3.2 Conducted Output Power and ERP 12
3.3 Peak-to-Average Ratio 13
3.4 Occupied Bandwidth 14
3.5 Conducted Band Edge Measurement 15
3.6 Emission Mask 16
3.7 Conducted Spurious Emission Measurement 17
3.8 Frequency Stability Measurement 18

4 RADIATED TEST ITEMS **19**

4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Radiated Spurious Emission Measurement 21

5 LIST OF MEASURING EQUIPMENT **22**

6 UNCERTAINTY OF EVALUATION **23**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG311713C	Rev. 01	Initial issue of report	Apr. 21, 2023

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.2	§2.1046	Conducted Output Power	—	Reporting only	-
	§90.542 (a)(7)	Effective Radiated Power	ERP < 3Watt	PASS	-
3.3	-	Peak-to-Average Ratio	—	Reporting only	-
3.4	§2.1049	Occupied Bandwidth	—	Reporting only	-
3.5	§2.1053 §90.543 (e)(2)(3)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.6	§2.1051 §90.210(n)	Emission Mask	Mask B	PASS	-
3.7	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	-
3.8	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	< ±1.25 ppm	PASS	-
4.4	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 23.43 dB at 1584.000 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Quectel Wireless Solutions Co., Ltd.
Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233,China

1.2 Manufacturer

Quectel Wireless Solutions Co., Ltd.
Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233,China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Smart Module
Brand Name	Quectel
Model Name	SC668S-NA
FCC ID	XMR2022SC668SNA
Tx Frequency	LTE Band 14: 788 MHz ~ 798 MHz
Rx Frequency	LTE Band 14: 758 MHz ~ 768 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	22.89 dBm
Antenna Gain	4.45 dBi
Type of Modulation	QPSK / 16QAM
Antenna Type	Fixed External Antenna
IMEI Code	Conducted: D1C22LT14000058 Radiation: D1C22LT14000064
HW Version	R1.0
SW Version	SC668SNANAR02A02
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Maximum Conducted Power and Emission Designator

LTE Band 14		QPSK		16QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
5	**790.5~795.5**	0.1932	4M50G7D	0.1914	4M49W7D
10	**793**	0.1945	9M03G7D	0.1914	9M03W7D

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, Part 90(R)
- ANSI C63.26-2015
- KDB 971168 D01 Power Meas License Digital Systems v03r01
- KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (X-Plane)

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	v	-	-	-	v	v	-	-	v		v	v	v	v
	14	-	-		v	-	-	v	v	-	-	v		v		v	
Peak-to-Average Ratio	14			v	v			v	v	-	-	v		v		v	
26dB and 99% Bandwidth	14	-	-	v	v	-	-	v	v	-	-			v		v	
Conducted Band Edge	14	-	-	v		-	-	v	v	-	-	v		v	v		v
	14	-	-		v	-	-	v	v	-	-	v		v		v	
Emission Mask	14	-	-	v		-	-	v	v	-	-	v		v	v	v	v
	14	-	-		v	-	-	v	v	-	-	v		v		v	
Conducted Spurious Emission	14	-	-	v		-	-	v		-	-	v			v	v	v
	14	-	-		v	-	-	v		-	-	v				v	
Frequency Stability	14	-	-		v	-	-	v		-	-			v		v	
E.R.P	14	-	-	v		-	-	v	v	-	-	v		v	v	v	v
	14	-	-		v	-	-	v	v	-	-	v		v		v	
Radiated Spurious Emission	14	Worst Case													v	v	v
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																

2.2 Connection Diagram of Test System



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	Base Station	Anritsu	MT8820/8821	N/A	N/A	Unshielded, 1.8 m
3.	Test jig	N/A	N/A	N/A	N/A	N/A
4.	Antenna	N/A	N/A	N/A	N/A	N/A
5.	Adapter	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.20 dB

Example :

Offset(dB) = RF cable loss(dB)

= 4.20(dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 14 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge Measurement

3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.6 Emission Mask

3.6.1 Description of Emission Mask

<Emission Mask B>.

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

(1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.

(2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.

(3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 + 10 log (P) dB.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.7 Conducted Spurious Emission Measurement

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±1.25 ppm of the center frequency.

3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Feb. 07, 2023~ Feb. 08, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Feb. 07, 2023~ Feb. 08, 2023	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 15, 2022	Feb. 07, 2023~ Feb. 08, 2023	Jul. 14, 2023	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G,MAX 30dB	Oct. 12, 2022	Feb. 07, 2023	Oct. 11, 2023	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 16, 2022	Feb. 07, 2023	Oct. 15, 2023	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	May 24, 2022	Feb. 07, 2023	May 23, 2023	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1284	1GHz~18GHz	Jan. 04, 2023	Feb. 07, 2023	Jan. 03, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 04, 2023	Feb. 07, 2023	Jan. 03, 2024	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 04, 2023	Feb. 07, 2023	Jan. 03, 2024	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 04, 2023	Feb. 07, 2023	Jan. 03, 2024	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 12, 2022	Feb. 07, 2023	Oct. 11, 2023	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A02370	1Ghz-18Ghz	Oct. 12, 2022	Feb. 07, 2023	Oct. 11, 2023	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 07, 2023	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 07, 2023	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 07, 2023	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±0.48 dB
Occupied Channel Bandwidth	±0.1 %

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.3dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23℃
		Relative Humidity :	40~42%

Conducted Output Power(Average power)and ERP

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W)		
Channel				23330					
Frequency (MHz)				793				M	
10	QPSK	1	0		22.89			0.3304	
10	QPSK	1	49		22.81			0.3243	
10	QPSK	50	0		21.89			0.2624	
10	16QAM	1	0		22.82			0.3251	
Channel				23305	23330	23355	ERP(W)		
Frequency (MHz)				790.5	793	795.5	L	M	H
5	QPSK	1	0	22.85	22.86	22.80	0.3273	0.3281	0.3236
5	16QAM	1	0	22.41	22.82	22.27	0.2958	0.3251	0.2864

Peak-to-Average Ratio

Mode	LTE Band 14 / 10MHz		
Mod.	QPSK	16QAM	Limit: 13dB
RB Size	Full RB	Full RB	Result
Middle CH	4.81	6.20	PASS
Mode	LTE Band 14 / 5MHz		
Mod.	QPSK	16QAM	Limit: 13dB
RB Size	Full RB	Full RB	Result
Middle CH	3.94	3.94	PASS

LTE Band 14 / 10MHz

Middle Channel / Full RB/ QPSK



Middle Channel / Full RB/ 16QAM



LTE Band 14 / 5MHz
Middle Channel / Full RB/ QPSK



Middle Channel / Full RB/ 16QAM



26dB Bandwidth

Mode	LTE Band 14 : 26dB BW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	9.85	9.93
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	4.92	4.84

LTE Band 14

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 14

Middle Channel /5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 14 : 99%OBW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	9.03	9.03
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	4.50	4.49

LTE Band 14

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 14

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Conducted Band Edge

LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.52647 MHz	-65.60 dBm	-52.60 dB
758.000 MHz	769.000 MHz	100.000 kHz	768.54396 MHz	-64.60 dBm	-94.60 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.20779 MHz	-76.40 dBm	-41.40 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-21.50 dBm	-8.50 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.34615 MHz	20.23 dBm	-9.77 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.11089 MHz	-68.93 dBm	-33.93 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.33616 MHz	-63.76 dBm	-50.76 dB

Date: 7.FEB.2023 20:48:47

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.96204 MHz	-65.58 dBm	-52.58 dB
758.000 MHz	769.000 MHz	100.000 kHz	764.96154 MHz	-64.21 dBm	-94.21 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.00599 MHz	-76.39 dBm	-41.39 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.86364 MHz	-60.82 dBm	-47.82 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.65385 MHz	19.86 dBm	-10.14 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.83616 MHz	-58.58 dBm	-23.58 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.91558 MHz	-61.19 dBm	-48.19 dB

Date: 7.FEB.2023 21:00:53

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	757.54845 MHz	-65.70 dBm	-52.70 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.52198 MHz	-64.28 dBm	-94.28 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.43057 MHz	-76.40 dBm	-41.40 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-25.83 dBm	-12.83 dB
788.000 MHz	799.000 MHz	100.000 kHz	792.51099 MHz	6.70 dBm	-23.30 dB
799.000 MHz	805.000 MHz	6.250 kHz	800.49550 MHz	-63.71 dBm	-28.71 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.00250 MHz	-60.05 dBm	-47.05 dB

Date: 7.FEB.2023 20:53:49

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.13487 MHz	-65.73 dBm	-52.73 dB
758.000 MHz	769.000 MHz	100.000 kHz	762.64286 MHz	-64.71 dBm	-94.71 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.37163 MHz	-76.23 dBm	-41.23 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.95455 MHz	-55.22 dBm	-42.22 dB
788.000 MHz	799.000 MHz	100.000 kHz	796.50000 MHz	6.12 dBm	-23.88 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.00899 MHz	-42.27 dBm	-7.27 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.58691 MHz	-57.07 dBm	-44.07 dB

Date: 7.FEB.2023 21:05:55

LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge /1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.32567 MHz	-65.68 dBm	-52.68 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.79670 MHz	-63.99 dBm	-93.99 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.68831 MHz	-76.21 dBm	-41.21 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-22.36 dBm	-9.36 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.34615 MHz	19.47 dBm	-10.53 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.09291 MHz	-72.15 dBm	-37.15 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.79670 MHz	-64.08 dBm	-51.08 dB

Date: 7.FEB.2023 20:50:28

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.99401 MHz	-65.67 dBm	-52.67 dB
758.000 MHz	769.000 MHz	100.000 kHz	763.41209 MHz	-64.58 dBm	-94.58 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.99401 MHz	-76.26 dBm	-41.26 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.90260 MHz	-62.07 dBm	-49.07 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.66484 MHz	18.88 dBm	-11.12 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.83616 MHz	-61.41 dBm	-26.41 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.89061 MHz	-61.82 dBm	-48.82 dB

Date: 7.FEB.2023 21:02:33

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.88511 MHz	-65.70 dBm	-52.70 dB
758.000 MHz	769.000 MHz	100.000 kHz	758.74176 MHz	-64.48 dBm	-94.48 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.07093 MHz	-76.34 dBm	-41.34 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-27.06 dBm	-14.06 dB
788.000 MHz	799.000 MHz	100.000 kHz	792.13736 MHz	5.42 dBm	-24.58 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.38661 MHz	-63.84 dBm	-28.84 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.11738 MHz	-61.13 dBm	-48.13 dB

Date: 7.FEB.2023 20:52:08

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	755.28671 MHz	-65.74 dBm	-52.74 dB
758.000 MHz	769.000 MHz	100.000 kHz	764.43407 MHz	-64.33 dBm	-94.33 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.05395 MHz	-76.25 dBm	-41.25 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.94156 MHz	-53.95 dBm	-40.95 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.78571 MHz	5.26 dBm	-24.74 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.21279 MHz	-43.96 dBm	-8.96 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.66184 MHz	-57.74 dBm	-44.74 dB

Date: 7.FEB.2023 21:04:14

LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.74625 MHz	-65.61 dBm	-52.61 dB
758.000 MHz	769.000 MHz	100.000 kHz	762.43407 MHz	-64.29 dBm	-94.29 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.82418 MHz	-76.37 dBm	-41.37 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-35.64 dBm	-22.64 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.57692 MHz	20.34 dBm	-9.66 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.80220 MHz	-56.38 dBm	-21.38 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.19630 MHz	-46.45 dBm	-33.45 dB

Date: 7.FEB.2023 21:10:19

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.72228 MHz	-65.61 dBm	-52.61 dB
758.000 MHz	769.000 MHz	100.000 kHz	762.07143 MHz	-64.55 dBm	-94.55 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.67832 MHz	-76.26 dBm	-41.26 dB
775.000 MHz	788.000 MHz	100.000 kHz	779.77273 MHz	-43.64 dBm	-30.64 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.42308 MHz	19.90 dBm	-10.10 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.83217 MHz	-58.65 dBm	-23.65 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.64086 MHz	-61.10 dBm	-48.10 dB

Date: 7.FEB.2023 21:15:19

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.36264 MHz	-65.76 dBm	-52.76 dB
758.000 MHz	769.000 MHz	100.000 kHz	765.74176 MHz	-64.50 dBm	-94.50 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.66633 MHz	-76.38 dBm	-41.38 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-30.89 dBm	-17.89 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.46703 MHz	4.01 dBm	-25.99 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.00899 MHz	-45.31 dBm	-10.31 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.06743 MHz	-47.95 dBm	-34.95 dB

Date: 7.FEB.2023 21:16:59

LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.63736 MHz	-65.74 dBm	-52.74 dB
758.000 MHz	769.000 MHz	100.000 kHz	764.20330 MHz	-64.38 dBm	-94.38 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.81918 MHz	-76.35 dBm	-41.35 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-35.74 dBm	-22.74 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.57692 MHz	19.55 dBm	-10.45 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.79021 MHz	-60.65 dBm	-25.65 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.17133 MHz	-46.54 dBm	-33.54 dB

Date: 7.FEB.2023 21:11:59

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	751.73027 MHz	-65.65 dBm	-52.65 dB
758.000 MHz	769.000 MHz	100.000 kHz	758.47802 MHz	-64.43 dBm	-94.43 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.85614 MHz	-76.39 dBm	-41.39 dB
775.000 MHz	788.000 MHz	100.000 kHz	779.77273 MHz	-43.84 dBm	-30.84 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.41209 MHz	19.45 dBm	-10.55 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.85015 MHz	-63.15 dBm	-28.15 dB
805.000 MHz	810.000 MHz	100.000 kHz	806.68581 MHz	-61.41 dBm	-48.41 dB

Date: 7.FEB.2023 21:13:39

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
750.000 MHz	758.000 MHz	100.000 kHz	756.48551 MHz	-65.76 dBm	-52.76 dB
758.000 MHz	769.000 MHz	100.000 kHz	759.84066 MHz	-64.43 dBm	-94.43 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.59740 MHz	-76.42 dBm	-41.42 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-32.32 dBm	-19.32 dB
788.000 MHz	799.000 MHz	100.000 kHz	789.99451 MHz	2.31 dBm	-27.69 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.20080 MHz	-45.77 dBm	-10.77 dB
805.000 MHz	810.000 MHz	100.000 kHz	805.14735 MHz	-49.78 dBm	-36.78 dB

Date: 7.FEB.2023 21:18:39

Conducted Spurious Emission

LTE Band 14 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	632.66467 MHz	-68.98 dBm	-55.98 dB
805.000 MHz	1.000 GHz	100.000 kHz	940.89580 MHz	-68.00 dBm	-55.00 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-37.34 dBm	-24.34 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.97535 GHz	-53.37 dBm	-40.37 dB

Date: 7.FEB.2023 20:55:09

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	637.75812 MHz	-68.95 dBm	-55.95 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.92579 MHz	-67.21 dBm	-54.21 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58210 GHz	-37.11 dBm	-24.11 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.96535 GHz	-53.35 dBm	-40.35 dB

Date: 7.FEB.2023 20:57:52

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	632.66467 MHz	-68.80 dBm	-55.80 dB
805.000 MHz	1.000 GHz	100.000 kHz	805.43853 MHz	-65.17 dBm	-52.17 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58710 GHz	-37.04 dBm	-24.04 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.92686 GHz	-53.33 dBm	-40.33 dB

Date: 7.FEB.2023 20:59:12

LTE Band 14 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	634.11994 MHz	-69.01 dBm	-56.01 dB
805.000 MHz	1.000 GHz	100.000 kHz	806.21814 MHz	-47.30 dBm	-34.30 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57761 GHz	-38.24 dBm	-25.24 dB
3.000 GHz	8.000 GHz	1.000 MHz	6.91286 GHz	-53.41 dBm	-40.41 dB

Date: 7.FEB.2023 21:08:39

Mask

LTE Band 14 / 5MHz / QPSK

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Lowest Channel / 1RB





Lowest Channel / Full RB



LTE Band 14 / 5MHz / QPSK

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 5MHz / QPSK

Highest Channel / 1RB





Highest Channel / Full RB



LTE Band 14 / 5MHz / 16QAM

Highest Channel / 1RB





Highest Channel / Full RB



LTE Band 14 / 10MHz / QPSK

Middle Channel / 1RB





Middle Channel / Full RB



LTE Band 14 / 10MHz / 16QAM

Middle Channel / 1RB





Middle Channel / Full RB



Frequency Stability

Test Conditions		LTE Band 14 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0013	PASS
40	Normal Voltage	0.0034	
30	Normal Voltage	0.0021	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0006	
0	Normal Voltage	0.0023	
-10	Normal Voltage	0.0018	
-20	Normal Voltage	0.0015	
-30	Normal Voltage	0.0026	
20	Maximum Voltage	0.0007	
20	Normal Voltage	0.0008	
20	Minimum Voltage	0.0014	

Note:

1. Normal Voltage =3.8 V. ; Minimum Voltage =3.55 V. ; Maximum Voltage =4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

Field Strength of Spurious Radiated

Test Engineer :	Carry Xu	Temperature :	23~25℃
		Relative Humidity :	41~42%

LTE Band 14 / QPSK / RB Size 1 Offset 0									
Channel	Bandwidth	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
High	5MHz	1576	-67.53	-42.15	-25.38	-70.16	1.09	5.87	H
		2365.02	-60.00	-13	-47.00	-62.40	1.37	5.92	H
		3153.36	-61.68	-13	-48.68	-65.57	1.64	7.68	H
		1576.68	-66.89	-42.15	-24.74	-69.52	1.09	5.87	V
		2365.02	-60.89	-13	-47.89	-63.29	1.37	5.92	V
		3152	-61.47	-13	-48.47	-65.36	1.64	7.68	V
Middle	5MHz	1584	-66.64	-42.15	-24.49	-69.27	1.09	5.87	H
		2372.52	-60.57	-13	-47.57	-62.97	1.37	5.92	H
		3163.36	-61.46	-13	-48.46	-65.35	1.64	7.68	H
		1584	-67.03	-42.15	-24.88	-69.66	1.09	5.87	V
		2372.52	-61.31	-13	-48.31	-63.71	1.37	5.92	V
		3163.36	-61.00	-13	-48.00	-64.89	1.64	7.68	V
Low	5MHz	1584	-66.61	-42.15	-24.46	-69.24	1.09	5.87	H
		2380.02	-57.42	-13	-44.42	-59.82	1.37	5.92	H
		3176	-61.55	-13	-48.55	-65.44	1.64	7.68	H
		1584	-65.58	-42.15	-23.43	-68.21	1.09	5.87	V
		2380.02	-61.17	-13	-48.17	-63.57	1.37	5.92	V
		3176	-61.29	-13	-48.29	-65.18	1.64	7.68	V
	Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
	Test Result					PASS			

LTE Band 14 / QPSK / RB Size 1 Offset 0									
Channel	Bandwidth	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	10MHz	1576	-66.95	-42.15	-24.80	-69.58	1.09	5.87	H
		2365.77	-59.00	-13	-46.00	-61.40	1.37	5.92	H
		3154.36	-61.68	-13	-48.68	-65.57	1.64	7.68	H
		1576	-66.44	-42.15	-24.29	-69.07	1.09	5.87	V
		2365.77	-60.34	-13	-47.34	-62.74	1.37	5.92	V
		3154.36	-61.50	-13	-48.50	-65.39	1.64	7.68	V
	Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
	Test Result					PASS			