

TEST REPORT

Applicant Name: Shenzhen CWELL Electronic Technology Co., Ltd
Address: 8th Floor, Building 4, Block A, Hongchuang Technology Center,
Xikeng Community, Fucheng Street, Longhua District, 518110,
Shenzhen, China
Report Number: 2504A90225E-SA
FCC ID: 2A8NJ-V2000

Test Standard (s)

FCC 47 CFR part 2.1093

Sample Description

Product Type: 4G Feature Phone
Model No.: V2000
Multiple Model(s) No.: V3000, V4000
Trade Mark: UNIWA
Date Received: 2025-12-11
Issue Date: 2026-01-25

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Jack Yang

Jack Yang

SAR Engineer

Approved By:

Lance Li

Lance Li

SAR Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked. This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

Mode		Max. Reported SAR Level(s) (W/kg)	Limit (W/kg)
GSM 850	1g Head SAR	0.04	1.6
	1g Body SAR	0.12	
GSM 1900	1g Head SAR	0.05	
	1g Body SAR	0.28	
WCDMA Band 2	1g Head SAR	0.20	
	1g Body SAR	1.19	
WCDMA Band 4	1g Head SAR	0.18	
	1g Body SAR	1.12	
WCDMA Band 5	1g Head SAR	0.07	
	1g Body SAR	0.24	
LTE Band 2	1g Head SAR	0.29	
	1g Body SAR	1.18	
LTE Band 5	1g Head SAR	0.04	
	1g Body SAR	0.28	
LTE Band 12	1g Head SAR	0.04	
	1g Body SAR	0.35	
LTE Band 41	1g Head SAR	0.13	
	1g Body SAR	0.27	
LTE Band 66&4	1g Head SAR	0.29	
	1g Body SAR	1.06	
Simultaneous	1g Head SAR	0.66	
	1g Body SAR	1.56	

Applicable Standards	FCC 47 CFR part 2.1093 Radiation exposure evaluation: portable devices
	RF Exposure Procedures: TCB Workshop April 2019
	IEEE 1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
	KDB procedures KDB 447498 D01 General RF Exposure Guidance v06 KDB 648474 D04 Handset SAR v01r03 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D05 SAR for LTE Devices v02r05
Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in FCC 47 CFR part 2.1093 and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures. The results and statements contained in this report pertain only to the device(s) evaluated. Unless otherwise stated there are no any additions to, deviations, or exclusions from the method.	

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	5
EUT DESCRIPTION.....	6
TECHNICAL SPECIFICATION.....	6
REFERENCE, STANDARDS, AND GUIDELINES	7
SAR LIMITS	7
FACILITIES	8
DESCRIPTION OF TEST SYSTEM	9
Recommended Tissue Dielectric Parameters for Head liquid	14
EQUIPMENT LIST AND CALIBRATION	15
SAR MEASUREMENT SYSTEM VERIFICATION.....	16
LIQUID VERIFICATION	16
SYSTEM ACCURACY VERIFICATION	18
EUT TEST STRATEGY AND METHODOLOGY	20
TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR	20
CHEEK/TOUCH POSITION.....	21
EAR/TILT POSITION.....	21
TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS.....	22
TEST DISTANCE FOR SAR EVALUATION.....	22
SAR EVALUATION PROCEDURE	23
CONDUCTED OUTPUT POWER MEASUREMENT.....	24
DESCRIPTION OF TEST CONFIGURATION.....	25
Maximum Target Output Power.....	30
TEST RESULTS.....	31
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	48
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	49
STANDALONE SAR ESTIMATION:	50
SAR MEASUREMENT RESULTS.....	51
TEST RESULTS:.....	51
SAR Measurement Variability.....	62
SAR DUT HOLDER PERTURBATIONS	63
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION.....	64
SIMULTANEOUS TRANSMISSION:.....	64
SIMULTANEOUS SAR TEST EXCLUSION CONSIDERATIONS:	64
SAR Plots.....	65
APPENDIX A MEASUREMENT UNCERTAINTY	66
APPENDIX B EUT TEST POSITION PHOTOS	68
APPENDIX C CALIBRATION CERTIFICATES	69
APPENDIX D RETURN LOSS&IMPEDANCE MEASUREMENT	70

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2504A90225E-SA	Original Report	2026-01-25

EUT DESCRIPTION

This report has been prepared on behalf of **Shenzhen CWELL Electronic Technology Co., Ltd** and their product: **4G Feature Phone**, Model: **V2000, V3000, V4000**, FCC ID: 2A8NJ-V2000 or the EUT (Equipment under Test) as referred to in the rest of this report.

Note: The above models only differ in model name. Please refer to DOS letter for details. The applicant provided model "V2000" for testing.

Technical Specification

Device Type:	Portable
Exposure Category:	Population/Uncontrolled
Antenna Type(s):	Internal Antenna
Body-Worn Accessories:	None
Proximity Sensor:	None
Carrier Aggregation:	None
Operation Modes:	GSM Voice/GPRS Data, WCDMA, LTE and Bluetooth
Operation Frequency:	GSM 850:824-849MHz(TX);869-894MHz(RX) GSM 1900:1850-1910MHz(TX);1930-1990MHz(RX) WCDMA Band 2:1850-1910MHz(TX);1930-1990MHz(RX) WCDMA Band 4:1710-1755MHz(TX);2110-2155MHz(RX) WCDMA Band 5:824-849MHz(TX);869-894MHz(RX) LTE Band 2:1850-1910MHz(TX);1930-1990MHz(RX) LTE Band 4:1710-1755MHz(TX);2110-2155MHz(RX) LTE Band 5:824-849MHz(TX);869-894MHz(RX) LTE Band 12:699-716MHz(TX);729-746MHz(RX) LTE Band 41:2496-2690MHz(TX/RX) LTE Band 66:1710-1780MHz(TX);2110-2180MHz(RX)) Bluetooth:2402-2480MHz(TX/RX)
Dimensions (L*W*H):	136mm (L) *56mm (W) *14mm (H)(All models have the same size)
Rated Input Voltage:	DC 3.7V from Rechargeable Battery
Serial Number:	3E61-1
Date of Test:	2025-12-19~2025-12-27
Normal Operation:	Head, Body

REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

SAR Limits

FCC Limit(1g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.6	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that maybe incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg for 1g SAR applied to the EUT.

FACILITIES

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.


DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY8 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



DASY8 System Description

The DASY8 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer Win11 PRO and the DASY8 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY8 Measurement Server

The safeguarding equipment is connected to the DOOR CONTACTS connector of the DASY8 Measurement Server according to the diagram below. The two wire safety chains must be fully closed through all safety equipment and the DOOR CONTACTS connector on the Measurement Server to enable operation of the DASY8 system.

Data Acquisition Electronics

The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter, and a command decoder with a control logic unit. Transmission to the DASY8 Measurement Server is accomplished through an optical downlink for data and status information and an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts used for mechanical surface detection and probe collision detection.

The input impedance of both DAEs is 200M Ω ; the inputs are symmetric and floating. Common mode rejection is above 80 dB.

EX3DV4 E-Field Probes

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

SAM Twin Phantom

The SAM-Twin (Specific Anthropomorphic Mannequin) phantom has a fiberglass shell with a thickness of 2 mm, except in the ear region where the thickness is increased to 6 mm. The size of the phantom, including the top plate is 1.0×0.5m (1 full DASY8 platform slot). The filling volume is approximately 25 L. The phantom has three measurement areas, also called phantom sections, Left Head, Right Head, and Flat:

Left Head, Right Head to test exposure on the head. Please note that if the location of the peak is located in the upper part of the chin, the Chin20 phantoms should be used.

Flat to test exposure of small body-worn/hand-held devices (smartphones. . .). For larger devices (tablets, laptops) or measurements at low frequencies, the ELI phantom must be used.

Calibration Frequency Points for EX3DV4 E-Field Probes SN: 7896 Calibrated: 2025/12/11

Calibration Frequency Point (MHz)	Frequency Range (MHz)		Conversion Factor		
	From	To	X	Y	Z
750 Head	650	850	9.40	9.40	9.40
900 Head	850	1000	9.00	9.00	9.00
1750 Head	1650	1850	7.89	7.89	7.89
1900 Head	1850	2000	7.55	7.55	7.55
2300 Head	2200	2400	7.40	7.40	7.40
2450 Head	2400	2550	7.15	7.15	7.15
2600 Head	2550	2700	7.00	7.00	7.00
5250 Head	5140	5360	5.11	5.11	5.11
5600 Head	5490	5700	4.51	4.51	4.51
5800 Head	5700	5860	4.61	4.61	4.61

SAR Scan Procedures**Step 1: Power Reference Measurement**

Power reference measurements are performed during Area Scans and Zoom Scans if they have been enabled in the Application Preferences. The power reference measurements are anchored to the peak location found by the Fast Scan if available, else to the grid anchor point.

Step 2: Area Scan

Area Scans are used to determine the peak location of the measured field before doing a finer measurement around the hotspot.

Peak location can be found accurately even on coarse grids using the advanced interpolation routines implemented in DASY8. Area Scans measure a two dimensional volume covering the full device under test area. DASY8 uses Fast Averaged SAR algorithm to compute the 1 g and 10 g of simulated tissue from the Area Scan.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm $\pm$ 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm $\pm$ 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan (Cube Scan Averaging)

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue.

Zoom scans measure a three dimensional volume (cube). The bottom face of the cube is centered on the maximum of the preceding Area Scan in the same measurement group.

For maxima at border of the phantom, Auto extend zoom scan when maxima on boundary feature can be enabled in Application Preferences >> Scan Settings with Administrator access level.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1) \text{ mm}$	
Minimum zoom scan volume	x, y, z		$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power Monitoring Scan

Power monitoring scans are used to monitor the power drift of the device under test. The local SAR strength is measured at a reference position at the beginning and at the end of the scan. The power drift is computed using the formula:

$$P_{\text{drift}}[\text{dB}] = 10 \cdot \log_{10} (\text{SAR}_{\text{beginning}} / \text{SAR}_{\text{end}})$$

Power monitoring scans are available for fully integrated in Area and Zoom Scans. They can be enabled in Application Preferences >> Scan Settings.

For Area Scans, the reference point is defined as the maximum location of the preceding Fast Scan. A Fast Scan will be automatically performed if none has been performed and power monitoring is enabled. For Zoom Scans, it is defined at the first point of the measured grid.

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE1528:2013

Recommended Tissue Dielectric Parameters for Head liquid

Table A.3 – Dielectric properties of the head tissue-equivalent liquid

Frequency MHz	Relative permittivity ϵ_r	Conductivity (σ) S/m
300	45,3	0,87
450	43,5	0,87
<i>750</i>	<i>41,9</i>	<i>0,89</i>
835	41,5	0,90
900	41,5	0,97
1 450	40,5	1,20
<i>1 500</i>	<i>40,4</i>	<i>1,23</i>
<i>1 640</i>	<i>40,2</i>	<i>1,31</i>
<i>1 750</i>	<i>40,1</i>	<i>1,37</i>
1 800	40,0	1,40
1 900	40,0	1,40
2 000	40,0	1,40
<i>2 100</i>	<i>39,8</i>	<i>1,49</i>
<i>2 300</i>	<i>39,5</i>	<i>1,67</i>
2 450	39,2	1,80
<i>2 600</i>	<i>39,0</i>	<i>1,96</i>
3 000	38,5	2,40
<i>3 500</i>	<i>37,9</i>	<i>2,91</i>
<i>4 000</i>	<i>37,4</i>	<i>3,43</i>
<i>4 500</i>	<i>36,8</i>	<i>3,94</i>
<i>5 000</i>	<i>36,2</i>	<i>4,45</i>
<i>5 200</i>	<i>36,0</i>	<i>4,66</i>
<i>5 400</i>	<i>35,8</i>	<i>4,86</i>
<i>5 600</i>	<i>35,5</i>	<i>5,07</i>
<i>5 800</i>	<i>35,3</i>	<i>5,27</i>
<i>6 000</i>	<i>35,1</i>	<i>5,48</i>

NOTE For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5 800 MHz are provided (i.e. the values shown *in italics*). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6 000 MHz that were linearly extrapolated from the values at 3 000 MHz and 5 800 MHz.

EQUIPMENT LIST AND CALIBRATION


Equipment's List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52 52.10.4	N/A	NCR	NCR
DASY5 Measurement Server	DASY5 6.0.31	N/A	NCR	NCR
Data Acquisition Electronics	DAE4	1724	2025/03/14	2026/03/13
E-Field Probe	EX3DV4	7896	2025/12/11	2026/12/10
Mounting Device	MD4HHTV5	SD 000 H01 KA	NCR	NCR
SAM Twin Phantom	SAM-Twin V8.0	2124	NCR	NCR
Dipole, 750MHz	D750V3	1194	2023/2/17	2026/2/16
Dipole, 835MHz	D835V2	4d103	2024/12/02	2027/12/01
Dipole, 1800MHz	D1800V2	2d018	2023/9/26	2026/9/25
Dipole, 1900MHz	D1900V2	5d128	2024/12/2	2027/12/1
Dipole, 2600MHz	D2600V2	1073	2023/2/17	2026/2/16
Simulated Tissue Liquid Head(500-9500MHz)	HBBL600-10000V6	220406-1	Each Time	/
Network Analyzer	E5071B	MY42403851	2025/9/18	2026/9/17
Wideband Radio Communication Tester	CMW500	110566	2025/9/18	2026/9/17
Dielectric Assessment Kit	DAK-3.5	1320	NCR	NCR
Signal Generator	N5183A	MY47420360	2025/8/28	2026/8/27
Power Sensor	E9301A	MY55270006	2025/9/17	2026/9/16
Power Amplifier(80 – 1000MHz)	CBA 1G-070	T44328	2025/9/17	2026/9/16
Linear Power Amplifier (1 – 6GHz)	AS0860-40/45	1060913	2025/9/17	2026/9/16
Directional Coupler	4226-20	3315	2025/9/18	2026/9/17
6dB Attenuator	WA59-6-33	A329	NCR	NCR
Spectrum Analyzer	FSV40	101949	2025/9/17	2026/9/16
Thermometer	DTM3000	N/A	2025/9/18	2026/9/17
Temperature & Humidity Meter	JB913R	GZ-WS004	2025/9/18	2026/9/17

NCR: No Calibration Required.

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ' (S/m)	ϵ_r	σ' (S/m)	$\Delta\epsilon_r$	$\Delta\sigma'$ (S/m)	
704	Simulated Tissue Liquid Head	42.563	0.898	42.14	0.89	1.00	0.90	±5
707.5	Simulated Tissue Liquid Head	42.557	0.899	42.12	0.89	1.04	1.01	±5
711	Simulated Tissue Liquid Head	42.550	0.900	42.10	0.89	1.07	1.12	±5
750	Simulated Tissue Liquid Head	42.477	0.908	41.90	0.89	1.38	2.02	±5

*Liquid Verification above was performed on 2025/12/19

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ' (S/m)	ϵ_r	σ' (S/m)	$\Delta\epsilon_r$	$\Delta\sigma'$ (S/m)	
824.2	Simulated Tissue Liquid Head	42.571	0.920	41.55	0.90	2.46	2.22	±5
826.4	Simulated Tissue Liquid Head	42.502	0.922	41.54	0.90	2.32	2.44	±5
829	Simulated Tissue Liquid Head	42.422	0.924	41.52	0.90	2.17	2.67	±5
835	Simulated Tissue Liquid Head	42.236	0.929	41.50	0.90	1.77	3.22	±5
836.5	Simulated Tissue Liquid Head	42.189	0.931	41.50	0.90	1.66	3.44	±5
836.6	Simulated Tissue Liquid Head	42.186	0.931	41.50	0.90	1.65	3.44	±5
844	Simulated Tissue Liquid Head	41.956	0.937	41.50	0.91	1.10	2.97	±5
846.6	Simulated Tissue Liquid Head	41.876	0.939	41.50	0.91	0.91	3.19	±5
848.8	Simulated Tissue Liquid Head	41.807	0.941	41.50	0.91	0.74	3.41	±5

*Liquid Verification above was performed on 2025/12/21

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ' (S/m)	ϵ_r	σ' (S/m)	$\Delta\epsilon_r$	$\Delta\sigma'$ (S/m)	
1712.4	Simulated Tissue Liquid Head	40.691	1.381	40.13	1.35	1.40	2.30	± 5
1720	Simulated Tissue Liquid Head	40.857	1.374	40.12	1.35	1.84	1.78	± 5
1732.6	Simulated Tissue Liquid Head	41.130	1.363	40.11	1.36	2.54	0.22	± 5
1745	Simulated Tissue Liquid Head	41.399	1.351	40.10	1.37	3.24	-1.39	± 5
1752.6	Simulated Tissue Liquid Head	41.456	1.352	40.09	1.37	3.41	-1.31	± 5
1770	Simulated Tissue Liquid Head	41.105	1.391	40.06	1.38	2.61	0.80	± 5
1800	Simulated Tissue Liquid Head	40.501	1.458	40.00	1.40	1.25	4.14	± 5

*Liquid Verification above was performed on 2025/12/23

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ' (S/m)	ϵ_r	σ' (S/m)	$\Delta\epsilon_r$	$\Delta\sigma'$ (S/m)	
1850.2	Simulated Tissue Liquid Head	40.947	1.463	40.00	1.40	2.37	4.50	± 5
1852.4	Simulated Tissue Liquid Head	40.980	1.462	40.00	1.40	2.45	4.43	± 5
1860	Simulated Tissue Liquid Head	41.091	1.457	40.00	1.40	2.73	4.07	± 5
1880	Simulated Tissue Liquid Head	41.384	1.445	40.00	1.40	3.46	3.21	± 5
1900	Simulated Tissue Liquid Head	41.678	1.433	40.00	1.40	4.19	2.36	± 5
1907.6	Simulated Tissue Liquid Head	41.654	1.419	40.00	1.40	4.14	1.36	± 5
1909.8	Simulated Tissue Liquid Head	41.647	1.415	40.00	1.40	4.12	1.07	± 5

*Liquid Verification above was performed on 2025/12/25

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ' (S/m)	ϵ_r	σ' (S/m)	$\Delta\epsilon_r$	$\Delta\sigma'$ (S/m)	
2506	Simulated Tissue Liquid Head	39.654	1.814	39.12	1.85	1.37	-1.95	± 5
2549.5	Simulated Tissue Liquid Head	39.253	1.896	39.07	1.91	0.47	-0.73	± 5
2593	Simulated Tissue Liquid Head	40.068	1.974	39.00	1.95	2.74	1.23	± 5
2600	Simulated Tissue Liquid Head	40.202	1.987	39.00	1.96	3.08	1.38	± 5
2636.5	Simulated Tissue Liquid Head	40.378	2.045	38.96	2.00	3.64	2.25	± 5
2680	Simulated Tissue Liquid Head	40.587	2.031	38.90	2.04	4.34	-0.44	± 5

*Liquid Verification above was performed on 2025/12/27


System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- $s = 15 \text{ mm} \pm 0,2 \text{ mm}$ for $300 \text{ MHz} \leq f \leq 1\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $1\,000 \text{ MHz} < f \leq 6\,000 \text{ MHz}$;

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band (MHz)	Liquid Type	Input Power (mW)	Measured SAR (W/kg)		Normalized to 1W (W/kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2025/12/19	750	Head	100	1g	0.800	8.0	8.57	-6.651	± 10
2025/12/21	835	Head	100	1g	0.922	9.22	9.54	-3.354	± 10
2025/12/23	1800	Head	100	1g	3.84	38.4	39.3	-2.290	± 10
2025/12/25	1900	Head	100	1g	3.81	38.1	40.1	-4.988	± 10
2025/12/27	2600	Head	100	1g	5.28	52.8	56.8	-7.042	± 10

Note:

All the SAR values are normalized to 1Watt forward power.

SAR SYSTEM VALIDATION DATA


Please Refer to the Attachment of System Check.

EUT TEST STRATEGY AND METHODOLOGY

Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper $\frac{1}{4}$ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point". The "test device reference point" should be located at the same level as the center of the earpiece region. The "vertical centerline" should bisect the front surface of the handset at its top and bottom edges. A "ear reference point" is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the "phantom reference plane" defined by the three lines joining the center of each "ear reference point" (left and right) and the tip of the mouth.


A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the "N-F" line defined along the base of the ear spacer that contains the "ear reference point". For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane". This is called the "initial ear position". While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



Cheek/Touch Position

1. The device is brought toward the mouth of the head phantom by pivoting against the “ear reference point” or along the “N-F” line for the SCC-34/SC-2 head phantom.
2. This test position is established:
 3. When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.
 4. (or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.
5. For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek /Touch Position



Ear/Tilt Position

With the handset aligned in the “Cheek/Touch Position”:


1) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.

2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the “test device reference point” until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15° to 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the “Cheek/Touch” and “Ear/Tilt” positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional.

for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

Ear /Tilt 15° Position



Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

Test Distance for SAR Evaluation

In this case the EUT(Equipment Under Test) is set 5mm away from the phantom, the test distance is 5mm for body.

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.


All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.


CONDUCTED OUTPUT POWER MEASUREMENT

Test Procedure

The RF output of the transmitter was connected to the input of the Wireless Communication Test Set through Attenuator.



The RF output of the transmitter was connected to the input port of the Power Sensor through Attenuator.



Description of Test Configuration

EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in each operation mode.
Equipment Modifications:	No
EUT Exercise Software:	No

GSM/GPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900
 Press Connection control to choose the different menus
 Press RESET > choose all the reset all settings
 Connection Press Signal Off to turn off the signal and change settings
 Network Support > GSM + GPRS
 Main Service > Packet Data
 Service selection > Test Mode A – Auto Slot Config. off
 MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting
 > Slot configuration > Uplink/Gamma
 > 33 dBm for GPRS 850
 > 30 dBm for GPRS 1900
 BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel
 Frequency Offset > + 0 Hz
 Mode > BCCH and TCH
 BCCH Level > -85 dBm (May need to adjust if link is not stable)
 BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]
 Channel Type > Off
 P0 > 4 dB
 Slot Config > Unchanged (if already set under MS signal)
 TCH > choose desired test channel
 Hopping > Off

Main Timeslot > 3
 Network Coding Scheme > CS4 (GPRS)
 Bit Stream > 2E9-1 PSR Bit Stream
 AF/Rf Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
 Connection Press Signal on to turn on the signal and change settings

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP

TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP

TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4

WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	$\beta_d(SF)$	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	Ahs= β_{hs}/β_c	30/15			

HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	Ahs= β_{hs}/β_c	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9

	Reference E_FCI's	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27
--	-------------------	--	--	--

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		

HSPA+

Sub-test	β_c (Note3)	β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105
Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0). Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default. Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value. Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.											

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4.-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	N/A
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

TDD-LTE

LTE TDD Band 41 supports 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

We used configuration 0 for LTE TDD SAR test, that is 63.33%(1:1.58)for duty cycle.

Maximum Target Output Power

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
GSM 850	33.5	33.5	33.5
GPRS 1 TX Slot	33.5	33.5	33.5
GPRS 2 TX Slot	32	32	32
GPRS 3 TX Slot	30	30	30
GPRS 4 TX Slot	28	28	28
GSM 1900	30	30	30
GPRS 1 TX Slot	30	30	30
GPRS 2 TX Slot	27.5	27.5	27.5
GPRS 3 TX Slot	26	26	26
GPRS 4 TX Slot	24	24	24
WCDMA Band 2(RMC)	23	23	23
WCDMA Band 2(HSDPA/HSUPA/DC-HSDPA/HSPA+)	22	22	22
WCDMA Band 4	22	22	22
WCDMA Band 5(RMC)	24	24	24
WCDMA Band 5(HSDPA/HSUPA/DC-HSDPA/HSPA+)	23	23	23
LTE Band 2 1RB	24	24	24
LTE Band 2 50%RB	22.5	22.5	22.5
LTE Band 2 100%RB	22.5	22.5	22.5
LTE Band 4 1RB	24.5	24.5	24.5
LTE Band 4 50%RB	24	24	24
LTE Band 4 100%RB	23.5	23.5	23.5
LTE Band 5 1RB	24.5	24.5	24.5
LTE Band 5 50%RB	24	24	24
LTE Band 5 100%RB	23.5	23.5	23.5
LTE Band 12 1RB	24.5	24.5	24.5
LTE Band 12 50%RB	23.5	23.5	23.5
LTE Band 12 100%RB	23.5	23.5	23.5
LTE Band 41 1RB	23.6	23.6	23.6
LTE Band 41 50%RB	22.5	22.5	22.5
LTE Band 41 100%RB	22.5	22.5	22.5
LTE Band 66 1RB	25	25	25
LTE Band 66 50%RB	24	24	24
LTE Band 66 100%RB	23.5	23.5	23.5
BT	8	7	8
BT(Additional Channel)	9.5		

Test Results**GSM:**

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	251	848.8	33.05
	128	824.2	32.82
	190	836.6	32.95
GSM 1900	810	1909.8	29.78
	512	1850.2	29.84
	661	1880	29.91

GPRS:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	33.11	31.64	29.74	27.76
	190	836.6	32.82	31.53	29.76	27.70
	251	848.8	32.95	31.49	29.67	27.67
GSM 1900	512	1850.2	29.76	27.22	25.60	23.60
	661	1880	29.83	27.16	25.52	23.53
	810	1909.8	29.92	27.39	25.61	23.46

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power for GSM

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	251	848.8	24.05
	128	824.2	23.82
	190	836.6	23.95
GSM 1900	810	1909.8	20.78
	512	1850.2	20.84
	661	1880	20.91

The time based average power for GPRS

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	24.11	25.64	25.49	24.76
	190	836.6	23.82	25.53	25.51	24.70
	251	848.8	23.95	25.49	25.42	24.67
GSM 1900	512	1850.2	20.76	21.22	21.35	20.60
	661	1880	20.83	21.16	21.27	20.53
	810	1909.8	20.92	21.39	21.36	20.46

Note:

1. Rohde & Schwarz Radio Communication Tester (CMW500) was used for the measurement of GSM peak and average output power for active timeslots.
2. For GSM voice, 1 timeslot has been activated with power level 5 (850 MHz band) and 0 (1900 MHz band).
3. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3(850 MHz band) and 3(1900 MHz band).

WCDMA:**WCDMA Band 2:**

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA	22.59	22.67	22.71
HSDPA Subset 1	21.22	20.65	20.64
HSDPA Subset 2	21.22	20.46	20.79
HSDPA Subset 3	21.27	20.55	20.77
HSDPA Subset 4	21.23	20.65	20.82
HSUPA Subset 1	21.33	20.56	20.79
HSUPA Subset 2	21.26	20.49	20.98
HSUPA Subset 3	21.24	20.63	20.89
HSUPA Subset 4	21.20	20.62	20.93
HSUPA Subset 5	21.35	20.56	20.88
DC-HSDPA Subset 1	21.00	21.26	21.07
DC-HSDPA Subset 2	21.10	21.38	21.04
DC-HSDPA Subset 3	21.12	21.30	21.04
DC-HSDPA Subset 4	21.21	21.13	21.09
HSPA+ Subset 1	20.99	20.82	20.88

WCDMA Band 4:

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA	21.88	21.96	21.79
HSDPA Subset 1	21.50	21.84	21.27
HSDPA Subset 2	21.59	21.74	21.20
HSDPA Subset 3	21.50	21.95	21.06
HSDPA Subset 4	21.57	21.71	20.96
HSUPA Subset 1	21.44	21.77	20.93
HSUPA Subset 2	21.57	21.79	21.05
HSUPA Subset 3	21.68	21.94	21.19
HSUPA Subset 4	21.60	21.97	21.08
HSUPA Subset 5	21.62	21.86	20.94
DC-HSDPA Subset 1	21.94	21.70	21.12
DC-HSDPA Subset 2	21.94	21.75	21.21
DC-HSDPA Subset 3	21.83	21.70	21.06
DC-HSDPA Subset 4	21.93	21.78	21.05
HSPA+ Subset 1	21.89	21.68	21.18

WCDMA Band 5:

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA	23.47	23.54	23.56
HSDPA Subset 1	21.84	21.83	21.78
HSDPA Subset 2	21.70	21.89	21.69
HSDPA Subset 3	21.87	21.93	21.71
HSDPA Subset 4	21.77	21.89	21.66
HSUPA Subset 1	21.96	22.08	21.78
HSUPA Subset 2	21.78	21.83	21.86
HSUPA Subset 3	21.75	22.00	21.79
HSUPA Subset 4	21.88	22.14	21.80
HSUPA Subset 5	21.99	21.98	21.82
DC-HSDPA Subset 1	22.01	21.93	21.96
DC-HSDPA Subset 2	21.77	21.92	21.91
DC-HSDPA Subset 3	21.74	21.86	21.99
DC-HSDPA Subset 4	21.72	21.84	21.80
HSPA+ Subset 1	21.84	21.97	21.96

Note:

1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in All 1.
2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than $\frac{1}{4}$ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

LTE Band 2:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	23.31	23.23	23.44
		RB1#3	23.28	23.23	23.35
		RB1#5	23.21	23.38	23.39
		RB3#0	23.22	22.92	23.35
		RB3#1	23.19	23.04	23.29
		RB3#3	23.11	23.12	23.41
		RB6#0	22.17	22.09	22.15
	16QAM	RB1#0	22.56	22.22	22.48
		RB1#3	22.50	22.07	22.40
		RB1#5	22.59	22.25	22.38
		RB3#0	22.21	21.98	22.60
		RB3#1	22.15	22.02	22.68
		RB3#3	22.17	22.14	22.56
		RB6#0	21.28	20.72	21.36
3M	QPSK	RB1#0	23.28	23.15	23.30
		RB1#8	23.15	23.31	23.41
		RB1#14	23.06	23.40	23.39
		RB8#0	22.11	22.03	22.26
		RB8#4	22.03	22.08	22.37
		RB8#7	21.94	22.02	22.25
		RB15#0	22.16	22.03	22.19
	16QAM	RB1#0	22.52	22.20	22.41
		RB1#8	22.52	22.11	22.34
		RB1#14	22.43	22.24	22.40
		RB8#0	21.01	21.15	21.21
		RB8#4	21.05	21.53	21.34
		RB8#7	21.08	21.44	21.15
		RB15#0	21.19	21.03	21.18
5M	QPSK	RB1#0	23.11	22.89	23.13
		RB1#12	23.05	22.92	23.18
		RB1#24	23.16	22.81	23.19
		RB12#0	22.07	22.07	22.31
		RB12#7	21.95	22.10	22.27
		RB12#13	22.01	22.08	22.27
		RB25#0	22.11	22.00	22.43
	16QAM	RB1#0	22.33	21.66	21.86
		RB1#12	22.35	21.81	21.94
		RB1#24	22.49	21.93	21.90
		RB12#0	21.07	21.08	21.27
		RB12#7	21.04	21.50	21.37
		RB12#13	21.05	21.49	21.21
		RB25#0	21.09	21.08	21.43

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	23.05	23.04	23.38
		RB1#25	23.24	22.98	23.42
		RB1#49	23.17	23.04	23.42
		RB25#0	22.04	21.97	22.25
		RB25#12	22.09	21.99	22.21
		RB25#25	22.05	22.22	22.25
		RB50#0	22.08	22.04	22.20
	16QAM	RB1#0	22.95	21.90	22.59
		RB1#25	22.96	21.97	22.74
		RB1#49	23.01	22.20	22.76
		RB25#0	21.09	21.46	21.65
		RB25#12	21.10	21.17	21.40
		RB25#25	21.47	21.54	21.38
		RB50#0	21.07	21.06	21.21
15M	QPSK	RB1#0	23.30	22.99	23.40
		RB1#37	23.16	23.17	23.51
		RB1#74	23.23	23.06	23.38
		RB36#0	22.06	22.12	22.17
		RB36#20	22.04	22.19	22.25
		RB36#39	22.11	22.05	22.25
		RB75#0	22.05	22.13	22.11
	16QAM	RB1#0	22.90	22.58	22.71
		RB1#37	22.94	22.58	22.82
		RB1#74	22.86	22.81	22.92
		RB36#0	21.00	21.25	21.04
		RB36#20	21.43	21.40	21.44
		RB36#39	21.36	21.31	21.21
		RB75#0	21.37	21.10	21.49
20M	QPSK	RB1#0	23.40	23.42	23.33
		RB1#49	23.39	23.37	23.48
		RB1#99	23.52	23.59	23.54
		RB50#0	22.03	21.96	22.05
		RB50#24	22.12	21.99	22.01
		RB50#50	22.19	22.38	22.15
		RB100#0	22.05	22.25	22.28
	16QAM	RB1#0	21.85	21.46	21.90
		RB1#49	21.98	21.35	22.05
		RB1#99	21.96	21.57	22.12
		RB50#0	21.03	21.04	21.02
		RB50#24	21.38	21.06	21.09
		RB50#50	21.32	21.41	21.07
		RB100#0	21.36	21.03	21.18

LTE Band 4:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	24.20	24.12	24.02
		RB1#3	24.27	24.25	24.07
		RB1#5	24.16	24.24	24.06
		RB3#0	23.90	23.95	23.99
		RB3#1	23.95	23.93	23.91
		RB3#3	23.93	23.99	23.94
		RB6#0	23.00	22.99	23.00
	16QAM	RB1#0	23.12	22.99	23.69
		RB1#3	23.10	23.11	23.67
		RB1#5	23.16	23.04	23.59
		RB3#0	23.02	23.33	23.60
		RB3#1	22.96	23.35	23.61
		RB3#3	23.14	23.28	23.65
		RB6#0	22.23	22.28	22.19
3M	QPSK	RB1#0	24.11	24.25	24.03
		RB1#8	24.12	24.15	23.97
		RB1#14	24.07	24.18	24.05
		RB8#0	23.00	23.07	23.06
		RB8#4	23.03	23.09	22.94
		RB8#7	22.91	22.98	22.97
		RB15#0	23.06	23.11	23.07
	16QAM	RB1#0	23.11	22.99	23.12
		RB1#8	23.10	23.11	23.04
		RB1#14	23.18	22.98	23.04
		RB8#0	22.36	21.93	21.92
		RB8#4	22.43	22.01	21.75
		RB8#7	22.05	21.99	21.83
		RB15#0	22.34	22.00	22.27
5M	QPSK	RB1#0	24.17	24.08	24.08
		RB1#12	24.07	24.02	24.04
		RB1#24	24.13	24.05	24.12
		RB12#0	22.98	23.02	22.98
		RB12#7	22.97	23.02	23.02
		RB12#13	23.01	23.01	22.98
		RB25#0	23.01	23.10	23.02
	16QAM	RB1#0	23.26	22.59	22.88
		RB1#12	23.25	22.63	22.97
		RB1#24	23.21	22.54	22.94
		RB12#0	22.28	21.91	22.48
		RB12#7	21.87	21.96	22.15
		RB12#13	21.90	21.93	22.19
		RB25#0	22.10	22.09	22.33

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	24.09	23.99	24.08
		RB1#25	24.05	24.05	24.06
		RB1#49	24.09	24.02	24.12
		RB25#0	22.97	22.88	22.88
		RB25#12	22.90	23.10	22.88
		RB25#25	23.13	23.03	23.11
		RB50#0	23.01	23.13	23.00
	16QAM	RB1#0	23.83	22.83	23.54
		RB1#25	23.70	22.88	23.48
		RB1#49	23.81	22.84	23.63
		RB25#0	21.97	22.17	22.56
		RB25#12	21.98	22.20	22.57
		RB25#25	22.47	22.15	22.08
		RB50#0	21.91	22.12	22.53
15M	QPSK	RB1#0	24.28	24.18	24.09
		RB1#37	24.24	24.26	24.07
		RB1#74	24.18	24.20	23.99
		RB36#0	22.94	22.94	22.97
		RB36#20	22.98	23.11	22.92
		RB36#39	22.99	23.02	23.09
		RB75#0	23.02	23.05	23.08
	16QAM	RB1#0	23.64	23.60	23.62
		RB1#37	23.67	23.66	23.59
		RB1#74	23.71	23.70	23.54
		RB36#0	21.83	22.06	22.61
		RB36#20	22.38	22.12	22.56
		RB36#39	22.01	22.44	22.54
		RB75#0	22.45	22.17	22.52
20M	QPSK	RB1#0	23.99	24.05	23.92
		RB1#49	23.96	24.32	24.15
		RB1#99	24.05	24.28	24.03
		RB50#0	22.93	22.93	23.05
		RB50#24	22.92	23.11	23.09
		RB50#50	23.03	23.03	23.07
		RB100#0	22.99	23.09	23.02
	16QAM	RB1#0	23.25	23.23	23.13
		RB1#49	23.21	23.34	22.99
		RB1#99	23.38	23.36	23.14
		RB50#0	21.95	22.45	21.99
		RB50#24	22.41	22.11	22.51
		RB50#50	21.85	22.56	22.54
		RB100#0	22.45	22.14	22.55

LTE Band 5:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	24.21	24.25	24.21
		RB1#3	24.12	24.42	24.08
		RB1#5	24.27	24.25	24.19
		RB3#0	23.97	23.96	23.90
		RB3#1	23.91	23.95	23.88
		RB3#3	23.90	23.94	23.94
		RB6#0	22.84	23.13	23.27
	16QAM	RB1#0	23.28	23.32	23.70
		RB1#3	23.27	23.63	23.96
		RB1#5	23.39	23.53	23.96
		RB3#0	23.26	23.71	23.21
		RB3#1	23.18	23.59	23.47
		RB3#3	23.13	23.55	23.53
		RB6#0	22.04	22.84	22.23
3M	QPSK	RB1#0	24.22	24.37	24.31
		RB1#8	24.11	24.26	24.39
		RB1#14	24.36	24.41	24.18
		RB8#0	23.10	23.13	23.25
		RB8#4	23.01	23.13	23.07
		RB8#7	23.18	23.21	23.27
		RB15#0	23.10	23.15	23.05
	16QAM	RB1#0	23.34	23.40	23.84
		RB1#8	23.19	23.54	23.88
		RB1#14	23.46	23.50	23.90
		RB8#0	22.15	22.54	22.52
		RB8#4	22.17	22.77	22.53
		RB8#7	22.42	22.64	22.06
		RB15#0	22.07	22.58	22.78
5M	QPSK	RB1#0	24.28	24.14	24.04
		RB1#12	24.14	24.09	24.15
		RB1#24	24.21	24.27	24.21
		RB12#0	23.14	23.12	23.33
		RB12#7	23.12	23.26	23.24
		RB12#13	23.19	23.24	23.27
		RB25#0	23.23	23.05	23.08
	16QAM	RB1#0	23.40	23.40	22.74
		RB1#12	23.58	23.48	22.80
		RB1#24	23.53	23.36	22.85
		RB12#0	22.09	22.63	22.40
		RB12#7	22.21	22.70	22.63
		RB12#13	22.18	22.69	22.51
		RB25#0	22.41	22.84	22.77

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	24.35	24.29	24.23
		RB1#25	24.31	24.46	24.34
		RB1#49	24.41	24.38	24.28
		RB25#0	23.31	23.47	23.32
		RB25#12	23.21	23.59	23.17
		RB25#25	23.24	23.46	23.12
		RB50#0	23.27	23.02	23.16
	16QAM	RB1#0	23.70	23.23	22.97
		RB1#25	23.94	23.38	23.08
		RB1#49	23.76	23.42	23.05
		RB25#0	22.07	22.63	22.33
		RB25#12	22.11	22.70	22.72
		RB25#25	22.47	22.27	22.86
		RB50#0	22.29	22.80	22.65

LTE Band 12:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	24.05	24.04	23.88
		RB1#3	23.96	23.98	23.96
		RB1#5	24.02	24.16	23.88
		RB3#0	23.44	23.47	23.49
		RB3#1	23.41	23.41	23.40
		RB3#3	23.41	23.48	23.34
		RB6#0	22.85	22.79	22.62
	16QAM	RB1#0	23.16	23.27	23.52
		RB1#3	23.15	23.11	23.66
		RB1#5	23.02	23.06	23.68
		RB3#0	22.89	23.21	23.06
		RB3#1	22.97	23.19	23.20
		RB3#3	22.99	23.17	23.19
		RB6#0	21.81	22.04	22.41
3M	QPSK	RB1#0	24.10	24.07	23.87
		RB1#8	23.99	24.11	23.85
		RB1#14	24.07	23.97	23.87
		RB8#0	23.17	22.95	22.74
		RB8#4	22.94	22.84	22.88
		RB8#7	22.98	22.80	22.78
		RB15#0	22.95	22.85	22.73
	16QAM	RB1#0	23.85	23.43	23.57
		RB1#8	23.83	23.24	23.46
		RB1#14	23.67	23.13	23.40
		RB8#0	22.16	22.20	22.11
		RB8#4	22.15	22.05	22.07
		RB8#7	22.70	22.07	22.47
		RB15#0	22.01	21.97	21.91
5M	QPSK	RB1#0	24.07	23.58	23.74
		RB1#12	24.02	23.63	24.01
		RB1#24	23.94	23.66	23.97
		RB12#0	22.90	23.07	22.80
		RB12#7	22.93	23.04	22.86
		RB12#13	22.88	22.89	22.70
		RB25#0	22.94	22.73	22.75
	16QAM	RB1#0	22.82	22.87	22.23
		RB1#12	22.80	22.57	22.38
		RB1#24	23.23	22.73	22.35
		RB12#0	22.08	22.44	22.05
		RB12#7	22.44	22.01	22.09
		RB12#13	22.39	21.88	21.71
		RB25#0	22.63	21.81	21.94

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	24.10	23.82	24.04
		RB1#25	24.11	24.09	24.02
		RB1#49	24.14	24.15	24.08
		RB25#0	22.98	23.07	22.84
		RB25#12	23.49	23.04	22.76
		RB25#25	22.89	23.23	22.65
		RB50#0	23.28	22.91	22.77
	16QAM	RB1#0	23.73	22.61	23.43
		RB1#25	24.06	22.78	23.30
		RB1#49	23.64	22.61	23.29
		RB25#0	22.41	22.51	22.00
		RB25#12	22.39	22.12	22.04
		RB25#25	22.45	22.16	22.06
		RB50#0	22.45	21.97	21.97

LTE Band 41:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	2549.5 MHz (dBm)	Middle Channel (dBm)	2636.5 MHz (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	22.15	22.04	22.24	23.39	23.30
		RB1#12	22.04	22.11	22.34	23.30	23.16
		RB1#24	22.05	22.10	22.36	23.29	23.36
		RB12#0	21.19	21.33	21.16	22.44	22.42
		RB12#7	21.38	21.31	21.20	22.45	22.42
		RB12#13	21.16	21.12	21.41	22.45	22.49
		RB25#0	21.15	21.23	21.19	22.39	22.42
	16QAM	RB1#0	21.62	21.61	21.73	22.79	22.64
		RB1#12	21.69	21.67	21.81	22.84	22.88
		RB1#24	21.62	21.60	21.89	22.86	22.76
		RB12#0	20.54	20.59	20.53	21.55	21.50
		RB12#7	20.51	20.51	20.54	21.50	21.53
		RB12#13	20.59	20.57	20.54	21.53	21.55
		RB25#0	20.55	20.55	20.60	21.53	21.58
10M	QPSK	RB1#0	22.18	22.16	22.16	23.34	23.29
		RB1#25	22.26	22.30	22.35	23.45	23.41
		RB1#49	22.31	22.19	22.36	23.46	23.46
		RB25#0	21.11	21.20	21.28	22.32	22.32
		RB25#12	21.26	21.16	21.36	22.41	22.40
		RB25#25	21.32	21.19	21.34	22.51	22.41
		RB50#0	21.07	21.19	21.38	22.39	22.32
	16QAM	RB1#0	21.34	21.19	22.74	23.01	22.90
		RB1#25	21.11	21.18	23.12	23.14	23.17
		RB1#49	21.27	21.14	23.08	23.19	23.09
		RB25#0	20.56	20.57	20.58	21.49	21.48
		RB25#12	20.52	20.55	20.53	21.51	21.42
		RB25#25	20.53	20.58	20.56	21.44	21.51
		RB50#0	20.57	20.58	20.52	21.49	21.56
15M	QPSK	RB1#0	22.18	22.20	22.23	23.34	23.30
		RB1#37	22.34	22.22	22.38	23.37	23.40
		RB1#74	22.24	22.25	22.41	23.45	23.41
		RB36#0	21.10	21.16	21.32	22.43	22.52
		RB36#20	21.32	21.34	21.39	22.42	22.41
		RB36#39	21.16	21.18	21.30	22.41	22.34
		RB75#0	21.15	21.09	21.34	22.38	22.41
	16QAM	RB1#0	21.15	21.21	21.63	23.39	23.26
		RB1#37	21.18	21.29	21.98	23.43	23.44
		RB1#74	21.12	21.11	21.97	23.40	23.44
		RB36#0	20.55	20.53	20.53	21.51	21.51
		RB36#20	20.57	20.55	20.51	21.58	21.66
		RB36#39	20.58	20.51	20.63	21.63	21.73
		RB75#0	20.53	20.50	20.50	21.56	21.63

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	2549.5 MHz (dBm)	Middle Channel (dBm)	2636.5 MHz (dBm)	High Channel (dBm)
20M	QPSK	RB1#0	22.15	22.17	22.43	22.96	23.15
		RB1#49	22.25	22.14	22.79	23.14	23.32
		RB1#99	22.43	22.31	22.88	23.25	23.47
		RB50#0	21.04	21.05	21.56	22.28	22.20
		RB50#24	21.08	21.21	21.72	22.39	22.29
		RB50#50	21.29	21.21	21.67	22.29	22.35
		RB100#0	21.15	21.18	21.89	21.90	21.97
	16QAM	RB1#0	21.75	21.74	21.68	21.83	21.76
		RB1#49	21.87	21.87	21.91	21.83	21.90
		RB1#99	21.76	21.80	21.65	22.20	22.22
		RB50#0	20.58	20.59	20.58	21.40	21.41
		RB50#24	20.61	20.59	20.51	21.53	21.64
		RB50#50	20.50	20.57	20.59	21.50	21.49
		RB100#0	20.66	20.66	20.64	21.49	21.50

LTE Band 66:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	24.36	24.30	24.26
		RB1#3	24.49	24.33	24.19
		RB1#5	24.43	24.40	24.24
		RB3#0	23.97	23.95	23.85
		RB3#1	23.92	23.84	23.93
		RB3#3	23.96	23.86	23.99
		RB6#0	23.32	23.23	23.02
	16QAM	RB1#0	23.89	23.54	23.75
		RB1#3	23.86	23.49	23.85
		RB1#5	23.85	23.65	23.94
		RB3#0	23.60	23.19	23.27
		RB3#1	23.53	23.19	23.22
		RB3#3	23.52	23.21	23.24
		RB6#0	22.37	22.19	21.95
3M	QPSK	RB1#0	24.31	24.15	24.33
		RB1#8	24.27	24.22	24.38
		RB1#14	24.43	24.17	24.25
		RB8#0	23.28	23.20	23.07
		RB8#4	23.22	23.10	23.18
		RB8#7	23.30	23.34	23.10
		RB15#0	23.43	23.09	23.15
	16QAM	RB1#0	23.87	23.89	23.57
		RB1#8	23.91	23.81	23.63
		RB1#14	24.00	23.80	23.64
		RB8#0	22.20	22.42	22.13
		RB8#4	22.16	22.27	22.01
		RB8#7	22.31	22.30	22.14
		RB15#0	22.32	22.22	21.95
5M	QPSK	RB1#0	24.40	24.11	24.09
		RB1#12	24.43	24.11	24.01
		RB1#24	24.44	24.10	24.08
		RB12#0	23.33	23.16	22.98
		RB12#7	23.37	23.24	23.03
		RB12#13	23.38	23.28	23.09
		RB25#0	23.28	23.34	23.06
	16QAM	RB1#0	22.85	23.39	22.92
		RB1#12	22.89	23.44	22.95
		RB1#24	22.93	23.43	22.92
		RB12#0	22.19	22.39	22.02
		RB12#7	22.17	22.26	22.02
		RB12#13	22.19	22.22	21.89
		RB25#0	22.44	22.20	22.28

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	24.30	24.15	24.08
		RB1#25	24.30	24.24	24.12
		RB1#49	24.39	24.39	24.24
		RB25#0	23.32	23.22	23.10
		RB25#12	23.38	23.24	23.12
		RB25#25	23.32	23.19	23.18
		RB50#0	23.44	23.34	23.16
	16QAM	RB1#0	23.89	23.67	23.64
		RB1#25	23.96	23.63	23.71
		RB1#49	24.02	23.60	23.74
		RB25#0	22.29	22.28	22.08
		RB25#12	22.20	22.11	22.05
		RB25#25	22.33	22.23	22.00
		RB50#0	22.27	22.23	22.12
15M	QPSK	RB1#0	24.33	24.15	24.30
		RB1#37	24.30	24.11	24.38
		RB1#74	24.37	24.13	24.27
		RB36#0	23.34	23.13	22.99
		RB36#20	23.42	23.33	23.11
		RB36#39	23.31	23.22	23.15
		RB75#0	23.20	23.17	23.12
	16QAM	RB1#0	23.88	23.78	23.66
		RB1#37	23.90	23.85	23.61
		RB1#74	24.04	23.85	23.54
		RB36#0	22.06	22.21	22.00
		RB36#20	22.12	22.21	21.93
		RB36#39	22.14	22.09	22.02
		RB75#0	22.27	22.09	22.06
20M	QPSK	RB1#0	24.35	24.11	24.36
		RB1#49	24.53	24.27	24.24
		RB1#99	24.54	24.42	24.49
		RB50#0	23.65	23.51	23.53
		RB50#24	23.66	23.58	23.57
		RB50#50	23.67	23.57	23.55
		RB100#0	23.26	23.24	23.17
	16QAM	RB1#0	23.25	23.31	22.93
		RB1#49	23.31	23.35	23.03
		RB1#99	23.43	23.26	23.08
		RB50#0	22.23	22.05	22.03
		RB50#24	22.27	21.99	21.96
		RB50#50	22.22	22.17	22.02
		RB100#0	22.25	22.15	21.98

Bluetooth:

Mode	Channel frequency (MHz)	Duty cycle (%)	RF Output Power (dBm)
GFSK	2402	/	6.84
	2441		5.49
	2480		6.63
$\pi/4$ -DQPSK	2402	/	7.36
	2441		5.85
	2480		7.43
8DPSK	2402	/	7.24
	2441		5.86
	2480		7.69

Additional Channel power:

Mode	Channel frequency (MHz)	Duty cycle (%)	RF Output Power (dBm)
GFSK	2409	/	8.87
$\pi/4$ -DQPSK	2408	/	9.38
8DPSK	2406	/	9.45

STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

Antennas Location:

Top

Left

Right

EUT Front View

Bluetooth ANT

WWAN Main ANT

Bottom

Antenna Distance To Edge(TRX)

Antenna Distance To Edge(mm)						
Antenna	Back	Front	Left	Right	Top	Bottom
WWAN Antenna(GSM/WCDMA/LTE)	< 5	10	< 5	< 5	120	< 5
BT Antenna	< 5	10	< 5	50	69	58

Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
BT	2480	9.5	8.91	0	2.8	3	YES

NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

According to KDB 447498 D01 General RF Exposure Guidance v06, clause 4.3. General SAR test exclusion guidance:

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

Standalone SAR estimation:

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Estimated (W/kg)
BT Head	2480	9.5	8.91	0	0.37@1g
BT Body	2480	9.5	8.91	5	0.37@1g

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})} / x]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetry evaluation.

Test Results:

Temperature:	20.2-21.7℃	20.5-21.6℃	20.4-21.8℃	20.3-21.6℃	20.5-21.8℃
Relative Humidity:	43-55%	42-57%	44-59%	41-56%	40-58%
ATM Pressure:	101.4 kPa	101.2 kPa	101.5 kPa	101.3 kPa	101.1 kPa
Test Date:	2025/12/19	2025/12/21	2025/12/23	2025/12/25	2025/12/27

Testing was performed by Devon Liang, Jack Yang, Ryse Chai.

GSM 850:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	824.2	GSM	/	/	/	/	/	/
	836.6	GSM	32.82	33.5	1.169	0.023	0.03	/
	848.8	GSM	/	/	/	/	/	/
Head Left Tilt	824.2	GSM	/	/	/	/	/	/
	836.6	GSM	32.82	33.5	1.169	0.023	0.03	/
	848.8	GSM	/	/	/	/	/	/
Head Right Cheek	824.2	GSM	/	/	/	/	/	/
	836.6	GSM	32.82	33.5	1.169	0.03	0.04	1#
	848.8	GSM	/	/	/	/	/	/
Head Right Tilt	824.2	GSM	/	/	/	/	/	/
	836.6	GSM	32.82	33.5	1.169	0.026	0.03	/
	848.8	GSM	/	/	/	/	/	/
Body Front (5mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	31.53	32.0	1.114	0.022	0.02	/
	848.8	GPRS	/	/	/	/	/	/
Body Back (5mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	31.53	32.0	1.114	0.104	0.12	2#
	848.8	GPRS	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is $> 0.5\text{ dB}$, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 3DL+2UL is the worst case.
6. The head only supports GSM voice mode.
7. The Body test is based on the mode with the highest average power.

GSM 1900:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1850.2	GSM	/	/	/	/	/	/
	1880	GSM	29.84	30.0	1.038	0.048	0.05	3#
	1909.8	GSM	/	/	/	/	/	/
Head Left Tilt	1850.2	GSM	/	/	/	/	/	/
	1880	GSM	29.84	30.0	1.038	0.022	0.02	/
	1909.8	GSM	/	/	/	/	/	/
Head Right Cheek	1850.2	GSM	/	/	/	/	/	/
	1880	GSM	29.84	30.0	1.038	0.031	0.03	/
	1909.8	GSM	/	/	/	/	/	/
Head Right Tilt	1850.2	GSM	/	/	/	/	/	/
	1880	GSM	29.84	30.0	1.038	0.002	0.01	/
	1909.8	GSM	/	/	/	/	/	/
Body Front (5mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	27.16	27.5	1.081	0.094	0.10	/
	1909.8	GPRS	/	/	/	/	/	/
Body Back (5mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	27.16	27.5	1.081	0.257	0.28	4#
	1909.8	GPRS	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is $> 0.5\text{ dB}$, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 3DL+2UL is the worst case.
6. The head only supports GSM voice mode.
7. The Body test is based on the mode with the highest average power.

WCDMA Band 2:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	22.67	23.0	1.079	0.183	0.20	5#
	1907.6	RMC	/	/	/	/	/	/
Head Left Tilt	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	22.67	23.0	1.079	0.045	0.05	/
	1907.6	RMC	/	/	/	/	/	/
Head Right Cheek	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	22.67	23.0	1.079	0.169	0.18	/
	1907.6	RMC	/	/	/	/	/	/
Head Right Tilt	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	22.67	23.0	1.079	0.033	0.04	/
	1907.6	RMC	/	/	/	/	/	/
Body Front (5mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	22.67	23.0	1.079	0.591	0.64	/
	1907.6	RMC	/	/	/	/	/	/
Body Back (5mm)	1852.4	RMC	22.59	23.0	1.099	1.08	1.19	6#
	1880	RMC	22.67	23.0	1.079	1.05	1.13	/
	1907.6	RMC	22.71	23.0	1.069	1.07	1.14	/

WCDMA Band 4:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	21.96	22.0	1.009	0.183	0.18	7#
	1752.6	RMC	/	/	/	/	/	/
Head Left Tilt	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	21.96	22.0	1.009	0.067	0.07	/
	1752.6	RMC	/	/	/	/	/	/
Head Right Cheek	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	21.96	22.0	1.009	0.171	0.17	/
	1752.6	RMC	/	/	/	/	/	/
Head Right Tilt	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	21.96	22.0	1.009	0.07	0.07	/
	1752.6	RMC	/	/	/	/	/	/
Body Front (5mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	21.96	22.0	1.009	0.704	0.71	/
	1752.6	RMC	/	/	/	/	/	/
Body Back (5mm)	1712.4	RMC	21.88	22.0	1.028	1.09	1.12	8#
	1732.6	RMC	21.96	22.0	1.009	1.08	1.09	/
	1752.6	RMC	21.79	22.0	1.050	1.05	1.10	/

WCDMA Band 5:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.54	24.0	1.112	0.062	0.07	9#
	846.6	RMC	/	/	/	/	/	/
Head Left Tilt	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.54	24.0	1.112	0.057	0.06	/
	846.6	RMC	/	/	/	/	/	/
Head Right Cheek	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.54	24.0	1.112	0.026	0.03	/
	846.6	RMC	/	/	/	/	/	/
Head Right Tilt	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.54	24.0	1.112	0.019	0.02	/
	846.6	RMC	/	/	/	/	/	/
Body Front (5mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.54	24.0	1.112	0.024	0.03	/
	846.6	RMC	/	/	/	/	/	/
Body Back (5mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.54	24.0	1.112	0.218	0.24	10#
	846.6	RMC	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same antenna while testing SAR.
3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC(reference measurement Channel) Configured in All 1.
4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than $\frac{1}{4}$ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is $< 75\%$ of SAR limit.
5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

LTE Band 2:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	23.59	24.0	1.099	0.155	0.17	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	22.38	22.5	1.028	0.141	0.14	/
Head Left Tilt	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	23.59	24.0	1.099	0.065	0.07	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	22.38	22.5	1.028	0.025	0.03	/
Head Right Cheek	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	23.59	24.0	1.099	0.264	0.29	11#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	22.38	22.5	1.028	0.201	0.21	/
Head Right Tilt	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	23.59	24.0	1.099	0.049	0.05	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	22.38	22.5	1.028	0.046	0.05	/
Body Front (5mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	23.59	24.0	1.099	0.549	0.60	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	22.38	22.5	1.028	0.458	0.47	/
Body Back (5mm)	1860	20	1RB	23.52	24.0	1.117	1.01	1.13	/
	1880	20	1RB	23.59	24.0	1.099	1.07	1.18	12#
	1900	20	1RB	23.54	24.0	1.112	0.93	1.03	/
	1880	20	50%RB	22.38	22.5	1.028	0.746	0.77	/
	1880	20	100%RB	22.25	22.5	1.059	0.709	0.75	/

LTE Band 5:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.46	24.5	1.009	0.041	0.04	13#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.59	24.0	1.099	0.033	0.04	/
Head Left Tilt	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.46	24.5	1.009	0.035	0.04	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.59	24.0	1.099	0.028	0.03	/
Head Right Cheek	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.46	24.5	1.009	0.03	0.03	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.59	24.0	1.099	0.024	0.03	/
Head Right Tilt	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.46	24.5	1.009	0.028	0.03	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.59	24.0	1.099	0.024	0.03	/
Body Front (5mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.46	24.5	1.009	0.026	0.03	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.59	24.0	1.099	0.02	0.02	/
Body Back (5mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.46	24.5	1.009	0.28	0.28	14#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.59	24.0	1.099	0.21	0.23	/

LTE Band 12:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.15	24.5	1.084	0.031	0.03	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	23.23	23.5	1.064	0.025	0.03	/
Head Left Tilt	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.15	24.5	1.084	0.022	0.02	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	23.23	23.5	1.064	0.017	0.02	/
Head Right Cheek	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.15	24.5	1.084	0.036	0.04	15#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	23.23	23.5	1.064	0.027	0.03	/
Head Right Tilt	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.15	24.5	1.084	0.023	0.02	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	23.23	23.5	1.064	0.019	0.02	/
Body Front (5mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.15	24.5	1.084	0.055	0.06	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	23.23	23.5	1.064	0.025	0.03	/
Body Back (5mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.15	24.5	1.084	0.319	0.35	16#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	23.23	23.5	1.064	0.254	0.27	/

LTE Band 41:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.88	23.6	1.180	0.074	0.09	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	21.67	22.5	1.211	0.053	0.06	/
Head Left Tilt	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.88	23.6	1.180	0.024	0.03	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	21.67	22.5	1.211	0.016	0.02	/
Head Right Cheek	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.88	23.6	1.180	0.113	0.13	17#
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	21.67	22.5	1.211	0.086	0.10	/
Head Right Tilt	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.88	23.6	1.180	0.013	0.02	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	21.67	22.5	1.211	0.012	0.01	/
Body Front (5mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.88	23.6	1.180	0.061	0.07	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	21.67	22.5	1.211	0.048	0.06	/
Body Back (5mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	22.88	23.6	1.180	0.23	0.27	18#
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	21.67	22.5	1.211	0.18	0.22	/

LTE Band 66&4:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	24.42	25.0	1.143	0.179	0.20	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	23.57	24.0	1.104	0.137	0.15	/
Head Left Tilt	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	24.42	25.0	1.143	0.079	0.09	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	23.57	24.0	1.104	0.063	0.07	/
Head Right Cheek	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	24.42	25.0	1.143	0.255	0.29	19#
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	23.57	24.0	1.104	0.193	0.21	/
Head Right Tilt	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	24.42	25.0	1.143	0.08	0.09	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	23.57	24.0	1.104	0.063	0.07	/
Body Front (5mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	24.42	25.0	1.143	0.621	0.71	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	23.57	24.0	1.104	0.464	0.51	/
Body Back (5mm)	1720	20	1RB	24.54	25.0	1.112	0.828	0.92	/
	1745	20	1RB	24.42	25.0	1.143	0.927	1.06	/
	1770	20	1RB	24.49	25.0	1.125	0.941	1.06	20#
	1745	20	50%RB	23.57	24.0	1.104	0.694	0.77	/
	1745	20	100%RB	23.24	23.5	1.062	0.713	0.76	/

Note:

1. The frequency range of LTE Band 41 is 2496~2690MHz. Per KDB 447498 D01, according to the following formula Calculate N_c is 5.

2. KDB procedures the following should be applied to determine the number of required test channels. The test channels should be evenly spread across the transmission frequency band of each wireless mode.

$$N_c = \text{Round}\{[100(f_{\text{high}} - f_{\text{low}})/f_c]^{0.5} \times (f_c/100)^{0.2}\},$$

where

- N_c is the number of test channels, rounded to nearest integer,
- f_{high} and f_{low} are the highest and lowest channel frequencies within the transmission band,
- f_c is the mid-band channel frequency,
- all frequencies are in MHz.

3. The power class 3 used for LTE Band 41 SAR testing.

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.

2. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 v02r05 SAR for LTE Devices.

3. KDB 941225 D05 v02r05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is $> 0.5\text{ dB}$ higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is $> 1.45\text{ W/kg}$

4. KDB 941225 D05 v02r05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is $< 1.45\text{ W/kg}$, tests for the remaining required test channels are optional.

5. KDB 941225 D05 v02r05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are $\leq 0.8\text{ W/kg}$.

6. KDB 941225 D05 v02r05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
7. KDB 941225 D05 v02r05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is > 0.5 dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.
8. The E-UTRA Operating Band 4 is a subset of band 66, and they are same in modulation type, therefore, they were considered as one frequency band during SAR measurement.

SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results:

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The Highest Measured SAR Configuration in Each Frequency Band

Body

SAR probe calibration point)	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
1900 Head	WCDMA Band 2	1852.4	Body Back	1.08	1.05	1.03
1750 Head	WCDMA Band 4	1712.4	Body Back	1.09	1.02	1.07

Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 .
2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements.

SAR DUT HOLDER PERTURBATIONS

In accordance with TCB workshop October 2016:

1) SAR perturbation due to test device holders, depending on antenna locations, buttons locations on phones or device, form factor (e.g. dongles etc.), the measured SAR could be influenced by the relative positions of the test device and its holder

2) SAR measurement standards have included protocols to evaluate this with a flat phantom, with and without the device holder

3) When the highest reported SAR of an antenna is > 1.2 W/kg, holder perturbation verification is required for each antenna, using the highest SAR configuration among all applicable frequency bands in the same exact device and holder positions used for head and body SAR measurements; i.e. same device/button locations in the holder

PerIEEE 1528: 2013/Annex E/E.4.1.1: Device holder perturbation tolerance for a specific test device: Type B
When it is unknown if a device holder perturbs the fields of a test device, the SAR uncertainty shall be assessed with a flat phantom (see Clause 5) by comparing the SAR with and without the device holder according to the following tests:

The SAR tolerance for device holder disturbance is computed using Equation (E.21) and entered in the corresponding row of the appropriate uncertainty table with an assumed rectangular probability distribution and $\nu_i = \infty$ degrees of freedom:

$$SAR_{\text{tolerance}} [\%] = 100 \times \left(\frac{SAR_{\text{w/holder}} - SAR_{\text{w/o holder}}}{SAR_{\text{w/o holder}}} \right) \quad (\text{E.21})$$

The Highest Measured SAR Configuration among all applicable Frequency Band

Head

Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		The Device holder perturbation uncertainty
			With holder	Without holder	
/	/	/	/	/	/

Body

Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		The Device holder perturbation uncertainty
			With holder	Without holder	
/	/	/	/	/	/

SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA/LTE) + Bluetooth	√	×

Simultaneous SAR test exclusion considerations:

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		Σ SAR < 1.6W/kg
		SAR1	SAR2	
WWAN(GSM/WCDMA/LTE) + Bluetooth	Head	0.29	0.37	0.66
	Body	1.19	0.37	1.56

Conclusion:

Sum of SAR: Σ SAR $\leq$ 1.6 W/kg therefore simultaneous transmission SAR with Volume Scans is **not required**.

SAR Plots

Please Refer to the Attachment.

APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/ Uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard Uncertainty ± %, (1 g)	Standard Uncertainty ± %, (10 g)
Measurement system							
Probe calibration	7.5	N	1	1	1	7.5	7.5
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Modulation response	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions—reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	3.9	R	$\sqrt{3}$	1	1	2.3	2.3
Test sample related							
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Device holder uncertainty	4.5	N	1	1	1	4.5	4.5
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
SAR scaling	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Phantom and tissue parameters							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.9	1.6
Liquid conductivity measurement	5.5	N	1	0.78	0.71	4.3	3.9
Liquid permittivity measurement	2.9	N	1	0.23	0.26	0.7	0.8
Liquid conductivity—temperature uncertainty	1.7	R	$\sqrt{3}$	0.78	0.71	0.8	0.7
Liquid permittivity—temperature uncertainty	2.7	R	$\sqrt{3}$	0.23	0.26	0.4	0.4

Combined standard uncertainty		RSS				12.8	12.7
Expanded uncertainty 95 % confidence interval)						25.6	25.3

APPENDIX B EUT TEST POSITION PHOTOS

Please Refer to the Attachment.

APPENDIX C CALIBRATION CERTIFICATES

Please Refer to the Attachment.

APPENDIX D RETURN LOSS&IMPEDANCE MEASUREMENT

Please Refer to the Attachment.

******* END OF REPORT *******