

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

|                     |                                                                                                          |
|---------------------|----------------------------------------------------------------------------------------------------------|
| Product Description | Wireless Speaker Cup                                                                                     |
| Test Model          | Tiki Tumblerz                                                                                            |
| Series Model        | Coastal Cupz, Music Mugz, BC-001, BC-002, BC-003, BC-004, BC-005, BC-006, BC-007, BC-008, BC-009, BC-010 |
| FCC ID              | 2A8R8-BS3                                                                                                |

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

BLE:

$P_t = -9.353 \text{ dBm} = 0.12 \text{ mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.12 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.440(\text{GHz})}] = 0.037 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

BR/EDR:

$P_t = -7.685 \text{ dBm} = 0.17 \text{ mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (0.17 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.441(\text{GHz})}] = 0.053 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.