


TEST REPORT

Applicant: Fibocom Auto Inc.
EUT Description: 5G Module
Model: AN758-NA
Brand: Fibocom
FCC ID: 2A8RBAN758NA
Standards: FCC 47 CFR Part 2.1091
Date of Receipt: 2025/02/27
Date of Issue: 2025/04/11

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.



Huang Kun
Approved By:



Chen Chengfu
Reviewed By:

Revision History

Rev.	Issue Date	Description	Revised by
01	2025/03/28	Original	Chen Chengfu
02	2025/04/11	Updated the Tune up of GSM 1900, LTE Band 48, NR Band n48/n77/78.	Chen Chengfu

Table of Contents

1	General Description	4
1.1	Lab Information.....	4
1.1.1	Testing Location	4
1.1.2	Test Facility / Accreditations	4
1.2	Client Information	4
1.2.1	Applicant.....	4
1.2.2	Manufacturer.....	4
1.3	Product Information.....	5
2	Maximum Permissible RF Exposure	7
2.1	RF Exposure Limit Introduction	7
2.2	Equations	8
3	RF Exposure Results	9
3.1	Standalone Exposure Calculations	9
3.2	Multiple Sources Exposure Calculations.....	11

1 General Description

1.1 Lab Information

1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014

Tel.: +86-755-27212361

Contact Email: info@towewireless.com

1.1.2 Test Facility / Accreditations

A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory. Designation Number: CN1353.

ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0152

Company Number: 31000

1.2 Client Information

1.2.1 Applicant

Applicant:	Fibocom Auto Inc.
Address:	13th Floor,Building A,Building 6,Shenzhen International Innovation Valley,Xili Community,Xili Street,Nanshan District,Shenzhen

1.2.2 Manufacturer

Manufacturer:	Fibocom Auto Inc.
Address:	13th Floor,Building A,Building 6,Shenzhen International Innovation Valley,Xili Community,Xili Street,Nanshan District,Shenzhen

1.3 Product Information

EUT Description:	5G Module	
Model:	AN758-NA	
Brand:	Fibocom	
Hardware Version:	V1.0	
Software Version:	/	
IMEI:	862818061792653	
Antenna Type:	☒ External, ☐ Integrated	
Power Class:	Class 2: NR Band 41; NR Band 77; NR Band 78; Class 3: Others;	
Antenna Gain:	Band	Ant (dBi)
	GSM 850	1.32
	PCS 1900	1.93
	WCDMA Band II	1.93
	WCDMA Band IV	2.86
	WCDMA Band V	1.32
	LTE Band 2	1.93
	LTE Band 4	2.86
	LTE Band 5	1.32
	LTE Band 7	1.07
	LTE Band 12	1.58
	LTE Band 13	1.94
	LTE Band 14	2.19
	LTE Band 17	1.58
	LTE Band 25	1.93
	LTE Band 26 (814 ~ 824 MHz)	1.61
	LTE Band 26 (824 ~ 849 MHz)	1.32
	LTE Band 38	0.93
	LTE Band 41	1.52
	LTE Band 48	1.99
	LTE Band 66	3.53
	LTE Band 71	0
	NR Band n2	1.93
	NR Band n5	1.32
	NR Band n7	1.07
	NR Band n12	1.58
	NR Band n14	2.19
	NR Band n25	1.93
	NR Band n38	0.93
	NR Band n41	1.52
	NR Band n48	1.99

	NR Band n66	3.53
	NR Band n71	0
	NR Band n77 (3450 to 3550 MHz)	1.42
	NR Band n77 (3700 to 3980 MHz)	3.27
	NR Band n78 (3450 to 3550 MHz)	1.42
	NR Band n78 (3700 to 3800 MHz)	2.58
LTE CA/ENDC Mode:	LTE CA: LTE UL CA_48C; LTE UL CA_66C; ENDC: DC_71A_n78A; DC_4A_n78A; DC_5A_n78A; DC_7A_n78A; DC_2A_n78A; DC_12A_n78A; DC_5A_n77A; DC_66A_n77A; DC_7A_n77A; DC_14A_n77A; DC_13A_n77A; DC_2A_n77A; DC_12A_n77A; DC_25A_n77A; DC_26A_n77A;	
Remark: The above EUT's information was declared by applicant, please refer to the specifications or user manual for more detailed description.		

2 Maximum Permissible RF Exposure

2.1 RF Exposure Limit Introduction

§1.1310 the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b).

- (1) Table 1 to § 1.1310(e)(1) sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3~3.0	614	1.63	*(100)	≤6
3.0~30	1842/f	4.89/f	*(900/f ²)	<6
30~300	61.4	0.163	1.0	<6
300~1500			f/300	<6
1500~100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3~1.34	614	1.63	*(100)	<30
1.34~30	824/f	2.19/f	*(180/f ²)	<30
30~300	27.5	0.073	0.2	<30
300~1500			f/1500	<30
1500~100000			1.0	<30

Note: f = frequency in MHz. * = Plane-wave equivalent power density.

- (2) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. The phrase *fully aware* in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. In situations when an untrained person is transient through a location where occupational/controlled limits apply, he or she must be made aware of the potential for exposure and be supervised by trained personnel pursuant to § 1.1307(b)(2) of this part where use of time averaging is required to ensure compliance with the general population exposure limit. The phrase exercise control means that an exposed person is allowed and also knows how to reduce or avoid exposure by administrative or engineering work practices, such as use of personal protective equipment or time averaging of exposure.
- (3) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure. For example, RF sources intended for consumer use shall be subject to the limits for general population/uncontrolled exposure in this section.

The MPE was calculated at 20cm to show compliance with the power density limit.

2.2 Equations

Power Density is given by:

$$S = \frac{\text{EIRP}}{4\pi R^2}$$

Where:

S = Power density in mW/cm²

EIRP= Equivalent isotropic Radiated power in mW

R = Distance from transmitting antenna in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

Distance:

$$R = \sqrt{\frac{\text{EIRP}}{4\pi S}}$$

Where:

S = Power density in mW/cm²

EIRP= Equivalent isotropic Radiated power in mW

R = Distance from transmitting antenna in cm

EIRP:

$$\text{EIRP} = P + G$$

Where:

EIRP = Equivalent isotropic Radiated power in Mw

P = Output power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

Source-Based Duty Cycle:

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

Source-based time-averaged EIRP = (DC / 100)* EIRP

Where:

DC = Duty Cycle in %, as applicable

EIRP= Equivalent isotropic Radiated power in mW

MIMO and colocated transmitters (identical limit for all transmitters):

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the PG (in linear units) of each transmitter.

Total EIRP = (EIRP 1) + (EIRP 2) + ... + (EIRP n)

MIMO and colocated transmitters:

For multiple colocated transmitters operating simultaneously in frequency bands where different limit apply:

The power density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as

Power density of chain or transmitter / limit applicable to the chain or transmitter.

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

3 RF Exposure Results

3.1 Standalone Exposure Calculations

For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.

The manufacturing configures output power so that the maximum power, after accounting for manufacturing tolerances, will never exceed the maximum power level measured.

The antenna gain in the tables below is the maximum antenna gain among various channels within the specified band.

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	EIRP/ERP (dBm)	EIRP/ERP Limit (dBm)	EIRP/ERP (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Gain According to EIRP/ERP (dBi)	Gain According to Pd (dBi)	Maximum Gain Allowed (dBi)	Results
GSM 850	824.2	1.32	35.00	34.17	38.45	314.7748	0.0517	0.5495	5.60	11.58	5.60	Pass
PCS 1900	1850.2	1.93	31.00	32.93	33.00	236.5920	0.0734	1.0000	2.00	13.27	2.00	Pass
WCDMA Band II	1852.4	1.93	25.70	27.63	33.00	579.4287	0.1798	1.0000	7.30	9.38	7.30	Pass
WCDMA Band IV	1712.4	2.86	25.70	28.56	30.00	717.7943	0.2759	1.0000	4.30	8.45	4.30	Pass
WCDMA Band V	826.4	1.32	25.70	24.87	38.45	306.9022	0.0504	0.5509	14.90	11.70	11.70	Pass
LTE Band 2	1850.7	1.93	25.70	27.63	33.00	579.4287	0.1798	1.0000	7.30	9.38	7.30	Pass
LTE Band 4	1710.7	2.86	25.70	28.56	30.00	717.7943	0.2759	1.0000	4.30	8.45	4.30	Pass
LTE Band 5	824.70	1.32	25.70	24.87	38.45	306.9022	0.0504	0.5498	14.90	11.69	11.69	Pass
LTE Band 7	2502.50	1.07	25.70	26.77	33.00	475.3352	0.1210	1.0000	7.30	10.24	7.30	Pass
LTE Band 12	699.7	1.58	25.70	25.13	34.77	325.8367	0.0568	0.4665	11.22	10.72	10.72	Pass
LTE Band 13	779.5	1.94	25.70	25.49	34.77	353.9973	0.0671	0.5197	11.22	10.82	10.82	Pass
LTE Band 14	790.5	2.19	25.70	25.74	34.77	374.9730	0.0753	0.5270	11.22	10.64	10.64	Pass
LTE Band 17	706.5	1.58	25.70	25.13	34.77	325.8367	0.0568	0.4710	11.22	10.76	10.76	Pass
LTE Band 25	1850.7	1.93	25.70	27.63	33.00	579.4287	0.1798	1.0000	7.30	9.38	7.30	Pass
LTE Band 26 (814 to 824 MHz)	814.7	1.61	25.70	25.16	50.00	328.0953	0.0576	0.5431	26.45	11.35	11.35	Pass
LTE Band 26 (824 to 849 MHz)	824.7	1.32	25.70	24.87	38.45	306.9022	0.0504	0.5498	14.90	11.69	11.69	Pass
LTE Band 38	2572.5	0.93	25.70	26.63	33.00	460.2566	0.1134	1.0000	7.30	10.38	7.30	Pass
LTE Band 41	2498.5	1.52	25.70	27.22	33.00	527.2299	0.1488	1.0000	7.30	9.79	7.30	Pass
LTE Band 48/CA_48C	3552.5	1.99	19.00	20.99	23.00	125.6030	0.0395	1.0000	4.00	16.02	4.00	Pass
LTE Band 66/CA_66C	1710.7	3.53	25.70	29.23	30.00	837.5293	0.3756	1.0000	4.30	7.78	4.30	Pass
LTE Band 71	665.5	0.00	25.70	23.55	34.77	226.4644	0.0275	0.4437	11.22	12.08	11.22	Pass

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	EIRP/ERP (dBm)	EIRP/ERP Limit (dBm)	EIRP/ERP (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Gain According to EIRP/ERP (dBi)	Gain According to Pd (dBi)	Maximum Gain Allowed (dBi)	Results
NR Band n2	1852.5	1.93	25.00	26.93	33.00	493.1738	0.1530	1.0000	8.00	10.08	8.00	Pass
NR Band n5	826.5	1.32	25.00	24.17	38.45	261.2161	0.0429	0.5510	15.60	12.40	12.40	Pass
NR Band n7	2502.5	1.07	25.00	26.07	33.00	404.5759	0.1030	1.0000	8.00	10.94	8.00	Pass
NR Band n12	701.5	1.58	25.00	24.43	34.77	277.3320	0.0484	0.4677	11.92	11.43	11.43	Pass
NR Band n14	790.5	2.19	25.00	25.04	34.77	319.1538	0.0641	0.5270	11.92	11.34	11.34	Pass
NR Band n25	1852.5	1.93	25.00	26.93	33.00	493.1738	0.1530	1.0000	8.00	10.08	8.00	Pass
NR Band n38	2572.5	0.93	25.00	25.93	33.00	391.7419	0.0965	1.0000	8.00	11.08	8.00	Pass
NR Band n41	2501.01	1.52	28.00	29.52	33.00	895.3648	0.2528	1.0000	5.00	7.49	5.00	Pass
NR Band n48	3552.51	1.99	20.50	22.49	23.00	177.4189	0.0558	1.0000	2.50	14.52	2.50	Pass
NR Band n66	1712.5	3.53	25.00	28.53	30.00	712.8530	0.3197	1.0000	5.00	8.48	5.00	Pass
NR Band n71	665.5	0.00	25.00	22.85	34.77	192.7525	0.0234	0.4437	11.92	12.78	11.92	Pass
NR Band n77 (3450~3550)	3455.01	1.42	26.50	27.92	30.00	619.4411	0.1709	1.0000	3.50	9.09	3.50	Pass
NR Band n77 (3700~3980)	3705	3.27	26.50	29.77	30.00	948.4185	0.4006	1.0000	3.50	7.24	3.50	Pass
NR Band n78 (3450~3550)	3455.01	1.42	26.50	27.92	30.00	619.4411	0.1709	1.0000	3.50	9.09	3.50	Pass
NR Band n78 (3700~3800)	3705	2.58	26.50	29.08	30.00	809.0959	0.2916	1.0000	3.50	7.93	3.50	Pass

Remark:

1. "Maximum Power" comes from the largest "Tune-up" provided by the customer.

3.2 Multiple Sources Exposure Calculations

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table(A) and Table(B). To comply with the MPE, the fraction of the MPE in terms of E2, H2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity.

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Operating Band	Frequency (MHz)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	MEs
GSM 850	824.2	0.0517	0.5495	0.0941
PCS 1900	1850.2	0.0734	1.0000	0.0734
WCDMA Band II	1852.4	0.1798	1.0000	0.1798
WCDMA Band IV	1712.4	0.2759	1.0000	0.2759
WCDMA Band V	826.4	0.0504	0.5509	0.0915
LTE Band 2	1850.7	0.1798	1.0000	0.1798
LTE Band 4	1710.7	0.2759	1.0000	0.2759
LTE Band 5	824.70	0.0504	0.5498	0.0917
LTE Band 7	2502.50	0.1210	1.0000	0.1210
LTE Band 12	699.7	0.0568	0.4665	0.1219
LTE Band 13	779.5	0.0671	0.5197	0.1291
LTE Band 14	790.5	0.0753	0.5270	0.1429
LTE Band 17	706.5	0.0568	0.4710	0.1207
LTE Band 25	1850.7	0.1798	1.0000	0.1798
LTE Band 26 (814 to 824 MHz)	814.7	0.0576	0.5431	0.1061
LTE Band 26 (824 to 849 MHz)	824.7	0.0504	0.5498	0.0917
LTE Band 38	2572.5	0.1134	1.0000	0.1134
LTE Band 41	2498.5	0.1488	1.0000	0.1488
LTE Band 48/CA_48C	3552.5	0.0395	1.0000	0.0395
LTE Band 66/CA_66C	1710.7	0.3756	1.0000	0.3756
LTE Band 71	665.5	0.0275	0.4437	0.0619

Operating Band	Frequency (MHz)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	MEs
NR Band n2	1852.5	0.1530	1.0000	0.1530
NR Band n5	826.5	0.0429	0.5510	0.0779
NR Band n7	2502.5	0.1030	1.0000	0.1030
NR Band n12	701.5	0.0484	0.4677	0.1035
NR Band n14	790.5	0.0641	0.5270	0.1216
NR Band n25	1852.5	0.1530	1.0000	0.1530
NR Band n38	2572.5	0.0965	1.0000	0.0965
NR Band n41	2501.01	0.2528	1.0000	0.2528
NR Band n48	3552.51	0.0558	1.0000	0.0558
NR Band n66	1712.5	0.3197	1.0000	0.3197
NR Band n71	665.5	0.0234	0.4437	0.0527
NR Band n77 (3450~3550)	3455.01	0.1709	1.0000	0.1709
NR Band n77 (3700~3980)	3705	0.4006	1.0000	0.4006
NR Band n78 (3450~3550)	3455.01	0.1709	1.0000	0.1709
NR Band n78 (3700~3800)	3705	0.2916	1.0000	0.2916

The product also has multiple transmitters. The Simultaneous Transmission Possibilities are as below: EN_DC

The worst-case combination:

Combination	Total MEs	Limit	Conclusion
DC_66A_n77A	$0.3756 + 0.4006 = 0.7762$	<1	PASS

~The End~