

MPE TEST REPORT

Applicant Alliedstar Medical Equipment Co., Ltd.
FCC ID 2A8SG-N25AX
Product Intraoral Scanner Wireless Adapter
Brand Alliedstar / Straumann Sirios
Model N25AX
Report No. EFTA26060351-IE-13-M1V1
Issue Date September 9, 2026

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 §1.1310, §2.1091**. The test results show that the equipment tested can demonstrate compliance with the requirements as documented in this report.



Prepared by: Wei Fangying



Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	July 21, 2026
Rev.1	Updated information.	September 9, 2026
Note: This revised report (Report No.: EFTA26060351-IE-13-M1V1) supersedes and replaces the previously issued report (Report No.: EFTA26060351-IE-13-M1). Please discard or destroy the previously issued report and dispose of it accordingly.		

Table of Contents

1	Test Laboratory	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
2	Description of Equipment Under Test	5
3	Maximum Tune up and Antenna Gain	7
4	MPE Limit.....	8
5	RF Exposure Evaluation Result.....	9
	ANNEX A: The EUT Appearance	10

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

2 Description of Equipment Under Test

Client Information

Applicant	Alliedstar Medical Equipment Co., Ltd.
Applicant address	Floor 3-4, Unit2, Building 3, No.222, West third section, WaihuanRoad, Yanjiang District, Ziyang, 641300, Sichuan, P.R. China
Manufacturer	Alliedstar Medical Equipment Co., Ltd.
Manufacturer address	Floor 3-4, Unit2, Building 3, No.222, West third section, WaihuanRoad, Yanjiang District, Ziyang, 641300, Sichuan, P.R. China

General Technologies

EUT Description			
Model	N25AX		
SN	GHBA0009		
Hardware Version	D		
Software Version	1.X.X.X		
Frequency	Band	TX (MHz)	RX (MHz)
	Wi-Fi 5GHz (U-NII-1)	5150 ~ 5250	5150 ~ 5250
	Wi-Fi 5GHz (U-NII-3)	5725~5850	5725~5850
	Wi-Fi 6GHz (U-NII-5)	5925~6425	5925~6425
	Wi-Fi 6GHz (U-NII-6)	6425~6525	6425~6525
	Wi-Fi 6GHz (U-NII-7)	6525~6875	6525~6875
	Wi-Fi 6GHz (U-NII-8)	6875~7125	6875~7125
Date of Testing	(Original) June 25, 2025 ~ February 3, 2026 (Variant) July 7, 2026 - July 9, 2026		
Date of Sample Received	(Original) April 3, 2025 (Variant) June 29, 2026		
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. 3. This device only operates when powered by a laptop via a cable, and the length of the cable connecting the device to the laptop 20 cm.			

N25AX (Report No.: EFTA26060351-IE-13-M1V1) is a variant model of N25AX (Report No.: EFTA25040032-IE-13-M1V1).

All data cited in this report are derived from the original report (Report No.: EFTA25040032-IE-13-M1V1), and no supplementary testing was conducted in this assessment.

The difference is show in the below:

1. Explanation of Appearance Differences

The firmware version of the lower layer of the programmable circuit board ASSEMBLY AG0374 is upgraded to AV0027_C ->AV0027_D, and change eMMC which causes the version of the upper layer programmable circuit board ASSEMBLY to be upgraded, so the labels are different:AG0374_D->AG0374_E.

2. Explanation of Circuit Differences

The PCBA label differs due to a firmware version change and eMMC change causing a change in the ASSEMBLY version; otherwise, there are no changes.

3. Explanation of Functional Differences

Consistent in function

4. AG0374_E eMMC information

Manufacturer	Manufacturer Part Number	Density
MACRONIX	MX52LM04A11XVW	4GB
MACRONIX	MX52LM04A11XSI	4GB
MACRONIX	MX52LM08A11XVW	8GB
MACRONIX	MX52LM08A11XWI	8GB

The detailed product change description please refers to the Difference Declaration Letter.

3 Maximum Tune up and Antenna Gain

Note: Please refer to the original report (Report No.: EFTA25040032-IE-13-M1V1) for the Maximum Tune up and Antenna Gain.

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. * = Plane-wave equivalent power density.*

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

Note: Please refer to the original report (Report No.: EFTA25040032-IE-13-M1V1) for the Maximum Permissible Exposure.

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Note: Please refer to the original report (Report No.: EFTA25040032-IE-13-M1V1) for the RF Exposure Evaluation Result.

Note: For this device, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****