



FCC TEST REPORT

FCC ID:2A8VY-JT-932

Report Number..... : ZKT-220914L6809E

Date of Test..... Sep. 19, 2022 to Sep. 27, 2022

Date of issue..... : Sep. 27, 2022

Total number of pages..... 38

Test Result : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Chongqing Jiantao Technology Co., Ltd

Address : 10-1, Building 4, No. 2, Gang'an Second Road, Jiangbei District, Chongqing

Manufacturer's name : Chongqing Jiantao Technology Co., Ltd

Address : 10-1, Building 4, No. 2, Gang'an Second Road, Jiangbei District, Chongqing

Test specification:

Standard..... : FCC CFR Title 47 Part 15 Subpart C Section 15.231
ANSI C63.10:2013

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No..... : TRF-EL-108_V0

Test Report Form(s) Originator..... : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : wireless calling system

Trademark : N/A

Model/Type reference..... : Refer For Section 3.1 Model Number

Ratings..... : Input: AC100-240V 50/60Hz 0.5A
Output: DC12V 1A



Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Tested by (name + signature).....: Alen He

Reviewer (name + signature).....: Joe Liu

Approved (name + signature).....: Lake Xie





Table of Contents	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
4. EMC EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	12
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 TEST RESULTS	12
4.2 RADIATED EMISSION MEASUREMENT	15
4.2.1 RADIATED EMISSION LIMITS	15
4.2.2 TEST PROCEDURE	16
4.2.3 TEST SETUP	17
4.2.4 EUT OPERATING CONDITIONS	18
4.2.5 TEST RESULTS	18
5.1 APPLIED PROCEDURES / LIMIT	27
5.2 TEST PROCEDURE	27
5.3 DEVIATION FROM STANDARD	27
5.4 TEST SETUP	27
5.5 EUT OPERATION CONDITIONS	27
5.6 TEST RESULTS	28
6. CALCULATION OF AVERAGE FACTOR	30
7. DWELL TIME	34
7.1 APPLICABLE STANDARD	34
7.2 TEST PROCEDURE	34
7.5 EUT OPERATION CONDITIONS	34
7.6 TEST RESULTS	35



Table of Contents

Page

8. ANTENNA REQUIREMENT	37
9. TEST SETUP PHOTO	38
10. EUT CONSTRUCTIONAL DETAILS	38



1. VERSION

Report No.	Version	Description	Approved
ZKT-220914L6809E	Rev.01	Initial issue of report	Sep. 27, 2022



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.231) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.209,15.231b	Fundamental &Radiated Spurious Emission Measurement	PASS	
15.231c	Occupy Bandwidth	PASS	
15.231a	Dwell time	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033
CAB identifier: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8dB
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	wireless calling system
Trade Name	N/A
Model Name	JT-932
Serial Model	JT-9301, JT-9303, JT-935, JT-938, JT-911S, JT-916, JT-916S, JT-919, JT-9101, JT-951, JT-362, JT-350, JT-352, JT-204S, JT-2041, JT-860, JT-203Q, JT-204Q, JT-601Q, JT-223Q, JT-30XX, JT-31XX, JT-32XX, JT-33XX, JT-1154D, JT-W2, JT-W5, JT-W6, JT-D2, JT-D5.
Model Difference	Only the model names are different for different market requirement.
Hardware version	V1.0
Software version	V1.0
Operation Frequency:	424.8-469.025MHz
Modulation Type:	ASK/FSK
Antenna Type:	External antenna with RP-SMA connector
Antenna Gain:	2dBi
Ratings	Input: AC100-240V 50/60Hz 0.5A Output: DC12V 1A



3.2 DESCRIPTION OF TEST MODES


For All Emission	
Final Test Mode	Description
Transmitting mode	Keep the EUT in continuously transmitting mode

Note:

- (1) New battery is used during the test

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

RE Spurious emissions



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	wireless calling system	N/A	JT-932	N/A	EUT
E-2	Switching Adapter	N/A	DSA-12PFU-12	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	Oct. 18, 2021	Oct. 17, 2022
2	Spectrum Analyzer (1GHz-40GHz)	R&S	FSQ	100363	Oct. 17, 2021	Oct. 16, 2022
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 18, 2021	Oct. 17, 2022
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	Oct. 17, 2021	Oct. 16, 2022
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	Oct. 17, 2021	Oct. 16, 2022
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 17, 2021	Oct. 16, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	Oct. 18, 2021	Oct. 17, 2022
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2021	Oct. 17, 2022
9	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Oct. 18, 2021	Oct. 17, 2022
10	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Oct. 18, 2021	Oct. 17, 2022
11	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Oct. 18, 2021	Oct. 17, 2022
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 22, 2021	Oct. 21, 2022
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2021	Oct. 21, 2022
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 17, 2021	Oct. 16, 2022
15	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 22, 2021	Oct. 21, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
17	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
18	RF Software	MW	MTS8310	V2.0.0.0	\	\
19	Turntable	MF	MF-7802BS	N/A	\	\
20	Antenna tower	MF	MF-7802BS	N/A	\	\
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2021	Oct. 21, 2022

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 22, 2021	Oct. 21, 2022
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 22, 2021	Oct. 21, 2022
3	Test Cable	N/A	C01	N/A	Oct. 18, 2021	Oct. 17, 2022
4	Test Cable	N/A	C02	N/A	Oct. 18, 2021	Oct. 17, 2022
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 17, 2021	Oct. 16, 2022
6	Absorbing Clamp	DZ	ZN23201	15034	Oct. 17, 2021	Oct. 16, 2022
7	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	\	\



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS

(Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN .

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 TEST RESULTS



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1804	20.05	9.63	29.68	64.47	-34.79	QP	P	
2	0.1804	5.54	9.63	15.17	54.47	-39.30	AVG	P	
3	1.9305	6.95	9.71	16.66	56.00	-39.34	QP	P	
4	1.9305	2.01	9.71	11.72	46.00	-34.28	AVG	P	
5	3.1394	17.47	9.62	27.09	56.00	-28.91	QP	P	
6 *	3.1394	7.57	9.62	17.19	46.00	-28.81	AVG	P	
7	7.7491	5.89	9.59	15.48	60.00	-44.52	QP	P	
8	7.7491	-2.09	9.59	7.50	50.00	-42.50	AVG	P	
9	12.6001	0.26	9.77	10.03	60.00	-49.97	QP	P	
10	12.6001	-4.31	9.77	5.46	50.00	-44.54	AVG	P	
11	18.8438	0.68	9.64	10.32	60.00	-49.68	QP	P	
12	18.8438	-4.01	9.64	5.63	50.00	-44.37	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.4664	8.24	9.62	17.86	56.58	-38.72	QP	P	
2	0.4664	0.90	9.62	10.52	46.58	-36.06	AVG	P	
3	1.2061	6.37	9.56	15.93	56.00	-40.07	QP	P	
4	1.2061	0.74	9.56	10.30	46.00	-35.70	AVG	P	
5	2.6225	8.54	9.66	18.20	56.00	-37.80	QP	P	
6	2.6225	-0.81	9.66	8.85	46.00	-37.15	AVG	P	
7 *	3.1661	13.06	9.61	22.67	56.00	-33.33	QP	P	
8	3.1661	1.64	9.61	11.25	46.00	-34.75	AVG	P	
9	5.6210	2.62	9.53	12.15	60.00	-47.85	QP	P	
10	5.6210	-3.26	9.53	6.27	50.00	-43.73	AVG	P	
11	6.2588	1.41	9.53	10.94	60.00	-49.06	QP	P	
12	6.2588	-3.44	9.53	6.09	50.00	-43.91	AVG	P	

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Mesurement Level = Reading level + Correct Factor



4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.231(b) limit in the table below has to be followed.

Frequencies(MHz)	Field Strength(micorvolts/meter)	Measurement Distance(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



FUNDAMENTAL AND HARMONICS EMISSION LIMITS

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66 - 40.70	2,250	225
70 - 130	1,250	125
130 - 174	1,250 to 3,750 **	125 to 375 **
174 - 260	3,750	375
260 - 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12,500	1,250

** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW setting	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.




- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case was X axis and the emissions were reported

4.2.3 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.5 TEST RESULTS

Radiated Spurious Emission (Below 9KHz – 30MHz)

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	---
Test Voltage :	DC 12V		
Test Mode :	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



Radiated Spurious Emission (Between 30MHz – 1GHz)

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode (424.80MHz)		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	45.6947	29.22	-16.05	13.17	40.00	-26.83	QP
2	83.5221	35.82	-20.75	15.07	40.00	-24.93	QP
3	272.2776	31.19	-17.13	14.06	46.00	-31.94	QP
4	322.1885	31.85	-15.38	16.47	46.00	-29.53	QP
5 *	424.8000	85.08	-12.54	72.54	100.50	-27.96	peak
6	836.2443	32.21	-4.33	27.88	46.00	-18.12	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode (424.80MHz)		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	34.0363	37.70	-16.63	21.07	40.00	-18.93	QP
2	36.3814	36.08	-16.23	19.85	40.00	-20.15	QP
3	47.9940	33.19	-16.35	16.84	40.00	-23.16	QP
4	82.6481	42.20	-20.79	21.41	40.00	-18.59	QP
5	144.8417	31.33	-16.31	15.02	43.50	-28.48	QP
6 *	424.8000	81.13	-12.54	68.59	100.50	-31.91	peak

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode (450.325MHz)		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	82.6482	35.28	-20.79	14.49	40.00	-25.51	QP
2	150.5378	28.86	-15.79	13.07	43.50	-30.43	QP
3	272.2776	30.67	-17.13	13.54	46.00	-32.46	QP
4	420.5803	37.73	-12.65	25.08	46.00	-20.92	QP
5 *	450.3250	84.65	-11.83	72.82	101.40	-28.58	peak
6	818.8341	30.95	-4.37	26.58	46.00	-19.42	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode (450.325MHz)		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	34.0365	35.42	-16.63	18.79	40.00	-21.21	QP
2	47.9940	33.64	-16.35	17.29	40.00	-22.71	QP
3	66.4989	33.60	-18.10	15.50	40.00	-24.50	QP
4	77.3212	42.15	-20.08	22.07	40.00	-17.93	QP
5	150.5378	30.73	-15.79	14.94	43.50	-28.56	QP
6 *	450.3250	78.50	-11.83	66.67	101.40	-34.73	peak

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode (469.025MHz)		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.5591	29.43	-15.72	13.71	40.00	-26.29	QP
2	81.2117	35.61	-20.86	14.75	40.00	-25.25	QP
3	146.8877	28.92	-16.10	12.82	43.50	-30.68	QP
4	452.7197	36.32	-11.79	24.53	46.00	-21.47	QP
5 *	469.0250	80.84	-11.48	69.36	101.90	-32.54	peak
6	807.4291	30.58	-4.40	26.18	46.00	-19.82	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode (469.025MHz)		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.6375	33.59	-16.19	17.40	40.00	-22.60	QP
2	47.9940	33.25	-16.35	16.90	40.00	-23.10	QP
3	82.6482	41.23	-20.79	20.44	40.00	-19.56	QP
4	147.9214	32.15	-16.00	16.15	43.50	-27.35	QP
5 *	469.0250	78.56	-11.48	67.08	101.90	-34.82	peak
6	758.0408	33.17	-5.61	27.56	46.00	-18.44	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.



For average Emission

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
424.8	72.54	-2.316	70.22	80.5	10.28	Horizontal
849.6	26.78	-2.316	24.46	60.5	30.04	Horizontal
450.325	72.83	-2.224	70.6	81.4	10.8	Horizontal
900.65	30.24	-2.224	28.01	61.4	33.39	Horizontal
469.025	69.36	-2.197	67.13	81.9	14.77	Horizontal
938.05	23.56	-2.197	21.33	61.9	40.57	Horizontal

Notes: 1. Average emission Level = Peak Level + Duty cycle factor

2. Duty cycle level please see clause 6.

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
424.8	68.59	-2.316	66.27	80.5	14.23	Vertical
849.6	26.78	-2.316	24.46	60.5	36.04	Vertical
450.325	66.67	-2.224	64.44	81.4	16.96	Vertical
900.65	30.24	-2.224	28.01	61.4	33.39	Vertical
469.025	67.08	-2.197	64.85	81.9	17.05	Vertical
938.05	23.56	-2.197	21.33	61.9	40.57	Vertical

Notes: 1. Average emission Level = Peak Level + Duty cycle factor

2. Duty cycle level please see clause 6.



Radiated Spurious Emission (1GHz to 10th harmonics)

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.231/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
1816.80	49.59	PK	228	1.5	H	-14.38	35.21	74.00	-38.79
1816.80	49.56	PK	50	1.5	V	-14.38	35.18	74.00	-38.82
2725.20	47.52	PK	298	1.8	H	-12.87	34.65	74.00	-39.35
2725.20	47.16	PK	117	1.3	V	-12.87	34.29	74.00	-39.71

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.231/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
1811.02	46.55	PK	299	1.1	H	-14.38	32.17	74.00	-41.83
1811.02	47.52	PK	66	1.9	V	-14.38	33.14	74.00	-40.86
2716.87	51.11	PK	113	1.0	H	-12.87	38.24	74.00	-35.76
2716.87	40.03	PK	191	1.5	V	-12.87	27.16	74.00	-46.84

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.231/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
1826.12	46.52	PK	57	1.8	H	-14.38	32.14	74.00	-41.86
1826.12	62.59	PK	301	1.4	V	-14.38	48.21	74.00	-25.79
2737.25	44.56	PK	59	1.1	H	-12.87	31.69	74.00	-42.31
2737.25	46.82	PK	146	1.1	V	-12.87	33.95	74.00	-40.05

The PK value is less than the limit of the average value, the report is not recorded

Notes: 1.Average emission Level = Peak Level + Duty cycle factor

2.Duty cycle level please see clause 6.



5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

According to FCC 15.231(c) requirement:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating between 70 MHz to 900 MHz. Those devices operating above 900 MHz, the emission spurious shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

B. $W(20dBc) \text{ Limit} = 0.25\% * f(\text{MHz}) = 0.25\% * 424.8\text{MHz} = 1.062\text{MHz}$

$W(20dBc) \text{ Limit} = 0.25\% * f(\text{MHz}) = 0.25\% * 450.325\text{MHz} = 1.1258\text{MHz}$

$W(20dBc) \text{ Limit} = 0.25\% * f(\text{MHz}) = 0.25\% * 469.025 \text{ MHz} = 1.1725\text{MHz}$

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	1-5%OBW
VB	$\geq RBW$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : $RBW= 1-5\%OBW$, $VBW \geq RBW$, Sweep time = Auto.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULTS


Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	DC 12V
Test Mode :	TX Mode		

Frequency	20dB Bandwidth (kHz)	Limit (MHz)	Result
424.8MHz	67.19	1.062	PASS
450.325MHz	65.56	1.1258	PASS
469.025MHz	65.65	1.1725	PASS






Mode 2



Mode 3





6. CALCULATION OF AVERAGE FACTOR

The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 3MHz resolution bandwidth.

1.424.8MHz Cycle

Averaging factor in dB = $20\log(\text{duty cycle})$

The duration of one cycle = 94ms

The duty cycle is simply the on-time divided the duration of one cycle

$$\text{Duty Cycle} = (72) / 94$$

$$= 72\text{ms} / 94\text{ms}$$

$$= 0.7659$$

Therefore, the averaging factor is found by $20\log 0.7659 = -2.316\text{dB}$

2.450.325MHz Cycle

Averaging factor in dB = $20\log(\text{duty cycle})$

The duration of one cycle = 93ms

The duty cycle is simply the on-time divided the duration of one cycle

$$\text{Duty Cycle} = (72) / 93$$

$$= 72\text{ms} / 93\text{ms}$$

$$= 0.7741$$

Therefore, the averaging factor is found by $20\log 0.7741 = -2.224\text{dB}$

3.469.025MHz Cycle

Averaging factor in dB = $20\log(\text{duty cycle})$

The duration of one cycle = 93ms

The duty cycle is simply the on-time divided the duration of one cycle

$$\text{Duty Cycle} = (73) / 94$$

$$= 73\text{ms} / 94\text{ms}$$

$$= 0.7765$$

Therefore, the averaging factor is found by $20\log 0.7765 = -2.197\text{dB}$

Test plot as follows:

Note: During the 100ms, the amount of pulse and on-time of pulse are the same for every pulse train.

(On time = The duration of one cycle)