



RF TEST REPORT

Product Name: EasyScan M05

Model Name: M05, M05 Pro

FCC ID: 2A8YS-M05

Issued For : Wuhan Eleph-Print Tech Co.,Ltd

701, Blk B, Huishang Bldg, 2 Wudayuan Rd, Wuhan, Hubei, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT24A033HA01

Sample Received Date: Jan. 10, 2024

Date of Test: Jan. 10, 2024 – Jan. 30, 2024

Date of Issue: Jan. 30, 2024

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Wuhan Eleph-Print Tech Co.,Ltd
Address: 701, Blk B, Huishang Bldg, 2 Wudayuan Rd, Wuhan, Hubei,China
Manufacturer: Wuhan Eleph-Print Tech Co.,Ltd
Address: 701, Blk B, Huishang Bldg, 2 Wudayuan Rd, Wuhan, Hubei,China
Product Name: EasyScan M05
Trademark: EPiC
Model Name: M05, M05 Pro
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR §2.1093 KDB 447498 D01 General RF Exposure Guidance v06	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





TABLE OF CONTENTS

1 . GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST LABORATORY	6
2 . FCC 47CFR §2.1093 REQUIREMENT	7
2.1 TEST STANDARDS	7
2.5 TEST RESULT	8



Revision History

Rev.	Issue Date	Revisions
00	Jan. 30 2024	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	EasyScan M05	
Trademark:	EPiC	
Model Name:	M05	
Series Model:	M05 Pro	
Model Difference:	Only the model name is different.	
Product Description:	Operation Frequency:	IEEE 802.11b/g/n(20MHz): 2412~2462MHz IEEE 802.11n(40MHz):2422~2452MHz
		IEEE 802.11a/n(HT20)/ ac(VHT20)/ax(HE20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ ac(VHT40)/ax(HE40): 5.190GHz-5.230GHz IEEE 802.11 ac(VHT80)/ax(HE80): 5.210GHz
		IEEE 802.11a/n(HT20)/ ac(VHT20)/ax(HE20): 5.260GHz-5.320GHz IEEE 802.11 n(HT40)/ ac(VHT40)/ax(HE40): 5.270GHz-5.310GHz IEEE 802.11 ac(VHT80)/ax(HE80): 5.290GHz
		IEEE 802.11a/n(HT20)/ ac(VHT20)/ax(HE20): 5.500GHz-5.700GHz IEEE 802.11 n(HT40)/ ac(VHT40)/ax(HE40): 5.510GHz-5.670GHz IEEE 802.11 ac(VHT80)/ax(HE80): 5.530GHz- 5.610GHz
		IEEE 802.11a/n(HT20)/ ac(VHT20)/ax(HE20): 5.745GHz-5.825GHz IEEE 802.11a/n(HT40)/ac(VHT40)/ax(HE40): 5.755GHz-5.795GHz IEEE 802.11 ac(VHT80)/ax(HE80): 5.775GHz
		IEEE 802.11ac(VHT80)/ax(HE80): 5.775GHz
	Modulation Type:	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM 802.11ax(OFDM, OFDMA): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	Antenna Designation:	FPC
	Antenna Gain(dBi)	1
More details of EUT technical specification, please refer to the User Manual.		
Test Channel:	Please refer to the Note 3.	
Rating:	Input: DC 12-17.6V	
Battery:	Capacity: 1950mAh Rated Voltage: 15.4V Max Charge Voltage: 12V	



	Max Charge Current: 2A
Hardware Version:	M05_V1.0.0
Software Version:	Easy Point Access M V1.00.00Beta.apk
Connecting I/O Port(s):	Please refer to the Note 1.

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136



2. FCC 47CFR §2.1093 REQUIREMENT

2.1 TEST STANDARDS

RF EXPOSURE EVALUATION METHOD- KDB 447498 D01V06

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Note: 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



2.5 TEST RESULT

Turn up Result

Mode	Turn up Power
2.4G WIFI-802.11b	5±1dBm
2.4G WIFI-802.11g	5±1dBm
2.4G WIFI-802.11n(HT20)	5±1dBm
2.4G WIFI-802.11n(HT40)	5±1dBm
5G WIFI-802.11a	6±1dBm
5G WIFI-802.11n(HT20)	6±1dBm
5G WIFI-802.11n(HT40)	6±1dBm
5G WIFI-802.11ac(VHT20)	6±1dBm
5G WIFI-802.11ac(VHT40)	6±1dBm
5G WIFI-802.11ac(VHT80)	6±1dBm
5G WIFI-802.11ax(HE20)	6±1dBm
5G WIFI-802.11ax(HE40)	6±1dBm
5G WIFI-802.11ax(HE80)	6±1dBm



The result of worst mode:

2.4G WIFI

ANT Gain (G)

Antenna number: 1

Antenna A gain : 1dBi

MIMO technology Directional gain=1dBi

(gain of antenna in linear scale=1.259)

Mode	frequency (GHz)	Maximum Peak Conducted Output Power (dBm)	Tune up Power (dBm)	Tune up Power (mW)	Result	Limit
2.4G WIFI	2.422	5.55	6	3.98	1.2391	3

5G WIFI

ANT Gain (G)

Antenna number: 2

Antenna A gain : 1dBi

Antenna B gain : 1dBi

MIMO technology Directional gain= 4.01dBi

(gain of antenna in linear scale=2.518)

Mode	frequency (GHz)	Maximum Peak Conducted Output Power (dBm)	Tune up Power (dBm)	Tune up Power (mW)	Result	Limit
5G WIFI	5.5	6.97	7	5.01	2.3508	3

Note:

2.4G WiFi& 5G WiFi can not Synchronous transmission; only the worst case recorded.

Threshold at which no SAR required is $2.3508 \leq 3$ for 1-g SAR, Separation distance is 5mm.

*****END OF THE REPORT*****