



CTC Laboratories, Inc.

TEST REPORT

Report No.: CTC2025521702
FCC ID 2A92ZRW-3
IC 29863-RW3
Applicant..... Complete Genomics, Inc.
Address..... 2904 ORCHARD PARKWAY San Jose, CA 95134 United States
Manufacturer..... Complete Genomics, Inc.
Address..... 2904 ORCHARD PARKWAY San Jose, CA 95134 United States
Product Name..... Core driver board
Trade Mark..... /
Model/Type reference..... RW Module V3.0
Listed Model(s) /
Standard..... FCC CFR Title 47 Part 15 Subpart C Section 15.247
RSS 247 Issue 4
Test Report Form No CTC-TR-057_A2
Master TRF Dated 2025-05-12
Date of receipt of test sample...: Aug. 19, 2025
Date of testing..... Aug. 19, 2025 ~ Sep. 22, 2025
Date of issue..... Sep. 26, 2025
Result..... PASS

Compiled by:

(Printed name+signature) Alicia Liu

Alicia

Supervised by:

(Printed name+signature) Eric Zhang

Eric Zhang

Approved by:

(Printed name+signature) Totti Zhao

Totti Zhao

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test result in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



Table of Contents

Page

1. TEST SUMMARY	3
1.1. TEST STANDARDS	3
1.2. REPORT VERSION	3
1.3. TEST DESCRIPTION	3
1.4. TEST FACILITY	4
1.5. MEASUREMENT UNCERTAINTY	4
1.6. ENVIRONMENTAL CONDITIONS	5
2. GENERAL INFORMATION	6
2.1. CLIENT INFORMATION	6
2.2. GENERAL DESCRIPTION OF EUT	6
2.3. ACCESSORY EQUIPMENT INFORMATION	7
2.4. OPERATION STATE	8
2.5. MEASUREMENT INSTRUMENTS LIST	9
3. TEST ITEM AND RESULTS	11
3.1. CONDUCTED EMISSION	11
3.2. RADIATED EMISSION	14
3.3. BAND EDGE EMISSIONS (RADIATED)	21
3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED)	22
3.5. 20dB BANDWIDTH	35
3.6. CHANNEL SEPARATION	39
3.7. NUMBER OF HOPPING CHANNEL	41
3.8. DWELL TIME	43
3.9. PEAK OUTPUT POWER	48
3.10. DUTY CYCLE	50
3.11. ANTENNA REQUIREMENT	51



1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

[RSS 247 Issue 4](#): RSS-247-Digital Transmission Systems, Frequency Hopping Systems and Licence-Exempt Local Area Network Devices in 902-928 MHz, 2400-2483.5 MHz, 5150-5350 MHz, and 5470-5895MHz bands.

[RSS-Gen Issue 5](#): General Requirements for Compliance of Radio Apparatus.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices.

[ANSI C63.10-2020](#): American National Standard for Testing Unlicensed Wireless Devices.

1.2. Report Version

Revised No.	Report No.	Date of issue	Description
01	CTC2025521702	Sep. 26, 2025	Original

1.3. Test Description

FCC Part 15 Subpart C (15.247)/ RSS 247 Issue 4				
Test Item	Standard Section		Result	Test Engineer
	FCC	IC		
Antenna Requirement	15.203	/	Pass	Marrow
Conducted Emission	15.207	RSS-Gen 8.8	Pass	Marrow
Restricted Bands	15.205	RSS-Gen 8.10	Pass	Marrow
Hopping Channel Separation	15.247(a)(1)	RSS 247 5.1 (b)	Pass	Marrow
Dwell Time	15.247(a)(1)(i)	RSS 247 5.1 (c)	Pass	Marrow
Peak Output Power	15.247(b)(2)	RSS 247 5.4 (a)	Pass	Marrow
Number of Hopping Frequency	15.247(a)(1)(i)	RSS 247 5.1 (c)	Pass	Marrow
Conducted Band Edge and Spurious Emissions	15.247(d)	RSS 247 5.5	Pass	Marrow
Radiated Band Edge and Spurious Emissions	15.205&15.209&15.247(d)	RSS 247 5.5	Pass	Marrow
Radiated Spurious Emission	15.247(d)&15.209	RSS 247 5.5&RSS-Gen 8.9	Pass	Marrow
20dB Bandwidth	15.247(a)(1)(i)	RSS 247 5.1 (c)	Pass	Marrow

Note: The measurement uncertainty is not included in the test result.



1.4. Test Facility

CTC Laboratories, Inc.

Add: Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhuhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.



Test Items	Measurement Uncertainty	Notes
20dB Emission Bandwidth	$\pm 0.0196\%$	(1)
Carrier Frequency Separation	$\pm 1.9\%$	(1)
Number of Hopping Channel	$\pm 1.9\%$	(1)
Time of Occupancy	$\pm 0.028\%$	(1)
Max Peak Conducted Output Power	± 0.743 dB	(1)
Band-edge Spurious Emission	± 1.328 dB	(1)
Conducted RF Spurious Emission	9kHz-1GHz: ± 0.746 dB 1GHz-26GHz: ± 1.328 dB	(1)
Conducted Emissions 9kHz~30MHz	± 3.08 dB	(1)
Radiated Emissions 30~1000MHz	± 4.51 dB	(1)
Radiated Emissions 1~18GHz	± 5.84 dB	(1)
Radiated Emissions 18~40GHz	± 6.12 dB	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.6. Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	21°C ~ 27°C
Relative Humidity:	40% ~ 60%
Air Pressure:	101kPa



2. GENERAL INFORMATION

2.1. Client Information

Applicant:	Complete Genomics, Inc.
Address:	2904 ORCHARD PARKWAY San Jose, CA 95134 United States
Manufacturer:	Complete Genomics, Inc.
Address:	2904 ORCHARD PARKWAY San Jose, CA 95134 United States
Factory:	Wuhan MGI Tech Co.,Ltd.
Address:	Address 1: Building 24, Stage 3.1, BioLake Accelerator, No.388 2nd Gaoxin Road, East Lake High-Tech Development Zone, 430075 Wuhan, P.R. China Address 2: No.66, 7th Guanggu Road, East Lake High-Tech Development Zone, 430075, Wuhan, P.R. China

2.2. General Description of EUT

Product Name:	Core driver board
Trade Mark:	/
Model/Type reference:	RW Module V3.0
Listed Model(s):	/
Model Different:	/
Sample ID:	CTC250818-004-S002
Power supply:	DC 5V
Hardware version:	V1.0
Software version:	V1.0
RF ID Specification	
Modulation:	ASK
Operation frequency:	902.25MHz ~ 927.75MHz
Channel number:	52
Channel separation:	0.5MHz
Antenna J6, J7 type*1:	Planar Antenna
EC-UHF-ANT-NF0014A gain*2:	-5.31dBi Max
EC-UHF-ANT-NF0015 gain*2:	-9.94dBi Max

Note:

*1: Antennas do not support MIMO, and can only be transmitted in a single mode at a time.

J6--EC-UHF-ANT-NF0015, J7--EC-UHF-ANT-NF0014A

*2: Two different types of antennas have different antenna gains and operate at different times.



2.3. Accessory Equipment Information

Equipment Information			
Name	Model	S/N	Manufacturer
Notebook	ThinkPad T430	MP246QDR	Lenovo
Cable Information			
Name	Shielded Type	Ferrite Core	Length
USB Cable	Unshielded	Without	80cm
Test Software Information			
Name	Version	/	/
EC-UHF-A-6 DEMO	V6.1	/	/



2.4. Operation State

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. Channels 01/26/50 were selected for testing.

Operation Frequency List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	902.25	14	908.75	27	915.25	40	921.75
02	902.75	15	909.25	28	915.75	41	922.25
03	903.25	16	909.75	29	916.25	42	922.75
04	903.75	17	910.25	30	916.75	43	923.25
05	904.25	18	910.75	31	917.25	44	923.75
06	904.75	19	911.25	32	917.75	45	924.25
07	905.25	20	911.75	33	918.25	46	924.75
08	905.75	21	912.25	34	918.75	47	925.25
09	906.25	22	912.75	35	919.25	48	925.75
10	906.75	23	913.25	36	919.75	49	926.25
11	907.25	24	913.75	37	920.25	50	926.75
12	907.75	25	914.25	38	920.75	51	927.25
13	908.25	26	914.75	39	921.25	52	927.75

Note: The display in grey were the channel selected for testing.

Test mode

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit
For AC power line conducted emissions:
The engineering test program was provided and enabled to make EUT continuous transmit
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.



2.5. Measurement Instruments List

RF Test System - SRD						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
1	Spectrum Analyzer	R&S	FSV40-N	101654	Dec. 13, 2024	Dec. 12, 2025
2	RF Control Unit	Tonscend	JS0806-2	/	Aug. 22, 2024	Aug. 21, 2025
3	RF Control Unit	Tonscend	JS0806-2	/	Aug. 22, 2025	Aug. 21, 2026
Test Software						
Name		Manufacturer			Software Version	
JS1120-3		Tonscend			V3.3.38	

Radiated emission						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Dec. 18, 2024	Dec. 17, 2025
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-648	Dec. 12, 2024	Dec. 11, 2025
3	Pre-Amplifier	SONOMA	310	186194	Dec. 13, 2024	Dec. 12, 2025
4	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 13, 2024	Dec. 12, 2025
5	Test Receiver	R&S	ESCI7	100967	Dec. 13, 2024	Dec. 12, 2025
6	RE32L-001	HUBENR	/	009 (9kHz-1GHz)	Feb. 09, 2025	Feb. 08, 2026
7	RE32L-002	HUBENR	/	010 (9kHz-1GHz)	Feb. 09, 2025	Feb. 08, 2026
8	RE32L-003	HUBENR	/	011 (9kHz-1GHz)	Feb. 09, 2025	Feb. 08, 2026
9	RE32H-001	HUBENR	/	012 (1GHz-18GHz)	Feb. 09, 2025	Feb. 08, 2026
10	RE32H-002	HUBENR	/	013 (1GHz-18GHz)	Feb. 09, 2025	Feb. 08, 2026
11	3m chamber 2	Frankonia	EE025	/	Oct. 19, 2024	Oct. 18, 2027
Test Software						
Name		Manufacturer			Software Version	
EZ-EMC		FARA			FA-03A2	

Conducted emission						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
1	LISN	R&S	ENV216	101112	Dec. 13, 2024	Dec. 12, 2025
2	LISN	R&S	ENV216	101113	Dec. 13, 2024	Dec. 12, 2025
3	EMI Test Receiver	R&S	ESCI	100524	Dec. 13, 2024	Dec. 12, 2025
4	ISN CAT6	Schwarzbeck	NTFM 8158	CAT6-8158-0046	Dec. 13, 2024	Dec. 12, 2025
5	ISN CAT5	Schwarzbeck	NTFM 8158	CAT5-8158-0046	Dec. 13, 2024	Dec. 12, 2025
6	CE-001	COMM	/	001	Feb. 09, 2025	Feb. 08, 2026
Test Software						
Name		Manufacturer			Software Version	
EMC32		R&S			6.10.10	

CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



Note: 1. The Cal. Interval was one year.

2. The Cal. Interval was three year of the chamber

3. The cable loss has calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Conducted Emission


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207/ RSS – Gen 8.8

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration



Test Procedure


1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.

Test Mode

Please refer to the clause 2.4.

**Test Results**

Test Voltage:	AC 120V/60 Hz
Terminal:	Line
Remark:	Only worse case is reported.

**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.152410	39.4	1000.00	9.000	On	L1	10.8	26.5	65.9	
0.495650	36.1	1000.00	9.000	On	L1	11.0	20.0	56.1	
12.493580	34.1	1000.00	9.000	On	L1	13.3	25.9	60.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.503610	31.6	1000.00	9.000	On	L1	11.0	14.4	46.0	
10.824240	32.0	1000.00	9.000	On	L1	12.9	18.0	50.0	
19.833430	29.1	1000.00	9.000	On	L1	14.8	20.9	50.0	

Emission Level= Read Level+ Correct Factor



Test Voltage:	AC 120V/60 Hz
Terminal:	Neutral
Remark:	Only worse case is reported.



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.152410	39.5	1000.00	9.000	On	N	10.8	26.4	65.9	
0.499610	34.7	1000.00	9.000	On	N	10.7	21.3	56.0	
24.790920	31.9	1000.00	9.000	On	N	15.4	28.1	60.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.495650	30.7	1000.00	9.000	On	N	10.7	15.4	46.1	
0.524080	22.1	1000.00	9.000	On	N	10.7	23.9	46.0	
21.307990	26.2	1000.00	9.000	On	N	14.9	23.8	50.0	

Emission Level= Read Level+ Correct Factor

3.2. Radiated Emission

Limit


FCC CFR Title 47 Part 15 Subpart C Section 15.209/ RSS – Gen 8.9

Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m).

Test Configuration



Below 30MHz Test Setup




CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) 9k – 150kHz:
RBW=300 Hz, VBW=1 kHz, Sweep=auto, Detector function=peak, Trace=max hold
 - (3) 0.15M – 30MHz:
RBW=10 kHz, VBW=30 kHz, Sweep=auto, Detector function=peak, Trace=max hold
 - (4) 30M - 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (5) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW $\geq$ 1/T Peak detector for Average value.Note 1: For the 1/T& Duty Cycle please refer to clause 3.10 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result

9 KHz~30 MHz


From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



30MHz-1GHz

Ant. Pol.	Horizontal
Test Mode:	TX Mode 902.25MHz
Remark:	Only worse case is reported.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	72.0333	38.75	-19.35	19.40	40.00	-20.60	QP
2	96.2833	50.88	-20.34	30.54	43.50	-12.96	QP
3	144.4600	45.78	-16.54	29.24	43.50	-14.26	QP
4	216.5633	54.03	-18.65	35.38	46.00	-10.62	QP
5	384.3733	46.36	-13.22	33.14	46.00	-12.86	QP
6 *	732.9266	45.52	-5.03	40.49	46.00	-5.51	QP


Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value



Ant. Pol.	Vertical
Test Mode:	TX Mode 902.25MHz
Remark:	Only worse case is reported.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	60.0700	41.63	-17.73	23.90	40.00	-16.10	QP
2	96.2833	46.96	-20.34	26.62	43.50	-16.88	QP
3	232.7300	48.07	-18.25	29.82	46.00	-16.18	QP
4	383.4033	45.12	-13.26	31.86	46.00	-14.14	QP
5	546.0400	41.05	-8.91	32.14	46.00	-13.86	QP
6 *	806.0000	43.22	-3.19	40.03	46.00	-5.97	QP

Remarks:

- Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- Margin value = Level -Limit value



Above 1GHz

Ant. Pol.	Horizontal
Test Mode:	TX Mode 902.25MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1498.000	47.73	-6.93	40.80	74.00	-33.20	peak
2 *	1777.000	60.72	-6.60	54.12	74.00	-19.88	peak
3	3199.000	41.10	-2.03	39.07	74.00	-34.93	peak
4	3952.000	40.98	0.39	41.37	74.00	-32.63	peak
5	4510.000	42.69	1.36	44.05	74.00	-29.95	peak
6	8017.000	40.28	10.97	51.25	74.00	-22.75	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	TX Mode 902.25MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1390.000	53.61	-7.07	46.54	74.00	-27.46	peak
2	1501.000	49.01	-6.93	42.08	74.00	-31.92	peak
3 *	1804.000	69.18	-6.51	62.67	74.00	-11.33	peak
4	2707.000	54.02	-2.85	51.17	74.00	-22.83	peak
5	4510.000	44.07	1.36	45.43	74.00	-28.57	peak
6	8902.000	40.25	11.62	51.87	74.00	-22.13	peak

Remarks:

1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor

2.Margin value = Level -Limit value



Ant. Pol.	Horizontal
Test Mode:	TX Mode 915.25MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1096.000	49.48	-8.06	41.42	74.00	-32.58	peak
2	1354.000	47.37	-7.12	40.25	74.00	-33.75	peak
3	1495.000	54.08	-6.94	47.14	74.00	-26.86	peak
4 *	1831.000	62.27	-6.38	55.89	74.00	-18.11	peak
5	4576.000	43.35	1.54	44.89	74.00	-29.11	peak
6	7135.000	40.32	9.67	49.99	74.00	-24.01	peak

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value

Ant. Pol.	Vertical
Test Mode:	TX Mode 915.25MHz
Remark:	No report for the emission which more than 20 dB below the prescribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1198.000	48.77	-7.72	41.05	74.00	-32.95	peak
2	1573.000	48.63	-6.91	41.72	74.00	-32.28	peak
3 *	1831.000	66.08	-6.38	59.70	74.00	-14.30	peak
4	2746.000	52.49	-2.74	49.75	74.00	-24.25	peak
5	4576.000	43.98	1.54	45.52	74.00	-28.48	peak
6	7975.000	40.04	10.96	51.00	74.00	-23.00	peak

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value



Ant. Pol.	Horizontal
Test Mode:	TX Mode 927.75MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1069.000	55.47	-8.15	47.32	74.00	-26.68	peak
2	1354.000	47.14	-7.12	40.02	74.00	-33.98	peak
3	1855.000	56.41	-6.26	50.15	74.00	-23.85	peak
4	4639.000	44.86	1.65	46.51	74.00	-27.49	peak
5	7543.000	40.04	10.21	50.25	74.00	-23.75	peak
6 *	8860.000	40.89	11.59	52.48	74.00	-21.52	peak

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value

Ant. Pol.	Vertical
Test Mode:	TX Mode 927.75MHz
Remark:	No report for the emission which more than 20 dB below the pre-scribed limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1495.000	51.91	-6.94	44.97	74.00	-29.03	peak
2 *	1855.000	63.30	-6.26	57.04	74.00	-16.96	peak
3	2782.000	49.15	-2.69	46.46	74.00	-27.54	peak
4	3838.000	41.12	-0.06	41.06	74.00	-32.94	peak
5	4639.000	45.12	1.65	46.77	74.00	-27.23	peak
6	8440.000	39.94	10.83	50.77	74.00	-23.23	peak

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Margin value = Level - Limit value




3.3. Band Edge Emissions (Radiated)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d)/ RSS – 247 5.5

Restricted Frequency Band (MHz)	(dBuV/m)(at 3m)	
	Peak	Average
2310 ~ 2390	74	54
2483.5 ~ 2500	74	54

Test Configuration



Test Procedure


1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.

Test Mode

Please refer to the clause 2.4.

Test Results

NA




3.4. Band edge and Spurious Emissions (Conducted)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

RSS-247 (5.5): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Configuration



Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW ≥ RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test Mode

Please refer to the clause 2.4.

Test Results

(1) Band edge Conducted Test

Test Mode	Antenna	Frequency [MHz]	Ref Level[dBm]	Result[dBm]	Limit[dBm]	Verdict
RF ID	Ant J6	902.25	14.89	-10.30	≤-5.11	PASS
		927.75	14.91	-19.78	≤-5.09	PASS
		Hop_902.25	14.94	-8.47	≤-5.06	PASS
		Hop_927.75	14.93	-6.23	≤-5.07	PASS
RF ID	Ant J7	902.25	14.94	-5.26	≤-5.06	PASS
		927.75	14.78	-7.63	≤-5.22	PASS

CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-057_A2


For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com




		Hop_902.25	14.96	-17.27	≤ -5.04	PASS
		Hop_927.75	14.90	-7.16	≤ -5.10	PASS




RF ID_Low_Ant J6_902.25



RF ID_High_Ant J6_927.75




RF ID_Low_Hop_Ant J6_902.25



Date: 26.AUG.2025 15:14:01

RF ID_High_Hop_Ant J6_927.75



Date: 26.AUG.2025 15:08:22

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict,
Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2




RF ID_Low_Ant J7_902.25




Date: 27.AUG.2025 08:48:02

RF ID_High_Ant J7_927.75




Date: 27.AUG.2025 09:00:21

RF ID_Low_Hop_Ant J7_902.25



RF ID_High_Hop_Ant J7_927.75



CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict,
Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com


TRF No: CTC-TR-057_A2

**(2) Conducted Spurious Emissions Test**

Test Mode	Antenna	Frequency [MHz]	Freq Range [MHz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
RF ID	Ant J6	902.25	Reference	14.74	14.74	---	PASS
			30~10000	14.80	-31.89	≤ -5.22	PASS
		915.25	Reference	15.87	15.87	---	PASS
			30~10000	14.84	-30.95	≤ -4.13	PASS
		927.75	Reference	15.03	15.03	---	PASS
			30~10000	14.81	-30.28	≤ -4.97	PASS
RF ID	Ant J7	902.25	Reference	14.76	14.76	---	PASS
			30~10000	14.75	-34.03	≤ -5.24	PASS
		915.25	Reference	14.42	14.42	---	PASS
			30~10000	14.57	-33.31	≤ -5.58	PASS
		927.75	Reference	14.65	14.65	---	PASS
			30~10000	14.64	-32.43	≤ -5.35	PASS




RF ID_902.25_Ant J6_0~Reference



Date: 26.AUG.2025 15:45:32

RF ID_902.25_Ant J6_30~10000



Date: 26.AUG.2025 16:46:28


RF ID_915.25_Ant J6_0~Reference

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



RF ID_915.25_Ant J6_30~10000




RF ID_927.75_Ant J6_0~Reference

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict,
Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-057_A2

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com



RF ID_927.75_Ant J6_30~10000




RF ID_902.25_Ant J7_0~Reference

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-057_A2

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com



RF ID_902.25_Ant J7_30~10000




RF ID_915.25_Ant J7_0~Reference

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



RF ID_915.25_Ant J7_30~10000




RF ID_927.75_Ant J7_0~Reference

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



RF ID_927.75_Ant J7_30~10000



CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2




3.5. 20dB Bandwidth

Limit

The maximum 20 dB bandwidth of the hopping channel shall be 500 kHz.

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. OCB and 20dB Spectrum Setting:
 - (1) Set RBW = 1% ~ 5% occupied bandwidth.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Note: The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

Test Mode

Please refer to the clause 2.4.

Test Results

Test Mode	Antenna	Frequency [MHz]	20dB Band-width[kHz]	Limit[kHz]	Verdict
RF ID	Ant J6	902.25	167.83	≤ 500	PASS
		915.25	167.83	≤ 500	PASS
		927.75	167.83	≤ 500	PASS
	Ant J7	902.25	167.83	≤ 500	PASS
		915.25	167.83	≤ 500	PASS
		927.75	167.83	≤ 500	PASS




RF ID_EBW_Ant J6_902.25




Date: 26.AUG.2025 14:36:50

RF ID_EBW_Ant J6_915.25




Date: 26.AUG.2025 14:35:41

RF ID_EBW_Ant J6_927.75



RF ID_EBW_Ant J7_902.25




RF ID_EBW_Ant J7_915.25

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict,
Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



RF ID EBW Ant J7 927.75



CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict,
Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



3.6. Channel Separation


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)/ RSS-247 5.1 b :

FCC 15.247: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively

RSS-247: FHSs shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.


Test Mode

Please refer to the clause 2.4.


**Test Results**

Test Mode	Antenna	Frequency [MHz]	Result[kHz]	Limit[kHz]	Verdict
RF ID	Ant J6	Hop_915.25	500.5	>173.7	PASS
	Ant J7	Hop_915.25	500.5	>173.7	PASS

RF ID_Hop_Ant J6_915.25



RF ID_Hop_Ant J7_915.25



CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



3.7. Number of Hopping Channel


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)(i)/ RSS-247 5.1 c :

FCC 15.247: (i) For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

RSS-247: For FHSs in the band 902-928 MHz: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20-second period. If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10-second period. The maximum 20 dB bandwidth of the hopping channel shall be 500 kHz.

Test Configuration



Test Procedure



1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Peak Detector: RBW=100 kHz, VBW $\geq$ RBW, Sweep time= Auto.

Test Mode

Please refer to the clause 2.4.

**Test Result**

Test Mode	Antenna	Channel number	Limit	Result
RF ID	Ant J6	52	≥25.00	Pass
	Ant J7	52	≥25.00	Pass

RF ID_Ant J6_Hop**RF ID_Ant J7_Hop**

CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luh Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



3.8. Dwell Time


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)(i)/ RSS-247 5.1 c :

FCC 15.247: For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

RSS-247: For FHSs in the band 902-928 MHz: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20-second period. If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10-second period.

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Spectrum Setting: RBW=1MHz, VBW $\geq$ RBW.
 - (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
 - (3) Sweep Time is more than once pulse time.
 - (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
 - (5) Measure the maximum time duration of one single pulse.
 - (6) Set the EUT for packet transmitting.

Test Mode

Please refer to the clause 2.4.

**Test Result**

Test Mode	Antenna	Frequency [MHz]	Pulse Time(ms)	Total of Dwell(ms)	Limit(Second)	Verdict
RF ID	Ant J6	915.25	3.26	226.78	≤ 0.4	PASS
	Ant J7	915.25	3.26	226.78	≤ 0.4	PASS

Note:

1. (Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) x (period specified in the requirements / analyzer sweep time)

$$2 \times (400/20000) = 0.04 \text{ (ms)}$$


2. (Average time of occupancy) = (transmit time per hop) x (number of hops in the period specified in the requirements)


$$3.26 \times 30 \times 0.04 = 3.91 \text{ (ms)}$$

3. (Total dwell time) = (Average time of occupancy) x (Channel number)


$$3.91 \times 58 = 226.78 \text{ (ms)}$$

Based on the above algorithm, calculate the dwell time for the other antennas.





RF ID_Ant J6_915.25 - 3




RF ID_Ant J7_915.25 - 1

CTC Laboratories, Inc.


Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict,
Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com


TRF No: CTC-TR-057_A2



RF ID_Ant J7_915.25 - 2



RF ID_Ant J7_915.25 - 3



CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cncaq.com

TRF No: CTC-TR-057_A2



3.9. Peak Output Power


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(2) / RSS-247 5.4 a:

FCC 15.247: For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

RSS-247: For FHSs operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1.0 W, and the e.i.r.p. shall not exceed 4 W if the hopset uses 50 or more hopping channels; the maximum peak conducted output power shall not exceed 0.25 W and the e.i.r.p. shall not exceed 1 W if the hopset uses less than 50 hopping channels.

Test Configuration



Test Procedure

1. The maximum conducted output power may be measured using a broadband RF power meter.
2. Power measurements were performed only when the EUT was transmitting at its AVG power control level using a broadband power meter with a pulse sensor.
3. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.
4. Record the measurement data.

Test Mode

Please refer to the clause 2.4.

**Test Result**

Test Mode	Antenna	Frequency [MHz]	Result[dBm]	Limit[dBm]	Gain	Result [dBm]	E.i.r.p Limit [dBm]	Verdict
RF ID	Ant J6	902.25	15.15	≤30	-10.20	4.95	≤36	PASS
		915.25	15.14	≤30	-10.20	4.94	≤36	PASS
		927.75	15.09	≤30	-10.20	4.89	≤36	PASS
	Ant J7	902.25	14.70	≤30	-5.53	9.17	≤36	PASS
		915.25	14.67	≤30	-5.53	9.14	≤36	PASS
		927.75	14.68	≤30	-5.53	9.15	≤36	PASS




3.10. Duty Cycle

Limit

None, for report purposes only.

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:
Set analyzer center frequency to test channel center frequency.
Set the span to 0Hz
Set the RBW to 8MHz
Set the VBW to 8MHz
Detector: Peak
Sweep time: Auto
Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode

Please refer to the clause 2.4.

Test Result

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
RF ID	Ant J6	902.25	3.18	10.44	30.46	0.31	1
		915.25	3.18	10.44	30.46	0.31	1
		927.75	3.18	10.44	30.46	0.31	1
	Ant J7	902.25	3.21	10.44	30.75	0.31	1
		915.25	3.27	10.44	31.32	0.31	1
		927.75	3.27	10.44	31.32	0.31	1



3.11. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The directional gain of the antenna less than 6dBi, please refer to the EUT internal photographs antenna photo.

*****THE END*****