

Product Name : E7165UO-4IN1ANT-V1.0

History List

[illegible]

E7165UO-4IN1ANT-V1.0 Specification

1. Explanation of part number :

[illegible]

(1) Model Name : E7165UO

(2) Frequency : 1575Mhz, 2400-2500MHz, 5150-5850MHz

(3) Suffix :V1.0

2. Electrical Specification :

2-1. Frequency Band:

Frequency Band	MHz
GPS&BT&WIFI	1575Mhz, 2400-2500MHz, 5150-5850MHz


2-2. Impedance

50 ohm nominal

UNLESS OTHER SPECIFIED TOLERANCES ON :		 深圳市可信华成通信科技有限公司 SHENZHEN CITY KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD	
$X \pm 2$ $X.X \pm 0.1$ $X.XX \pm 0.05$ $ANGLES = \pm$ $HOLEDIA = \pm$			
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY :Huangshiyong	CHECKED BY : Xiaokunxiong		
DESIGNED BY : Lishenghua	APPROVED BY : Wangwei		
TITLE : <u>E7165UO-4IN1ANT-V1.0</u> Specification		DOCUMENT NO.	PAGE REV A0

2-3. VSWR ,Efficiency ,Matching and Active Data :

2-3.1 VSWR:

Frequency Band	1575	2400	2500	5150	5950																		
2-3-1. Typical Value:	≤ 2	≤ 2.5	≤ 2	≤ 3.0	≤ 3.0																		
2-3-2Measuring Method	1. A 50Ω coaxial cable is connected to the fpcb antenna. Then this cable is connected to a network analyzer to measure the VSWR. 2. Keeping this jig away from metal at least 20 cm.																						
2-3-3Picture	▶Tr1 S11 SWR 1.000/ Ref 1.000 [F1 M] <table data-bbox="453 792 722 893"><tr><th>Point</th><th>Frequency (GHz)</th><th>SWR</th></tr><tr><td>1</td><td>1.5754200</td><td>1.7973</td></tr><tr><td>2</td><td>2.4000000</td><td>2.0136</td></tr><tr><td>3</td><td>2.5000000</td><td>2.3615</td></tr><tr><td>4</td><td>5.1500000</td><td>2.2945</td></tr><tr><td>5</td><td>5.8500000</td><td>3.1041</td></tr></table>					Point	Frequency (GHz)	SWR	1	1.5754200	1.7973	2	2.4000000	2.0136	3	2.5000000	2.3615	4	5.1500000	2.2945	5	5.8500000	3.1041
Point	Frequency (GHz)	SWR																					
1	1.5754200	1.7973																					
2	2.4000000	2.0136																					
3	2.5000000	2.3615																					
4	5.1500000	2.2945																					
5	5.8500000	3.1041																					

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±

SCALE : UNIT : mm

DRAWN BY :Huangshiyong CHECKED BY : Xiaokunxiong

DESIGNED BY : Lishenghua APPROVED BY : Wangwei

TITLE : **E7165UO-4IN1ANT-V1.0Specification**



深圳市可信华成通信科技有限公司

SHENZHEN CITY KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.


PAGE REV.
A0

2-4. Measure and Chamber

2-4-1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

2-4-2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)
5. Test equipment: CMW500, 8960

UNLESS OTHER SPECIFIED TOLERANCES ON : X=±2 X.X=±0.1 X.XX=±0.05 ANGLES=± HOLEDIA=±		 深圳市可信华成通信科技有限公司 SHENZHEN CITY KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY :Huangshiyong	CHECKED BY : Xiaokunxiong		
DESIGNED BY : Lishenghua	APPROVED BY : Wangwei		
TITLE : E7165UO-4IN1ANT-V1.0Specification		DOCUMENT NO.	PAGE REV. A0

2-4-3 Antenna OTA








2.4G	1	11Mbps	12.83	11Mbps	-83.26
	6	11Mbps	12.73	11Mbps	-83.75
	11	11Mbps	13.19	11Mbps	-85.99
5G	36	6Mbps	11.6	54Mbps	-68.78
	48	6Mbps	11.86	54Mbps	-71.47
	149	6Mbps	12.53	54Mbps	-70.78
	165	6Mbps	12.9	54Mbps	-70.93

2-4-4 Antenna Efficiency

GPS				2.4G WIFI				5G WIFI			
Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)	Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)	Frequency (MHz)	Gain (dBi)	Efficiency (dB)	Efficiency (%)
1550	3.27	-5.08	31%	2400	4.39	-3.17	48%	5150	1.72	-5.83	26%
1555	2.30	-5.48	28%	2410	4.58	-3.17	48%	5200	1.66	-5.77	26%
1560	2.25	-5.20	30%	2420	5.01	-2.97	51%	5250	1.99	-5.74	27%
1565	2.09	-5.24	30%	2430	4.52	-3.09	49%	5300	1.99	-5.31	29%
1570	1.93	-5.20	30%	2440	4.30	-3.19	48%	5350	2.39	-5.22	30%
1575	1.75	-4.82	33%	2450	4.61	-3.03	50%	5400	2.53	-5.13	31%
1580	1.46	-4.70	34%	2460	4.19	-3.07	49%	5450	2.57	-5.11	31%
1585	1.58	-4.45	36%	2470	3.77	-3.22	48%	5500	3.04	-5.03	31%
1590	1.84	-4.10	39%	2480	3.88	-3.15	48%	5550	2.52	-5.16	31%
1595	1.69	-4.19	38%	2490	3.72	-3.17	48%	5600	2.32	-5.40	29%
1600	1.68	-4.04	39%	2500	3.27	-3.36	46%	5650	2.39	-5.53	28%
								5700	1.07	-6.10	25%
								5750	0.83	-6.06	25%
								5800	1.22	-5.66	27%
								5850	-0.43	-7.06	20%


UNLESS OTHER SPECIFIED TOLERANCES ON :		 深圳市可信华成通信科技有限公司 SHENZHEN CITY KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD	
X=±2 X.X=±0.1 X.XX=±0.05		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
ANGLES=±			

3. 3D Radiation Pattern



UNLESS OTHER SPECIFIED TOLERANCES ON :		 深圳市可信华成通信科技有限公司 SHENZHEN CITY KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD	
X=±2	X.X=±0.1		
ANGLES=±		HOLEDIA=±	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY :Huangshiyong	CHECKED BY : Xiaokunxiong		
DESIGNED BY : Lishenghua	APPROVED BY : Wangwei		
TITLE : <u>E7165UO-4IN1ANT-V1.0</u> Specification		DOCUMENT NO.	PAGE REV. A0

4. Antenna Dimensions:



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±

SCALE :

UNIT : mm

DRAWN BY :Huangshiyong

CHECKED BY : Xiaokunxiong

DESIGNED BY : Lishenghua

APPROVED BY : Wangwei

TITLE : E7165UO-4IN1ANT-V1.0Specification



深圳市可信华成通信科技有限公司

SHENZHEN CITY KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF KEXIN HUACHENG COMMUNICATION TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT NO.

PAGE REV. A0