

1		2		3		4		5		6									
A							版本	标记	变更描述		修定者	修定日期	生效日期						
							A0		初版发行		邱平秀宇	2024-5-22							
B	OSCAL Portable Power Station(Lithium-ion battery) Model: PowerMax 2400 SE Total Output Power: 2400W AC Output*4: 120V~50Hz/60Hz,Total 2400W USB-A Output: 5V~2.4A,12W Max USB-A QC3.0 Output*3: 5V~3A,9V~2A,12V~1.5A,18W Max Type-C PD3.0 Output*2: 5/9/12/15V~3A,20V~5A,Shared 100W DC5521 Output*2: 12V~6A Max,Total 72W Anderson output interface: 12V~10A Max,Shared 120W Car Charge Output: 12V~10A Max,Shared 120W Battery Capacity: 44.8V~,45Ah,2016Wh AC Input: 100-120V~,15A Max,50Hz/60Hz,1500W Max Solar Input: 12-60V~,20A Max,1200W Max Discharging Temperature: -10°C~45°C Charging Temperature Of Cells: 0°C~45°C FCC ID:2A98M-PM2400SE IFpR34/141[3P14S]M/-10+40/80 Made in China Manufacturer:Shenzhen Doke Communication Co., Ltd Warnings 1. Do not disconnect, disassemble or repair by yourself 2. Do not drop, deform, impact, cut or spearing with a sharp object. 3. Do not place near open fame or incinerate. 4. Do not sit or put heavy things on battery. Keep away from moisture or liquid. 5. Do not parallel connection with different batteries. 6. Do not connect batteries in series. 7. Recharge battery in every six months. 8. Disposal of batteries should follow local regulations. Li-ion 30 RoHS FC BC						B												
																			C
D	D2400美规铭牌 料号：A26090D24000003 尺寸：139.6*69.6mm R=9.8mm 材质：哑银龙 印刷：黑底银字						尺寸公差		制定			名称				D			
							0~5 ±0.05 5~10 ±0.08 10~25 ±0.10 25~50 ±0.12 ≥50 ±0.15		审核			编码							
									批准			图号							
							THIRD ANGLE PROJECTION		比例		1:1	单位	mm						
									版本		A0	页码	1 OF 1						
1		2		3		4		5		6									

Label location:

