



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street,
Bao'an District, Shenzhen, China

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No......: **CTA22112100603**

FCC ID.....: **2A9DQ-BBH**

Compiled by

(position+printed name+signature) .: File administrators Zoey Cao

Supervised by

(position+printed name+signature) .: Project Engineer Amy Wen

Approved by

(position+printed name+signature) .: RF Manager Eric Wang

Date of issue: Dec. 09, 2022

Testing Laboratory Name: **Shenzhen CTA Testing Technology Co., Ltd.**

Address.....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community,
Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.....: **Shenzhen Alpha Optik Technology Co.,Ltd.**

Address: Room 801, 8th Floor, Building 1, Hengtaiyu Building, Tonghui Road,
Fenghuang Street, Guangming District, Shenzhen, China

Test specification

Standard: **FCC Part 15 Subpart E 15.407**

TRF Originator.....: Shenzhen CTA Testing Technology Co., Ltd.

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: **Smart Portable Projector**

Trade Mark: staratlas

Manufacturer: Shenzhen Alpha Optik Technology Co.,Ltd.

Model/Type reference: L36

Listed Models: L36P, L36T, L38, L38P, L38T

Modulation: OFDM

Frequency: From 5180MHz-5240MHz, 5745MHz-5825MHz

Ratings: DC 10.8V From Battery and DC 15V From external circuit

Result: **PASS**

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

TEST REPORT

Equipment under Test : Smart Portable Projector

Model /Type : L36

Serial Models : L36P, L36T, L38, L38P, L38T

Applicant : Shenzhen Alpha Optik Technology Co.,Ltd.

Address : Room 801, 8th Floor, Building 1, Hengtaiyu Building, Tonghui Road,
Fenghuang Street, Guangming District, Shenzhen, China

Manufacturer : Shenzhen Alpha Optik Technology Co.,Ltd.

Address : 2A 1st floor Baoxing Science and Technology Park, Light Source
Five Road ,Guangming District, Shenzhen, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1	TEST STANDARDS	4
2	SUMMARY	5
2.1	General Remarks	5
2.2	Product Description	5
2.3	Equipment Under Test	5
2.4	Short description of the Equipment under Test (EUT)	5
2.5	EUT operation mode	6
2.6	Block Diagram of Test Setup	6
2.7	Related Submittal(s) / Grant (s)	6
2.8	Modifications	6
3	TEST ENVIRONMENT	7
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Environmental conditions	7
3.4	Test Description	8
3.5	Statement of the measurement uncertainty	8
3.6	Equipments Used during the Test	9
4	TEST CONDITIONS AND RESULTS.....	10
4.1	AC Power Conducted Emission	10
4.2	Radiated Emissions	13
4.3	Maximum Conducted Average Output Power	20
4.4	Power Spectral Density	26
4.5	Emission Bandwidth (26dB Bandwidth)	46
4.6	Minimum Emission Bandwidth (6dB Bandwidth)	55
4.7	Frequency Stability	66
5	TEST SETUP PHOTOS OF THE EUT	69
6	PHOTOS OF THE EUT	70

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v01r02

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Nov. 21, 2022
Testing commenced on	:	Nov. 21, 2022
Testing concluded on	:	Dec. 09, 2022

2.2 Product Description

Product Description:	Smart Portable Projector			
Model:	L36			
Power supply:	DC 10.8V From Battery and DC 15V From external circuit			
Adapter information:	Mode: BSG065B-1503000 Input:AC100-240V, 50/60Hz Output:DC 15V, 3A			
testing sample ID:	CTA221121006-1# (Engineer sample), CTA221121006-2# (Normal sample)			
Hardware version:	V1.0			
Software version:	V1.0			
WIFI				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a 802.11n 802.11ac 802.11ax	802.11n 802.11ac 802.11ax	N/A	N/A
Operation frequency:	5180MHz-5240MHz 5745MHz-5825MHz	5190MHz-5230MHz 5755MHz-5795MHz	N/A	N/A
Modulation:	OFDM	OFDM	N/A	N/A
Channel number:	9	4	N/A	N/A
Channel separation:	20MHz	40MHz	N/A	N/A
Antenna type:	Internal antenna			
Antenna gain:	2.95 dBi for Ant 0 and Ant 1			

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 10.8V From Battery and DC 15V From external circuit

2.4 Short description of the Equipment under Test (EUT)

This is a Smart Portable Projector.

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

For more details, refer to the user's manual of the EUT.

2.5 EUT operation mode

The Applicant provides communication tools software (AT command) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.


All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

Operating band	20MHz		40MHz		80MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180	38	5190	--	--
	40	5200				
	44	5220	46	5230		
	48	5240				
U-NII 3 (5725MHz-5850MHz)	149	5745	151	5755	--	--
	153	5765				
	157	5785	159	5795		
	161	5805				
	165	5825	--	--	--	--

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

2.6 Block Diagram of Test Setup



2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	25 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	25 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

AC Power Conducted Emission

Temperature:	24 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.407(a)	Emission Bandwidth(26dBm Bandwidth)	PASS ^{Note1}
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dBm Bandwidth)	PASS ^{Note2}
FCC Part 15.407(a)	Maximum Conducted Output Power	PASS
FCC Part 15.407(a)	Peak Power Spectral Density	PASS
FCC Part 15.407(g)	Frequency Stability	PASS
FCC Part 15.407(b)	Undesirable emission	PASS
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.407(h)	Dynamic Frequency Selection	N/A ^{Note 3}
FCC Part 15.203/15.247(b)	Antenna Requirement	PASS

Note 1: Apply to U-NII 1 band.

Note 2: Apply to U-NII 3 band only.

Note 3: This device not work in DFS band.

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power	11a/OFDM	6 Mbps
Power Spectral Density	11n(20MHz),11ac/ax(20MHz)/OFDM	7.2 Mbps
Emission Bandwidth(26dBm Bandwidth)		
Minimum Emission Bandwidth(6dBm Bandwidth)	11n(40MHz),11ac/ax(40MHz)/OFDM	15.0Mbps
Undesirable emission		
Frequency Stability		

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen CTA Testing Technology Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd.:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn


3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	CTA-308	2022/08/03	2023/08/02
LISN	R&S	ENV216	CTA-314	2022/08/03	2023/08/02
EMI Test Receiver	R&S	ESPI	CTA-307	2022/08/03	2023/08/02
EMI Test Receiver	R&S	ESCI	CTA-306	2022/08/03	2023/08/02
Spectrum Analyzer	Agilent	N9020A	CTA-301	2022/08/03	2023/08/02
Spectrum Analyzer	R&S	FSP	CTA-337	2022/08/03	2023/08/02
Vector Signal generator	Agilent	N5182A	CTA-305	2022/08/03	2023/08/02
Analog Signal Generator	R&S	SML03	CTA-304	2022/08/03	2023/08/02
Universal Radio Communication	CMW500	R&S	CTA-302	2022/08/03	2023/08/02
Temperature and humidity meter	Chigo	ZG-7020	CTA-326	2022/08/03	2023/08/02
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	CTA-310	2021/08/07	2024/08/06
Horn Antenna	Schwarzbeck	BBHA 9120D	CTA-309	2021/08/07	2024/08/06
Loop Antenna	Zhinan	ZN30900C	CTA-311	2021/08/07	2024/08/06
Horn Antenna	Beijing Hangwei Dayang	OBH100400	CTA-336	2021/08/07	2024/08/06
Amplifier	Schwarzbeck	BBV 9745	CTA-312	2022/08/03	2023/08/02
Amplifier	Taiwan chengyi	EMC051845B	CTA-313	2022/08/03	2023/08/02
Directional coupler	NARDA	4226-10	CTA-303	2022/08/03	2023/08/02
High-Pass Filter	XingBo	XBLBQ-GTA18	CTA-402	2022/08/03	2023/08/02
High-Pass Filter	XingBo	XBLBQ-GTA27	CTA-403	2022/08/03	2023/08/02
Automated filter bank	Tonscend	JS0806-F	CTA-404	2022/08/03	2023/08/02
Power Sensor	Agilent	U2021XA	CTA-405	2022/08/03	2023/08/02
Amplifier	Schwarzbeck	BBV9719	CTA-406	2022/08/03	2023/08/02

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :


Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.


TEST RESULTS

Remark:

1. All modes of 802.11a/n were tested at Low, Middle, and High channel; only the worst result of 802.11a CH36 was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:



Power supply:	DC 15V from Adapter AC 120V/60Hz	Polarization	N
---------------	-------------------------------------	--------------	---



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading[dB μV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2710	10.50	29.97	40.47	61.09	20.62	16.03	26.53	51.09	24.56	PASS
2	0.4845	10.50	25.15	35.65	56.26	20.61	14.35	24.85	46.26	21.41	PASS
3	1.1702	10.50	22.86	33.36	56.00	22.64	12.13	22.63	46.00	23.37	PASS
4	4.0261	10.50	17.63	28.13	56.00	27.87	4.86	15.36	46.00	30.64	PASS
5	13.1639	10.50	13.54	24.04	60.00	35.96	7.86	18.36	50.00	31.64	PASS
6	24.1647	10.50	14.53	25.03	60.00	34.97	-1.62	8.88	50.00	41.12	PASS

Note: 1). QP Value (dBμV) = QP Reading (dBμV) + Factor (dB)

2). Factor (dB) = insertion loss of LISN (dB) + Cable loss (dB)

3). QPMargin(dB) = QP Limit (dBμV) - QP Value (dBμV)

4). AVMargin(dB) = AV Limit (dBμV) - AV Value (dBμV)

4.2 Radiated Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) Note1
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

- Setting test receiver/spectrum as following table states:


Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak


TEST RESULTS

Remark:

- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for below 1GHz test, only the worst case 802.11a low channel of U-NII 1 band was recorded.
- All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz





For 1GHz to 40GHz

Note: All 802.11a / 802.11n/ac/ax (HT20) /802.11n/ac/ax (HT40) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.

U-NII 1 & 802.11a Mode (above 1GHz)

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00 (5180MHz)	5150.00	56.53	PK	H	68.20	11.67	59.96	33.04	5.45	41.92	-3.43
	5150.00	47.63	AV	H	54.00	6.37	51.06	33.04	5.45	41.92	-3.43
	10360.00	51.85	PK	H	68.20	16.35	38.83	38.83	10.12	45.28	3.67
	--	--	--	--	--	--	--	--	--	--	--
44.00 (5220MHz)	10400.00	51.56	PK	H	68.20	16.64	47.88	38.85	10.13	45.3	3.68
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5240MHz)	5350.50	47.09	PK	H	68.20	21.11	50.36	32.84	5.97	42.08	-3.27
	10480.00	51.17	PK	H	68.20	17.03	47.43	38.89	10.19	45.34	3.74
	--	--	--	--	--	--	--	--	--	--	--

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00 (5180MHz)	5150.00	54.80	PK	V	68.20	13.40	58.23	33.04	5.45	41.92	-3.43
	5150.00	47.42	AV	V	54.00	6.58	50.85	33.04	5.45	41.92	-3.43
	10360.00	51.62	PK	V	68.20	16.58	47.95	38.83	10.12	45.28	3.67
	--	--	--	--	--	--	--	--	--	--	--
44.00 (5220MHz)	10400.00	51.61	PK	V	68.20	16.59	47.93	38.85	10.13	45.3	3.68
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5240MHz)	5350.50	51.72	PK	V	68.20	16.48	54.99	32.84	5.97	42.08	-3.27
	10480.00	51.52	PK	V	68.20	16.68	47.78	38.89	10.19	45.34	3.74
	--	--	--	--	--	--	--	--	--	--	--

U-NII 3 & 802.11a Mode (above 1GHz)

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
	5720.00	55.32	PK	H	68.20	12.88	58.10	33.42	6.04	42.24	-2.78
149.00 (5745MHz)	5720.00	47.57	AV	H	54.00	6.43	50.35	33.42	6.04	42.24	-2.78
	11490.00	50.79	PK	H	68.20	17.41	46.31	39.02	10.91	45.45	4.48
	--	--	--	--	--	--	--	--	--	--	--
157.00 (5785MHz)	11570.00	51.48	PK	H	68.20	16.72	47.03	38.93	10.95	45.43	4.45
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5825MHz)	5855.00	51.69	PK	H	68.20	16.51	53.88	33.91	6.17	42.27	-2.19
	11650.00	52.64	PK	H	68.20	15.56	48.06	38.83	11.16	45.41	4.58
	--	--	--	--	--	--	--	--	--	--	--

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
	5720.00	56.49	PK	V	68.20	11.71	59.27	33.42	6.04	42.24	-2.78
149.00 (5745MHz)	5720.00	47.32	AV	V	54.00	6.68	50.10	33.42	6.04	42.24	-2.78
	11490.00	49.62	PK	V	68.20	18.58	45.14	39.02	10.91	45.45	4.48
	--	--	--	--	--	--	--	--	--	--	--
157.00 (5785MHz)	11570.00	51.26	PK	V	68.20	16.94	46.81	38.93	10.95	45.43	4.45
	--	--	--	--	--	--	--	--	--	--	--
48.00 (5825MHz)	5855.00	51.38	PK	V	68.20	16.82	53.57	33.91	6.17	42.27	-2.19
	11650.00	52.38	PK	V	68.20	15.82	47.80	38.83	11.16	45.41	4.58
	--	--	--	--	--	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW 1MHz VBW 3MHz Peak detector is for PK value; RBW 1MHz VBW 10Hz Peak detector is for AV value.
6. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;

4.3 Maximum Conducted Average Output Power

Limit

For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results**U-NII 1****ANT 1**

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11a	36	14.24	24.0	Pass
	44	14.43		
	48	14.78		
802.11n(HT20)	36	13.11	24.0	Pass
	44	13.29		
	48	13.58		
802.11n(HT40)	38	12.35	24.0	Pass
	46	12.25		
802.11ac(HT20)	36	12.99	24.0	Pass
	44	12.14		
	48	12.56		
802.11ac(HT40)	38	12.57	24.0	Pass
	46	12.37		
802.11ax(HT20)	36	12.27	24.0	Pass
	44	12.84		
	48	12.79		
802.11ax(HT40)	38	12.47	24.0	Pass
	46	12.34		

ANT 2

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11a	36	14.14	24.0	Pass
	44	14.80		
	48	14.06		
802.11n(HT20)	36	12.76	24.0	Pass
	44	12.52		
	48	12.66		
802.11n(HT40)	38	12.36	24.0	Pass
	46	12.54		
802.11ac(HT20)	36	12.76	24.0	Pass
	44	12.56		
	48	12.12		
802.11ac(HT40)	38	12.39	24.0	Pass
	46	12.57		
802.11ax(HT20)	36	12.80	24.0	Pass
	44	12.51		
	48	12.73		
802.11ax(HT40)	38	12.32	24.0	Pass
	46	12.54		

U-NII 3

ANT 1

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11a	149	14.89	30.00	Pass
	157	14.64		
	165	14.27		
802.11n(HT20)	149	13.78	30.00	Pass
	157	13.63		
	165	13.31		
802.11n(HT40)	151	13.61	30.00	Pass
	159	13.22		
802.11ac(HT20)	149	13.09	30.00	Pass
	157	13.85		
	165	13.50		
802.11ac(HT40)	151	13.83	30.00	Pass
	159	13.52		
802.11ax(HT20)	149	13.01	30.00	Pass
	157	13.92		
	165	13.61		
802.11ax(HT40)	151	13.86	30.00	Pass
	159	13.46		

ANT 2

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11a	149	12.56	30.00	Pass
	157	12.61		
	165	12.39		
802.11n(HT20)	149	11.43	30.00	Pass
	157	11.40		
	165	11.13		
802.11n(HT40)	151	11.19	30.00	Pass
	159	11.77		
802.11ac(HT20)	149	11.62	30.00	Pass
	157	11.53		
	165	11.25		
802.11ac(HT40)	151	11.18	30.00	Pass
	159	11.86		
802.11ax(HT20)	149	11.46	30.00	Pass
	157	11.34		
	165	11.15		
802.11ax(HT40)	151	11.14	30.00	Pass
	159	11.76		

For MIMO:

U-NII 1

Type	Channel	Output power (dBm) ANT1	Output power (dBm) ANT2	Output power (dBm) MIMO	Limit (dBm)	Result
802.11n(HT20)	36	13.11	14.14	16.67	24.0	Pass
	44	13.29	14.80	17.12		
	48	13.58	14.06	16.84		
802.11n(HT40)	38	12.35	12.76	15.57	24.0	Pass
	46	12.25	12.52	15.40		
802.11ac(HT20)	36	12.99	12.66	15.84	24.0	Pass
	44	12.14	12.36	15.26		
	48	12.56	12.54	15.56		
802.11ac(HT40)	38	12.57	12.76	15.68	24.0	Pass
	46	12.37	12.56	15.48		
802.11ax(HT20)	36	12.27	12.12	15.21	24.0	Pass
	44	12.84	12.39	16.55		
	48	12.79	12.57	15.60		
802.11ax(HT40)	38	12.47	12.80	15.53	24.0	Pass
	46	12.34	12.51	15.59		

U-NII 3

Type	Channel	Output power (dBm) ANT1	Output power (dBm) ANT2	Output power (dBm) MIMO	Limit (dBm)	Result
802.11n(HT20)	149	13.78	11.43	15.77	30.0	Pass
	157	13.63	11.40	15.67		
	165	13.31	11.13	15.37		
802.11n(HT40)	151	13.61	11.19	15.58	30.0	Pass
	159	13.22	11.77	15.57		
802.11ac(HT20)	149	13.09	11.62	15.43	30.0	Pass
	157	13.85	11.53	15.85		
	165	13.50	11.25	15.53		
802.11ac(HT40)	151	13.83	11.18	15.71	30.0	Pass
	159	13.52	11.86	15.78		
802.11ax(HT20)	149	13.01	11.46	15.31	30.0	Pass
	157	13.92	11.34	15.83		
	165	13.61	11.15	15.56		
802.11ax(HT40)	151	13.86	11.14	15.72	30.0	Pass
	159	13.46	11.76	15.70		

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

4.4 Power Spectral Density

Limit

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. ^{note1, note2}

Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 510KHz for U-NII 3 band.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to encompass the entire EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

Test Configuration



Test Results**ANT 1**

Type	Bands	Channel	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)	Result
802.11a	U-NII 1	36	2.70	11.0	Pass
		44	1.90		
		48	2.00		
802.11n (HT20)	U-NII 1	36	1.28		
		44	0.49		
		48	0.45		
802.11n (HT40)	U-NII 1	38	-2.23		
		46	-2.47		
802.11ac (HT20)	U-NII 1	36	1.15		
		44	0.28		
		48	0.48		
802.11ac (HT40)	U-NII 1	38	-2.00		
		46	-2.36		
802.11ax (HT20)	U-NII 1	36	1.45		
		44	0.95		
		48	0.65		
802.11ax (HT40)	U-NII 1	38	-2.11		
		46	-2.39		

Type	Bands	Channel	Power Spectral Density (dBm/300KHz)	Power Spectral Density (dBm/500KHz)	Limit (dBm/500KHz)	Result
802.11a	U-NII 3	149	0.49	2.71	30.0	Pass
		157	0.21	2.43		
		165	-0.21	2.01		
802.11n (HT20)	U-NII 3	149	-0.85	1.37		
		157	-0.13	2.09		
		165	-0.45	1.77		
802.11n (HT40)	U-NII 3	151	-3.87	-1.65		
		159	-3.31	-1.09		
802.11ac (HT20)	U-NII 3	149	-0.56	1.66		
		157	0.11	2.33		
		165	-0.27	1.95		
802.11ac (HT40)	U-NII 3	151	-3.79	-1.57		
		159	-2.94	-0.72		
802.11ax (HT20)	U-NII 3	149	-0.60	1.62		
		157	0.14	2.36		
		165	-0.07	2.15		
802.11ax (HT40)	U-NII 3	151	-3.75	-1.53		
		159	-3.06	-0.84		

Remark: P.S.D(dBm/500KHz)= P.S.D(dBm/300KHz)+10 log (500 kHz/300KHz).

ANT 2

Type	Bands	Channel	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)	Result
802.11a	U-NII 1	36	2.43	11.0	Pass
		44	1.87		
		48	2.15		
802.11n (HT20)	U-NII 1	36	0.78		
		44	0.31		
		48	0.44		
802.11n (HT40)	U-NII 1	38	-2.35		
		46	-2.35		
802.11ac (HT20)	U-NII 1	36	0.78		
		44	0.32		
		48	0.88		
802.11ac (HT40)	U-NII 1	38	-2.32		
		46	-2.32		
802.11ax (HT20)	U-NII 1	36	0.81		
		44	0.29		
		48	0.52		
802.11ax (HT40)	U-NII 1	38	-2.40		
		46	-2.34		

Type	Bands	Channel	Power Spectral Density (dBm/300KHz)	Power Spectral Density (dBm/500KHz)	Limit (dBm/500KHz)	Result
802.11a	U-NII 3	149	-1.97	0.25	30.0	Pass
		157	-1.86	0.36		
		165	-2.02	0.20		
802.11n (HT20)	U-NII 3	149	-3.26	-1.04		
		157	-3.32	-1.10		
		165	-3.66	-1.44		
802.11n (HT40)	U-NII 3	151	-6.37	-4.15		
		159	-6.77	-4.55		
802.11ac (HT20)	U-NII 3	149	-3.15	-0.93		
		157	-3.27	-1.05		
		165	-3.52	-1.30		
802.11ac (HT40)	U-NII 3	151	-6.40	-4.18		
		159	-6.68	-4.46		
802.11ax (HT20)	U-NII 3	149	-3.31	-1.09		
		157	-3.43	-1.21		
		165	-3.59	-1.37		
802.11ax (HT20)	U-NII 3	151	-6.39	-4.17		
		159	-6.81	-4.59		

Remark: P.S.D(dBm/500KHz)= P.S.D(dBm/300KHz)+10 log (500 kHz/300KHz).

For MIMO:

U-NII 1

Type	Channel	Power Spectral Density ANT1	Power Spectral Density ANT2	Power Spectral Density MIMO	Limit (dBm)	Result
802.11n(HT20)	36	1.28	2.43	4.90	11.0	PASS
	44	0.49	1.87	4.24		
	48	0.45	2.15	4.39		
802.11n(HT40)	38	-2.23	0.78	2.54		
	46	-2.47	0.31	2.15		
802.11ac(HT20)	36	1.15	0.44	3.82		
	44	0.28	-2.35	2.17		
	48	0.48	-2.35	2.30		
802.11ac(HT40)	38	-2.00	0.78	2.62		
	46	-2.36	0.32	2.19		
802.11ax(HT20)	36	1.45	0.88	4.18		
	44	0.95	-2.32	2.63		
	48	0.65	-2.32	2.42		
802.11ax(HT40)	38	-2.11	0.81	2.60		
	46	-2.39	0.29	2.16		

U-NII 3

Type	Channel	Power Spectral Density (dBm/500KHz) ANT1	Power Spectral Density (dBm/500KHz) ANT2	Power Spectral Density (dBm/500KHz) MIMO	Limit (dBm)	Result
802.11n(HT20)	149	1.37	-1.04	3.34	30.0	Pass
	157	2.09	-1.10	3.79		
	165	1.77	-1.44	3.47		
802.11n(HT40)	151	-1.65	-4.15	0.29		
	159	-1.09	-4.55	0.53		
802.11ac(HT20)	149	1.66	-0.93	3.57		
	157	2.33	-1.05	3.97		
	165	1.95	-1.30	3.63		
802.11ac(HT40)	151	-1.57	-4.18	0.33		
	159	-0.72	-4.46	0.81		
802.11ax(HT20)	149	1.62	-1.09	3.48		
	157	2.36	-1.21	3.94		
	165	2.15	-1.37	3.75		
802.11ax(HT40)	151	-1.53	-4.17	0.36		
	159	-0.84	-4.59	0.69		

Test plot as follows
ANT 1

802.11a


U-NII 1



U-NII 3




CH36



CH149



CH44



CH157



CH48

CH165

802.11n(HT20)

U-NII 1



U-NII 3



CH36



CH149



CH44



CH157



CH48

CH165

802.11n(HT40)

U-NII 1



U-NII 3



CH38



CH151



CH46



CH159



802.11ac(HT20)

U-NII 1



U-NII 3



CH36



CH149



CH44



CH157



CH48



CH165



802.11ac(HT40)

U-NII 1



U-NII 3



CH38



CH151



CH46



CH159



802.11ax(HT20)

U-NII 1



U-NII 3





CH36





CH149





802.11ax(HT40)





ANT 2

802.11a

U-NII 1



U-NII 3



CH36



CH149



CH44



CH157



CH48

CH165

802.11n(HT20)

U-NII 1



U-NII 3



CH36



CH149



CH44



CH157



CH48

CH165

802.11n(HT40)

U-NII 1



U-NII 3



CH38



CH151



CH46



CH159



802.11ac(HT20)

U-NII 1



U-NII 3



CH36



CH149



CH44



CH157



CH48

CH165

802.11ac(HT40)

U-NII 1



U-NII 3




CH38




CH151



CH46



CH159



802.11ax(HT20)

U-NII 1





U-NII 3



CH36

CH149




802.11ax(HT40)



CH38

CH151



4.5 Emission Bandwidth (26dB Bandwidth)


Limit

N/A

Test Procedure

1. Set resolution bandwidth (RBW) = approximately 1 % of the EBW.
2. Set the video bandwidth (VBW) > RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW / EBW ratio is approximately 1 %.

Test Configuration



Test Results

ANT 1

Type	Bands	Channel	26dB Bandwidth (MHz)	Limit (MHz)	Result
802.11a	U-NII 1	36	18.480	N/A	Pass
		44	18.360		
		48	18.440		
802.11n(HT20)	U-NII 1	36	19.360		
		44	19.360		
		48	19.400		
802.11n(HT40)	U-NII 1	38	40.720		
		46	41.120		
802.11ac(HT20)	U-NII 1	36	19.360		
		44	19.560		
		48	19.440		
802.11ac(HT40)	U-NII 1	38	40.960		
		46	40.880		
802.11ax(HT20)	U-NII 1	36	19.280		
		44	19.400		
		48	19.520		
802.11ax(HT40)	U-NII 1	38	41.040		
		46	41.040		


ANT 2

Type	Bands	Channel	26dB Bandwidth (MHz)	Limit (MHz)	Result
802.11a	U-NII 1	36	18.400	N/A	Pass
		44	19.280		
		48	18.520		
802.11n(HT20)	U-NII 1	36	19.480		
		44	19.480		
		48	19.400		
802.11n(HT40)	U-NII 1	38	40.800		
		46	40.960		
802.11ac(HT20)	U-NII 1	36	19.560		
		44	19.560		
		48	19.440		
802.11ac(HT40)	U-NII 1	38	41.120		
		46	41.040		
802.11ax(HT20)	U-NII 1	36	19.440		
		44	19.480		
		48	19.480		
802.11ax(HT40)	U-NII 1	38	41.040		
		46	40.800		

Test plot as follows:

ANT 1


802.11a



802.11n(HT20)



CH36



CH36



CH44



CH44



CH48

CH48


802.11n(HT40)



802.11ac(HT20)



CH38



CH36



CH46



CH44



CH48

802.11ac(HT40)



802.11ax(HT20)



CH38



CH36



CH46




CH44



CH40

802.11ax(HT40)

/



CH38

/




CH46

ANT 2

802.11a




802.11n(HT20)



CH36



CH36



CH44




CH44



CH48

CH48

802.11n(HT40)




802.11ac(HT20)



CH38




CH36



CH46



CH44




CH48

802.11ac(HT40)




802.11ax(HT20)




CH38




CH36



CH46




CH44



CH48

802.11ax(HT40)

/



CH38

/



CH46

4.6 Minimum Emission Bandwidth (6dB Bandwidth)


Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth 3 x RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration



Test Results

ANT 1

Type	Bands	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11a	U-NII 3	149	16.480	≥500KHz	Pass
		157	16.520		
		165	16.480		
802.11n(HT20)	U-NII 3	149	17.680		
		157	17.640		
		165	17.720		
802.11n(HT40)	U-NII 3	151	36.400		
		159	36.480		
802.11ac(HT20)	U-NII 3	149	17.680		
		157	17.680		
		165	17.680		
802.11ac(HT40)	U-NII 3	151	36.400		
		159	36.400		
802.11ax(HT20)	U-NII 3	149	17.680		
		157	17.720		
		165	17.680		
802.11ax(HT40)	U-NII 3	151	36.400		
		159	36.400		

ANT 2

	Bands	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11a	U-NII 3	149	16.560	≥500KHz	Pass
		157	16.520		
		165	16.520		
802.11n(HT20)	U-NII 3	149	17.720		
		157	17.720		
		165	17.680		
802.11n(HT40)	U-NII 3	151	36.400		
		159	36.400		
802.11ac(HT20)	U-NII 3	149	17.640		
		157	17.680		
		165	17.720		
802.11ac(HT40)	U-NII 3	151	36.400		
		159	36.400		
802.11ax(HT20)	U-NII 3	149	17.680		
		157	17.680		
		165	17.680		
802.11ax(HT40)	U-NII 3	151	36.400		
		159	36.400		


Test plot as follows:

ANT 1


802.11a




802.11n(HT20)



CH149




CH149




CH157




CH157




CH165




CH165




802.11n(HT40)



802.11ac(HT20)



CH151




CH149



CH159



CH157



CH165


802.11ac(HT40)



802.11ax(HT20)



CH151



CH149



CH159



CH157



CH165




CH165



802.11ax(HT40)

/



CH151


/



CH159

ANT 2

802.11a



802.11n(HT20)




CH149



CH149



CH157



CH157




CH165




CH165




802.11n(HT40)



802.11ac(HT20)



CH151



CH149



CH159




CH157




CH165


802.11ac(HT40)



802.11ax(HT20)



CH151



CH149



CH159




CH157



CH165

802.11ax(HT40)

/



CH151

/




CH159

4.7 Frequency Stability

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

TEST CONFIGURATION



TEST PROCEDURE

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Record worst case as below:

Ant1:

Reference Frequency: 802.11ac channel=36 frequency=5180MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
DC 10.8	-30	110.48	0.021328	Within the band of operation	Pass
	-20	173.93	0.033577		
	-10	145.65	0.028118		
	0	146.24	0.028232		
	10	145.76	0.028139		
	20	98.42	0.019000		
	30	167.13	0.032264		
	40	129.54	0.025008		
	50	128.67	0.024840		
DC 11.88	25	196.08	0.037853	Within the band of operation	Pass
DC 9.72	25	118.36	0.022849		



Reference Frequency: 802.11ac channel=149 frequency=5745MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
DC 10.8	-30	135.75	0.023629	Within the band of operation	Pass
	-20	129.80	0.022594		
	-10	167.28	0.029117		
	0	169.36	0.029480		
	10	136.43	0.023748		
	20	143.94	0.025055		
	30	116.07	0.020204		
	40	169.65	0.029530		
	50	160.41	0.027922		
DC 11.88	25	150.29	0.026160	Within the band of operation	Pass
DC 9.72	25	129.82	0.022597		

Ant2:

Reference Frequency: 802.11ac channel=36 frequency=5180MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
DC 10.8	-30	110.25	0.021284	Within the band of operation	Pass
	-20	174.37	0.033662		
	-10	145.94	0.028174		
	0	146.29	0.028241		
	10	146.08	0.028201		
	20	98.27	0.018971		
	30	167.74	0.032382		
	40	129.82	0.025062		
	50	129.16	0.024934		
DC 11.88	25	195.57	0.037755	Within the band of operation	Pass
DC 9.72	25	118.73	0.022921		

Reference Frequency: 802.11ac channel=149 frequency=5745MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
DC 10.8	-30	136.28	0.023721	Within the band of operation	Pass
	-20	128.75	0.022411		
	-10	167.67	0.029185		
	0	169.46	0.029497		
	10	136.83	0.023817		
	20	144.54	0.025159		
	30	116.58	0.020292		
	40	169.73	0.029544		
	50	160.69	0.027970		
DC 11.88	25	149.47	0.026017	Within the band of operation	Pass
DC 9.72	25	130.27	0.022675		

5 Test Setup Photos of the EUT



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: <http://www.cta-test.cn>

6 Photos of the EUT

Reference to the test report No. **CTA22112100601**

***** End of Report *****