

样品承认书

SPECIFICATION FOR APPROVAL

● 物料名称

Name of material: P601 天线 (P601 antenna)

● 供应商

Vendor Name : 深圳星联讯通科技有限公司

Shenzhen Starlink COMM. Technology Co., Ltd.
Room 403, Building A, Zhiyun Industrial Park, No. 13,
Huaxing Road, Tongsheng Community, Dalang Subdistrict,
Longhua District, Shenzhen City

● 物料描述

Material description: FPC焊接Cable (FPC weld
Cable)

● 物料料号

Material number: 1.4R. 3713.000064

● 物料丝印

Material screen printing: YX-P601-WIFI2-V3.0

供方确认 Supplier confirmation:		客户确认 customer confirmation:	
测试 test:	研发 RF:	测试 test:	研发 RF:
		采购 purchase:	
品质 quality:	审核 check:	品质 quality:	审核 check:

Directory

- 1、 face
- 2、 catalogue
- 3、 ICD drawing
- 4、 Antenna performance and precautions
- 5、 Full scale measurement report
- 6、 inspection specification
- 7、 Rohs data
- 8、 Salt spray test
- 9、 High and low temperature test


REVISION HISTORY

NO.	Date	Version		Update		Cnmment		Written	
1									
2									
3									
4									
5									
6									
7									
8									
9									
10									
11									
12									
13									
14									
15									
16									
17									
18									
19									
20									
21									


MADE:

CHECK:

3. ICD图纸



Antenna Matching Modification



Main antenna	Element	Value
	E1	N/C
	E2	0 Ω
	E3	N/C
	E4	

FS active efficiency of the main set

FS	Channel	TX (dBm)	RX (dBm)	FS	Channel	TX (dBm)	RX (dBm)	FS	Channel	TX (dBm)	RX (dBm)
2.4WIFI 11 B	1	17.48	-82.2	5G-WiFi A	36	16.26	-73.19				
	6	17.61	-81.69		149	16.23	-73.66				
	11	18	-82.26		165	16.12	-73.3				


WiFi2-s11




WiFi-2-Efficiency

Frequency/MHz	Efficiency / dB	Efficiency / %	MaxGain/dBi	Frequency/MHz	Efficiency / dB	Efficiency / %	MaxGain/dBi	Frequency/MHz	Efficiency / dB	Efficiency / %	MaxGain/dBi
2400	-2.18	60.53	4.22	5000	-3.87	40.99	4.51	5500	-3.84	41.34	5.59
2410	-2.24	59.7	4.23	5020	-3.75	42.19	4.8	5520	-3.96	40.21	5.36
2420	-2.14	61.09	4.01	5040	-3.91	40.62	4.8	5540	-3.73	42.36	5.52
2430	-2.13	61.24	4.18	5060	-3.62	43.43	5.2	5560	-3.94	40.36	5.26
2440	-2.27	59.29	3.98	5080	-3.80	41.73	5.09	5580	-3.92	40.51	5.20
2450	-2.13	61.24	4.1	5100	-3.71	42.57	5.16	5600	-3.79	41.81	5.37
2460	-2.34	58.34	3.93	5120	-3.68	42.81	5.24	5620	-3.74	42.28	5.24
2470	-2.18	60.81	4.04	5140	-3.61	43.59	5.17	5640	-3.88	40.96	5.08
2480	-2.17	60.67	4.12	5160	-3.89	40.84	4.85	5660	-3.80	41.73	5.09
2490	-2.04	62.52	4.27	5180	-3.58	43.83	5.11	5680	-3.84	41.27	5.11
2500	-2.21	60.12	4.12	5200	-3.63	43.36	5.07	5700	-4.04	39.41	4.84
				5220	-3.73	42.34	4.83	5720	-3.93	40.43	4.98
				5240	-3.66	43.04	4.91	5740	-3.77	41.97	4.72
				5260	-3.54	44.24	4.95	5760	-3.82	41.48	4.60
				5280	-3.72	42.42	4.7	5780	-3.95	40.26	4.58
				5300	-3.49	44.73	4.89	5800	-3.85	41.20	4.32
				5320	-3.84	41.28	4.39	5820	-3.67	42.97	4.00
				5340	-3.65	43.2	4.52	5840	-3.84	41.27	4.13
				5360	-3.61	43.59	4.57	5860	-3.95	40.24	4.05
				5380	-3.50	44.65	4.55	5880	-3.98	40.04	4.19
				5400	-3.69	42.73	4.29	5900	-3.90	40.72	4.33
				5420	-3.56	44.08	4.23	5920	-3.87	40.99	4.53
				5440	-3.67	42.96	4.02	5940	-3.81	41.61	4.15
				5460	-3.82	41.51	3.7	5960	-3.61	43.58	4.54
				5480	-3.69	42.73	3.81	5980	-3.78	41.86	4.27
								6000	-3.72	42.51	4.44

WiFi-2 ANTenna direct pattern



Antenna assembly drawing



Shenzhen yGalax Technologies Limited				File NO#		
				MADE DATE		
	FPC ante inspection specification			PAGE		
				VISION	A0	
1. purpose: Strict inspection, control the use of defective products, ensure product quality requirements. .						
2. range of application: FPC Ante.						
3. work content						
	item	content	tool	inspection standard	defect describe	FAULT GRADE
pack age		INDENTIFI CATION	by sight	The outer package has clear label, indicating the product name, specification, quantity, date, etc.	The mark is not clear and cannot be read.	MIN
		MATERIAL	by sight	Uniform packaging, clean and tidy, no damage, no impact on handling, storage, no wrong loading, mixed loading, less loading.	Packaging is not uniform, dirty, wet, damage, affect handling, storage.	MIN
face		FACIAL	by sight	No breakage, copper exposure, cracking, color difference, glue benefit on FPC, no oxidation, brittle crack on golden finger.	FPC has damage, copper exposure, cracking, color difference, glue, gold finger oxidation, brittle crack.	MAJ
stru ctur e		size	Vernie r	Circuit board size (length, width and height) is the same as	The dimensions are different from the pattern.	MAJ
		material proof	sample	Same as the sample.	The material is different from the template	MAJ
func tion		electropl ating	model	Gold finger gilded bright, 100% coverage.	Plating is not bright, plating coverage is low.	MAJ
		FIT	Frame	Attach the FPC to the housing, and the preset paste position is consistent, no more or less.	Attach the FPC to the housing, and the preset position of the paste is not consistent, there is more or less.	MAJ
MADE BY:			Audit:		Approver:	

RoHS Restricted Substance Composition sheet

Product information provided												
customer name		Metarial NO#		Project name		manufacturer				green mark		
		YX-P601-WIFI2-V3.0		P601		Shenzhen Starlink COMM.				/		
Product composition information												
item	part name	part NO#	VOLUME UP	Third party test report		Limit substance content PPM						remark
				DATE	number	(Pb)	(Cd)	(Hg)	(Cr ⁶⁺)	(PBB)	(PBDE)	
1	3M adhesive	/	honjingxinban	2021/1/13	SHAEC2100467601	O	O	O	O	O	O	
2	COPPER CLAD LAMINATE	/	caigelundi	2021/3/3	SHAEC2103249001	O	O	O	O	O	O	
3	ink	/	kaiyao	2021/8/17	ERT2102095	O	O	O	O	O	O	
4	electroplating	/	jiahongtai	2021-5-13	A2210168276101001E	O	O	O	O	O	O	

填写人：

填写人公司/部门：品质部

Salt spray test report

date: 20250527

product name	P601	customer name	
supplier	Shenzhen Starlink COMM.	National test standard	GB/T 2423.2-2008
Sample situation	QTY: 5PCS		
	MATERIAL: One - sided half - half colloidal electrolytic copper	plating thickness : ≥3U"	
TEST DATE	FROM 20220525 9:00 TO 20220527 9: 00 TOTAL 48 H		
TEST TYPE:	☒ NSS	☐ ASS	☐ CASS
test condition	saline solution: 5%		PH:7.0
	the temperature inside the box: 35°C		relative humidity: 85%
	Spray way: ☒ continue ☐ gap		compressed air pressure: 1kg/cm²
	Salt spray sedimentation rate: 1-2ml/80cm2/h		Fog fluid collection:
	test cycle: A loop		Spray time: 48 h
test result	Appearance after test: The appearance is intact without significant change.		
	Coating: no peeling, no corrosion		
	Surface spraying, screen printing: no shedding, no bubbles		

NOTE:

1, salt spray test operating standards in accordance with the People's Republic of China national standard GB/T2423.17-2008

2. The test results shall be determined according to the national standard GB/T6461-02 of the People's Republic of China

test date:

check:

High and low temperature test records

product name	P601	customer name		
test QTY	6 pcs	TEST DATE	2025/5/21	
cycle-index	1	test time	48H	
test condition high temperature: + <u>65</u> °C humidity: <u>90</u> % RH low temperature: - <u> </u> °C test: high-temp: <u>48</u> H low-temp: <u> </u> H				
test project	Uncycled test		cycled test	
item	After the high temperature	After low temperature	After the high temperature	After low temperature
1	OK	/		
2	OK	/		
3	OK	/		
4	OK	/		
5	OK	/		
6	OK	/		
Post test defect:				
reason analysis:				
improvement measure:				
test result: ☒ pass ☐ fail				

AUDIT:

record: