

Appendix IV RF Exposure evaluation

FCC ID: 2A9EU-XK-B002S

According to 447498 D01 General RF Exposure Guidance v06

For 100 MHz to 6 GHz and test separation distances >50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B)



- 1) {[Power allowed at numeric threshold for 50 mm in step a)]+ [(test separation distance-50 mm)/(fHz-150)]} mW, for 100 MHz to 1500 MHz
- 2) {[Power allowed at numeric threshold for 50 mm in step a)]+ [(test separation distance - 50mm)-10]} mW, for > 1500 MHz and ≤ 6 GHz

Appendix B

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	mW
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465	
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462	



Prediction distance is 120mm

Mode	Frequency (MHz)	Measured Power	Max. Tune up Power	Max. Tune up Power	Limit	SAR Test Exclusion
		(dBm)	(dBm)	(mW)	(mW)	
BT EDR	2402-2480	6.48	7	5.0119	796	Yes
BT LE	2402-2480	6.60	7	5.0119	796	Yes
2.4G WIFI(ANT1)	2412-2462	15.52	16	39.8107	796	Yes
2.4G WIFI(ANT2)	2412-2462	15.75	16	39.8107	796	Yes
2.4G WIFI MIMO	2412-2462	17.90	18	63.0957	796	Yes
5G WIFI B1(ANT1)	5180-5240	18.16	19	79.4328	762	Yes
5G WIFI B1(ANT2)	5180-5240	17.93	18	63.0957	762	Yes
5G WIFI B1 MIMO	5180-5240	19.83	20	100.0000	762	Yes
5G WIFI B2(ANT1)	5260-5320	18.98	19	79.4328	762	Yes
5G WIFI B2(ANT2)	5260-5320	17.74	18	63.0957	762	Yes
5G WIFI B2 MIMO	5260-5320	21.51	22	158.4893	762	Yes
5G WIFI B3(ANT1)	5500-5700	17.03	18	63.0957	762	Yes
5G WIFI B3(ANT2)	5500-5700	17.41	18	63.0957	762	Yes
5G WIFI B3 MIMO	5500-5700	19.72	20	100.0000	762	Yes
5G WIFI B4(ANT1)	5745-5825	18.86	19	79.4328	762	Yes
5G WIFI B4(ANT2)	5745-5825	18.05	19	79.4328	762	Yes
5G WIFI B4 MIMO	5745-5825	21.08	22	158.4893	762	Yes

Maximum Simultaneous transmission MPE Ratios for BT+WIFI SISO

Max MPE Ratio BT/Limit	Max MPE ratio _{WIFI} /Limit	ΣMPE ratios	Limit	Result
0.00630	0.10424	0.11054	1	PASS

Maximum Simultaneous transmission MPE Ratios for BT+WIFI MIMO

Max MPE Ratio BT/Limit	Max MPE ratio _{WIFI} /Limit	ΣMPE ratios	Limit	Result
0.00630	0.20799	0.21429	1	PASS

Then SAR evaluation is not required.