



深圳市飞敏科技有限公司

ShenZhen City FeiMin Technology CO.,LTD.

产品承认书

SPECIFICATION FOR APPROVED

客户

CUSTOMER: SHENZHEN HAISAITO TECHNOLOGY CO LTD

产品名称

PRODUCTS: 2.4G antenna

客户料号

PART NO:

产品型号

Spec.: FM-S788-F2MAX-B

日期

Data: 2021.04.02

供应商 SUPPLIER		
拟制 PREPARED BY	审核 CHECKED BY	批准 APPROVED BY
Fang yuwei	Xia xingxi	Ma dongdong

客户 CUSTOMER		
承认 ACCEPTED BY	审核 CHECKED BY	批准 APPROVED BY

备注: 承认盖章后请回复一份承认书(或复印件)给我司, 其余由贵公司存档

REMARK: Please send us one(or copy) of this approval with stamp after accepting, other copies filed by the customer.

地址: 深圳市宝安区西乡街道固戍社区恒南一路C栋厂房303室

ADD: Room 303, Building C, Hengnan one Road, Gushu community, Xixiang Street, Bao' an District, Shenzhen City

电话 Tel: 0755-23035723

传真 Fax: 0755-23036702

邮箱 E-mail: ant001@fmant.cn

网址 HTTP: www.fmant.cn

Revision history

版本	日期	状态
A1	2021-04-02	首版


目录

产品承认书.....	1
1. 项目信息 Project Information.....	3
1.1. 外观尺寸 Appearance and Dimensions	3
2. 电气性能 Electrical Characteristics	4
2.1. 测试环境条件 Test Environment Conditions.....	4
2.2. 测试方法 Measurement method	4
2.2.1. 电压驻波比 VSWR.....	4
2.2.2. 回波损耗 Log Mag	5
2.3. 测试系统 Test system.....	5
2.4. 无源数据 No-source test data	6
2.4.1. 3D Radiation Drawing.....	6
2.4.2. directional drawing of horizontal plane.....	7
3. 天线装配位置	7
4. 可靠性测试 Reliability test.....	8
5. 产品包装规范 Product packaging specification	9

ANTENNA SPECIFICATION

1. 项目信息 Project Information

1.1.外观尺寸 Appearance and Dimensions




2. 电气性能 Electrical Characteristics


2.1.测试环境条件 Test Environment Conditions

温度 Temperature	Ordinary Temperature (5 to 35℃)
湿度 Humidity	Ordinary Humidity (25 to 85% RH)

2.2.测示方法 Measurement method




2.2.1. 电压驻波比 VSWR




ANTENNA SPECIFICATION

2.2.2. 回波损耗 Log Mag



2.3. 测试系统 Test system




ANTENNA SPECIFICATION

2.4. 无源数据 No-source test data

2.4.1. 效率及增益 Efficiency and Gain


Frequency (MHz)	Gain (dBi)	Efficiency (%)
2400 MHz	2.39	55.82
2410 MHz	2.41	53.15
2420 MHz	2.73	58.17
2430 MHz	2.77	59.51
2440 MHz	2.53	61.38
2450 MHz	2.06	60.98
2460 MHz	2.33	58.39
2470 MHz	2.3	36.17
2480 MHz	1.92	52.01
2490 MHz	3.26	53.32
2500 MHz	3.39	53.01

2.4.1. 3D Radiation Drawing



ANTENNA SPECIFICATION

2.4.2. directional drawing of horizontal plane



3. Antenna mounting position

- 1、Be careful not to be too close to the metal part during installation to avoid affecting the antenna performance.
- 2、This antenna is only applicable to this model. The position of the antenna cannot be changed at will. If it is used on other machines, the effect will become worse, which has nothing to do with our company.

4. 可靠性测试 Reliability test

project	Test methods and conditions	Specifications and requirements
Storage environment	Test temperature、 : 1、 temperature-30℃~+80℃ 2、 humidity 45%-85% 3、 pressure 86Kpa-106Kpa	No obvious change in appearance All electrical parameters are consistent with those before the test
Salt spray test	c o n c e n t r a t i o n 50 ± 10g/l (约 5%);PH6.5-7.2;6H.	
Vibration test	f r e q u e n c y 10-2000-10HZ	
Drop Test	1M drop	
Pulling force test	pull: ≥12N	
Constant temperature	Temperature and humidity : 40℃ ± 2℃, 90-95%RH	
High and low temperature test	5 cycles	

