

FCC 47 CFR MPE REPORT

Hisense Home Appliances Group Co.,Ltd. Qingdao Branch

Wi-Fi&BLE Intelligent controls module

Model Number: HL3215STG

FCC ID: 2A9F9HL3215STG

Applicant:	Hisense Home Appliances Group Co.,Ltd. Qingdao Branch
Address:	Hisense R/D center, #399 SongLing Road,Qingdao, Shandong 266000, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2211040
Date of Test:	Sep. 30~Nov. 06, 2022
Date of Report:	Nov. 07, 2022

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
BLE	2402	6.71	4.688
	2440	7.86	6.109
	2480	8.81	7.603
IEEE 802.11b	2412	19.29	84.918
	2437	19.33	85.704
	2462	20.31	107.399
IEEE 802.11g	2412	20.28	106.660
	2437	20.53	112.980
	2462	21.73	148.936
IEEE 802.11n HT20	2412	20.72	118.032
	2437	20.83	121.060
	2462	21.82	152.055

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
				(dBi)	(Linear)			
2.4G Band								
BLE	8.81	8±1	9	0	1.000	0.0016	1	Complies
IEEE 802.11b	20.31	20±1	21	0	1.000	0.0250	1	Complies
IEEE 802.11g	21.73	21±1	22	0	1.000	0.0315	1	Complies
IEEE 802.11n HT20	21.82	21±1	22	0	1.000	0.0315	1	Complies

End of Test Report