

FCC PART 15C REPORT FOR CERTIFICATION

On Behalf of

Hisense Home Appliances Group Co., Ltd. Qingdao Branch

Wi-Fi/BLE Intelligent controls module

Model Number: HLW3215-TG

Additional Model: HLW3215-TG01

FCC ID: 2A9F9HLW32155V

Applicant :	Hisense Home Appliances Group Co., Ltd. Qingdao Branch
Address:	Hisense R/D center, #399 SongLing Road, Qingdao,
	Shandong 266104, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808


Report Number:	ESTE-R2212050
Date of Test:	Nov. 11~Dec. 01, 2022
Date of Report:	Dec. 05, 2022

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT).....	5
1.2. Antenna Information	5
1.3. Information of RF Cable	5
2. SUMMARY OF TEST	6
2.1. Summary of test result	6
2.2. Test Facilities	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test.....	8
2.5. Block Diagram	8
2.6. Test Mode.....	9
2.7. Power Setting of Test Software.....	10
2.8. Duty Cycle	10
2.9. Channel List.....	11
2.10. Test Equipment List.....	12
3. 6DB BANDWIDTH.....	13
3.1. Limit	13
3.2. Test Setup.....	13
3.3. Spectrum Analyzer Setting	13
3.4. Test Procedure.....	13
3.5. Test Result	13
4. MAXIMUM PEAK OUTPUT POWER.....	14
4.1. Limit	14
4.2. Test Setup.....	14
4.3. Spectrum Analyzer Setting	14
4.4. Test Procedure.....	14
4.5. Test Result	14
5. POWER SPECTRAL DENSITY	15
5.1. Limit	15
5.2. Test Setup.....	15
5.3. Spectrum Analyzer Setting	15
5.4. Test Procedure.....	15
5.5. Test Result	15
6. CONDUCTED BAND EDGE	16
6.1. Limit	16
6.2. Test Setup.....	16
6.3. Spectrum Analyzer Setting	16
6.4. Test Procedure.....	16
6.5. Test Result	16
7. CONDUCTED SPURIOUS EMISSIONS.....	17
7.1. Limit	17
7.2. Test Setup.....	17

7.3.	Spectrum Analyzer Setting	17
7.4.	Test Procedure.....	17
7.5.	Test Result	17
8.	RADIATED SPURIOUS EMISSIONS AND BAND EDGE	18
8.1.	Limit	18
8.2.	Test Setup.....	19
8.3.	Spectrum Analyzer Setting	20
8.4.	Test Procedure.....	21
8.5.	Test Result	22
9.	ANTENNA REQUIREMENTS	54
9.1.	Limit	54
9.2.	Test Result	54
10.	APPENDIX	55
11.	TEST SETUP PHOTO	80
12.	EUT PHOTO.....	81

EST Technology Co., Ltd.

Applicant: Address:	Hisense Home Appliances Group Co., Ltd. Qingdao Branch Hisense R/D center, #399 SongLing Road, Qingdao, Shandong 266104, China		
Manufacturer: Address:	Hisense Home Appliances Group Co., Ltd. Qingdao Branch Hisense R/D center, #399 SongLing Road, Qingdao, Shandong 266104, China		
Factory: Address:	Shenzhen Shi Xinzhongxin Technology Co., Ltd 1st, 2nd, 3rd, A2, A3, Building A1, East Ring Industrial Zone, No. 293, Nanpu Road, Shangliao Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong 518125, China		
E.U. T:	Wi-Fi/BLE Intelligent controls module		
Model Number:	HLW3215-TG		
Additional Model:	HLW3215-TG01 Note: HLW3215-TG with pin header, HLW3215-TG01 without pin header.		
Power Supply:	DC 5V		
Trade Name:	Hisense	Serial No.:	-----
Date of Receipt:	Nov. 11, 2022	Date of Test:	Nov. 11~Dec. 01, 2022
Test Specification:	FCC Part 15 Subpart C (15.247) ANSI C63.10:2013 FCC KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Prepared by:	Reviewed by:	Date: Dec. 05, 2022	
 Ring Yang / Assistant	 Seven Wang / Engineer	 Approved by:  Iceman Hu / Manager	
Other Aspects: None.			
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	Wi-Fi/BLE Intelligent controls module
Model Number	:	HLW3215-TG
Software Version	:	N/A
Hardware Version	:	N/A
Operation frequency	:	2412MHz~2462MHz
Number of channel	:	IEEE 802.11b/g/n HT20: 11 Channels
Max Output Power (PEAK)	:	IEEE 802.11b:21.23dBm IEEE 802.11g:23.14dBm IEEE 802.11n HT20:22.95dBm
Modulation Type	:	DSSS OFDM
Sample Type	:	Prototype production

Note: For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.2. Antenna Information

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	PCB	-	0

Note: This information is provided by the applicant

1.3. Information of RF Cable

Cable Loss(dB)	Provided by
1.0	Hisense Home Appliances Group Co., Ltd. Qingdao Branch
Note: 1.The customer declared the loss value of the RF Cable, and the test results of this report only apply to the sample as received. 2. This information is provided by the applicant.	

2. SUMMARY OF TEST

2.1. Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	6dB Bandwidth	15.247(a)(2)	PASS
2	Maximum Peak Output Power	15.247(b)(3)	PASS
3	Power Spectral Density	15.247(e)	PASS
4	Conducted Band Edge	15.247(d)	PASS
5	Conducted Spurious Emissions	15.247(d)	PASS
6	Radiated Spurious Emissions and Band Edge	15.205 15.209 15.247(d)	PASS
7	AC Power Line Conducted Emissions	15.207	N/A
8	Antenna Requirement	15.203	PASS

Note: "N/A" denotes test is not applicable in this test report.

2.2. Test Facilities

EMC Lab : Certificated by CNAS, CHINA
 Registration No.: L5288
 This Certificate is valid until: November 12, 2023

Certificated by FCC, USA
 Designation Number: CN1215
 This Certificate is valid until: January 31, 2024

Certificated by A2LA, USA
 Registration No.: 4366.01
 This Certificate is valid until: January 31, 2024

Certificated by Industry Canada
 CAB identifier No.: CN0035
 This Certificate is valid until: January 31, 2024

Certificated by VCCI, Japan
 Registration No.: C-14103; T-20073; R-13663;
 R-20103; G-20097
 Date of registration: Apr. 20, 2020
 This Certificate is valid until: Apr. 19, 2023

Certificated by TUV Rheinland, Germany
 Registration No.: UA 50413872 0001
 Date of registration: July 31, 2018

Certificated by Intertek
 Registration No.: 2011-RTL-L2-64
 Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
 Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (Below 30MHz)	$\pm 1.62\text{ dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 25GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	1.08dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


2.4. Assistant equipment used for test

Code	Equipment	Manufacturer	Model No.	Equipment No.	Serial No.
A	Laptop computer	DELL	Inspiron 5493	EST-E316	5376699759

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	0.1m	USB Cable

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into 2.4G WIFI test mode by software before test.



(EUT: Wi-Fi/BLE Intelligent controls module)

2.6. Test Mode

The test mode was selected for the final test as listed below.

Test Item	Mode	Date Rate	Test Channel
6dB Bandwidth	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11 g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
Maximum Peak Output Power	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11 g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
Power Spectral Density	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11 g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
Conducted Band Edge	IEEE 802.11b	1Mbps	Low/ High
	IEEE 802.11 g	6Mbps	Low/ High
	IEEE 802.11n HT20	MCS0	Low/ High
Conducted Spurious Emissions	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11 g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
Radiated Spurious Emissions(Below 1GHz)	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11 g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
Radiated Spurious Emissions(Above 1GHz)	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11 g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
Radiated Band Edge	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11 g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High

Note: In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X, Y, Z), the worst case was found when positioned on **X-plane**.

2.7. Power Setting of Test Software

Software Name	Wifi_Test_Tool_V1.7.7.exe		
Frequency(MHz)	2412	2437	2462
IEEE 802.11b Setting	Auto	Auto	Auto
IEEE 802.11g Setting	Auto	Auto	Auto
IEEE 802.11n HT20 Setting	Auto	Auto	Auto

Note: This information is provided by the applicant.

2.8. Duty Cycle

Refer to section 10: Appendix A

Note:

1. If duty cycle $< 98\%$, the conducted average output power and average power spectral density should be add duty factor.
2. If duty cycle $\geq 98\%$, the EUT is consider to be transmitting continuously, the conducted average output power and average power spectral density no need to add duty factor (consider to be zero).
3. The conducted peak output power and peak power spectral density no need to consider duty factor.
4. The on-time time is transmission duration(T).

2.9. Channel List

IEEE 802.11b/802.11g/802.11n HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442		
3	2422	8	2447		
4	2427	9	2452		
5	2432	10	2457		

2.10. Test Equipment List

For radiated emission test(9kHz-30MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LIS AI	June 13,22	1 Year
Active Loop Antenna	SCHWARZB ECK	FMZB 1519B	EST-E054	LIS AI	June 13,22	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	N/A	EST-001	N/A	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LIS AI	June 13,22	1 Year
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LIS AI	June 13,22	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA9120D	EST-E031	LIS AI	June 13,22	1 Year
Horn Antenna	Com-Power	AHA-840	EST-E133	LIS AI	June 13,22	1 Year
Low Noise Amplifier	RF	TRLA-01018 0G45N	EST-E142	LIS AI	June 13,22	1 Year
Spectrum Analyzer	Rohde &Schwarz	FSV40	EST-E069	LIS AI	June 13,22	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A


For connect EUT antenna terminal test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
TS 1120	Tonscend	/	/	/	/	/
Test Software	Tonscend	TS1120-3	3.2.11	/	/	/
RF Control Unit	Tonscend	JS0806-2	EST-E134	LIS AI	June 13,22	1 Year
Signal and Spectrum Analyzer	Rohde &Schwarz	FSV 40	EST-E136	LIS AI	June 13,22	1 Year

3. 6dB BANDWIDTH

3.1. Limit

Systems using digital modulation techniques operate in the 2400-2483.5 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2. Test Setup



3.3. Spectrum Analyzer Setting

6dB Bandwidth

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth

Spectrum Parameters	Setting
RBW	300KHz(20MHz Bandwidth mode)/1MHz(40MHz Bandwidth mode)
VBW	1MHz(20MHz Bandwidth mode)/3MHz(40MHz Bandwidth mode)
Span	40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

3.5. Test Result


Refer to section 10: Appendix B

4. MAXIMUM PEAK OUTPUT POWER

4.1. Limit

For systems using digital modulation in 2400-2483.5MHz, the maximum peak output power is 1 Watt(30dBm).

4.2. Test Setup



4.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz
VBW	3MHz
Span	40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

4.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 4.3.
- Set the EUT transmit continuously with maximum output power.
- Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

4.5. Test Result


Refer to section 10: Appendix C

5. POWER SPECTRAL DENSITY

5.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2. Test Setup



5.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	3KHz
VBW	10KHz
Span	30MHz(20MHz Bandwidth mode)/60MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

5.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 5.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

5.5. Test Result


Refer to section 10: Appendix D

6. CONDUCTED BAND EDGE

6.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2. Test Setup



6.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	100MHz(20MHz Bandwidth mode)/200MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 6.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report

6.5. Test Result

Refer to section 10: Appendix E & F

7. CONDUCTED SPURIOUS EMISSIONS

7.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.2. Test Setup



7.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	26.5GHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

7.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 7.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

7.5. Test Result

Refer to section 10: Appendix E & G

8. RADIATED SPURIOUS EMISSIONS AND BAND EDGE

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:


- (1) Emission level dB μ V = 20 log Emission level μ V/m.
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. Test Setup


9kHz~30MHz



30~1000MHz



Above 1GHz



8.3. Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	AVG Measurement
	3MHz	Duty cycle $\geq 98\%$, VBW=10Hz
		Duty cycle $< 98\%$, VBW $\geq 1/T$
Start frequency	1GHz	
Stop frequency	25GHz	
Sweep Time	Auto	
Detector	PEAK	
Trace Mode	Max Hold	

Note :T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.8 for the on-time time.

8.4. Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 8.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

Note:


1. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
2. The frequency 2412MHz/2437MHz/2462MHz are fundamental frequency, which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

8.5. Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 121
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:24.3;Humi:50.2%;Press:101.35kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	143.49	12.27	1.14	20.72	34.13	43.50	9.37	QP
2	636.25	21.68	2.39	16.75	40.82	46.00	5.18	QP
3	647.89	21.96	2.52	16.11	40.59	46.00	5.41	QP
4	659.53	22.10	2.50	17.83	42.43	46.00	3.57	QP
5	683.78	22.16	2.42	17.13	41.71	46.00	4.29	QP
6	708.03	22.12	2.53	13.77	38.42	46.00	7.58	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 122 File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (144)

Date: 2022-11-28



Site no. : 1# 966 Chamber Data no. : 122
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 B(3M)
Env. / Ins. : Temp:24.3;Humi:50.2%;Press:101.35kPa
Engineer : JBR
EUT : Wi-Fi/BLE Intelligent controls module
Power : DC 5V
M/N : HLW3215-TG-5V
Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	143.49	12.27	1.14	21.62	35.03	43.50	8.47	QP
2	167.74	10.30	1.17	24.98	36.45	43.50	7.05	QP
3	515.97	19.06	2.13	20.72	41.91	46.00	4.09	QP
4	540.22	19.60	2.14	20.64	42.38	46.00	3.62	QP
5	659.53	22.10	2.50	18.14	42.74	46.00	3.26	QP
6	683.78	22.16	2.42	17.89	42.47	46.00	3.53	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.



Radiated Emissions Above 1G


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 83

File: \\EMC-966-1\test data\2022\RF\Q\Qingdao Hisense\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 83
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.00	32.43	4.91	45.43	43.97	45.88	54.00	8.12	Average
2	4824.00	32.43	4.91	45.43	59.06	60.97	74.00	13.03	Peak
3	7236.00	36.19	6.27	44.98	32.87	40.35	54.00	13.65	Average
4	7236.00	36.19	6.27	44.98	47.35	54.83	74.00	19.17	Peak
5	9653.00	38.13	7.46	44.57	41.21	52.23	74.00	21.77	Peak
6	14056.00	39.97	9.14	42.09	34.57	51.59	74.00	22.41	Peak
7	15858.00	38.04	9.61	44.71	39.62	52.56	74.00	21.44	Peak
8	17677.00	40.53	10.55	43.90	33.99	51.17	74.00	22.83	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 84

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 84
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.00	32.43	4.91	45.43	42.57	44.48	54.00	9.52	Average
2	4824.00	32.43	4.91	45.43	57.92	59.83	74.00	14.17	Peak
3	7236.00	36.19	6.27	44.98	41.40	48.88	74.00	25.12	Peak
4	11370.00	38.86	8.00	43.60	33.42	46.68	74.00	27.32	Peak
5	13767.00	39.93	8.86	42.00	32.80	49.59	74.00	24.41	Peak
6	15943.00	37.90	9.63	44.67	36.19	49.05	74.00	24.95	Peak
7	17660.00	40.48	10.54	43.91	35.59	52.70	74.00	21.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 85

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 85
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2437MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.00	32.54	4.93	45.41	41.85	43.91	54.00	10.09	Average
2	4874.00	32.54	4.93	45.41	57.69	59.75	74.00	14.25	Peak
3	7311.00	36.25	6.33	44.97	44.23	51.84	74.00	22.16	Peak
4	9755.00	38.15	7.52	44.55	40.19	51.31	74.00	22.69	Peak
5	12475.00	39.23	8.53	42.86	34.03	48.93	74.00	25.07	Peak
6	17915.00	41.32	10.67	43.79	33.67	51.87	74.00	22.13	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 86

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 86
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2437MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.00	32.54	4.93	45.41	42.28	44.34	54.00	9.66	Average
2	4874.00	32.54	4.93	45.41	58.50	60.56	74.00	13.44	Peak
3	7311.00	36.25	6.33	44.97	32.17	39.78	54.00	14.22	Average
4	7311.00	36.25	6.33	44.97	47.67	55.28	74.00	18.72	Peak
5	9755.00	38.15	7.52	44.55	39.03	50.15	74.00	23.85	Peak
6	14634.00	39.68	9.32	43.41	34.81	50.40	74.00	23.60	Peak
7	15909.00	37.95	9.62	44.69	37.66	50.54	74.00	23.46	Peak
8	17966.00	41.49	10.69	43.77	32.79	51.20	74.00	22.80	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 87

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 87
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.00	32.64	4.96	45.39	37.48	39.69	54.00	14.31	Average
2	4924.00	32.64	4.96	45.39	52.17	54.38	74.00	19.62	Peak
3	7386.00	36.31	6.39	44.95	41.91	49.66	74.00	24.34	Peak
4	11302.00	38.87	7.97	43.64	35.70	48.90	74.00	25.10	Peak
5	13954.00	39.99	9.07	41.87	33.10	50.29	74.00	23.71	Peak
6	15909.00	37.95	9.62	44.69	37.75	50.63	74.00	23.37	Peak
7	17966.00	41.49	10.69	43.77	33.83	52.24	74.00	21.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 88

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 88
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.00	32.64	4.96	45.39	39.28	41.49	54.00	12.51	Average
2	4924.00	32.64	4.96	45.39	55.85	58.06	74.00	15.94	Peak
3	7386.00	36.31	6.39	44.95	42.59	50.34	74.00	23.66	Peak
4	10996.00	38.90	7.86	43.85	33.98	46.89	74.00	27.11	Peak
5	13954.00	39.99	9.07	41.87	33.40	50.59	74.00	23.41	Peak
6	15875.00	38.01	9.61	44.70	37.23	50.15	74.00	23.85	Peak
7	17847.00	41.10	10.63	43.82	33.47	51.38	74.00	22.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 89

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 89
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.00	32.43	4.91	45.43	37.13	39.04	54.00	14.96	Average
2	4824.00	32.43	4.91	45.43	54.02	55.93	74.00	18.07	Peak
3	7236.00	36.19	6.27	44.98	39.98	47.46	74.00	26.54	Peak
4	10605.00	38.62	7.68	44.11	35.33	47.52	74.00	26.48	Peak
5	12577.00	39.32	8.56	42.79	33.56	48.65	74.00	25.35	Peak
6	14124.00	39.94	9.16	42.24	33.27	50.13	74.00	23.87	Peak
7	17626.00	40.37	10.52	43.92	33.87	50.84	74.00	23.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 90

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 90
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.00	32.43	4.91	45.43	51.09	53.00	74.00	21.00	Peak
2	7236.00	36.19	6.27	44.98	44.37	51.85	74.00	22.15	Peak
3	10894.00	38.83	7.81	43.91	34.54	47.27	74.00	26.73	Peak
4	14039.00	39.98	9.13	42.05	32.37	49.43	74.00	24.57	Peak
5	15926.00	37.93	9.62	44.68	36.32	49.19	74.00	24.81	Peak
6	18000.00	41.60	10.71	43.75	32.02	50.58	74.00	23.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 91

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 91
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2437MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.00	32.54	4.93	45.41	41.28	43.34	54.00	10.66	Average
2	4874.00	32.54	4.93	45.41	56.48	58.54	74.00	15.46	Peak
3	7311.00	36.25	6.33	44.97	45.23	52.84	74.00	21.16	Peak
4	9755.00	38.15	7.52	44.55	39.99	51.11	74.00	22.89	Peak
5	12186.00	38.97	8.36	43.05	38.14	52.42	74.00	21.58	Peak
6	15416.00	38.79	9.52	44.80	36.53	50.04	74.00	23.96	Peak
7	17609.00	40.31	10.51	43.93	35.07	51.96	74.00	22.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 92

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 92
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2437MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.00	32.54	4.93	45.41	51.35	53.41	74.00	20.59	Peak
2	7311.00	36.25	6.33	44.97	40.93	48.54	74.00	25.46	Peak
3	11149.00	38.89	7.92	43.74	33.91	46.98	74.00	27.02	Peak
4	14362.00	39.82	9.23	42.79	34.42	50.68	74.00	23.32	Peak
5	16555.00	38.08	9.95	44.40	35.49	49.12	74.00	24.88	Peak
6	17677.00	40.53	10.55	43.90	35.39	52.57	74.00	21.43	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 93

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 93
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.00	32.64	4.96	45.39	51.16	53.37	74.00	20.63	Peak
2	7386.00	36.31	6.39	44.95	38.37	46.12	74.00	27.88	Peak
3	12560.00	39.30	8.55	42.80	33.80	48.85	74.00	25.15	Peak
4	14056.00	39.97	9.14	42.09	34.72	51.74	74.00	22.26	Peak
5	15892.00	37.98	9.62	44.70	37.53	50.43	74.00	23.57	Peak
6	17626.00	40.37	10.52	43.92	34.96	51.93	74.00	22.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 94

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 94
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.00	32.64	4.96	45.39	37.28	39.49	54.00	14.51	Average
2	4924.00	32.64	4.96	45.39	52.28	54.49	74.00	19.51	Peak
3	7386.00	36.31	6.39	44.95	45.28	53.03	74.00	20.97	Peak
4	9840.00	38.17	7.57	44.54	29.14	40.34	54.00	13.66	Average
5	9840.00	38.17	7.57	44.54	43.19	54.39	74.00	19.61	Peak
6	14022.00	39.99	9.13	42.01	33.03	50.14	74.00	23.86	Peak
7	15926.00	37.93	9.62	44.68	36.49	49.36	74.00	24.64	Peak
8	17643.00	40.42	10.53	43.91	36.09	53.13	74.00	20.87	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 95

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 95
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.00	32.43	4.91	45.43	37.17	39.08	54.00	14.92	Average
2	4824.00	32.43	4.91	45.43	52.42	54.33	74.00	19.67	Peak
3	7236.00	36.19	6.27	44.98	41.12	48.60	74.00	25.40	Peak
4	10571.00	38.60	7.66	44.13	34.16	46.29	74.00	27.71	Peak
5	14311.00	39.84	9.22	42.67	34.34	50.73	74.00	23.27	Peak
6	15382.00	38.85	9.51	44.75	35.95	49.56	74.00	24.44	Peak
7	17660.00	40.48	10.54	43.91	35.42	52.53	74.00	21.47	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 96

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 96
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4824.00	32.43	4.91	45.43	40.84	42.75	54.00	11.25	Average
2	4824.00	32.43	4.91	45.43	55.58	57.49	74.00	16.51	Peak
3	7236.00	36.19	6.27	44.98	44.09	51.57	74.00	22.43	Peak
4	9653.00	38.13	7.46	44.57	37.38	48.40	74.00	25.60	Peak
5	12067.00	38.86	8.29	43.13	36.53	50.55	74.00	23.45	Peak
6	13954.00	39.99	9.07	41.87	33.68	50.87	74.00	23.13	Peak
7	17983.00	41.54	10.70	43.76	33.00	51.48	74.00	22.52	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 97

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 97
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2437MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.00	32.54	4.93	45.41	40.98	43.04	54.00	10.96	Average
2	4874.00	32.54	4.93	45.41	52.87	54.93	74.00	19.07	Peak
3	7311.00	36.25	6.33	44.97	40.84	48.45	74.00	25.55	Peak
4	9755.00	38.15	7.52	44.55	36.47	47.59	74.00	26.41	Peak
5	13631.00	39.89	8.71	42.09	32.54	49.05	74.00	24.95	Peak
6	15875.00	38.01	9.61	44.70	39.09	52.01	74.00	21.99	Peak
7	17983.00	41.54	10.70	43.76	33.40	51.88	74.00	22.12	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 98

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 98
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2437MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.00	32.54	4.93	45.41	51.90	53.96	74.00	20.04	Peak
2	7311.00	36.25	6.33	44.97	43.79	51.40	74.00	22.60	Peak
3	9772.00	38.15	7.53	44.55	40.91	52.04	74.00	21.96	Peak
4	12186.00	38.97	8.36	43.05	37.19	51.47	74.00	22.53	Peak
5	14668.00	39.67	9.33	43.49	36.49	52.00	74.00	22.00	Peak
6	17966.00	41.49	10.69	43.77	33.02	51.43	74.00	22.57	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 99

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V-EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 99
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2462MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.00	32.64	4.96	45.39	40.98	43.19	54.00	10.81	Average
2	4924.00	32.64	4.96	45.39	55.59	57.80	74.00	16.20	Peak
3	7386.00	36.31	6.39	44.95	41.85	49.60	74.00	24.40	Peak
4	9840.00	38.17	7.57	44.54	40.33	51.53	74.00	22.47	Peak
5	13988.00	40.00	9.11	41.93	32.52	49.70	74.00	24.30	Peak
6	15858.00	38.04	9.61	44.71	36.85	49.79	74.00	24.21	Peak
7	17677.00	40.53	10.55	43.90	34.79	51.97	74.00	22.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 100 File: \\EMC-966-1\test data\2022\RF\Q\Qingdao Hisense\HLW3215-TG-5V.EM6 (120) Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 100
Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
Engineer : JBR
EUT : Wi-Fi/BLE Intelligent controls module
Power : DC 5V
M/N : HLW3215-TG-5V
Test Mode : IEEE 802.11n HT20 TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.00	32.64	4.96	45.39	40.12	42.33	54.00	11.67	Average
2	4924.00	32.64	4.96	45.39	54.32	56.53	74.00	17.47	Peak
3	7386.00	36.31	6.39	44.95	40.59	48.34	74.00	25.66	Peak
4	9823.00	38.16	7.56	44.54	36.81	47.99	74.00	26.01	Peak
5	12322.00	39.09	8.44	42.96	35.00	49.57	74.00	24.43	Peak
6	14022.00	39.99	9.13	42.01	33.78	50.89	74.00	23.11	Peak
7	17643.00	40.42	10.53	43.91	35.93	52.97	74.00	21.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:


- The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.



Radiated Band Edge

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 61
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.43	3.47	46.48	55.80	50.22	74.00	23.78	Peak
2	2413.10	27.50	3.48	46.47	102.36	96.87	74.00	-22.87	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 62

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 62
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.43	3.47	46.48	49.62	44.04	74.00	29.96	Peak
2	2411.67	27.49	3.48	46.48	100.57	95.06	74.00	-21.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 63

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 63
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.72	27.64	3.50	46.45	98.34	93.03	74.00	-19.03	Peak
2	2483.50	27.70	3.51	46.44	57.03	51.80	74.00	22.20	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 64

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 64
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11b TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.00	27.64	3.50	46.45	101.37	96.06	74.00	-22.06	Peak
2	2483.50	27.70	3.51	46.44	58.99	53.76	74.00	20.24	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 65

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 65
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.43	3.47	46.48	59.14	53.56	74.00	20.44	Peak
2	2407.38	27.48	3.48	46.48	97.65	92.13	74.00	-18.13	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 66

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 66
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.43	3.47	46.48	53.17	47.59	74.00	26.41	Peak
2	2408.94	27.49	3.48	46.48	95.54	90.03	74.00	-16.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 67

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 67
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2466.20	27.65	3.51	46.45	95.15	89.86	74.00	-15.86	Peak
2	2483.50	27.70	3.51	46.44	52.57	47.34	74.00	26.66	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 68

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 68
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11g TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2458.52	27.63	3.50	46.46	101.92	96.59	74.00	-22.59	Peak
2	2483.50	27.70	3.51	46.44	58.38	53.15	74.00	20.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 69

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 69
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.43	3.47	46.48	58.73	53.15	74.00	20.85	Peak
2	2411.93	27.49	3.48	46.48	99.93	94.42	74.00	-20.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 70

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 70
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.43	3.47	46.48	49.82	44.24	74.00	29.76	Peak
2	2411.93	27.49	3.48	46.48	98.20	92.69	74.00	-18.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 71

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120)

Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 71
 Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
 Engineer : JBR
 EUT : Wi-Fi/BLE Intelligent controls module
 Power : DC 5V
 M/N : HLW3215-TG-5V
 Test Mode : IEEE 802.11n HT20 TX 2462MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.06	27.64	3.50	46.45	96.73	91.42	74.00	-17.42	Peak
2	2483.50	27.70	3.51	46.44	52.15	46.92	74.00	27.08	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 72 File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qingdao Hisense\\HLW3215-TG-5V.EM6 (120) Date: 2022-11-24



Site no. : 1# 966 Chamber Data no. : 72
Dis. / Ant. : 3m BBHA9120D 1-18G 2208 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:20.9°C;Humi:50%;Press:101.52kPa
Engineer : JBR
EUT : Wi-Fi/BLE Intelligent controls module
Power : DC 5V
M/N : HLW3215-TG-5V
Test Mode : IEEE 802.11n HT20 TX 2462MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.36	27.64	3.50	46.45	101.89	96.58	74.00	-22.58	Peak
2	2483.50	27.70	3.51	46.44	58.82	53.59	74.00	20.41	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. All channels had been pre-test, only of the worst case channels were reported.



9. ANTENNA REQUIREMENTS

9.1. Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

9.2. Test Result


The antennas used for this product is PCB antenna ,so compliance with antenna requirements.
(Please refer to the EUT photo for details)

10. APPENDIX

Appendix A: Duty Cycle Test Result

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2437	8.38	8.47	98.94
11G	Ant1	2437	1.39	1.41	98.58
11N20SISO	Ant1	2437	1.30	1.32	98.48


Test Graphs





Appendix B: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.560	2406.960	2416.520	0.5	PASS
		2437	10.040	2431.960	2442.000	0.5	PASS
		2462	10.000	2456.960	2466.960	0.5	PASS
11G	Ant1	2412	15.120	2404.400	2419.520	0.5	PASS
		2437	15.120	2429.400	2444.520	0.5	PASS
		2462	15.120	2454.400	2469.520	0.5	PASS
11N20SISO	Ant1	2412	13.760	2404.480	2418.240	0.5	PASS
		2437	13.800	2430.680	2444.480	0.5	PASS
		2462	13.800	2454.440	2468.240	0.5	PASS

Test Graphs









Appendix C: Maximum conducted output power


Test Result Peak

Test Mode	Antenna	Frequency [MHz]	Peak Power[dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	20.79	≤30.00	PASS
		2437	20.53	≤30.00	PASS
		2462	21.23	≤30.00	PASS
11G	Ant1	2412	23.14	≤30.00	PASS
		2437	22.78	≤30.00	PASS
		2462	23.14	≤30.00	PASS
11N20SISO	Ant1	2412	22.95	≤30.00	PASS
		2437	22.56	≤30.00	PASS
		2462	22.90	≤30.00	PASS

Test Graphs Peak







Appendix D: Maximum power spectral density Test Result

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-4.79	≤8.00	PASS
		2437	-5.00	≤8.00	PASS
		2462	-5.02	≤8.00	PASS
11G	Ant1	2412	-8.69	≤8.00	PASS
		2437	-9.70	≤8.00	PASS
		2462	-8.88	≤8.00	PASS
11N20SISO	Ant1	2412	-8.80	≤8.00	PASS
		2437	-9.36	≤8.00	PASS
		2462	-8.98	≤8.00	PASS

Test Graphs

