

8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for $f < 30$ MHz (150KHz to 30KHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	22.5° C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})(\text{dB})$;

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Test mode: 802.11 b

Frequency:

Channel 1: 2412 MHz

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dBμV/m)	Det.	Pol.	Verdict
4824.00	51.36	-7.42	43.94	74.00	30.06	PK+	V	PASS
4824.00	37.91	-7.42	30.49	54.00	23.51	AVG	V	PASS
6621.50	48.61	-1.27	47.34	74.00	26.66	PK+	V	PASS
6621.50	34.69	-1.27	33.42	54.00	20.58	AVG	V	PASS
8101.50	47.69	0.99	48.68	74.00	25.32	PK+	V	PASS
8101.50	32.20	0.99	33.19	54.00	20.81	AVG	V	PASS

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dBμV/m)	Det.	Pol.	Verdict
4823.50	51.90	-7.43	44.47	74.00	29.53	PK+	H	PASS
4823.50	38.27	-7.43	30.84	54.00	23.16	AVG	H	PASS
5719.50	50.03	-4.00	46.03	74.00	27.97	PK+	H	PASS
5719.50	35.55	-4.00	31.55	54.00	22.45	AVG	H	PASS
7750.00	47.51	0.84	48.35	74.00	25.65	PK+	H	PASS
7750.00	32.85	0.84	33.69	54.00	20.31	AVG	H	PASS

Test mode: 802.11 b

Frequency:

Channel 6:2437 MHz

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dBμV/m)	Det.	Pol.	Verdict
4874.00	51.67	-7.08	44.59	74.00	29.41	PK+	V	PASS
4874.00	37.84	-7.08	30.76	54.00	23.24	AVG	V	PASS
6652.00	47.75	-1.25	46.50	74.00	27.50	PK+	V	PASS
6652.00	33.04	-1.25	31.79	54.00	22.21	AVG	V	PASS
8672.50	47.65	2.09	49.74	74.00	24.26	PK+	V	PASS
8672.50	32.59	2.09	34.68	54.00	19.32	AVG	V	PASS

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dBμV/m)	Det.	Pol.	Verdict
4874.50	52.70	-7.08	45.62	74.00	28.38	PK+	H	PASS
4874.50	37.57	-7.08	30.49	54.00	23.51	AVG	H	PASS
6999.00	46.71	-0.44	46.27	74.00	27.73	PK+	H	PASS
6999.00	32.20	-0.44	31.76	54.00	22.24	AVG	H	PASS
8575.00	47.75	2.01	49.76	74.00	24.24	PK+	H	PASS
8575.00	32.25	2.01	34.26	54.00	19.74	AVG	H	PASS

Test mode: 802.11 b

Frequency:

Channel 11:2462 MHz

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dBμV/m)	Det.	Pol.	Verdict
4924.00	54.00	-6.66	47.34	74.00	26.66	PK+	V	PASS
4924.00	38.85	-6.66	32.19	54.00	21.81	AVG	V	PASS
6936.00	47.70	-0.75	46.95	74.00	27.05	PK+	V	PASS
6936.00	33.69	-0.75	32.94	54.00	21.06	AVG	V	PASS
8955.00	47.32	2.56	49.88	74.00	24.12	PK+	V	PASS
8955.00	32.11	2.56	34.67	54.00	19.33	AVG	V	PASS

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dBμV/m)	Det.	Pol.	Verdict
4923.50	56.67	-6.67	50.00	74.00	24.00	PK+	H	PASS
4923.50	43.09	-6.67	36.42	54.00	17.58	AVG	H	PASS
6231.50	46.45	-2.95	43.50	74.00	30.50	PK+	H	PASS
6231.50	32.83	-2.95	29.88	54.00	24.12	AVG	H	PASS
10546.50	46.03	4.67	50.70	74.00	23.30	PK+	H	PASS
10546.50	30.49	4.67	35.16	54.00	18.84	AVG	H	PASS

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11 n20 recorded was report as below:

Test mode: 802.11 n20 Frequency: Channel 1: 2412MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2364.12	H	58.60	74.00	43.19	54.00
2366.52	V	59.15	74.00	44.27	54.00

Test mode: 802.11 n20 Frequency: Channel 11: 2462MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2494.50	H	61.25	74.00	46.81	54.00
2494.29	V	59.31	74.00	44.47	54.00

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	Spurious Emission in Restricted Band 2310-2390MHz	
	802.11g	
	Channel 1: 2412MHz	Polarity: H




Test Model	Spurious Emission in Restricted Band 2310-2390MHz	
	802.11g	
	Channel 1: 2412MHz	Polarity: V



Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz	
	802.11g	
	Channel 11: 2462MHz	Polarity: H




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz	
	802.11g	
	Channel 11: 2462MHz	Polarity: V




- Spurious Emission below 1GHz (30MHz to 1GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11g recorded was report as below:

Project Information			
Mode:	2412 MHz	Voltage:	AC 120V/60Hz
Environment:	Temp: 25°C; Humi:60%	Engineer:	Jackson Xue




Final Data List										
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	32.134	64.64	-31.23	33.41	40.00	6.59	200	159	Vertical	Pass
2	39.313	64.12	-30.65	33.47	40.00	6.53	100	247	Vertical	Pass
3	51.926	64.95	-30.52	34.43	40.00	5.57	200	247	Vertical	Pass
4	65.044	69.29	-32.51	36.83	40.00	3.17	100	91	Vertical	Pass
5	68.379	70.98	-32.90	38.11	40.00	1.89	100	53	Vertical	Pass
6	72.106	67.96	-33.05	34.91	40.00	5.09	100	140	Vertical	Pass

Project Information			
Mode:	2412 MHz	Voltage:	AC 120V/60Hz
Environment:	Temp: 25℃; Humi:60%	Engineer:	Jackson Xue




Final Data List										
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	52.702	49.10	-30.65	18.45	40.00	21.55	200	135	Horizontal	Pass
2	64.150	63.52	-32.40	31.12	40.00	8.88	200	320	Horizontal	Pass
3	68.301	66.85	-32.90	34.00	40.00	6.00	100	165	Horizontal	Pass
4	71.524	63.67	-33.06	30.61	40.00	9.39	100	193	Horizontal	Pass
5	120.422	48.54	-33.17	15.37	43.50	28.13	200	112	Horizontal	Pass
6	266.727	49.54	-28.84	20.70	46.00	25.30	200	315	Horizontal	Pass

Project Information			
Mode:	2437 MHz	Voltage:	AC 120V/60Hz
Environment:	Temp: 25℃; Humi:60%	Engineer:	Jackson Xue



Final Data List										
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	32.134	62.16	-31.23	30.93	40.00	9.07	100	159	Vertical	Pass
2	39.314	60.62	-30.65	29.97	40.00	10.03	100	247	Vertical	Pass
3	51.926	62.45	-30.52	31.93	40.00	8.07	200	247	Vertical	Pass
4	64.733	65.37	-32.46	32.91	40.00	7.09	100	247	Vertical	Pass
5	72.106	64.37	-33.05	31.32	40.00	8.68	200	140	Vertical	Pass
6	297.191	44.35	-28.43	15.92	46.00	30.08	100	319	Vertical	Pass


Project Information			
Mode:	2437 MHz	Voltage:	AC 120V/60Hz
Environment:	Temp: 25℃; Humi:60%	Engineer:	Jackson Xue



Final Data List										
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	40.866	45.83	-30.50	15.33	40.00	24.67	200	160	Horizontal	Pass
2	52.703	49.36	-30.65	18.71	40.00	21.29	200	135	Horizontal	Pass
3	68.032	60.35	-32.85	27.50	40.00	12.50	100	181	Horizontal	Pass
4	94.421	40.28	-31.77	8.51	43.50	34.99	200	189	Horizontal	Pass
5	136.915	47.37	-34.00	13.37	43.50	30.13	200	320	Horizontal	Pass
6	266.727	47.91	-28.84	19.07	46.00	26.93	200	315	Horizontal	Pass

Project Information


Mode:	2462 MHz	Voltage:	AC 120V/60Hz
Environment:	Temp: 25°C; Humi:60%	Engineer:	Jackson Xue



Final Data List

NO.	Freq. [MHz]	QP Reading [dBµV/m]	Factor [dB]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	32.134	59.36	-31.23	28.13	40.00	11.87	100	159	Vertical	Pass
2	51.926	62.92	-30.52	32.40	40.00	7.60	100	247	Vertical	Pass
3	68.226	67.35	-32.87	34.48	40.00	5.52	100	109	Vertical	Pass
4	96.943	43.14	-31.56	11.58	43.50	31.92	200	193	Vertical	Pass
5	119.452	44.28	-33.09	11.19	43.50	32.31	100	322	Vertical	Pass
6	297.191	42.72	-28.43	14.29	46.00	31.71	100	319	Vertical	Pass

Project Information			
Mode:	2462 MHz	Voltage:	AC 120V/60Hz
Environment:	Temp: 25℃; Humi:60%	Engineer:	Jackson Xue



Final Data List										
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	40.866	45.14	-30.50	14.64	40.00	25.36	200	160	Horizontal	Pass
2	52.703	50.45	-30.65	19.80	40.00	20.20	200	135	Horizontal	Pass
3	68.032	64.58	-32.85	31.73	40.00	8.27	100	181	Horizontal	Pass
4	120.422	46.58	-33.17	13.41	43.50	30.09	200	112	Horizontal	Pass
5	266.727	47.14	-28.84	18.30	46.00	27.70	200	315	Horizontal	Pass
6	343.567	41.90	-26.82	15.08	46.00	30.92	100	264	Horizontal	Pass

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3conducted emission test setup


8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results


Pass

Project Information			
Mode:	TX	Voltage:	AC120V/60Hz
Environment:	Temp: 25℃; Humi:60%	Engineer:	Jo Liu



Final Data List											
NO.	Freq. [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.150	9.86	36.11	45.97	66.00	20.03	22.29	32.15	56.00	23.85	PASS
2	0.155	9.85	36.07	45.92	65.75	19.83	22.13	31.98	55.75	23.77	PASS
3	6.639	10.26	36.45	46.71	60.00	13.29	16.21	26.47	50.00	23.53	PASS
4	11.706	10.33	44.71	55.04	60.00	4.96	23.92	34.25	50.00	15.75	PASS
5	14.559	10.36	36.20	46.56	60.00	13.44	17.59	27.95	50.00	22.05	PASS
6	15.509	10.38	40.10	50.48	60.00	9.52	18.20	28.58	50.00	21.42	PASS

Project Information			
Mode:	TX	Voltage:	AC120V/60Hz
Environment:	Temp: 25℃; Humi:60%	Engineer:	Jo Liu



Final Data List											
NO.	Freq. [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.150	9.72	34.92	44.64	66.00	21.36	19.23	28.95	56.00	27.05	PASS
2	0.155	9.75	35.06	44.81	65.75	20.94	21.33	31.08	55.75	24.67	PASS
3	6.639	9.80	40.01	49.81	60.00	10.19	15.36	25.16	50.00	24.84	PASS
4	11.706	9.95	45.37	55.32	60.00	4.68	24.31	34.26	50.00	15.74	PASS
5	14.568	10.06	40.01	50.07	60.00	9.93	16.02	26.08	50.00	23.92	PASS
6	15.522	10.10	40.30	50.40	60.00	9.60	19.53	29.63	50.00	20.37	PASS

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

- The EUT has 1 antenna: one an PCB antenna for WIFI 2.4G, the gain is 2.5 dBi
- Note:
- ☒ Antenna uses a permanently attached antenna which is not replaceable.
 - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
 - ☐ The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

*** End of Report ***

声 明 Statement

1. 本报告无授权批准人签字及“检验报告专用章”无效;
This report will be void without authorized signature or special seal for testing report.
2. 未经许可本报告不得部分复制;
This report shall not be copied partly without authorization.
3. 本报告的检测结果仅对送测样品有效, 委托方对样品的代表性和资料的真实性负责;
The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.
4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内, 仅作为客户委托、科研、教学或内部质量控制等目的使用;
The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
5. 本检测报告以实测值进行符合性判定, 未考虑不确定度所带来的风险, 本实验室不承担相关责任, 特别约定、标准或规范中有明确规定的除外;
The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.
6. 对本检测报告若有异议, 请于收到报告之日起 20 日内提出;
Objections shall be raised within 20 days from the date receiving the report.