

EDM International RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Voltage Monitor Model: AP30 Hotstick

REPORT NUMBER

105251642MPK-003

ISSUE DATE

December 20, 2022

REVISED DATE

N/A

PAGES

9

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)**

Report Number: 105251642MPK-003

Project Number: G105251642

Report Issue Date: December 20, 2022

Product Designation: AP30 Hotstick unit

Model Tested: AP30-HS

FCC ID: 2A9GX-AP30HS

to

47CFR 2.1091

for

EDM INTERNATIONAL, INC.

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

EDM International, Inc.
4001 Automation Way
Fort Collins, CO 80525 USA

Report prepared by:



Juan Alapizco Vega / Project Engineer

Report reviewed by:



Minh Ly / EMC Team Lead

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 105251642MPK-003	
Equipment Under Test:	AP30 Hotstick Unit
Trade Name:	EDM International, Inc
Model(s) Tested:	AP30-HS
Applicant:	EDM International, Inc.
Contact:	Neil Hurst
Address:	EDM International, Inc. 4001 Automation Way Fort Collins, CO 80525
Country:	USA
Email:	nhurstst@edmlink.com
Applicable Regulation:	47CFR 2.1091

TABLE OF CONTENTS

<i>EDM International</i>	1
1.0 RF Exposure Summary	5
2.0 RF Exposure Limits	5
3.0 Test Results (Mobile Configuration)	6
4.0 Document History	9

1.0 RF Exposure Summary

Test	Reference FCC	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

AP30 Hotstick Unit, Model: AP30-HS consists of one radio: 914.5MHz carrier

3.3 Maximum RF Power

Tx Frequency (MHz)	EIRP (dBm)	Antenna Gain ¹ (dBi)	Note
914.5	-1.76	1.4	Radiated power measurements were taken from Report # 105251642MPK-004.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for 914MHz carrier.

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	Result
914.5	-1.76	0.667	0.00018	0.609	Compliant

¹Note: Antenna gains below 0 are considered as 0dBi.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0/ G105251642	JAV	ML	December 20. 2022	Original document