FCC RF Exposure

EUT Description: Wireless Microphone System

Model No.: WMX36, WXM36A, WXM36B, WXM36C, WXM36D, WXM36-1, WXM36-2, WXM36-3, WXM36-4

FCC ID: **2A9J3-WMX36**

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1－g and 10－g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤50 mm are determined by: [(max power of channel, including tune－up tolerance, mW)/(min. test separation distance, mm)] •[√f(GHz)]≤3.0 for 1－g SAR and ≤ 7.5 for 10－g extremity SAR,

Where:

Result=P/D* √ F

F= the RF channel transmit frequency in GHz

P=Maximum turn－up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

Frequency (MHz)	Output power （dBm）	Tune Up Power （dBm）	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm^2)	SAR Test Exclusion
560.5	3.45	3±1	4/2.512	5	0.376	3.0	Pass
Note: PK Output power= conducted power. Conducted power see the test report **HK2301100115-E**, antenna gain=1dBi							

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.376 which is<= 3, RF Exposure testing is not required.

Note: Exclusion Thresholds Results=[(*max. power of channel, including tune-up tolerance, mW*)/(*min. test separation distance, mm*)] ·[$\sqrt{f_{(GHz)}}$]

$f_{(GHz)}$ is the RF channel transmit frequency in GHz

Distance=5mm