

Prüfbericht-Nr.: Test report no.:	CN2517XR 002	Auftrags-Nr.: Order no.:	168570031	Seite 1 von 15 Page 1 of 15
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2025-08-14	
Auftraggeber: Client:	Xiamen Hongfa Electroacoustic Co., Ltd. No.91-101, Sunban South Rd., Jimei North Ind. Dist., Xiamen 361021, China			
Prüfgegenstand: Test item:	KEY FOB			
Bezeichnung / Typ-Nr.: Identification / Type no.:	HF3766R35434 (Trademark: HONGFA)			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 15.231			
Wareneingangsdatum: Date of sample receipt:	2025-09-22	Please refer to Photo Document		
Prüfmuster-Nr.: Test sample no.:	A004094809-004~028 A004094809-031			
Prüfzeitraum: Testing period:	2025-10-13 - 2025-11-26			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	genehmigt von: authorized by:			
Datum: Date:	2025-11-27	Ausstellungsdatum: Issue date:	2025-11-27	
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: 2A9J4-3766R35434			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN2517XR 002
Test report no.:

Seite 2 von 15
Page 2 of 15

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfbedingungen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN2517XR 002
Test Report No.:

Seite 3 von 15
Page 3 of 15

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 DEACTIVATION OF THE TRANSMISSION

RESULT: Pass

5.1.3 20dB EMISSION BANDWIDTH AND 99%dB BANDWIDTH

RESULT: Pass

5.1.4 FIELD STRENGTH OF FUNDAMENTAL AND UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	8
3.5	SUBMITTED DOCUMENTS.....	8
4	TEST SET-UP AND OPERATION MODES	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION	9
4.2	TEST OPERATION AND TEST SOFTWARE.....	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	9
4.5	TEST SETUP DIAGRAM	10
5	TEST RESULTS	11
5.1	ESSENTIAL REQUIREMENTS OF STANDARD	11
5.1.1	<i>Antenna Requirement</i>	<i>11</i>
5.1.2	<i>Deactivation of the Transmission</i>	<i>12</i>
5.1.3	<i>20dB Emission Bandwidth and 99%dB Bandwidth</i>	<i>13</i>
5.1.4	<i>Field strength of fundamental and Unwanted Emissions in the Spurious Domain</i>	<i>14</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	15
7	LIST OF TABLES.....	15

Prüfbericht - Nr.: CN2517XR 002
Test Report No.:

Seite 5 von 15
Page 5 of 15

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results.

Appendix B: Photographs of the Test Set-up.

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China

A2LA Certificate Number: 5162.01

FCC Registration No.: 694916

ISED Wireless Device Testing Laboratory: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (TS8997)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Signal Analyzer	R&S	FSV 40	101441	2025-09-23	2026-09-22
OSP	R&S	OSP 150	101017	2025-10-30	2026-10-29
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A	N/A
Test Software	R&S	WMS32 (V11.00.00)	N/A	N/A	N/A
Power Meter	R&S	NRP2	107105	2025-10-30	2026-10-29
Wideband Power Sensor	R&S	NRP-Z81	105677	2025-09-23	2026-09-22
Shielding Room	Albatross	SR1	APC17151-SR1	2024-09-14	2027-09-13
Unwanted Emission Testing (TS9975)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2025-09-22	2026-09-21
Signal Analyzer	R&S	FSV 40	101439	2025-09-22	2026-09-21
System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
Filterbank	R&S	Wlan	100759	2025-09-22	2026-09-21
OSP	R&S	OSP 120	102040	N/A	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2025-09-22	2026-09-21
Amplifier	R&S	SCU-18F	180070	2025-09-22	2026-09-21
Amplifier	R&S	SCU40A	100475	2025-09-22	2026-09-21
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-09-28	2026-09-27
Double-Ridged Antenna(1 -18 GHz)	ETS-LINDGREN	3117	00218717	2024-09-28	2026-09-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2024-09-28	2026-09-27
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A

3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-09-14	2027-09-13
--------------------------	-----------	--------	--------------	------------	------------

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	±4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a KEY which supports 125kHz (Receiver only) and 433.92MHz (transmitter only) wireless technologies.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	KEY FOB
Type Designation:	HF3766R35434 Note1: This product uses pin to pin chips from the same series, and the chips models used in this product are NCF29A1 and NCF29A3 respectively, since they belong to the same series of chips, so the chip HF3766R35434_NCF29A1 arranged fully test and the chip HF3766R35434_NCF29A3 was arranged Deactivation of the Transmission, Field strength and Spurious emissions additional test. Note2: The product has three different color appearances.
Trademark:	HONGFA
FCC ID:	2A9J4-3766R35434
Operating Voltage:	Battery operation (3Vdc, CR2032)
Operating Temperature Range:	-20°C ~ +60°C
Technical Specification of 433.92MHz	
Operating Frequencies:	433.92 MHz
Modulation Type:	FSK
Antenna Type:	Integral Antenna

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Transmitting with operating frequency 433.92MHz
- B. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- User Manual
- ID Label and Location Info
- Operation Description

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10:2020.

According to clause 3.1, all tests were performed on model HF3766R35434 (NCF29A1 and NCF29A3 versions) in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 4: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
DC power Supply	Topward	3303D	809332	0-30 Volts, 0-3 Amps

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Essential Requirements of Standard

5.1.1 Antenna Requirement

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.203 The following describes the three ways that can be used to demonstrate compliance to Section 15.203
Limit	: 1. Antenna permanently attached 2. Unique (non-standard) antenna connector 3. Professional installation

According to the manufacturer declared, the EUT have an Integral Antenna, permanent attachment (1) and no consideration of replacement, refer to section 3.2 for details.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Deactivation of the Transmission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.231
Basic standard	: ANSI C63.10:2020
Test requirement	: FCC Part 15.231 (a)(1)
Limits	: A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2025-10-13 to 2025-11-26
Input voltage	: DC 3V by battery
Operation mode	: A
Ambient temperature	: 24.8 °C
Relative humidity	: 53 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN2517XR 002
Test Report No.:Seite 13 von 15
Page 13 of 15

5.1.3 20dB Emission Bandwidth and 99%dB Bandwidth

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.231
Basic standard	: ANSI C63.10:2020
Test requirement	: FCC Part 15.231 (c)
Limit	: FCC Part 15.231 (c)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2025-10-13 to 2025-11-26
Input voltage	: DC 3V by battery
Operation mode	: A
Ambient temperature	: 24.8 °C
Relative humidity	: 53 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN2517XR 002
Test Report No.:Seite 14 von 15
Page 14 of 15

5.1.4 Field strength of fundamental and Unwanted Emissions in the Spurious Domain

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.231 & FCC Part 15.205 & FCC Part 15.209
Basic standard	: ANSI C63.10:2020
Test requirement	: CFR47 FCC Part 15.231 (b)(1)(2)(3)
Limits	: FCC Part 15.231 (b)
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2025-10-13 to 2025-11-26
Input voltage	: DC 3V by battery
Operation mode	: A
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: Refer to test result

For the measurement records, refer to the appendix A.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT	8
Table 4: List of Accessories and Auxiliary Equipment.....	9


Appendix A: Test Results

APPENDIX A: TEST RESULTS	1
APPENDIX A.1: TEST RESULTS OF DEACTIVATION OF THE TRANSMISSION	2
HF3766R35434_NCF29A1.....	2
HF3766R35434_NCF29A3.....	3
APPENDIX A.2: TEST RESULTS OF 20DB BANDWIDTH	4
HF3766R35434_NCF29A1.....	4
APPENDIX A.3: TEST RESULTS OF 99% BANDWIDTH.....	5
HF3766R35434_NCF29A1.....	5
APPENDIX A.4: TEST RESULTS OF FIELD STRENGTH OF FUNDAMENTAL AND UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN.....	6
HF3766R35434_NCF29A1.....	6
30MHz - 1GHz.....	6
Above 1GHz.....	8
HF3766R35434_NCF29A3.....	10
30MHz - 1GHz.....	10
Above 1GHz.....	12

Appendix A.1: Test Results of Deactivation of the Transmission


HF3766R35434_NCF29A1

Test Frequency (MHz)	On Time (s)	Limit (s)	Result
433.92	0.3362	5	Pass



HF3766R35434_NCF29A3


Test Frequency (MHz)	On Time (s)	Limit (s)	Result
433.92	0.3362	5	Pass



Appendix A.2: Test Results of 20dB Bandwidth

HF3766R35434_NCF29A1

Test Frequency (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Result
433.92	0.1679	1.0848	Pass




Date: 14.OCT.2025 04:58:49

Appendix A.3: Test Results of 99% Bandwidth

HF3766R35434_NCF29A1

Operation Frequency (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Result
433.92	0.157	1.0848	Pass



Date: 14.OCT.2025 04:56:26

Appendix A.4: Test Results of Field Strength of Fundamental and Unwanted Emissions in the Spurious Domain


Note: The highest waveform in the figure is 433.92MHz Fundamental.

HF3766R35434_NCF29A1

30MHz - 1GHz

EUT Information

EUT Name:	KEY FOB
Model:	HF3766R35434_NCF29A1
Test Mode:	433.92MHz
Order No/Sample No:	168570031/A004094809-009
Test Voltage:	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
49.996923	20.09	---	40.00	19.91	100.0	H	95.0	-18.4
105.175000	20.27	---	43.50	23.23	100.0	H	124.0	-18.9
218.515769	23.72	---	46.00	22.28	100.0	H	29.0	-18.7
433.893077	55.77	---	100.82	45.05	100.0	H	103.0	-13.1
433.893077	---	45.77	80.82	35.05	100.0	H	103.0	-13.1
943.292308	36.88	---	46.00	9.12	100.0	H	62.0	-4.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: KEY FOB
Model: HF3766R35434_NCF29A1
Test Mode: 433.92MHz
Order No/Sample No: 168570031/A004094809-009
Test Voltage: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
63.688846	19.81	---	40.00	20.19	100.0	V	0.0	-19.9
109.689231	20.55	---	43.50	22.95	100.0	V	258.0	-19.2
291.601539	24.88	---	46.00	21.12	100.0	V	225.0	-16.5
433.893077	49.04	---	100.82	51.78	100.0	V	281.0	-13.1
433.893077	---	39.04	80.82	41.78	100.0	V	281.0	-13.1
857.857692	34.99	---	46.00	11.01	100.0	V	357.0	-5.3


Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Above 1GHz

EUT Information

EUT Name:	KEY FOB
Model:	HF3766R35434_NCF29A1
Test Mode:	433.92MHz
Order No/Sample No:	168570031/A004094809-009
Test Voltage:	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1484.808333	---	34.27	54.00	19.73	150.0	H	30.0	2.7
1485.366667	41.34	---	74.00	32.66	150.0	H	23.0	2.7
2488.133333	---	38.08	54.00	15.92	150.0	H	35.0	8.9
2488.691667	47.82	---	74.00	26.18	150.0	H	10.0	8.9
4585.233333	52.09	---	74.00	21.91	150.0	H	81.0	13.5
4598.075000	---	42.51	54.00	11.49	150.0	H	302.0	13.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name: KEY FOB
Model: HF3766R35434_NCF29A1
Test Mode: 433.92MHz
Order No/Sample No: 168570031/A004094809-009
Test Voltage: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1470.291667	41.48	---	74.00	32.52	150.0	V	221.0	2.8
1484.808333	---	35.07	54.00	18.93	150.0	V	273.0	2.7
2114.050000	---	36.53	54.00	17.47	150.0	V	21.0	7.6
2119.075000	46.96	---	74.00	27.04	150.0	V	93.0	7.6
4489.200000	52.74	---	74.00	21.26	150.0	V	46.0	12.9
4545.033333	---	42.35	54.00	11.65	150.0	V	46.0	13.4

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
-----------------	------------------	------------------	----------------	-------------	-------------	-----	---------------	--------------

HF3766R35434_NCF29A3

30MHz - 1GHz

EUT Information

EUT Name:	KEY FOB
Model:	HF3766R35434_NCF29A3
Test Mode:	433.92MHz
Order No/Sample No:	168570031/A004094809-009
Test Voltage:	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.005000	14.82	---	40.00	25.18	100.0	H	236.0	-18.8
104.043333	11.11	---	43.50	32.39	100.0	H	286.0	-18.9
336.304444	14.99	---	46.00	31.01	100.0	H	188.0	-15.1
433.897222	57.86	---	100.82	42.96	100.0	H	324.0	-13.1
433.897222	---	47.86	80.82	32.96	100.0	H	324.0	-13.1
742.518889	24.16	---	46.00	21.84	100.0	H	197.0	-7.2

Final_Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: KEY FOB
Model: HF3766R35434_NCF29A3
Test Mode: 433.92MHz
Order No/Sample No: 168570031/A004094809-009
Test Voltage: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.705556	14.51	---	40.00	25.49	100.0	V	122.0	-18.7
107.438333	11.72	---	43.50	31.78	100.0	V	258.0	-19.1
370.416111	17.29	---	46.00	28.71	100.0	V	320.0	-14.4
433.897222	55.40	---	100.82	45.42	100.0	V	298.0	-13.1
433.897222	---	45.40	80.82	35.42	100.0	V	298.0	-13.1
936.950000	26.26	---	46.00	19.74	100.0	V	0.0	-4.4


Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Above 1GHz

EUT Information

EUT Name:	KEY FOB
Model:	HF3766R35434_NCF29A3
Test Mode:	433.92MHz
Order No/Sample No:	168570031/A004094809-009
Test Voltage:	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1390.450000	---	32.42	54.00	21.58	150.0	H	154.0	3.3
1391.566667	41.89	---	74.00	32.11	150.0	H	204.0	3.2
2192.216667	46.71	---	74.00	27.29	150.0	H	13.0	7.8
2198.916667	---	36.94	54.00	17.06	150.0	H	54.0	7.8
3499.833333	---	41.53	54.00	12.47	150.0	H	47.0	10.5
3564.041667	50.63	---	74.00	23.37	150.0	H	157.0	10.7

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name: KEY FOB
Model: HF3766R35434_NCF29A3
Test Mode: 433.92MHz
Order No/Sample No: 168570031/A004094809-009
Test Voltage: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1365.325000	---	32.51	54.00	21.49	150.0	V	262.0	3.5
1365.883333	42.03	---	74.00	31.97	150.0	V	280.0	3.5
2478.641667	47.65	---	74.00	26.35	150.0	V	18.0	8.9
2492.041667	---	38.24	54.00	15.76	150.0	V	5.0	8.9
3499.833333	49.47	---	74.00	24.53	150.0	V	50.0	10.5
3499.833333	---	42.12	54.00	11.88	150.0	V	50.0	10.5

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
-----------------	------------------	------------------	----------------	-------------	-------------	-----	---------------	--------------