




Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (35) of (71)

Test results (Above 1 000 MHz)

Mode: 802.11g

Distance of measurement: 3 meter

Channel: 1

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 004.30	45.50	Peak	H	-10.39	-	35.11	74.00	38.89
1 035.30	46.62	Peak	V	-10.20	-	36.42	74.00	37.58
1 327.87	45.21	Peak	V	-8.41	-	36.80	74.00	37.20
2 521.55	43.64	Peak	H	-1.60	-	42.04	74.00	31.96
4 820.10	47.52	Peak	V	4.82	-	52.34	74.00	21.66
4 824.60	44.05	Peak	H	4.86	-	48.91	74.00	25.09

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 386.62	58.64	Peak	V	-1.69	-	56.95	74.00	17.05
2 386.62	40.89	Average	V	-1.69	0.22	39.42	54.00	14.58
2 386.99	66.75	Peak	H	-1.69	-	65.06	74.00	8.94
2 386.99	48.35	Average	H	-1.69	0.22	46.88	54.00	7.12
2 389.03	68.49	Peak	H	-1.69	-	66.8	74.00	7.20
2 389.03	49.85	Average	H	-1.69	0.22	48.38	54.00	5.62
2 389.04	60.60	Peak	V	-1.69	-	58.91	74.00	15.09
2 389.04	42.95	Average	V	-1.69	0.22	41.48	54.00	12.52


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact kes@kes.co.kr




Restricted band // Horizontal // Peak




Restricted band // Vertical // Peak



Restricted band // Horizontal // Average



Restricted band // Vertical // Average





KES Co., Ltd.


3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:


KES-RF-23T0014

Page (37) of (71)


Horizontal // Peak for 1 GHz to 3 GHz




Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:


KES-RF-23T0014

Page (38) of (71)

Mode: 802.11g
Distance of measurement: 3 meter
Channel: 6

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 006.10	44.89	Peak	V	-10.38	-	34.51	74.00	39.49
1 047.30	45.51	Peak	H	-10.13	-	35.38	74.00	38.62
1 454.05	44.81	Peak	V	-7.68	-	37.13	74.00	36.87
2 517.95	43.65	Peak	H	-1.61	-	42.04	74.00	31.96



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (39) of (71)

Mode: 802.11g
Distance of measurement: 3 meter
Channel: 11


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 027.70	45.86	Peak	H	-10.25	-	35.61	74.00	38.39
1 033.10	45.36	Peak	V	-10.22	-	35.14	74.00	38.86
2 513.55	44.15	Peak	V	-1.62	-	42.53	74.00	31.47
2 544.55	44.63	Peak	H	-1.53	-	43.10	74.00	30.90
4 926.60	42.39	Peak	V	5.64	-	48.03	74.00	25.97


- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.51	71.20	Peak	H	-1.67	-	69.53	74.00	4.47
2 483.51	52.14	Average	H	-1.67	0.22	50.69	54.00	3.31
2 483.51	61.69	Peak	V	-1.67	-	60.69	74.00	13.31
2 483.51	43.23	Average	V	-1.67	0.22	41.78	54.00	12.22
2 484.46	70.65	Peak	H	-1.67	-	68.98	74.00	5.02
2 484.46	51.20	Average	H	-1.67	0.22	49.75	54.00	4.25
2 484.94	59.83	Peak	V	-1.67	-	58.16	74.00	15.84
2 484.94	41.43	Average	V	-1.67	0.22	39.98	54.00	14.02

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



Note.

1. Average test would be performed if the peak result were greater than the average limit.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (42) of (71)

Mode: 802.11n_HT20
Distance of measurement: 3 meter
Channel: 1

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 005.50	45.49	Peak	H	-10.39	-	35.10	74.00	38.90
1 164.48	46.62	Peak	V	-9.42	-	37.20	74.00	36.80
1 331.67	46.20	Peak	V	-8.39	-	37.81	74.00	36.19
2 555.34	44.88	Peak	H	-1.50	-	43.38	74.00	30.62
4 823.10	42.61	Peak	H	4.85	-	47.46	74.00	26.54
4 826.10	45.65	Peak	V	4.87	-	50.52	74.00	23.48

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 387.97	60.38	Peak	V	-1.69	-	58.69	74.00	15.31
2 387.97	39.96	Average	V	-1.69	0.12	38.39	54.00	15.61
2 388.00	67.69	Peak	H	-1.69	-	66	74.00	8.00
2 388.00	48.04	Average	H	-1.69	0.12	46.47	54.00	7.53
2 388.66	67.54	Peak	H	-1.69	-	65.85	74.00	8.15
2 388.66	46.05	Average	H	-1.69	0.12	44.48	54.00	9.52
2 388.86	59.39	Peak	V	-1.69	-	57.7	74.00	16.30
2 388.86	40.51	Average	V	-1.69	0.12	38.94	54.00	15.06

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.


3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:


KES-RF-23T0014

Page (43) of (71)


Restricted band // Horizontal // Peak




Restricted band // Vertical // Peak



Restricted band // Horizontal // Average



Restricted band // Vertical // Average



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.


3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:


KES-RF-23T0014

Page (44) of (71)


Horizontal // Peak for 1 GHz to 3 GHz




Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (45) of (71)


Mode: 802.11n_HT20

Distance of measurement: 3 meter

Channel: 6

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 000.10	47.78	Peak	V	-10.42	-	37.36	74.00	36.64
1 032.50	45.53	Peak	H	-10.22	-	35.31	74.00	38.69
1 198.28	49.77	Peak	V	-9.21	-	40.56	74.00	33.44
2 575.74	44.15	Peak	H	-1.44	-	42.71	74.00	31.29



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (46) of (71)

Mode: 802.11n_HT20
Distance of measurement: 3 meter
Channel: 11


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 049.90	46.29	Peak	H	-10.11	-	36.18	74.00	37.82
1 200.08	48.87	Peak	V	-9.20	-	39.67	74.00	34.33
1 329.47	47.24	Peak	V	-8.40	-	38.84	74.00	35.16
2 516.35	43.96	Peak	H	-1.62	-	42.34	74.00	31.66
4 923.60	43.80	Peak	V	5.62	-	49.42	74.00	24.58


- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.57	70.58	Peak	H	-1.67	-	68.91	74.00	5.09
2 483.57	46.69	Average	H	-1.67	0.12	45.14	54.00	8.86
2 483.62	60.48	Peak	V	-1.67	-	59.48	74.00	14.52
2 483.62	39.10	Average	V	-1.67	0.12	37.55	54.00	16.45
2 484.02	60.08	Peak	V	-1.67	-	58.41	74.00	15.59
2 484.02	38.96	Average	V	-1.67	0.12	37.41	54.00	16.59
2 484.04	69.38	Peak	H	-1.67	-	67.71	74.00	6.29
2 484.04	46.86	Average	H	-1.67	0.12	45.31	54.00	8.69

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



Note.

1. Average test would be performed if the peak result were greater than the average limit.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (49) of (71)

Mode: 802.11n_HT40
Distance of measurement: 3 meter
Channel: 3

- Spurious

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 120.09	46.12	Peak	H	-9.69	-	36.43	74.00	37.57
1 162.68	48.31	Peak	V	-9.43	-	38.88	74.00	35.12
1 329.70	46.60	Peak	V	-8.40	-	38.20	74.00	35.80
2 562.54	45.14	Peak	H	-1.48	-	43.66	74.00	30.34


- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 386.33	56.44	Peak	V	-1.69	-	54.75	74.00	19.25
2 386.33	37.65	Average	V	-1.69	0.23	36.19	54.00	17.81
2 387.44	63.85	Peak	H	-1.69	-	62.16	74.00	11.84
2 387.44	45.15	Average	H	-1.69	0.23	43.69	54.00	10.31
2 387.68	57.04	Peak	V	-1.69	-	55.35	74.00	18.65
2 387.68	39.54	Average	V	-1.69	0.23	38.08	54.00	15.92
2 388.33	64.35	Peak	H	-1.69	-	62.66	74.00	11.34
2 388.33	45.44	Average	H	-1.69	0.23	43.98	54.00	10.02


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr




Restricted band // Horizontal // Peak




Restricted band // Vertical // Peak




Restricted band // Horizontal // Average



Restricted band // Vertical // Average





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (52) of (71)

Mode: 802.11n_HT40


Distance of measurement: 3 meter

Channel: 6


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 044.50	45.71	Peak	H	-10.15	-	35.56	74.00	38.44
1 166.88	48.84	Peak	V	-9.40	-	39.44	74.00	34.56
1 331.47	47.39	Peak	V	-8.39	-	39.00	74.00	35.00
1 669.63	44.73	Peak	H	-5.61	-	39.12	74.00	34.88


Horizontal // Peak for 1 GHz to 3 GHz




Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF-23T0014

Page (53) of (71)

Mode: 802.11n_HT40

Distance of measurement: 3 meter

Channel: 9

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 007.10	45.93	Peak	H	-10.38	-	35.55	74.00	38.45
1 198.28	49.78	Peak	V	-9.21	-	40.57	74.00	33.43
1 666.43	45.53	Peak	H	-5.65	-	39.88	74.00	34.12
2 562.14	45.16	Peak	V	-1.48	-	43.68	74.00	30.32


- Band edge


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 484.07	55.39	Peak	V	-1.67	-	53.72	74.00	20.28
2 484.07	40.48	Average	V	-1.67	0.23	39.04	54.00	14.96
2 484.08	63.52	Peak	H	-1.67	-	62.52	74.00	11.48
2 484.08	48.35	Average	H	-1.67	0.23	46.91	54.00	7.09
2 484.37	54.47	Peak	V	-1.67	-	52.8	74.00	21.20
2 484.37	39.28	Average	V	-1.67	0.23	37.84	54.00	16.16
2 485.42	61.50	Peak	H	-1.67	-	59.83	74.00	14.17
2 485.42	47.13	Average	H	-1.67	0.23	45.69	54.00	8.31

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

The authenticity of the test report, contact kes@kes.co.kr





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.