TCT 通测检测
TESTING CENTRE TECHNOLOGY

TEST REPORT

FCC ID. ..... :	2A9LJ-ME65	
Test Report No..... :	TCT240513E035	
Date of issue..... :	Aug. 20, 2024	
Testing laboratory ..... :	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	Meferi Technologies Co., Ltd.	
Address..... :	4F, A6, Tianfu Software Park, No. 1129, Century City Road, High-tech Zone, 610041, Chengdu, Sichuan, 610041 China	
Manufacturer's name ... :	Meferi Technologies Co., Ltd.	
Address..... :	4F, A6, Tianfu Software Park, No. 1129, Century City Road, High-tech Zone, 610041, Chengdu, Sichuan, 610041 China	
Standard(s) ..... :	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name..... :	MOBILE COMPUTER	
Trade Mark ..... :	MEFERI	
Model/Type reference..... :	ME65, ME65P, ME65T, ME65H, ME65L, ME65S, ME68	
Rating(s)..... :	Refer to EUT description of page 3	
Date of receipt of test item ..... :	May 13, 2024	
Date (s) of performance of test..... :	May 13, 2024 ~ Aug. 20, 2024	
Tested by (+signature) ... :	Rleo LIU	Rleo Liu
Check by (+signature).... :	Beryl ZHAO	Beryl Zhao
Approved by (+signature):	Tomsin	Tomsin

SHENZHEN TONGCE TESTING LAB TCT

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information 3
1.1. EUT description 3
1.2. Model(s) list 3
1.3. Test Frequency 4
2. Test Result Summary 5
3. General Information 6
3.1. Test environment and mode 6
3.2. Description of Support Units 7
4. Facilities and Accreditations 8
4.1. Facilities 8
4.2. Location 8
4.3. Measurement Uncertainty 8
5. Test Results and Measurement Data 9
5.1. Antenna requirement 9
5.2. Conducted Emission 10
5.3. Maximum Conducted Output Power 14
5.4. 6dB Emission Bandwidth 20
5.5. 26dB Bandwidth and 99% Occupied Bandwidth 21
5.6. Power Spectral Density 22
5.7. Band edge 27
5.8. Unwanted Emissions 44
5.9. Frequency Stability Measurement 73
Appendix A: Test Result of Conducted Test
Appendix B: Photographs of Test Setup
Appendix C: Photographs of EUT

1. General Product Information

1.1. EUT description

Product Name.....:	MOBILE COMPUTER
Model/Type reference.....:	ME65
Sample Number.....:	TCT240513E003-0101
Operation Frequency .....:	Band 1: 5180 MHz~5240 MHz Band 2A: 5260 MHz~5320 MHz Band 2C: 5500 MHz~5700 MHz Band 3: 5745 MHz~5825 MHz
Channel Bandwidth.....:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz 802.11ax: 20MHz, 40MHz, 80MHz, 160MHz
Modulation Technology .....:	Orthogonal Frequency Division Multiplexing (OFDM)
Modulation Type.....:	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type.....:	Internal Antenna
Antenna Gain.....:	Band 1: Antenna 3: 1.28dBi, Antenna 2: 0.85dBi Band 2A: Antenna 3: 1.28dBi, Antenna 2: 1.09dBi Band 2C: Antenna 3: 0.68dBi, Antenna 2: 1.96dBi Band 3: Antenna 3: -0.67dBi, Antenna 2: 1.38dBi
Rating(s).....:	Adapter Information: Model: HJ-FC001K7-US Input: AC 100-240V, 50/60Hz, 0.6A Output: DC 5.0V, 3.0A/DC 9.0V, 2.0A/DC 12.0V, 1.5A, 18.0W Rechargeable Li-ion Battery DC 3.85V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	ME65	☒
Other models	ME65P, ME65T, ME65H, ME65L, ME65S, ME68	☐

Note: ME65 is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of ME65 can represent the remaining models.

1.3. Test Frequency

Band 1

20MHz		40MHz		80MHz		160MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180	38	5190	42	5210	50	5250
40	5200	46	5230				
48	5240						

Band 2A

20MHz		40MHz		80MHz		160MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
52	5260	54	5270	58	5290	50	5250
60	5300	62	5310				
64	5320						

Band 2C

20MHz		40MHz		80MHz		160MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
100	5500	102	5510	106	5530	114	5570
120	5600	118	5590	122	5610		
140	5700	134	5670				

Band 3

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745	151	5755	155	5775
157	5785	159	5795		
165	5825				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth& 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.

2. Fail: Test item does not meet the requirement.

3. N/A: Test case does not apply to the test object.

4. The test result judgment is decided by the limit of test standard.

5.For the band 5.15-5.25GHz, EUT meet the requirements of 15.407(a)(ii).

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Software:	
Software Information:	QRCT
Power Level:	11
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations with max. duty cycle.
The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a(SISO)	6 Mbps
802.11n(HT20) (MIMO)	6.5 Mbps
802.11n(HT40) (MIMO)	13.5 Mbps
802.11ac(VHT20) (MIMO)	6.5 Mbps
802.11ac(VHT40) (MIMO)	13.5 Mbps
802.11ac(VHT80) (MIMO)	29.3 Mbps
802.11ax(HE20) (MIMO)	6.5 Mbps

802.11ax(HE40) (MIMO)	13.5 Mbps
802.11ax(HE80) (MIMO)	29.3 Mbps
802.11ax(HE160) (MIMO)	58.5 Mbps
Final Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098
  SHENZHEN TONGCE TESTING LAB
  Designation Number: CN1205
  The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
- IC - Registration No.: 10668A
  SHENZHEN TONGCE TESTING LAB
  CAB identifier: CN0031
  The testing lab has been registered by Innovation, Science and Economic Development Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB
Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
TEL: +86-755-27673339

4.3. Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT test with two internal antennas for maximum gain which are detachable, and the gain is shown below.	

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
Unequal antenna gains, with equal transmit powers, if transmit signals are correlated, then Directional gain of B1= $10\log[(10^{1.28/20}+10^{0.85/20})^2/2]$ = 4.08dBi;
Directional gain of B2A = $10\log[(10^{1.28/20}+10^{1.09/20})^2/2]$ = 4.20dBi;
Directional gain of B2C = $10\log[(10^{0.68/20}+10^{1.96/20})^2/2]$ = 4.35dBi;
Directional gain of B3 = $10\log[(10^{-0.67/20}+10^{1.38/20})^2/2]$ = 3.43dBi.

Note: Above directional gain not applicable to power measurements.

5.2. Conducted Emission

5.2.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 C Section 15.207</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10:2013</td></tr>
<tr><td>Frequency Range:</td><td>150 kHz to 30 MHz</td></tr>
<tr><td>Receiver setup:</td><td>RBW=9 kHz, VBW=30 kHz, Sweep time=auto</td></tr>
<tr><td>Limits:</td><td>
<table>
<tr><td rowspan="2">Frequency range (MHz)</td><td colspan="2">Limit (dBuV)</td></tr>
<tr><td>Quasi-peak</td><td>Average</td></tr>
<tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr>
<tr><td>0.5-5</td><td>56</td><td>46</td></tr>
<tr><td>5-30</td><td>60</td><td>50</td></tr>
</table>
</td></tr>
<tr><td>Test Setup:</td><td>


Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m
</td></tr>
<tr><td>Test Mode:</td><td>Charging + Transmitting Mode</td></tr>
<tr><td>Test Procedure:</td><td>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</td></tr>
<tr><td>Test Result:</td><td>PASS</td></tr>
</table>

5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESCI3	100898	Jun. 26, 2025
LISN	Schwarzbeck	NSLK 8126	8126453	Jan. 31, 2025
Attenuator	N/A	10dB	164080	Jun. 26, 2025
Line-5	TCT	CE-05	/	Jun. 26, 2025
EMI Test Software	EZ_EMC	EMEC-3A1	1.1.4.2	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: *L1* | Temperature: 24.5 (℃) | Humidity: 51 %

Limit: FCC Part 15C Conduction(QP) | Power: AC 120 V/60 Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	35.74	10.02	45.76	66.00	-20.24	QP	
2		0.1500	15.93	10.02	25.95	56.00	-30.05	AVG	
3		0.5321	30.47	9.31	39.78	56.00	-16.22	QP	
4		0.5321	16.20	9.31	25.51	46.00	-20.49	AVG	
5		0.9858	27.33	8.91	36.24	56.00	-19.76	QP	
6		0.9858	13.74	8.91	22.65	46.00	-23.35	AVG	
7		2.3020	25.25	10.08	35.33	56.00	-20.67	QP	
8		2.3020	11.85	10.08	21.93	46.00	-24.07	AVG	
9		6.9218	24.18	10.50	34.68	60.00	-25.32	QP	
10		6.9218	10.00	10.50	20.50	50.00	-29.50	AVG	
11	*	16.4378	35.81	10.61	46.42	60.00	-13.58	QP	
12		16.4378	16.44	10.61	27.05	50.00	-22.95	AVG	

Note:

Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = LISN factor + Cable loss
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)
Q.P. =Quasi-Peak
AVG =average
** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: N | Temperature: 24.5 (℃) | Humidity: 51 %

Limit: FCC Part 15C Conduction(QP) | Power: AC 120 V/60 Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1900	32.44	10.01	42.45	64.04	-21.59	QP	
2		0.1900	15.50	10.01	25.51	54.04	-28.53	AVG	
3		0.5540	27.24	9.27	36.51	56.00	-19.49	QP	
4		0.5540	14.94	9.27	24.21	46.00	-21.79	AVG	
5		1.3939	23.39	9.91	33.30	56.00	-22.70	QP	
6		1.3939	8.72	9.91	18.63	46.00	-27.37	AVG	
7		2.6018	21.23	10.05	31.28	56.00	-24.72	QP	
8		2.6018	5.60	10.05	15.65	46.00	-30.35	AVG	
9		7.0380	23.63	10.48	34.11	60.00	-25.89	QP	
10		7.0380	8.61	10.48	19.09	50.00	-30.91	AVG	
11	*	12.9260	33.40	10.62	44.02	60.00	-15.98	QP	
12		12.9260	18.96	10.62	29.58	50.00	-20.42	AVG	

Note: *1. Freq. = Emission frequency in MHz*

Reading level (dBµV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)

Limit (dBµV) = Limit stated in standard

Margin (dB) = Measurement (dBµV) – Limits (dBµV)

Q.P. =Quasi-Peak

AVG =average

** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80), 802.11ax(HE20), 802.11ax(HE40), 802.11ax(HE80), 802.11ax(HE160)) and the worst case Mode (Channel 159 and 802.11 ac(VHT40) transmit with antenna 2) was submitted only.

5.3. Maximum Conducted Output Power

5.3.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E
Limit:	Frequency Band (MHz) / Limit 5180 - 5240 / 24dBm(250mW) for client device 5260 - 5320 / 24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz 5470 - 5725 / 24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz 5745 - 5825 / 30dBm(1W)
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 5. Measure the conducted output power and record the results in the test report.
Test Result:	PASS
Remark:	Conducted output power= measurement power +10log(1/x), X is duty cycle=1, so 10log(1/1)=0 Conducted output power= measurement power

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Power Meter	Agilent	E4418B	MY45100357	Jun. 26, 2025
Power Sensor	Agilent	8184A	MY41096530	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.3.3. Test Data

Configuration Band 1 (5180 - 5240 MHz) / Antenna 3+Antenna 2						
Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
		Ant3	Ant2	Total		
11a	CH36	8.34	8.68	/	24	PASS
11a	CH40	8.15	8.37	/	24	PASS
11a	CH48	7.82	8.38	/	24	PASS
11n(HT20)	CH36	8.09	8.24	11.18	24	PASS
11n(HT20)	CH40	8.05	8.25	11.16	24	PASS
11n(HT20)	CH48	7.71	8.29	11.02	24	PASS
11n(HT40)	CH38	8.25	8.93	11.61	24	PASS
11n(HT40)	CH46	7.88	9.04	11.51	24	PASS
11ac(VHT20)	CH36	8.05	8.43	11.25	24	PASS
11ac(VHT20)	CH40	7.99	8.34	11.18	24	PASS
11ac(VHT20)	CH48	7.68	8.52	11.13	24	PASS
11ac(VHT40)	CH38	8.28	8.85	11.58	24	PASS
11ac(VHT40)	CH46	7.87	8.99	11.48	24	PASS
11ac(VHT80)	CH42	7.82	8.70	11.29	24	PASS
11ax(HE160)	CH50	7.91	9.22	11.62	24	PASS
11ax(HE20)	CH36	8.24	8.76	11.52	24	PASS
11ax(HE20)	CH40	8.12	8.62	11.39	24	PASS
11ax(HE20)	CH48	7.77	8.76	11.30	24	PASS
11ax(HE40)	CH38	7.99	8.83	11.44	24	PASS
11ax(HE40)	CH46	7.67	9.04	11.42	24	PASS
11ax(HE80)	CH42	7.30	9.08	11.29	24	PASS

Configuration Band 2A (5260 - 5320 MHz) / Antenna 3+Antenna 2								
Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)			26 dB Bandwidth (MHz)	11dBm+ 10logB (dBm)	Output Power Limit (dBm)	Result
		Ant3	Ant2	Total				
11a	CH52	7.61	8.92	/	20.00	24.01	24	PASS
11a	CH60	7.90	9.35	/	19.90	23.99	23.99	PASS
11a	CH64	7.56	9.71	/	19.97	24.00	24	PASS
11n(HT20)	CH52	7.44	8.95	11.27	21.19	24.26	24	PASS
11n(HT20)	CH60	7.82	9.23	11.59	21.16	24.26	24	PASS
11n(HT20)	CH64	7.58	9.56	11.69	21.08	24.24	24	PASS
11n(HT40)	CH54	7.51	9.25	11.48	40.42	27.07	24	PASS
11n(HT40)	CH62	7.95	9.60	11.86	40.28	27.05	24	PASS
11ac(VHT20)	CH52	7.38	9.00	11.28	21.03	24.23	24	PASS
11ac(VHT20)	CH60	7.84	9.23	11.60	21.03	24.23	24	PASS
11ac(VHT20)	CH64	7.57	9.58	11.70	21.12	24.25	24	PASS
11ac(VHT40)	CH54	7.50	9.26	11.48	40.42	27.07	24	PASS
11ac(VHT40)	CH62	7.93	9.72	11.93	40.44	27.07	24	PASS
11ac(VHT80)	CH58	7.35	9.51	11.57	82.56	30.17	24	PASS
11ax(HE20)	CH52	7.46	9.08	11.36	20.84	24.19	24	PASS
11ax(HE20)	CH60	7.89	9.35	11.69	21.25	24.27	24	PASS
11ax(HE20)	CH64	7.62	9.66	11.77	20.84	24.19	24	PASS
11ax(HE40)	CH54	7.29	9.19	11.35	40.27	27.05	24	PASS
11ax(HE40)	CH62	7.72	9.56	11.75	39.54	26.97	24	PASS
11ax(HE80)	CH58	7.11	9.54	11.50	80.56	30.06	24	PASS

Note: The maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz

Configuration Band 2C (5500 - 5700 MHz) / Antenna 3+Antenna 2								
Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)			26 dB Bandwidth (MHz)	11dBm+ 10logB (dBm)	Output Power Limit (dBm)	Result
		Ant3	Ant2	Total				
11a	CH100	7.38	10.13	/	20.16	24.04	24	PASS
11a	CH120	7.56	9.27	/	20.06	24.02	24	PASS
11a	CH140	7.98	9.82	/	20.07	24.03	24	PASS
11n(HT20)	CH100	7.21	9.98	11.82	20.94	24.21	24	PASS
11n(HT20)	CH120	7.41	9.14	11.37	20.95	24.21	24	PASS
11n(HT20)	CH140	7.88	9.68	11.88	20.94	24.21	24	PASS
11n(HT40)	CH102	7.09	10.10	11.86	40.18	27.04	24	PASS
11n(HT40)	CH118	7.55	9.30	11.52	40.53	27.08	24	PASS
11n(HT40)	CH134	7.54	9.50	11.64	39.96	27.02	24	PASS
11ac(VHT20)	CH100	7.10	10.03	11.82	21.04	24.23	24	PASS
11ac(VHT20)	CH120	7.31	9.14	11.33	21.13	24.25	24	PASS
11ac(VHT20)	CH140	7.87	9.68	11.88	20.93	24.21	24	PASS
11ac(VHT40)	CH102	7.72	10.14	12.11	40.44	27.07	24	PASS
11ac(VHT40)	CH118	8.24	9.34	11.84	40.29	27.05	24	PASS
11ac(VHT40)	CH134	8.18	9.49	11.89	40.29	27.05	24	PASS
11ac(VHT80)	CH106	7.85	9.75	11.91	82.37	30.16	24	PASS
11ac(VHT80)	CH122	8.13	9.27	11.75	82.86	30.18	24	PASS
11ax(HE160)	CH100	8.66	9.20	11.95	160.3	33.05	24	PASS
11ax(HE20)	CH114	7.76	9.98	12.02	20.98	24.22	24	PASS
11ax(HE20)	CH120	8.21	9.18	11.73	21.01	24.22	24	PASS
11ax(HE20)	CH140	8.48	9.69	12.14	21.15	24.25	24	PASS
11ax(HE40)	CH102	7.94	9.97	12.08	39.80	27.00	24	PASS
11ax(HE40)	CH118	8.35	9.15	11.78	40.40	27.06	24	PASS
11ax(HE40)	CH134	8.07	9.32	11.75	39.51	26.97	24	PASS
11ax(HE80)	CH106	8.04	9.58	11.89	80.82	30.08	24	PASS
11ax(HE80)	CH122	8.13	9.10	11.65	80.58	30.06	24	PASS

Note: The maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz

Configuration Band 3 (5745 - 5825 MHz) / Antenna 3+Antenna 2						
Mode	Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
		Ant3	Ant2	Total		
11a	CH149	8.08	9.32	/	30	PASS
11a	CH157	9.12	9.26	/	30	PASS
11a	CH165	9.87	9.54	/	30	PASS
11n(HT20)	CH149	7.93	8.62	11.30	30	PASS
11n(HT20)	CH157	8.97	9.13	12.06	30	PASS
11n(HT20)	CH165	9.62	9.89	12.77	30	PASS
11n(HT40)	CH151	8.50	9.69	12.15	30	PASS
11n(HT40)	CH159	9.59	10.15	12.89	30	PASS
11ac(VHT20)	CH149	7.94	9.25	11.65	30	PASS
11ac(VHT20)	CH157	8.98	9.68	12.35	30	PASS
11ac(VHT20)	CH165	9.63	9.66	12.66	30	PASS
11ac(VHT40)	CH151	8.67	9.51	12.12	30	PASS
11ac(VHT40)	CH159	9.75	10.37	13.08	30	PASS
11ac(VHT80)	CH155	9.13	9.92	12.55	30	PASS
11ax(HE20)	CH149	8.09	9.43	11.82	30	PASS
11ax(HE20)	CH157	9.18	9.90	12.57	30	PASS
11ax(HE20)	CH165	9.87	10.00	12.95	30	PASS
11ax(HE40)	CH151	8.45	9.78	12.18	30	PASS
11ax(HE40)	CH159	9.45	10.04	12.77	30	PASS
11ax(HE80)	CH155	8.79	9.58	12.21	30	PASS

5.4. 6dB Emission Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. 26dB Bandwidth and 99% Occupied Bandwidth

5.5.1. Test Specification

Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Power Spectral Density

5.6.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device) ≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725 ≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz The e.i,r,p spectral density for Band 1 5150MHz – 5250 MHz should not exceed 10dBm/MHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Combiner Box	Ascentest	AT890-RFB	/	/

5.6.3. Test data

Configuration Band 1 (5180 - 5240 MHz) / Antenna 3+Antenna 2						
Mode	Test channel	Power Spectral Density(dBm/MHz)			Limit (dBm/MHz)	Result
		Ant3	Ant2	Total		
11a	CH36	-3.19	-2.85	/	11	PASS
11a	CH40	-3.24	-3.12	/	11	PASS
11a	CH48	-3.64	-3.06	/	11	PASS
11n(HT20)	CH36	-3.62	-3.51	-0.55	11	PASS
11n(HT20)	CH40	-3.67	-3.50	-0.57	11	PASS
11n(HT20)	CH48	-3.97	-3.46	-0.70	11	PASS
11n(HT40)	CH38	-6.40	-5.87	-3.12	11	PASS
11n(HT40)	CH46	-6.82	-5.63	-3.17	11	PASS
11ac(VHT20)	CH36	-3.61	-3.28	-0.43	11	PASS
11ac(VHT20)	CH40	-3.68	-3.37	-0.51	11	PASS
11ac(VHT20)	CH48	-3.99	-3.18	-0.56	11	PASS
11ac(VHT40)	CH38	-6.46	-5.86	-3.14	11	PASS
11ac(VHT40)	CH46	-6.81	-5.68	-3.20	11	PASS
11ac(VHT80)	CH42	-9.89	-9.08	-6.46	11	PASS
11ax(HE160)	CH50	-12.51	-10	-8.07	11	PASS
11ax(HE20)	CH36	-2.84	-2.38	0.41	11	PASS
11ax(HE20)	CH40	-3.10	-2.58	0.18	11	PASS
11ax(HE20)	CH48	-3.32	-2.32	0.22	11	PASS
11ax(HE40)	CH38	-5.46	-4.91	-2.17	11	PASS
11ax(HE40)	CH46	-6.32	-4.93	-2.56	11	PASS
11ax(HE80)	CH42	-9.86	-8.20	-5.94	11	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power spectral density (PSD) measurements when antenna gains are not equal,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi =4.08<6,
So limit=11

Configuration Band 2A (5260-5320MHz) /Antenna 3+Antenna 2						
Mode	Test channel	Power Spectral Density(dBm/MHz)			Limit (dBm/MHz)	Result
		Ant3	Ant2	Total		
11a	CH52	-3.99	-2.48	/	11	PASS
11a	CH60	-3.68	-2.08	/	11	PASS
11a	CH64	-4.00	-1.69	/	11	PASS
11n(HT20)	CH52	-4.45	-2.78	-0.52	11	PASS
11n(HT20)	CH60	-3.94	-2.40	-0.09	11	PASS
11n(HT20)	CH64	-4.21	-2.11	-0.02	11	PASS
11n(HT40)	CH54	-7.35	-5.47	-3.30	11	PASS
11n(HT40)	CH62	-6.89	-5.11	-2.90	11	PASS
11ac(VHT20)	CH52	-4.39	-2.67	-0.44	11	PASS
11ac(VHT20)	CH60	-4.00	-2.45	-0.15	11	PASS
11ac(VHT20)	CH64	-4.22	-2.12	-0.03	11	PASS
11ac(VHT40)	CH54	-7.40	-5.44	-3.30	11	PASS
11ac(VHT40)	CH62	-6.89	-4.93	-2.79	11	PASS
11ac(VHT80)	CH58	-10.56	-8.33	-6.29	11	PASS
11ax(HE20)	CH52	-3.68	-1.87	0.33	11	PASS
11ax(HE20)	CH60	-3.37	-1.40	0.74	11	PASS
11ax(HE20)	CH64	-3.52	-1.23	0.78	11	PASS
11ax(HE40)	CH54	-6.63	-4.77	-2.59	11	PASS
11ax(HE40)	CH62	-6.16	-4.32	-2.13	11	PASS
11ax(HE80)	CH58	-9.53	-7.46	-5.36	11	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power spectral density (PSD) measurements when antenna gains are not equal,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi =4.20<6,
So limit=11

Configuration Band 2C (5500-5700 MHz) /Antenna 3+Antenna 2						
Mode	Test channel	Power Spectral Density(dBm/MHz)			Limit (dBm/MHz)	Result
		Ant3	Ant2	Total		
11a	CH100	-4.14	-1.35	/	11	PASS
11a	CH120	-4.01	-2.16	/	11	PASS
11a	CH140	-3.48	-1.64	/	11	PASS
11n(HT20)	CH100	-4.61	-1.76	0.06	11	PASS
11n(HT20)	CH120	-4.36	-2.58	-0.37	11	PASS
11n(HT20)	CH140	-3.89	-2.03	0.15	11	PASS
11n(HT40)	CH102	-7.79	-4.58	-2.88	11	PASS
11n(HT40)	CH118	-7.29	-5.42	-3.24	11	PASS
11n(HT40)	CH134	-7.40	-5.18	-3.14	11	PASS
11ac(VHT20)	CH100	-4.68	-1.67	0.09	11	PASS
11ac(VHT20)	CH120	-4.46	-2.57	-0.40	11	PASS
11ac(VHT20)	CH140	-3.84	-2.04	0.16	11	PASS
11ac(VHT40)	CH102	-7.05	-4.59	-2.64	11	PASS
11ac(VHT40)	CH118	-6.54	-5.38	-2.91	11	PASS
11ac(VHT40)	CH134	-6.62	-5.22	-2.85	11	PASS
11ac(VHT80)	CH106	-9.94	-8.15	-5.94	11	PASS
11ac(VHT80)	CH122	-9.59	-8.56	-6.03	11	PASS
11ax(HE160)	CH114	-11.53	-10.71	-8.09	11	PASS
11ax(HE20)	CH100	-3.31	-0.96	1.03	11	PASS
11ax(HE20)	CH120	-2.75	-1.94	0.68	11	PASS
11ax(HE20)	CH140	-2.24	-1.17	1.34	11	PASS
11ax(HE40)	CH102	-6.31	-3.91	-1.94	11	PASS
11ax(HE40)	CH118	-5.56	-4.72	-2.11	11	PASS
11ax(HE40)	CH134	-5.78	-4.39	-2.02	11	PASS
11ax(HE80)	CH106	-8.77	-7.06	-4.82	11	PASS
11ax(HE80)	CH122	-8.65	-7.29	-4.91	11	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power spectral density (PSD) measurements when antenna gains are not equal,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi =4.35<6,
So limit=11

Configuration Band 3(5745-5825MHz) / Antenna 3+Antenna 2						
Mode	Test channel	Power Spectral Density(dBm/MHz)			Limit (dBm/MHz)	Result
		Ant3	Ant2	Total		
11a	CH149	-6.13	-4.93	/	30	PASS
11a	CH157	-5.16	-5.02	/	30	PASS
11a	CH165	-4.48	-4.82	/	30	PASS
11n(HT20)	CH149	-6.56	-6.01	-3.27	30	PASS
11n(HT20)	CH157	-5.58	-5.38	-2.47	30	PASS
11n(HT20)	CH165	-4.95	-4.89	-1.91	30	PASS
11n(HT40)	CH151	-8.94	-7.93	-5.40	30	PASS
11n(HT40)	CH159	-8.00	-7.50	-4.73	30	PASS
11ac(VHT20)	CH149	-6.58	-5.42	-2.95	30	PASS
11ac(VHT20)	CH157	-5.6	-5.11	-2.34	30	PASS
11ac(VHT20)	CH165	-4.95	-5.06	-1.99	30	PASS
11ac(VHT40)	CH151	-8.83	-7.97	-5.37	30	PASS
11ac(VHT40)	CH159	-7.84	-7.21	-4.50	30	PASS
11ac(VHT80)	CH155	-11.45	-11.01	-8.21	30	PASS
11ax(HE20)	CH149	-6.05	-4.83	-2.39	30	PASS
11ax(HE20)	CH157	-4.87	-4.11	-1.46	30	PASS
11ax(HE20)	CH165	-4.18	-3.92	-1.04	30	PASS
11ax(HE40)	CH151	-8.44	-7.08	-4.70	30	PASS
11ax(HE40)	CH159	-7.49	-6.95	-4.20	30	PASS
11ax(HE80)	CH155	-11.05	-10.32	-7.66	30	PASS

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:
For power spectral density (PSD) measurements when antenna gains are not equal,
Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$] dBi=3.43<6,
So limit=30

5.7. Band edge

5.7.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC CFR47 Part 15E Section 15.407</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10 2013</td></tr>
<tr><td>Limit:</td><td>In un-restricted band:
For Band 1&2A&2C: -27dBm/MHz
For Band 3:
<table>
<tr><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td></tr>
<tr><td>< 650</td><td>-27</td><td>5850~5855</td><td>27~15.6</td></tr>
<tr><td>5650~5700</td><td>-27~10</td><td>5855~5875</td><td>15.6~10</td></tr>
<tr><td>5700~5720</td><td>10~15.6</td><td>5875~5925</td><td>10~-27</td></tr>
<tr><td>5720~5725</td><td>15.6~27</td><td>> 5925</td><td>-27</td></tr>
</table>
E[dBμV/m] = EIRP[dBm] + 95.2 @3m
In restricted band:
<table>
<tr><td>Detector</td><td>Limit@3m</td></tr>
<tr><td>Peak</td><td>74dBμV/m</td></tr>
<tr><td>AVG</td><td>54dBμV/m</td></tr>
</table></td></tr>
<tr><td>Test Setup:</td><td> 
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting mode with modulation</td></tr>
<tr><td>Test Procedure:</td><td>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold</td></tr>
</table>

	Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESCI7	100529	Jan. 31, 2025
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 31, 2025
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jan. 31, 2025
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 26, 2025
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 02, 2025
Coaxial cable	SKET	RE-03-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-L	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-L	/	Jun. 26, 2025
Antenna Mast	Keleto	RE-AM	/	/
EMI Test Software	EZ_EMC	FA-03A2 RE+	1.1.4.2	/

5.7.3. Test Data

AX20-5180



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	51.09	-8.94	42.15	74.00	-31.85	peak	P	
2 *	5150.000	39.95	-8.94	31.01	54.00	-22.99	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	51.00	-8.94	42.06	74.00	-31.94	peak	P	
2 *	5150.000	40.02	-8.94	31.08	54.00	-22.92	AVG	P	

AX40-5190



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	51.29	-8.94	42.35	74.00	-31.65	peak	P	
2 *	5150.000	40.69	-8.94	31.75	54.00	-22.25	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	57.00	-8.94	48.06	74.00	-25.94	peak	P	
2 *	5150.000	43.51	-8.94	34.57	54.00	-19.43	AVG	P	

AX80-5210



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	52.31	-8.94	43.37	74.00	-30.63	peak	P	
2 *	5150.000	40.48	-8.94	31.54	54.00	-22.46	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	54.30	-8.94	45.36	74.00	-28.64	peak	P	
2 *	5150.000	44.35	-8.94	35.41	54.00	-18.59	AVG	P	

AX160-5250



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	51.75	-8.94	42.81	74.00	-31.19	peak	P	
2	5150.000	40.66	-8.94	31.72	54.00	-22.28	AVG	P	
3	5350.000	53.23	-8.45	44.78	74.00	-29.22	peak	P	
4 *	5350.000	41.87	-8.45	33.42	54.00	-20.58	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	53.47	-8.94	44.53	74.00	-29.47	peak	P	
2	5150.000	43.26	-8.94	34.32	54.00	-19.68	AVG	P	
3	5350.000	57.46	-8.45	49.01	74.00	-24.99	peak	P	
4 *	5350.000	46.54	-8.45	38.09	54.00	-15.91	AVG	P	

AX20-5320



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	50.88	-8.45	42.43	74.00	-31.57	peak	P	
2 *	5350.000	39.74	-8.45	31.29	54.00	-22.71	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	51.34	-8.45	42.89	74.00	-31.11	peak	P	
2 *	5350.000	40.00	-8.45	31.55	54.00	-22.45	AVG	P	

AX40-5310



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	56.70	-8.45	48.25	74.00	-25.75	peak	P	
2 *	5350.000	42.91	-8.45	34.46	54.00	-19.54	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	58.50	-8.45	50.05	74.00	-23.95	peak	P	
2 *	5350.000	47.30	-8.45	38.85	54.00	-15.15	AVG	P	

AX80-5290



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	52.15	-8.45	43.70	74.00	-30.30	peak	P	
2 *	5350.000	41.32	-8.45	32.87	54.00	-21.13	AVG	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	58.07	-8.45	49.62	74.00	-24.38	peak	P	
2 *	5350.000	47.53	-8.45	39.08	54.00	-14.92	AVG	P	

AX20-5500



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5460.000	51.45	-8.04	43.41	68.20	-24.79	peak	P	
2 *	5460.000	39.36	-8.04	31.32	54.00	-22.68	AVG	P	
3	5470.000	50.50	-8.02	42.48	68.20	-25.72	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5460.000	50.02	-8.04	41.98	68.20	-26.22	peak	P	
2 *	5460.000	39.59	-8.04	31.55	54.00	-22.45	AVG	P	
3	5470.000	50.54	-8.02	42.52	68.20	-25.68	peak	P	

AX40-5510



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5460.000	51.80	-8.04	43.76	68.20	-24.44	peak	P	
2 *	5460.000	39.83	-8.04	31.79	54.00	-22.21	AVG	P	
3	5470.000	52.48	-8.02	44.46	68.20	-23.74	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5460.000	52.07	-8.04	44.03	68.20	-24.17	peak	P	
2	5460.000	41.67	-8.04	33.63	54.00	-20.37	AVG	P	
3 *	5470.000	58.43	-8.02	50.41	68.20	-17.79	peak	P	

AX80-5530



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5460.000	55.87	-8.04	47.83	68.20	-20.37	peak	P	
2 *	5460.000	43.58	-8.04	35.54	54.00	-18.46	AVG	P	
3	5470.000	55.35	-8.02	47.33	68.20	-20.87	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5460.000	57.31	-8.04	49.27	68.20	-18.93	peak	P	
2	5460.000	45.00	-8.04	36.96	54.00	-17.04	AVG	P	
3 *	5470.000	59.23	-8.02	51.21	68.20	-16.99	peak	P	

AX160-5570



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5460.000	51.07	-8.04	43.03	68.20	-25.17	peak	P	
2 *	5460.000	40.64	-8.04	32.60	54.00	-21.40	AVG	P	
3	5470.000	52.42	-8.02	44.40	68.20	-23.80	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5460.000	56.85	-8.04	48.81	68.20	-19.39	peak	P	
2	5460.000	42.27	-8.04	34.23	54.00	-19.77	AVG	P	
3	5470.000	53.87	-8.02	45.85	68.20	-22.35	peak	P	

AX20-5825



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5929.600	51.98	-6.58	45.40	68.20	-22.80	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5931.800	51.69	-6.57	45.12	68.20	-23.08	peak	P	

AX40-5795



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5931.690	52.02	-6.57	45.45	68.20	-22.75	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5928.930	51.44	-6.58	44.86	68.20	-23.34	peak	P	

AX80-5775



Site: 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5953.290	52.20	-6.48	45.72	68.20	-22.48	peak	P	



Site: 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 22.9(℃) Humidity: 63 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5941.410	52.15	-6.54	45.61	68.20	-22.59	peak	P	

Note: *All modulation (802.11a, 802.11n, 802.11ac, 802.11ax) have been tested, only the worst case in 802.11ax be reported.*

5.8. Unwanted Emissions

5.8.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205
Test Method:	KDB 789033 D02 v02r01
Frequency Range:	9kHz to 40GHz
Measurement Distance:	3 m
Antenna Polarization:	Horizontal & Vertical
Operation mode:	Transmitting mode with modulation

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

Limit:

Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

In restricted bands:

Frequency	Detector	Limit@3m
Above 1G	Peak	74dBμV/m
	AVG	54dBμV/m

Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(KHz)	300
0.490-1.705	24000/F(KHz)	3
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

In un-restricted bands: 68.2dBuV/m

Test setup:

For radiated emissions below 30MHz



	30MHz to 1GHz  Above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the groundat a 3 meter camber. The table was rotated 360 degrees todetermine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, whichwas mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and thenthe antenna was tuned to heights from 1 meter to 4 meters and the rotatablewas turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and SpecifiedBandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limitspecified, then testing could be stopped and the peak values of the EUT wouldbe reported. Otherwise the emissions that did not have 10dB margin would bere-tested one by one using peak, quasi-peak or average method as specified andthen reported in a data sheet.
Test results:	PASS

5.8.2. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



Site: 3m Anechoic Chamber1 Polarization: ***Horizontal*** Temperature: 24.7(C) Humidity: 52 %

Limit: FCC Part 15C RE_3m Power: DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	41.4215	24.87	-12.32	12.55	40.00	-27.45	QP	P	
2	63.5356	25.49	-13.44	12.05	40.00	-27.95	QP	P	
3	148.4410	24.47	-11.31	13.16	43.50	-30.34	QP	P	
4	321.0608	24.75	-9.68	15.07	46.00	-30.93	QP	P	
5	489.0269	26.69	-6.75	19.94	46.00	-26.06	QP	P	
6 *	804.6028	25.46	-1.44	24.02	46.00	-21.98	QP	P	

Vertical:



Site: 3m Anechoic Chamber1 Polarization: ***Vertical*** Temperature: 24.7(C) Humidity: 52 %

Limit: FCC Part 15C RE_3m Power: DC 3.85 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	31.7313	24.77	-13.53	11.24	40.00	-28.76	QP	P	
2 *	43.5057	24.44	-12.54	11.90	40.00	-28.10	QP	P	
3	50.4089	24.46	-12.68	11.78	40.00	-28.22	QP	P	
4	87.1117	25.91	-16.67	9.24	40.00	-30.76	QP	P	
5	144.3348	26.63	-11.71	14.92	43.50	-28.58	QP	P	
6	422.0577	24.88	-7.88	17.00	46.00	-29.00	QP	P	

Note: *1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported*

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80), 802.11ax(HE20), 802.11ax(HE40), 802.11ax(HE80), 802.11ax(HE160)) and the worst case Mode (Channel 159 and 802.11 ac(VHT40) transmit with antenna 2) was submitted only.

3.Measurement (dBμV) = Reading level + Correction Factor, correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.41	---	1.78	40.19	---	68.2	---	-28.01
15540	H	39.95	---	5.21	45.16	---	74	54	-8.84
---	H	---	---	---	---	---	---	---	---
10360	V	38.56	---	1.78	40.34	---	68.2	---	-27.86
15540	V	40.72	---	5.21	45.93	---	74	54	-8.07
---	V	---	---	---	---	----	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.85	---	1.83	41.68	---	68.2	---	-26.52
15600	H	40.16	---	5.23	45.39	---	74	54	-8.61
---	H	---	---	---	---	---	---	---	---
10400	V	40.43	---	1.83	42.26	---	68.2	---	-25.94
15600	V	41.02	---	5.23	46.25	---	74	54	-7.75
---	V	---	---	---	---	----	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	38.14	---	1.85	39.99	---	68.2	---	-28.21
15720	H	39.68	---	5.25	44.93	---	74	54	-9.07
---	H	---	---	---	---	---	---	---	---
10480	V	38.42	---	1.85	40.27	---	68.2	---	-27.93
15720	V	40.59	---	5.25	45.84	---	74	54	-8.16
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	41.69	---	1.78	43.47	---	68.2	---	-24.73
15540	H	40.82	---	5.21	46.03	---	74	54	-7.97
---	H	---	---	---	---	---	---	---	---
10360	V	42.03	---	1.78	43.81	---	68.2	---	-24.39
15540	V	41.45	---	5.21	46.66	---	74	54	-7.34
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.66	---	1.83	42.49	---	68.2	---	-25.71
15600	H	41.14	---	5.23	46.37	---	74	54	-7.63
---	H	---	---	---	---	---	---	---	---
10400	V	40.25	---	1.83	42.08	---	68.2	---	-26.12
15600	V	39.86	---	5.23	45.09	---	74	54	-8.91
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.57	---	1.85	43.42	---	68.2	---	-24.78
15720	H	41.61	---	5.25	46.86	---	74	54	-7.14
---	H	---	---	---	---	---	---	---	---
10480	V	40.24	---	1.85	42.09	---	68.2	---	-26.11
15720	V	39.98	---	5.25	45.23	---	74	54	-8.77
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.86	---	1.80	41.66	---	68.2	---	-26.54
15570	H	41.57	---	5.22	46.79	---	74	54	-7.21
---	H	---	---	---	---	---	---	---	---
10380	V	40.92	---	1.80	42.72	---	68.2	---	-25.48
15570	V	39.21	---	5.22	44.43	---	74	54	-9.57
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.66	---	1.85	43.51	---	68.2	---	-24.69
15690	H	39.01	---	5.08	44.09	---	74	54	-9.91
---	H	---	---	---	---	---	---	---	---
10460	V	41.44	---	1.85	43.29	---	68.2	---	-24.91
15690	V	40.36	---	5.08	45.44	---	74	54	-8.56
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	40.34	---	1.78	42.12	---	68.2	---	-26.08
15540	H	39.81	---	5.21	45.02	---	74	54	-8.98
---	H	---	---	---	---	---	---	---	---
10360	V	38.56	---	1.78	40.34	---	68.2	---	-27.86
15540	V	39.07	---	5.21	44.28	---	74	54	-9.72
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.61	---	1.83	41.44	---	68.2	---	-26.76
15600	H	40.12	---	5.23	45.35	---	74	54	-8.65
---	H	---	---	---	---	---	---	---	---
10400	V	39.78	---	1.83	41.61	---	68.2	---	-26.59
15600	V	39.44	---	5.23	44.67	---	74	54	-9.33
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.74	---	1.85	39.59	---	68.2	---	-28.61
15720	H	38.98	---	5.25	44.23	---	74	54	-9.77
---	H	---	---	---	---	---	---	---	---
10480	V	38.21	---	1.85	40.06	---	68.2	---	-28.14
15720	V	39.46	---	5.25	44.71	---	74	54	-9.29
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.86	---	1.80	42.66	---	68.2	---	-25.54
15570	H	39.74	---	5.22	44.96	---	74	54	-9.04
---	H	---	---	---	---	---	---	---	---
10380	V	38.39	---	1.80	40.19	---	68.2	---	-28.01
15570	V	39.52	---	5.22	44.74	---	74	54	-9.26
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.56	---	1.85	40.41	---	68.2	---	-27.79
15690	H	39.91	---	5.08	44.99	---	74	54	-9.01
---	H	---	---	---	---	---	---	---	---
10460	V	39.47	---	1.85	41.32	---	68.2	---	-26.88
15690	V	40.33	---	5.08	45.41	---	74	54	-8.59
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.82	---	1.84	43.66	---	68.2	---	-24.54
15630	H	39.57	---	5.17	44.74	---	74	54	-9.26
---	H	---	---	---	---	---	---	---	---
10420	V	41.23	---	1.84	43.07	---	68.2	---	-25.13
15630	V	39.99	---	5.17	45.16	---	74	54	-8.84
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	39.06	---	1.78	40.84	---	68.2	---	-27.36
15540	H	40.45	---	5.21	45.66	---	74	54	-8.34
---	H	---	---	---	---	---	---	---	---
10360	V	38.13	---	1.78	39.91	---	68.2	---	-28.29
15540	V	40.58	---	5.21	45.79	---	74	54	-8.21
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.68	---	1.83	41.51	---	68.2	---	-26.69
15600	H	40.45	---	5.23	45.68	---	74	54	-8.32
---	H	---	---	---	---	---	---	---	---
10400	V	39.72	---	1.83	41.55	---	68.2	---	-26.65
15600	V	39.13	---	5.23	44.36	---	74	54	-9.64
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.99	---	1.85	39.84	---	68.2	---	-28.36
15720	H	39.58	---	5.25	44.83	---	74	54	-9.17
---	H	---	---	---	---	---	---	---	---
10480	V	38.46	---	1.85	40.31	---	68.2	---	-27.89
15720	V	39.31	---	5.25	44.56	---	74	54	-9.44
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.34	---	1.80	42.14	---	68.2	---	-26.06
15570	H	39.52	---	5.22	44.74	---	74	54	-9.26
---	H	---	---	---	---	---	---	---	---
10380	V	38.01	---	1.80	39.81	---	68.2	---	-28.39
15570	V	38.95	---	5.22	44.17	---	74	54	-9.83
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.74	---	1.85	40.59	---	68.2	---	-27.61
15690	H	39.36	---	5.08	44.44	---	74	54	-9.56
---	H	---	---	---	---	---	---	---	---
10460	V	39.08	---	1.85	40.93	---	68.2	---	-27.27
15690	V	40.53	---	5.08	45.61	---	74	54	-8.39
---	V	---	---	---	---	----	---	---	---

11ax(HE80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.75	---	1.84	43.59	---	68.2	---	-24.61
15630	H	39.31	---	5.17	44.48	---	74	54	-9.52
---	H	---	---	---	---	---	---	---	---
10420	V	41.62	---	1.84	43.46	---	68.2	---	-24.74
15630	V	39.14	---	5.17	44.31	---	74	54	-9.69
---	V	---	---	---	---	----	---	---	---

11ax(HE160) CH50:5250									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBµV)	AV reading (dBµV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBµV/m)	AV limit (dBµV/m)	Margin (dB)
					Peak (dBµV/m)	AV (dBµV/m)			
10500	H	41.02	---	1.86	42.88	---	68.2	---	-25.32
15750	H	39.58	---	5.03	44.61	---	74	54	-9.39
---	H	---	---	---	---	---	---	---	---
10500	V	41.11	---	1.86	42.97	---	68.2	---	-25.23
15750	V	39.96	---	5.03	44.99	---	74	54	-9.01
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBµV/m)-Average limit (dBµV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

Modulation Type: Band 2A									
11a CH52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	38.14	---	1.87	40.01	---	68.2	---	-28.19
15780	H	39.35	---	5.01	44.36	---	74	54	-9.64
---	H	---	---	---	---	---	---	---	---
10520	V	41.72	---	1.87	43.59	---	68.2	---	-24.61
15780	V	40.58	---	5.01	45.59	---	74	54	-8.41
---	V	---	---	---	---	----	---	---	---
11a CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	44.88	---	1.89	46.77	---	74	54	-7.23
15900	H	40.45	---	4.93	45.38	---	74	54	-8.62
---	H	---	---	---	---	---	---	---	---
10600	V	45.13	---	1.89	47.02	---	74	54	-6.98
15900	V	41.69	---	4.93	46.62	---	74	54	-7.38
---	V	---	---	---	---	----	---	---	---
11a CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	44.55	---	1.94	46.49	---	74	54	-7.51
15960	H	39.78	---	4.83	44.61	---	74	54	-9.39
---	H	---	---	---	---	---	---	---	---
10640	V	45.04	---	1.94	46.98	---	74	54	-7.02
15960	V	41.23	---	4.83	46.06	---	74	54	-7.94
---	V	---	---	---	---	----	---	---	---
11n(HT20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	41.78	---	1.87	43.65	---	68.2	---	-24.55
15780	H	40.26	---	5.01	45.27	---	74	54	-8.73
---	H	---	---	---	---	---	---	---	---
10520	V	38.59	---	1.87	40.46	---	68.2	---	-27.74
15780	V	39.61	---	5.01	44.62	---	74	54	-9.38
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	44.89	---	1.89	46.78	---	74	54	-7.22
15900	H	39.42	---	4.93	44.35	---	74	54	-9.65
---	H	---	---	---	---	---	---	---	---
10600	V	45.95	---	1.89	47.84	---	74	54	-6.16
15900	V	41.36	---	4.93	46.29	---	74	54	-7.71
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	46.11	---	1.94	48.05	---	74	54	-5.95
15960	H	42.68	---	4.83	47.51	---	74	54	-6.49
---	H	---	---	---	---	---	---	---	---
10640	V	44.45	---	1.94	46.39	---	74	54	-7.61
15960	V	40.92	---	4.83	45.75	---	74	54	-8.25
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	41.41	---	1.87	43.28	---	68.2	---	-24.92
15810	H	39.53	---	4.99	44.52	---	74	54	-9.48
---	H	---	---	---	---	---	---	---	---
10540	V	37.67	---	1.87	39.54	---	68.2	---	-28.66
15810	V	40.92	---	4.99	45.91	---	74	54	-8.09
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	45.63	---	1.92	47.55	---	74	54	-6.45
15930	H	40.78	---	4.88	45.66	---	74	54	-8.34
---	H	---	---	---	---	---	---	---	---
10620	V	44.15	---	1.92	46.07	---	74	54	-7.93
15930	V	39.39	---	4.88	44.27	---	74	54	-9.73
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	40.56	---	1.87	42.43	---	68.2	---	-25.77
15780	H	39.41	---	5.01	44.42	---	74	54	-9.58
---	H	---	---	---	---	---	---	---	---
10520	V	40.79	---	1.87	42.66	---	68.2	---	-25.54
15780	V	40.22	---	5.01	45.23	---	74	54	-8.77
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	43.54	---	1.89	45.43	---	74	54	-8.57
15900	H	40.26	---	4.93	45.19	---	74	54	-8.81
---	H	---	---	---	---	---	---	---	---
10600	V	44.03	---	1.89	45.92	---	74	54	-8.08
15900	V	40.88	---	4.93	45.81	---	74	54	-8.19
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	43.45	---	1.94	45.39	---	74	54	-8.61
15960	H	39.61	---	4.83	44.44	---	74	54	-9.56
---	H	---	---	---	---	---	---	---	---
10640	V	44.87	---	1.94	46.81	---	74	54	-7.19
15960	V	39.23	---	4.83	44.06	---	74	54	-9.94
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	40.77	---	1.87	42.64	---	68.2	---	-25.56
15810	H	39.23	---	4.99	44.22	---	74	54	-9.78
---	H	---	---	---	---	---	---	---	---
10540	V	39.59	---	1.87	41.46	---	68.2	---	-26.74
15810	V	39.83	---	4.99	44.82	---	74	54	-9.18
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	44.54	---	1.92	46.46	---	74	54	-7.54
15930	H	39.73	---	4.88	44.61	---	74	54	-9.39
---	H	---	---	---	---	---	---	---	---
10620	V	43.89	---	1.92	45.81	---	74	54	-8.19
15930	V	40.03	---	4.88	44.91	---	74	54	-9.09
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) C58:5290MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10580	H	45.85	---	1.88	47.73	---	74	54	-6.27
15870	H	42.46	---	4.96	47.42	---	74	54	-6.58
---	H	---	---	---	---	---	---	---	---
10580	V	44.13	---	1.88	46.01	---	74	54	-7.99
15870	V	40.92	---	4.96	45.88	---	74	54	-8.12
---	V	---	---	---	---	----	---	---	---

11ax(HE20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	40.45	---	1.87	42.32	---	68.2	---	-25.88
15780	H	39.88	---	5.01	44.89	---	74	54	-9.11
---	H	---	---	---	---	---	---	---	---
10520	V	40.71	---	1.87	42.58	---	68.2	---	-25.62
15780	V	39.64	---	5.01	44.65	---	74	54	-9.35
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	44.33	---	1.89	46.22	---	74	54	-7.78
15900	H	40.72	---	4.93	45.65	---	74	54	-8.35
---	H	---	---	---	---	---	---	---	---
10600	V	44.54	---	1.89	46.43	---	74	54	-7.57
15900	V	41.28	---	4.93	46.21	---	74	54	-7.79
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	45.53	---	1.94	47.47	---	74	54	-6.53
15960	H	41.72	---	4.83	46.55	---	74	54	-7.45
---	H	---	---	---	---	---	---	---	---
10640	V	46.14	---	1.94	48.08	---	74	54	-5.92
15960	V	41.23	---	4.83	46.06	---	74	54	-7.94
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	40.95	---	1.87	42.82	---	68.2	---	-25.38
15810	H	39.12	---	4.99	44.11	---	74	54	-9.89
---	H	---	---	---	---	---	---	---	---
10540	V	39.87	---	1.87	41.74	---	68.2	---	-26.46
15810	V	40.03	---	4.99	45.02	---	74	54	-8.98
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	44.51	---	1.92	46.43	---	74	54	-7.57
15930	H	39.67	---	4.88	44.55	---	74	54	-9.45
---	H	---	---	---	---	---	---	---	---
10620	V	45.83	---	1.92	47.75	---	74	54	-6.25
15930	V	40.14	---	4.88	45.02	---	74	54	-8.98
---	V	---	---	---	---	----	---	---	---

11ax(HE80) C58:5290MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10580	H	45.07	---	1.88	46.95	---	74	54	-7.05
15870	H	39.36	---	4.96	44.32	---	74	54	-9.68
---	H	---	---	---	---	---	---	---	---
10580	V	45.25	---	1.88	47.13	---	74	54	-6.87
15870	V	40.69	---	4.96	45.65	---	74	54	-8.35
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBµV/m)-Average limit (dBµV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

Modulation Type: Band 2C									
11a CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	44.58	---	2.21	46.79	---	74	54	-7.21
16500	H	39.21	---	5.32	44.53	---	68.2	---	-23.67
---	H	---	---	---	---	---	---	---	---
11000	V	45.96	---	2.21	48.17	---	74	54	-5.83
16500	V	40.73	---	5.32	46.05	---	68.2	---	-22.15
---	V	---	---	---	---	----	---	---	---
11a CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	45.12	---	2.34	47.46	---	74	54	-6.54
16800	H	40.75	---	5.62	46.37	---	68.2	---	-21.83
---	H	---	---	---	---	---	---	---	---
11200	V	44.83	---	2.34	47.17	---	74	54	-6.83
16800	V	39.04	---	5.62	44.66	---	68.2	---	-23.54
---	V	---	---	---	---	----	---	---	---
11a CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	42.21	---	2.47	44.68	---	74	54	-9.32
17100	H	40.67	---	6.00	46.67	---	68.2	---	-21.53
---	H	---	---	---	---	---	---	---	---
11400	V	43.14	---	2.47	45.61	---	74	54	-8.39
17100	V	40.59	---	6.00	46.59	---	68.2	---	-21.61
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	45.64	---	2.21	47.85	---	74	54	-6.15
16500	H	39.35	---	5.32	44.67	---	68.2	---	-23.53
---	H	---	---	---	---	---	---	---	---
11000	V	46.14	---	2.21	48.35	---	74	54	-5.65
16500	V	41.87	---	5.32	47.19	---	68.2	---	-21.01
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	45.37	---	2.34	47.71	---	74	54	-6.29
16800	H	40.12	---	5.62	45.74	---	68.2	---	-22.46
---	H	---	---	---	---	---	---	---	---
11200	V	44.48	---	2.34	46.82	---	74	54	-7.18
16800	V	39.75	---	5.62	45.37	---	68.2	---	-22.83
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	44.66	---	2.47	47.13	---	74	54	-6.87
17100	H	40.23	---	6.00	46.23	---	68.2	---	-21.97
---	H	---	---	---	---	---	---	---	---
11400	V	44.98	---	2.47	47.45	---	74	54	-6.55
17100	V	39.44	---	6.00	45.44	---	68.2	---	-22.76
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	45.12	---	2.21	47.33	---	74	54	-6.67
16530	H	39.95	---	5.34	45.29	---	68.2	---	-22.91
---	H	---	---	---	---	---	---	---	---
11020	V	45.28	---	2.21	47.49	---	74	54	-6.51
16530	V	37.63	---	5.34	42.97	---	68.2	---	-25.23
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	44.82	---	2.32	47.14	---	74	54	-6.86
16770	H	39.35	---	5.60	44.95	---	68.2	---	-23.25
---	H	---	---	---	---	---	---	---	---
11180	V	44.79	---	2.32	47.11	---	74	54	-6.89
16770	V	41.21	---	5.60	46.81	---	68.2	---	-21.39
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	44.84	---	2.40	47.24	---	74	54	-6.76
17010	H	41.13	---	5.96	47.09	---	68.2	---	-21.11
---	H	---	---	---	---	---	---	---	---
11340	V	45.69	---	2.40	48.09	---	74	54	-5.91
17010	V	38.37	---	5.96	44.33	---	68.2	---	-23.87
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	45.45	---	2.21	47.66	---	74	54	-6.34
16500	H	39.87	---	5.32	45.19	---	68.2	---	-23.01
---	H	---	---	---	---	---	---	---	---
11000	V	44.36	---	2.21	46.57	---	74	54	-7.43
16500	V	39.79	---	5.32	45.11	---	68.2	---	-23.09
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	44.88	---	2.34	47.22	---	74	54	-6.78
16800	H	39.45	---	5.62	45.07	---	68.2	---	-23.13
---	H	---	---	---	---	---	---	---	---
11200	V	43.93	---	2.34	46.27	---	74	54	-7.73
16800	V	39.12	---	5.62	44.74	---	68.2	---	-23.46
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	43.77	---	2.47	46.24	---	74	54	-7.76
17100	H	38.15	---	6.00	44.15	---	68.2	---	-24.05
---	H	---	---	---	---	---	---	---	---
11400	V	43.28	---	2.47	45.75	---	74	54	-8.25
17100	V	39.36	---	6.00	45.36	---	68.2	---	-22.84
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	44.96	---	2.21	47.17	---	74	54	-6.83
16530	H	39.35	---	5.34	44.69	---	68.2	---	-23.51
---	H	---	---	---	---	---	---	---	---
11020	V	43.68	---	2.21	45.89	---	74	54	-8.11
16530	V	38.12	---	5.34	43.46	---	68.2	---	-24.74
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	45.51	---	2.32	47.83	---	74	54	-6.17
16770	H	36.72	---	5.60	42.32	---	68.2	---	-25.88
---	H	---	---	---	---	---	---	---	---
11180	V	44.83	---	2.32	47.15	---	74	54	-6.85
16770	V	37.99	---	5.60	43.59	---	68.2	---	-24.61
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	45.14	---	2.40	47.54	---	74	54	-6.46
17010	H	36.93	---	5.96	42.89	---	68.2	---	-25.31
---	H	---	---	---	---	---	---	---	---
11340	V	44.72	---	2.40	47.12	---	74	54	-6.88
17010	V	39.35	---	5.96	45.31	---	68.2	---	-22.89
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH106: 5530MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11060	H	43.83	---	2.22	46.05	---	74	54	-7.95
16590	H	40.24	---	5.37	45.61	---	68.2	---	-22.59
---	H	---	---	---	---	---	---	---	---
11060	V	42.65	---	2.22	44.87	---	74	54	-9.13
16590	V	41.17	---	5.37	46.54	---	68.2	---	-21.66
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH122: 5610MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11220	H	44.37	---	2.34	46.71	---	74	54	-7.29
16830	H	38.15	---	5.67	43.82	---	68.2	---	-24.38
---	H	---	---	---	---	---	---	---	---
11220	V	43.88	---	2.34	46.22	---	74	54	-7.78
16830	V	39.42	---	5.67	45.09	---	68.2	---	-23.11
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	44.12	---	2.21	46.33	---	74	54	-7.67
16500	H	39.85	---	5.32	45.17	---	68.2	---	-23.03
---	H	---	---	---	---	---	---	---	---
11000	V	44.36	---	2.21	46.57	---	74	54	-7.43
16500	V	39.71	---	5.32	45.03	---	68.2	---	-23.17
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	43.82	---	2.34	46.16	---	74	54	-7.84
16800	H	39.47	---	5.62	45.09	---	68.2	---	-23.11
---	H	---	---	---	---	---	---	---	---
11200	V	42.51	---	2.34	44.85	---	74	54	-9.15
16800	V	39.77	---	5.62	45.39	---	68.2	---	-22.81
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	44.69	---	2.47	47.16	---	74	54	-6.84
17100	H	38.34	---	6.00	44.34	---	68.2	---	-23.86
---	H	---	---	---	---	---	---	---	---
11400	V	43.98	---	2.47	46.45	---	74	54	-7.55
17100	V	39.71	---	6.00	45.71	---	68.2	---	-22.49
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	43.56	---	2.21	45.77	---	74	54	-8.23
16530	H	39.82	---	5.34	45.16	---	68.2	---	-23.04
---	H	---	---	---	---	---	---	---	---
11020	V	43.45	---	2.21	45.66	---	74	54	-8.34
16530	V	38.03	---	5.34	43.37	---	68.2	---	-24.83
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	44.97	---	2.32	47.29	---	74	54	-6.71
16770	H	36.82	---	5.60	42.42	---	68.2	---	-25.78
---	H	---	---	---	---	---	---	---	---
11180	V	44.23	---	2.32	46.55	---	74	54	-7.45
16770	V	37.15	---	5.60	42.75	---	68.2	---	-25.45
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	45.24	---	2.40	47.64	---	74	54	-6.36
17010	H	36.37	---	5.96	42.33	---	68.2	---	-25.87
---	H	---	---	---	---	---	---	---	---
11340	V	44.86	---	2.40	47.26	---	74	54	-6.74
17010	V	39.59	---	5.96	45.55	---	68.2	---	-22.65
---	V	---	---	---	---	----	---	---	---

11ax(HE80) CH106: 5530MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11060	H	44.12	---	2.22	46.34	---	74	54	-7.66
16590	H	40.58	---	5.37	45.95	---	68.2	---	-22.25
---	H	---	---	---	---	---	---	---	---
11060	V	43.63	---	2.22	45.85	---	74	54	-8.15
16590	V	40.94	---	5.37	46.31	---	68.2	---	-21.89
---	V	---	---	---	---	----	---	---	---

11ax(HE80) CH122: 5610MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11220	H	44.11	---	2.34	46.45	---	74	54	-7.55
16830	H	38.57	---	5.67	44.24	---	68.2	---	-23.96
---	H	---	---	---	---	---	---	---	---
11220	V	44.84	---	2.34	47.18	---	74	54	-6.82
16830	V	39.36	---	5.67	45.03	---	68.2	---	-23.17
---	V	---	---	---	---	----	---	---	---

11ax(HE160) CH114: 5570MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11140	H	44.45	---	2.27	46.72	---	74	54	-7.28
16710	H	38.01	---	5.56	43.57	---	68.2	---	-24.63
---	H	---	---	---	---	---	---	---	---
11140	V	44.68	---	2.27	46.95	---	74	54	-7.05
16710	V	39.23	---	5.56	44.79	---	68.2	---	-23.41
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

Modulation Type: Band 3									
11a CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	44.74	---	2.48	47.22	---	74	54	-6.78
17235	H	37.56	---	6.50	44.06	---	68.2	---	-24.14
---	H	---	---	---	---	---	---	---	---
11490	V	45.17	---	2.48	47.65	---	74	54	-6.35
17235	V	38.35	---	6.50	44.85	---	68.2	---	-23.35
---	V	---	---	---	---	----	---	---	---
11a CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	43.44	---	2.42	45.86	---	74	54	-8.14
17355	H	38.71	---	7.03	45.74	---	68.2	---	-22.46
---	H	---	---	---	---	---	---	---	---
11570	V	43.85	---	2.42	46.27	---	74	54	-7.73
17355	V	39.23	---	7.03	46.26	---	68.2	---	-21.94
---	V	---	---	---	---	----	---	---	---
11a CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	43.47	---	2.41	45.88	---	74	54	-8.12
17475	H	36.13	---	7.41	43.54	---	68.2	---	-24.66
---	H	---	---	---	---	---	---	---	---
11650	V	43.66	---	2.41	46.07	---	74	54	-7.93
17475	V	38.24	---	7.41	45.65	---	68.2	---	-22.55
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	44.58	---	2.48	47.06	---	74	54	-6.94
17235	H	38.12	---	6.50	44.62	---	68.2	---	-23.58
---	H	---	---	---	---	---	---	---	---
11490	V	44.46	---	2.48	46.94	---	74	54	-7.06
17235	V	37.05	---	6.50	43.55	---	68.2	---	-24.65
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	44.63	---	2.42	47.05	---	74	54	-6.95
17355	H	39.14	---	7.03	46.17	---	68.2	---	-22.03
---	H	---	---	---	---	---	---	---	---
11570	V	44.95	---	2.42	47.37	---	74	54	-6.63
17355	V	39.48	---	7.03	46.51	---	68.2	---	-21.69
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	45.25	---	2.41	47.66	---	74	54	-6.34
17475	H	37.66	---	7.41	45.07	---	68.2	---	-23.13
---	H	---	---	---	---	---	---	---	---
11650	V	45.13	---	2.41	47.54	---	74	54	-6.46
17475	V	39.98	---	7.41	47.39	---	68.2	---	-20.81
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	44.76	---	2.47	47.23	---	74	54	-6.77
17265	H	37.21	---	6.62	43.83	---	68.2	---	-24.37
---	H	---	---	---	---	---	---	---	---
11510	V	44.55	---	2.47	47.02	---	74	54	-6.98
17265	V	38.47	---	6.62	45.09	---	68.2	---	-23.11
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	44.36	---	2.40	46.76	---	74	54	-7.24
17385	H	38.71	---	7.15	45.86	---	68.2	---	-22.34
---	H	---	---	---	---	---	---	---	---
11590	V	44.25	---	2.40	46.65	---	74	54	-7.35
17385	V	37.84	---	7.15	44.99	---	68.2	---	-23.21
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	44.69	---	2.48	47.17	---	74	54	-6.83
17235	H	37.44	---	6.50	43.94	---	68.2	---	-24.26
---	H	---	---	---	---	---	---	---	---
11490	V	44.81	---	2.48	47.29	---	74	54	-6.71
17235	V	38.57	---	6.50	45.07	---	68.2	---	-23.13
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	43.61	---	2.42	46.03	---	74	54	-7.97
17355	H	36.34	---	7.03	43.37	---	68.2	---	-24.83
---	H	---	---	---	---	---	---	---	---
11570	V	43.75	---	2.42	46.17	---	74	54	-7.83
17355	V	38.18	---	7.03	45.21	---	68.2	---	-22.99
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	44.24	---	2.41	46.65	---	74	54	-7.35
17475	H	38.63	---	7.41	46.04	---	68.2	---	-22.16
---	H	---	---	---	---	---	---	---	---
11650	V	44.15	---	2.41	46.56	---	74	54	-7.44
17475	V	40.07	---	7.41	47.48	---	68.2	---	-20.72
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	44.52	---	2.47	46.99	---	74	54	-7.01
17265	H	37.17	---	6.62	43.79	---	68.2	---	-24.41
---	H	---	---	---	---	---	---	---	---
11510	V	43.65	---	2.47	46.12	---	74	54	-7.88
17265	V	36.24	---	6.62	42.86	---	68.2	---	-25.34
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	43.32	---	2.40	45.72	---	74	54	-8.28
17385	H	37.17	---	7.15	44.32	---	68.2	---	-23.88
---	H	---	---	---	---	---	---	---	---
11590	V	42.56	---	2.40	44.96	---	74	54	-9.04
17385	V	38.43	---	7.15	45.58	---	68.2	---	-22.62
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	44.85	---	2.44	47.29	---	74	54	-6.71
17325	H	38.32	---	6.89	45.21	---	68.2	---	-22.99
---	H	---	---	---	---	---	---	---	---
11550	V	44.98	---	2.44	47.42	---	74	54	-6.58
17325	V	38.24	---	6.89	45.13	---	68.2	---	-23.07
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	45.23	---	2.48	47.71	---	74	54	-6.29
17235	H	37.74	---	6.50	44.24	---	68.2	---	-23.96
---	H	---	---	---	---	---	---	---	---
11490	V	44.99	---	2.48	47.47	---	74	54	-6.53
17235	V	38.04	---	6.50	44.54	---	68.2	---	-23.66
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	43.49	---	2.42	45.91	---	74	54	-8.09
17355	H	36.71	---	7.03	43.74	---	68.2	---	-24.46
---	H	---	---	---	---	---	---	---	---
11570	V	44.53	---	2.42	46.95	---	74	54	-7.05
17355	V	38.26	---	7.03	45.29	---	68.2	---	-22.91
---	V	---	---	---	---	----	---	---	---

11ax(HE20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	43.42	---	2.41	45.83	---	74	54	-8.17
17475	H	38.97	---	7.41	46.38	---	68.2	---	-21.82
---	H	---	---	---	---	---	---	---	---
11650	V	43.61	---	2.41	46.02	---	74	54	-7.98
17475	V	39.55	---	7.41	46.96	---	68.2	---	-21.24
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	43.72	---	2.47	46.19	---	74	54	-7.81
17265	H	37.16	---	6.62	43.78	---	68.2	---	-24.42
---	H	---	---	---	---	---	---	---	---
11510	V	43.58	---	2.47	46.05	---	74	54	-7.95
17265	V	36.61	---	6.62	43.23	---	68.2	---	-24.97
---	V	---	---	---	---	----	---	---	---

11ax(HE40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	44.59	---	2.40	46.99	---	74	54	-7.01
17385	H	37.48	---	7.15	44.63	---	68.2	---	-23.57
---	H	---	---	---	---	---	---	---	---
11590	V	43.66	---	2.40	46.06	---	74	54	-7.94
17385	V	38.17	---	7.15	45.32	---	68.2	---	-22.88
---	V	---	---	---	---	----	---	---	---

11ax(HE80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	44.83	---	2.44	47.27	---	74	54	-6.73
17325	H	38.12	---	6.89	45.01	---	68.2	---	-23.19
---	H	---	---	---	---	---	---	---	---
11550	V	45.05	---	2.44	47.49	---	74	54	-6.51
17325	V	38.67	---	6.89	45.56	---	68.2	---	-22.64
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

5.9. Frequency Stability Measurement

5.9.1. Test Specification

Test Requirement:	FCC Part15 Section 15.407(g) &Part2 J Section 2.1055
Test Method:	ANSI C63.10: 2013
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Setup:	
Test Procedure:	The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test Result:	PASS
Remark:	Pre-scan was performed at Antenna 3 and Antenna 2, the worst case was found. Only the test data 802.11ax of Antenna 2 was shown in this report.

Test plots as follows:

Test mode:	802.11ax(HE20)	Frequency(MHz):	5180
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5180	0	PASS
35		5180	0	PASS
25		5180	0	PASS
15		5180	0	PASS
5		5180	0	PASS
0		5180	0	PASS
20	3.27V	5180	0	PASS
	3.85V	5180	0	PASS
	4.43V	5180	0	PASS

Test mode:	802.11ax(HE20)	Frequency(MHz):	5200
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5200.02	20000	PASS
35		5200.02	20000	PASS
25		5200	0	PASS
15		5200	0	PASS
5		5200	0	PASS
0		5200	0	PASS
20	3.27V	5200	0	PASS
	3.85V	5200	0	PASS
	4.43V	5200	0	PASS

Test mode:	802.11ax(HE20)	Frequency(MHz):	5240
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5240	0	PASS
35		5240	0	PASS
25		5240	0	PASS
15		5240	0	PASS
5		5240	0	PASS
0		5240	0	PASS
20	3.27V	5240	0	PASS
	3.85V	5240	0	PASS
	4.43V	5240	0	PASS

Test mode:	802.11ax(HE20)	Frequency(MHz):	5745	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5745.02	20000	PASS
35		5745.02	20000	PASS
25		5745	0	PASS
15		5745	0	PASS
5		5745	0	PASS
0		5745	0	PASS
20	3.27V	5745	0	PASS
	3.85V	5745	0	PASS
	4.43V	5745.02	20000	PASS

Test mode:	802.11ax(HE20)	Frequency(MHz):	5785	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5785.02	20000	PASS
35		5785.02	20000	PASS
25		5785	0	PASS
15		5785	0	PASS
5		5785	0	PASS
0		5785.02	20000	PASS
20	3.27V	5785	0	PASS
	3.85V	5785	0	PASS
	4.43V	5785	0	PASS

Test mode:	802.11ax(HE20)	Frequency(MHz):	5825	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5825	0	PASS
35		5825	0	PASS
25		5825	0	PASS
15		5825	0	PASS
5		5825	0	PASS
0		5825.02	20000	PASS
20	3.27V	5825	0	PASS
	3.85V	5825.02	20000	PASS
	4.43V	5825	0	PASS

Test mode:	802.11ax(HE40)	Frequency(MHz):	5190
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5190	0	PASS
35		5190.04	40000	PASS
25		5190	0	PASS
15		5190	0	PASS
5		5190.04	40000	PASS
0		5190	0	PASS
20	3.27V	5190	0	PASS
	3.85V	5190	0	PASS
	4.43V	5190	0	PASS

Test mode:	802.11ax(HE40)	Frequency(MHz):	5230
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5230	0	PASS
35		5230.04	40000	PASS
25		5230	0	PASS
15		5230.04	40000	PASS
5		5230	0	PASS
0		5230.04	40000	PASS
20	3.27V	5230	0	PASS
	3.85V	5230	0	PASS
	4.43V	5230	0	PASS

Test mode:	802.11ax(HE40)	Frequency(MHz):	5755
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5755	0	PASS
35		5755	0	PASS
25		5755	0	PASS
15		5755	0	PASS
5		5755.04	40000	PASS
0		5755	0	PASS
20	3.27V	5755.04	40000	PASS
	3.85V	5755	0	PASS
	4.43V	5755	0	PASS

Test mode:	802.11ax(HE40)	Frequency(MHz):	5795	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5795	0	PASS
35		5795	0	PASS
25		5795	0	PASS
15		5795	0	PASS
5		5795	0	PASS
0		5795	0	PASS
20	3.27V	5795	0	PASS
	3.85V	5795.04	40000	PASS
	4.43V	5795	0	PASS

Test mode:	802.11ax(HE80)	Frequency(MHz):	5210	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5210	0	PASS
35		5210	0	PASS
25		5210	0	PASS
15		5210	0	PASS
5		5210	0	PASS
0		5210	0	PASS
20	3.27V	5210	0	PASS
	3.85V	5210	0	PASS
	4.43V	5210	0	PASS

Test mode:	802.11ax(HE80)	Frequency(MHz):	5775	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5775	0	PASS
35		5775	0	PASS
25		5775	0	PASS
15		5775	0	PASS
5		5775	0	PASS
0		5775	0	PASS
20	3.27V	5775	0	PASS
	3.85V	5775	0	PASS
	4.43V	5775	0	PASS

Test mode:	802.11ax(HE160)	Frequency(MHz):	5250	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5250	0	PASS
35		5250	0	PASS
25		5250	0	PASS
15		5250	0	PASS
5		5250	0	PASS
0		5250	0	PASS
20	3.27V	5250	0	PASS
	3.85V	5250	0	PASS
	4.43V	5250	0	PASS

Test mode:	802.11ax(HE160)	Frequency(MHz):	5570	
Temperature (°C)	Voltage(V_{DC})	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.85V	5570	0	PASS
35		5570	0	PASS
25		5570	0	PASS
15		5570	0	PASS
5		5570	0	PASS
0		5570	0	PASS
20	3.27V	5570	0	PASS
	3.85V	5570	0	PASS
	4.43V	5570	0	PASS

Appendix A: Test Result of Conducted Test

Antenna 3

Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)
NVNT	a	5180	Ant3	99.68
NVNT	a	5200	Ant3	99.70
NVNT	a	5240	Ant3	99.69
NVNT	n20	5180	Ant3	99.88
NVNT	n20	5200	Ant3	99.88
NVNT	n20	5240	Ant3	99.87
NVNT	n40	5190	Ant3	99.89
NVNT	n40	5230	Ant3	99.89
NVNT	ac20	5180	Ant3	99.87
NVNT	ac20	5200	Ant3	99.88
NVNT	ac20	5240	Ant3	99.87
NVNT	ac40	5190	Ant3	99.87
NVNT	ac40	5230	Ant3	99.88
NVNT	ac80	5210	Ant3	99.78
NVNT	ax160	5250	Ant3	99.71
NVNT	ax20	5180	Ant3	99.88
NVNT	ax20	5200	Ant3	99.89
NVNT	ax20	5240	Ant3	99.88
NVNT	ax40	5190	Ant3	99.86
NVNT	ax40	5230	Ant3	99.83
NVNT	ax80	5210	Ant3	99.74
NVNT	a	5260	Ant3	99.67
NVNT	a	5300	Ant3	99.68
NVNT	a	5320	Ant3	99.67
NVNT	n20	5260	Ant3	99.87
NVNT	n20	5300	Ant3	99.87
NVNT	n20	5320	Ant3	99.87
NVNT	n40	5270	Ant3	99.89
NVNT	n40	5310	Ant3	99.89
NVNT	ac20	5260	Ant3	99.87
NVNT	ac20	5300	Ant3	99.88
NVNT	ac20	5320	Ant3	99.88
NVNT	ac40	5270	Ant3	99.88
NVNT	ac40	5310	Ant3	99.89
NVNT	ac80	5290	Ant3	99.79
NVNT	ax20	5260	Ant3	99.87
NVNT	ax20	5300	Ant3	99.87
NVNT	ax20	5320	Ant3	99.88
NVNT	ax40	5270	Ant3	99.83
NVNT	ax40	5310	Ant3	99.86
NVNT	ax80	5290	Ant3	99.75
NVNT	a	5500	Ant3	99.67

NVNT	a	5600	Ant3	99.68
NVNT	a	5700	Ant3	99.69
NVNT	n20	5500	Ant3	99.87
NVNT	n20	5600	Ant3	99.88
NVNT	n20	5700	Ant3	99.87
NVNT	n40	5510	Ant3	99.89
NVNT	n40	5590	Ant3	99.87
NVNT	n40	5670	Ant3	99.88
NVNT	ac20	5500	Ant3	99.87
NVNT	ac20	5600	Ant3	99.88
NVNT	ac20	5700	Ant3	99.87
NVNT	ac40	5510	Ant3	99.89
NVNT	ac40	5590	Ant3	99.88
NVNT	ac40	5670	Ant3	99.88
NVNT	ac80	5530	Ant3	99.80
NVNT	ac80	5610	Ant3	99.78
NVNT	ax160	5570	Ant3	99.72
NVNT	ax20	5500	Ant3	99.89
NVNT	ax20	5600	Ant3	99.88
NVNT	ax20	5700	Ant3	99.88
NVNT	ax40	5510	Ant3	99.85
NVNT	ax40	5590	Ant3	99.83
NVNT	ax40	5670	Ant3	99.87
NVNT	ax80	5530	Ant3	99.75
NVNT	ax80	5610	Ant3	99.73
NVNT	a	5745	Ant3	99.69
NVNT	a	5785	Ant3	99.68
NVNT	a	5825	Ant3	99.69
NVNT	n20	5745	Ant3	99.87
NVNT	n20	5785	Ant3	99.88
NVNT	n20	5825	Ant3	99.87
NVNT	n40	5755	Ant3	99.87
NVNT	n40	5795	Ant3	99.87
NVNT	ac20	5745	Ant3	99.88
NVNT	ac20	5785	Ant3	99.88
NVNT	ac20	5825	Ant3	99.87
NVNT	ac40	5755	Ant3	99.87
NVNT	ac40	5795	Ant3	99.88
NVNT	ac80	5775	Ant3	99.79
NVNT	ax20	5745	Ant3	99.88
NVNT	ax20	5785	Ant3	99.88
NVNT	ax20	5825	Ant3	99.88
NVNT	ax40	5755	Ant3	99.87
NVNT	ax40	5795	Ant3	99.87
NVNT	ax80	5775	Ant3	99.75

Test Graphs

Duty Cycle NVNT a 5180MHz Ant3



Duty Cycle NVNT a 5200MHz Ant3



Duty Cycle NVNT a 5240MHz Ant3



Duty Cycle NVNT n20 5180MHz Ant3