



TEST REPORT

Reference No...... : WTZ22F10214929W002
FCC ID : 2A9O8-BCD35AW
Applicant..... : Foshan Alpicool Electric Appliance Co., LTD.
Address..... : 13A ,Xinlong Road, ShilongJiyue Industrial Zone, Xintang Village,
Lunjiao Town ,Shunde District, Foshan City, Guangdong,China
Manufacturer : The same as above
Address..... : The same as above
Product Name..... : Car Refrigerator
Model No..... : BCD35AW, BCD35, BCD35W, BCD35A, BCD25, BCD25W, BCD25A,
BCD25AW
Test specification..... : FCC CFR47 Part 1 Subpart I (Section 1.1307): 2020
Date of Receipt sample : 2022-11-17
Date of Test : 2022-12-02 to 2022-12-06
Date of Issue..... : 2023-01-31
Test Report Form No. : WEW-MPE-01A
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Foshan) Co., Ltd.

Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City,
Chencun, Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398

Fax:+86-757-23811381

E-mail:info@waltek.com.cn

Tested by:

Kyrie Yun

Approved by:





1 Revision History

Test Report No.	Date of Issue	Description	Status
WTZ22F10214929W002	2023-01-31	Original	Valid

WALTEK



2 Contents

	Page
1 REVISION HISTORY.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T	4
3.2 TECHNICAL CHARACTERISTICS OF EUT	4
3.3 DISCLAIMER.....	4
4 MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
4.1 STANDARD APPLICABLE.....	5
4.2 MPE CALCULATION METHOD.....	6
4.3 MPE CALCULATION RESULT.....	6

WALTEK



3 General Information

3.1 General Description of E.U.T

Product Name	: Car Refrigerator
Model No.	: BCD35AW, BCD35, BCD35W, BCD35A, BCD25, BCD25W, BCD25A, BCD25AW
Model Description	: All models are identical except for the appearance, color and volume. Therefore the full tests were performed on model BCD35AW.
Rated Voltage.....	: DC 12/24V, 45W
Battery Capacity	: ---
Power Adapter	: GRT60-145410 Input: 100-240V~, 50/60Hz, 1.5A; Output: DC 14.5V, 4.1A

3.2 Technical Characteristics of EUT

Bluetooth Version	: V4.2 (BLE mode)
Frequency Range	: 2402-2480MHz
RF Output Power	: -20.738dBm (Conducted)
Modulation	: GFSK
Data Rate	: 1Mbps
Quantity of Channels	: 40
Channel Separation.....	: 2MHz
Type of Antenna	: PCB Printed Antenna
Antenna Gain	: -0.19dBi

3.3 Disclaimer

The antenna gain information is provided by the customer. The laboratory is not responsible for the accuracy of the antenna gain information.



4 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

4.1 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; * = Plane-wave equivalents power density



4.2 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

4.3 MPE Calculation Result

Prediction distance (mm)	Prediction frequency (MHz)	Antenna Gain (dBi)	Numeric gain	Maximum Tune-up output power (dBm)	Maximum peak output power (mW)	PD (mW/cm ²)	Limit (mW/cm ²)
>200	2480	-0.19	0.96	-20.738	0.0084	0.0000016	1.0

Result: Pass

=====End of Report=====

WALTEK