



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20250300632E-04
Applicant: Ultimea Technology (Shenzhen) Limited
Address of Applicant: 20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Soundbar
Model No.: U4122, U4123, U4121, U4124, U4125
Test Model No.: U4122
Brand Name: ULTIMEA
FCC ID: 2A9OO-U4122S
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2025-03-24
Date of Test: 2025-03-24 to 2025-04-22
Date of Issue: 2025-5-6
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20250300632E-04	Rev.01	Initial report	2025-5-6

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE	5
3.4 GENERAL DESCRIPTION OF BT	5
3.5 GENERAL DESCRIPTION OF BT	5
4 RF EXPOSURE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	6
4.2 1.1.3 EUT RF EXPOSURE EVALUATION	7

3 General Information

3.1 Client Information

Applicant:	Ultimea Technology (Shenzhen) Limited
Address of Applicant:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Manufacturer:	Ultimea Technology (Shenzhen) Limited
Address of Manufacturer:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Factory:	Guangzhou Panyu Juda Car Audio Equipment Co., Ltd
Address of Factory:	NO.5 Building, No.139, Zhouxing Street, Dongchong Town, Nansha District, Guangzhou City, Guangdong Province, China

3.2 General Description of EUT

Product Name:	Soundbar
Model No.:	U4122, U4123, U4121, U4124, U4125
Test Model No.:	U4122
Trade Mark:	ULTIMEA
Software Version:	77
Hardware Version:	V1.2
EUT Power Supply:	Model:FX65C-240300Z Input:100-240V~50/60Hz 2A Output:24V 3.0A
	Model:GQ72A-240300-AU Input:100-240V~50/60Hz 2A Output:24V 3.0A
Simultaneous Transmission	☒ Simultaneous TX is supported and evaluated in this report. ☐ Simultaneous TX is not supported.

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	5.3
Module information:	ATS2853
Modulation Type:	GFSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	40
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	PCB antenna
Antenna Gain:	3.28dBi

3.4 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	5.3
Module information:	ATS2853
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	PCB antenna
Antenna Gain:	3.28dBi

3.5 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	5.3
Module information:	ATS2835P
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna
Antenna Gain:	4.36dBi

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 1.1.3 EUT RF Exposure Evaluation

1) For BLE (ATS2853)

Antenna Gain: 3.28dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.13 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	7.14	7 ± 1	8	6.310
Middle(2440MHz)	7.48	7.5 ± 1	8.5	7.079
Highest(2480MHz)	7.23	7.5 ± 1	8.5	7.079

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
7.079	3.28	0.000299729	1.0	PASS

Note: 1) Refer to report No. CQASZ20250300632E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (7.079 * 2.13) / (4 * 3.1416 * 20^2) = 0.000299729$

2) For BT (ATS2853)

Antenna Gain: 3.28dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.13 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	8.98	9±1	10	10.000
Middle(2441MHz)	8.77	9±1	10	10.000
Highest(2480MHz)	8.95	9±1	10	10.000
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	9.24	9.5±1	10.5	11.220
Middle(2441MHz)	9.01	9±1	10	10.000
Highest(2480MHz)	9.49	9.5±1	10.5	11.220
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	9.73	10±1	11	12.589
Middle(2441MHz)	9.35	9.5±1	10.5	11.220
Highest(2480MHz)	9.75	10±1	11	12.589

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
12.589	3.28	0.00533	1.0	PASS

Note: 1) Refer to report No. CQASZ20250300632E-02 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (12.589 \cdot 2.13) / (4 \cdot 3.1416 \cdot 20^2) = 0.00533$

3) For BT (ATS2835P)

Antenna Gain: 4.36dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.73 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	7.07	7±1	8	6.310
Middle(2441MHz)	7.16	7±1	8	6.310
Highest(2480MHz)	7.26	7.5±1	8.5	7.079
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	6.89	7±1	8	6.310
Middle(2441MHz)	6.92	7±1	8	6.310
Highest(2480MHz)	7.06	7±1	8	6.310
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	7.14	7±1	8	6.310
Middle(2441MHz)	7.26	7.5±1	8.5	7.079
Highest(2480MHz)	7.24	7.5±1	8.5	7.079

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
7.079	4.36	0.0038435	1.0	PASS

Note: 1) Refer to report No. CQASZ20250300632E-03 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (2.73 * 2.73) / (4 * 3.1416 * 20^2) = 0.0038435$

Simultaneous TX:

$\text{BLE(ATS2853)} + \text{BT(ATS2853)} + \text{BT(ATS2835P)} \leq 1$

$0.000299729 + 0.00533 + 0.0038435 \leq 1$

*** END OF REPORT ***