






Date: 16.APR 2025 12:49:28

3DH5_Ant1_2402




Date: 16.APR 2025 20:20:20

3DH5_Ant1_2441




Date: 16.APR 2025 20:22:14

3DH5_Ant1_2480



Date: 16.APR.2025 20:22:58

5.5 Carrier Frequencies Separation


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

TestMode	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Hop	0.997	≥ 0.627	PASS
2DH5	Hop	1.02	≥ 0.813	PASS
3DH5	Hop	1.006	≥ 0.833	PASS


Mode	20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.94	≥ 0.627
$\pi/4$ DQPSK	1.22	≥ 0.813
8DPSK	1.25	≥ 0.833

Test plot as follows:






5.6 Hopping Channel Number


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15

Test plot as follows:





5.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass


Measurement Data


TestMode	Freq(MHz)	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Hop	0.370	320	0.118	≤0.4	PASS
DH3	Hop	1.610	160	0.258	≤0.4	PASS
DH5	Hop	2.850	110	0.314	≤0.4	PASS
2DH1	Hop	0.378	330	0.125	≤0.4	PASS
2DH3	Hop	1.621	160	0.259	≤0.4	PASS
2DH5	Hop	2.862	120	0.343	≤0.4	PASS
3DH1	Hop	0.376	330	0.124	≤0.4	PASS
3DH3	Hop	1.620	170	0.275	≤0.4	PASS
3DH5	Hop	2.863	110	0.315	≤0.4	PASS

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test plot as follows:






Date: 16.APR.2025 12:54:42




Date: 16.APR.2025 12:54:48

DH5_Ant1_Hop




Date: 16.APR.2025 12:53:00




Date: 16.APR 2025 12:53:06

2DH1_Ant1_Hop




Date: 16.APR 2025 13:01:03




Date: 16.APR 2025 13:01:08

2DH3_Ant1_Hop




Date: 16.APR 2025 13:02:29




Date: 16.APR 2025 13:02:35

2DH5_Ant1_Hop




Date: 16.APR 2025 13:00:28




Date: 16.APR 2025 13:00:33

3DH1_Ant1_Hop




Date: 16.APR 2025 20:26:50




Date: 16.APR 2025 20:26:56

3DH3_Ant1_Hop




Date: 16.APR 2025 20:27:45




Date: 16.APR 2025 20:27:50

3DH5_Ant1_Hop




Date: 16.APR 2025 20:26:02



Date: 16.APR.2025 20:26:07


5.8 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

TestMode	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Low	2402	6.83	-49.29	≤ -13.17	PASS
	High	2480	6.95	-49.15	≤ -13.05	PASS
	Low	Hop_2402	6.06	-49.77	≤ -13.94	PASS
	High	Hop_2480	7.06	-50.22	≤ -12.94	PASS
2DH5	Low	2402	6.68	-50.61	≤ -13.32	PASS
	High	2480	6.29	-50.02	≤ -13.71	PASS
	Low	Hop_2402	1.17	-51.18	≤ -18.83	PASS
	High	Hop_2480	5.33	-51.51	≤ -14.67	PASS
3DH5	Low	2402	6.85	-50.07	≤ -13.15	PASS
	High	2480	7.19	-50.4	≤ -12.81	PASS
	Low	Hop_2402	7.07	-50.36	≤ -12.93	PASS
	High	Hop_2480	6.40	-51.47	≤ -13.6	PASS


Test plot as follows:






Date: 16.APR 2025 20:41:09

DH5 Ant1 High Hop 2480




Date: 16.APR 2025 20:41:27

2DH5 Ant1 Low 2402




Date: 16.APR 2025 12:47:41

2DH5 Ant1 High 2480




Date: 16.APR 2025 12:49:39

2DH5_Ant1_Low_Hop_2402




Date: 16.APR 2025 12:58:29

2DH5_Ant1_High_Hop_2480




Date: 16.APR 2025 13:02:48

3DH5_Ant1_Low_2402




Date: 16.APR 2025 20:20:31

3DH5_Ant1_High_2480




Date: 16.APR 2025 20:23:09

3DH5_Ant1_Low_Hop_2402




Date: 16.APR 2025 20:24:13

3DH5_Ant1_High_Hop_2480



Date: 16.APR.2025 20:28:47

5.9 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Pass

DH5_Ant1_2402_0~Reference




Date: 16.APR.2025 12:43:34

DH5_Ant1_2402_30~1000




Date: 16.APR.2025 12:43:39

DH5_Ant1_2402_1000~26500




Date: 16.APR 2025 12:43:49

DH5_Ant1_2441_0~Reference




Date: 16.APR 2025 12:44:17

DH5_Ant1_2441_30~1000




Date: 16.APR 2025 12:44:22

DH5_Ant1_2441_1000~26500




Date: 16.APR 2025 12:44:32

DH5_Ant1_2480_0~Reference




Date: 16.APR 2025 12:46:57

DH5_Ant1_2480_30~1000




Date: 16.APR 2025 12:47:02

DH5_Ant1_2480_1000~26500




Date: 16.APR 2025 12:47:12

2DH5_Ant1_2402_0~Reference



Date: 16.APR 2025 12:48:05

2DH5_Ant1_2402_30~1000



Date: 16.APR 2025 12:48:10

2DH5_Ant1_2402_1000~26500