



SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V06

Report Template Revision Date: 2026-01-30



中国认可
国际互认
检测
TESTING
CNAS L5785

Test Report

Report No.: CQASZ20260100274E-02

Applicant: Ultimea Technology (Shenzhen) Limited

Address of Applicant: 20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China

Equipment Under Test (EUT):

Product: Soundbar

Model No.: U412C, U412A, U412B, U412D, U512P, U2524, U2525, U2526, U2527

Test Model No.: U412C

Brand Name: ULTIMEA

FCC ID: 2A900-U412CS

Standards: 47 CFR Part 15, Subpart C
KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2020

Date of Receipt: 2026-03-19

Date of Test: 2026-03-19 to 2026-05-20

Date of Issue: 2026-7-24

Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above.

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260100274E-02	Rev.01	Initial report	2026-7-24

Note:

Model No.: U412C, U412A, U412B, U412D, U512P, U2524, U2525, U2526, U2527

The U412C and U2524 are two different adapter models. Models U412C, U412A, U412B, U412D and U512P differ only in model designation. Similarly, models U2524, U2525, U2526 and U2527 are distinguished solely by their model numbers.

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 ADDITIONAL INSTRUCTIONS.....	8
4.4 TEST ENVIRONMENT	9
4.5 DESCRIPTION OF SUPPORT UNITS	9
4.6 TEST CONFIGURATION	9
4.7 STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	10
4.8 TEST LOCATION	11
4.9 TEST FACILITY	11
4.10 DEVIATION FROM STANDARDS	11
4.11 OTHER INFORMATION REQUESTED BY THE CUSTOMER	11
4.12 EQUIPMENT LIST	12
5 TEST RESULTS AND MEASUREMENT DATA	13
5.1 ANTENNA REQUIREMENT	13
5.2 CONDUCTED EMISSIONS	14
5.3 CONDUCTED PEAK OUTPUT POWER	24
5.4 6dB OCCUPY BANDWIDTH	30
5.5 POWER SPECTRAL DENSITY	34
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS	38
5.7 SPURIOUS RF CONDUCTED EMISSIONS.....	41
5.8 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	50
5.8.1 <i>Spurious Emissions</i>	50
6 PHOTOGRAPHS - EUT TEST SETUP	63
6.1 RADIATED SPURIOUS EMISSION	63
6.2 CONDUCTED EMISSIONS TEST SETUP	64
6.3 RF CONDUCTED MEASUREMENT	65
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	66

4 General Information

4.1 Client Information

Applicant:	Ultimea Technology (Shenzhen) Limited
Address of Applicant:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Manufacturer:	Ultimea Technology (Shenzhen) Limited
Address of Manufacturer:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Factory:	Zhong Shan City Richsound Electronic Industrial Ltd.
Address of Factory:	No 16, East ShaGang Road, GangKou Town, ZhongShan City, GuangDong, 528447, China

4.2 General Description of EUT

Product Name:	Soundbar
Model No.:	U412C, U412A, U412B, U412D, U512P, U2524, U2525, U2526, U2527
Test Model No.:	U412C
Trade Mark:	ULTIMEA
Software Version:	V31
Hardware Version:	V0.3
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V6.0
Modulation Type:	GFSK
Transfer Rate:	1Mbps, 2Mbps
Number of Channel:	40
Product Type:	☒ Mobile ☐ Portable ☐ Fix Location
Test Software of EUT:	FCC BT Tool V2.2.4
Antenna Type:	FPC antenna
Antenna Gain:	2.43dBi
Module Model:	ATS2853P2
Power Supply:	U412C Power supply DC18V form adapter GQ48-180300-AU Input:100-240~50/60Hz 1.5A Max Output:18.0V=3.0A Power supply DC18V form adapter FX48-180300-C INPUT:100-240~50/60Hz 1A Max OUTPUT:18.0V=3.0A
	U2524 Power supply DC18V form adapter

	GQ36-180200-AU Input:100-240~50/60Hz 1.0A Max Output:18.0V=2.0A
	U2524 Power supply DC18V form adapter FX36-180200C Input:100-240~50/60Hz 0.8A Output:18.0V=2.0A (36.0W)
Simultaneous Transmission	☒ Simultaneous TX is supported and evaluated in this report. ☐ Simultaneous TX is not supported.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

4.3 Additional Instructions

EUT Test Software Settings:		
Mode:	☒ Special software is used. ☐ Through engineering command into the engineering mode. engineering command: *##3646633#*#*	
EUT Power level:	Class4 (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
GFSK	CH0	2402
	CH19	2440
	CH39	2480

Run Software:



4.4 Test Environment

Operating Environment:	
Temperature:	24.5°C
Humidity:	59% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.


1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Test configuration



4.7 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty
1	Radiated Emission (Below 1GHz)	5.12dB
2	Radiated Emission (Above 1GHz)	4.60dB
3	Conducted Disturbance (0.15~30MHz)	3.34dB
4	Radio Frequency	3×10^{-8}
5	Duty cycle	0.6 %
6	Occupied Bandwidth	1.1%
7	RF conducted power	0.86dB
8	RF power density	0.74
9	Conducted Spurious emissions	0.86dB
10	Temperature test	0.8°C
11	Humidity test	2.0%
12	Supply voltages	0.5 %
13	Frequency Error	5.5 Hz

4.8 Test Location

All tests were performed at:

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community,
Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

4.9 Test Facility

- **A2LA (Certificate No. 4742.01)**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory is accredited by the

American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.10 Deviation from Standards

None.

4.11 Other Information Requested by the Customer

None.

4.12 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU26	CQA-038	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU40	CQA-075	2025/9/1	2026/8/31
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2025/9/1	2026/8/31
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2025/9/1	2026/8/31
Preamplifier	EMCI	EMC184055SE	CQA-089	2025/9/1	2026/8/31
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2025/9/1	2026/8/31
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2025/9/1	2026/8/31
Antenna Connector	CQA	RFC-01	CQA-080	2025/9/1	2026/8/31
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2025/9/1	2026/8/31
Power meter	R&S	NRVD	CQA-029	2025/9/1	2026/8/31
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2025/9/1	2026/8/31
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
LISN	R&S	ENV216	CQA-003	2025/9/1	2026/8/31
Coaxial cable	CQA	N/A	CQA-C009	2025/9/1	2026/8/31
DC power	KEYSIGHT	E3631A	CQA-028	2025/9/1	2026/8/31

Test software:


	Manufacturer	Software brand	Software version
Radiated Emissions test software	Tonscend	JS1120-3	Version:8
Conducted Emissions test software	Audix	e3	Version:9
RF Conducted test software	Audix	e3	V3.5.39

Note:

The temporary antenna connector is soldered on the pcb board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.


5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is FPC antenna. The connection/connection type between the antenna to the EUT's antenna port is: unique coupling. This is either permanently attachment or a unique coupling that satisfies the requirement.	

5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2020 on conducted measurement.		


Test Setup:	
Test Mode:	Through Pre-scan, find the transmitting mode at the lowest channel is the worst case.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

Measurement Data

U412C

1#

Live line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.345	9.92	9.55	19.47	49.08	-29.61	Average	Line
2	0.345	17.32	9.55	26.87	59.08	-32.21	QP	Line
3	0.515	8.89	9.72	18.61	46.00	-27.39	Average	Line
4	0.515	17.18	9.72	26.90	56.00	-29.10	QP	Line
5	0.795	8.77	9.84	18.61	46.00	-27.39	Average	Line
6	0.795	17.49	9.84	27.33	56.00	-28.67	QP	Line
7	0.965	9.26	9.72	18.98	46.00	-27.02	Average	Line
8	0.965	18.34	9.72	28.06	56.00	-27.94	QP	Line
9 PP	1.345	10.69	10.53	21.22	46.00	-24.78	Average	Line
10 QP	1.345	19.16	10.53	29.69	56.00	-26.31	QP	Line
11	1.650	7.25	11.10	18.35	46.00	-27.65	Average	Line
12	1.650	15.61	11.10	26.71	56.00	-29.29	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	AV	0.450	11.01	9.65	20.66	46.88	-26.22	Average	Neutral
2	PP	0.450	26.15	9.65	35.80	56.88	-21.08	QP	Neutral
3		0.475	9.14	9.68	18.82	46.43	-27.61	Average	Neutral
4		0.475	20.69	9.68	30.37	56.43	-26.06	QP	Neutral
5		0.770	8.53	9.85	18.38	46.00	-27.62	Average	Neutral
6		0.770	15.67	9.85	25.52	56.00	-30.48	QP	Neutral
7		0.975	9.00	9.72	18.72	46.00	-27.28	Average	Neutral
8		0.975	15.83	9.72	25.55	56.00	-30.45	QP	Neutral
9		1.175	9.66	9.71	19.37	46.00	-26.63	Average	Neutral
10		1.175	16.92	9.71	26.63	56.00	-29.37	QP	Neutral
11		1.345	9.91	9.72	19.63	46.00	-26.37	Average	Neutral
12		1.345	17.05	9.72	26.77	56.00	-29.23	QP	Neutral

Measurement Data

2#

Live line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.475	9.12	9.68	18.80	46.43	-27.63	Average	Line
2	0.475	17.44	9.68	27.12	56.43	-29.31	QP	Line
3	0.625	8.84	9.83	18.67	46.00	-27.33	Average	Line
4	0.625	17.33	9.83	27.16	56.00	-28.84	QP	Line
5	1.030	9.42	9.78	19.20	46.00	-26.80	Average	Line
6 QP	1.030	18.13	9.78	27.91	56.00	-28.09	QP	Line
7 PP	1.360	9.08	10.56	19.64	46.00	-26.36	Average	Line
8	1.360	17.29	10.56	27.85	56.00	-28.15	QP	Line
9	1.485	8.44	10.80	19.24	46.00	-26.76	Average	Line
10	1.485	16.46	10.80	27.26	56.00	-28.74	QP	Line
11	1.775	6.96	11.31	18.27	46.00	-27.73	Average	Line
12	1.775	14.96	11.31	26.27	56.00	-29.73	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	12.49	9.70	22.19	56.00	-33.81	Average	Neutral
2	0.150	24.82	9.70	34.52	66.00	-31.48	QP	Neutral
3	0.170	12.40	9.66	22.06	54.96	-32.90	Average	Neutral
4	0.170	22.16	9.66	31.82	64.96	-33.14	QP	Neutral
5	0.185	12.40	9.63	22.03	54.26	-32.23	Average	Neutral
6	0.185	24.15	9.63	33.78	64.26	-30.48	QP	Neutral
7	0.285	10.37	9.50	19.87	50.67	-30.80	Average	Neutral
8	0.285	17.38	9.50	26.88	60.67	-33.79	QP	Neutral
9	0.340	10.13	9.53	19.66	49.20	-29.54	Average	Neutral
10	0.340	17.16	9.53	26.69	59.20	-32.51	QP	Neutral
11 AV	0.445	11.07	9.65	20.72	46.97	-26.25	Average	Neutral
12 PP	0.445	24.13	9.65	33.78	56.97	-23.19	QP	Neutral

Remark:


1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Measurement Data

U2524

3#

Live line:




	Freq	Read		Limit	Over		
	MHz	Level	Factor	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.400	9.30	9.61	18.91	47.85	-28.94	Average
2	0.400	18.05	9.61	27.66	57.85	-30.19	QP
3	0.665	8.72	9.87	18.59	46.00	-27.41	Average
4	0.665	17.34	9.87	27.21	56.00	-28.79	QP
5	1.125	9.68	10.03	19.71	46.00	-26.29	Average
6	1.125	18.22	10.03	28.25	56.00	-27.75	QP
7 PP	1.230	10.24	10.28	20.52	46.00	-25.48	Average
8 QP	1.230	18.47	10.28	28.75	56.00	-27.25	QP
9	1.390	8.62	10.62	19.24	46.00	-26.76	Average
10	1.390	17.32	10.62	27.94	56.00	-28.06	QP
11	1.520	8.23	10.88	19.11	46.00	-26.89	Average
12	1.520	16.11	10.88	26.99	56.00	-29.01	QP

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	PP	0.445	10.16	9.65	19.81	46.97	-27.16	Average	Neutral
2		0.445	24.63	9.65	34.28	56.97	-22.69	QP	Neutral
3		0.470	9.36	9.67	19.03	46.51	-27.48	Average	Neutral
4		0.470	21.40	9.67	31.07	56.51	-25.44	QP	Neutral
5	AV	0.575	8.45	9.78	18.23	46.00	-27.77	Average	Neutral
6		0.575	15.58	9.78	25.36	56.00	-30.64	QP	Neutral
7		0.680	8.44	9.88	18.32	46.00	-27.68	Average	Neutral
8		0.680	15.50	9.88	25.38	56.00	-30.62	QP	Neutral
9		1.055	9.34	9.70	19.04	46.00	-26.96	Average	Neutral
10		1.055	15.85	9.70	25.55	56.00	-30.45	QP	Neutral
11		1.190	9.59	9.71	19.30	46.00	-26.70	Average	Neutral
12		1.190	16.35	9.71	26.06	56.00	-29.94	QP	Neutral

Measurement Data

4#

Live line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.270	10.71	9.52	20.23	51.12	-30.89	Average	Line
2	0.270	17.96	9.52	27.48	61.12	-33.64	QP	Line
3	1.035	9.80	9.79	19.59	46.00	-26.41	Average	Line
4	1.035	18.32	9.79	28.11	56.00	-27.89	QP	Line
5 PP	1.315	10.56	10.47	21.03	46.00	-24.97	Average	Line
6 QP	1.315	18.97	10.47	29.44	56.00	-26.56	QP	Line
7	1.450	8.37	10.74	19.11	46.00	-26.89	Average	Line
8	1.450	16.55	10.74	27.29	56.00	-28.71	QP	Line
9	1.550	8.24	10.93	19.17	46.00	-26.83	Average	Line
10	1.550	16.48	10.93	27.41	56.00	-28.59	QP	Line
11	1.795	6.41	11.34	17.75	46.00	-28.25	Average	Line
12	1.795	15.03	11.34	26.37	56.00	-29.63	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.170	12.73	9.66	22.39	54.96	-32.57	Average	Neutral
2	0.170	21.38	9.66	31.04	64.96	-33.92	QP	Neutral
3	0.240	10.72	9.55	20.27	52.10	-31.83	Average	Neutral
4	0.240	19.55	9.55	29.10	62.10	-33.00	QP	Neutral
5	0.360	9.41	9.56	18.97	48.73	-29.76	Average	Neutral
6	0.360	16.65	9.56	26.21	58.73	-32.52	QP	Neutral
7 AV	0.450	11.62	9.65	21.27	46.88	-25.61	Average	Neutral
8 PP	0.450	26.03	9.65	35.68	56.88	-21.20	QP	Neutral
9	0.830	8.87	9.81	18.68	46.00	-27.32	Average	Neutral
10	0.830	15.65	9.81	25.46	56.00	-30.54	QP	Neutral
11	1.295	10.09	9.71	19.80	46.00	-26.20	Average	Neutral
12	1.295	16.77	9.71	26.48	56.00	-29.52	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	30dBm
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

Operated Mode for Worst Duty Cycle:				
Test Mode	On time [Ton] (ms)	Period [Ttotal] (ms)	Duty Cycle(%)	Average correction factor(dB)
GFSK 1Mbps	2.16	2.50	86.40	0.63
GFSK 2Mbps	1.10	1.88	58.51	2.33

Remark:


- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;

Test Graph_GFSK 1Mbps Duty Cycle:



Date: 11 APR 2026 18:38:08

Test Graph_GFSK 2Mbps Duty Cycle:




Date: 11 APR 2026 18:41:26

Measurement Data


GFSK mode (1Mbps)			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	7.01	30.00	Pass
Middle	7.83	30.00	Pass
Highest	7.31	30.00	Pass
GFSK mode (2Mbps)			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	7.12	30.00	Pass
Middle	7.85	30.00	Pass
Highest	7.20	30.00	Pass

BLE 1M Ant1 2402




Date: 11.APR.2026 18:18:14

BLE 1M Ant1 2440




Date: 11.APR.2026 18:21:39

BLE 1M Ant1 2480




Date: 11.APR.2026 18:24:51

BLE 2M Ant1 2402




Date: 11.APR.2026 18:29:56

BLE 2M Ant1 2440




Date: 11.APR.2026 18:33:33

BLE 2M Ant1 2480



Date: 11 APR 2026 18:34:31


5.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	≥ 500 kHz
Instruments Used:	Refer to section 4.11 for details.
Test Results:	Pass

Measurement Data


GFSK mode (1Mbps)			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	0.67	≥500	Pass
Middle	0.68	≥500	Pass
Highest	0.70	≥500	Pass
GFSK mode (2Mbps)			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	1.14	≥500	Pass
Middle	1.14	≥500	Pass
Highest	1.16	≥500	Pass

BLE 1M Ant1 2402




Date: 11 APR 2026 18:18:03

BLE 1M Ant1 2440




Date: 11 APR 2026 18:21:29

BLE 1M Ant1 2480




Date: 11.APR.2026 18:24:41

BLE 2M Ant1 2402




Date: 11.APR.2026 18:29:45

BLE 2M Ant1 2440




Date: 11.APR.2026 18:33:23

BLE 2M Ant1 2480



Date: 11 APR 2026 18:34:21


5.5 Power Spectral Density


Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	≤8.00dBm/3kHz
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

Measurement Data

GFSK mode (1Mbps)			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-9.13	≤8.00	Pass
Middle	-8.26	≤8.00	Pass
Highest	-9.89	≤8.00	Pass
GFSK mode (2Mbps)			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-10.60	≤8.00	Pass
Middle	-9.94	≤8.00	Pass
Highest	-10.48	≤8.00	Pass


Test plot as follows:






Date: 11.APR.2026 18:24:56

BLE 2M Ant1 2402




Date: 11.APR.2026 18:30:01

BLE 2M Ant1 2440




Date: 11.APR.2026 18:33:38

BLE 2M Ant1 2480




Date: 11 APR 2026 18:34:37


5.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

TestMode	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Low	2402	6.59	-43.59	≤-13.41	PASS
	High	2480	6.78	-42.25	≤-13.22	PASS
BLE_2M	Low	2402	6.41	-27.97	≤-13.59	PASS
	High	2480	6.85	-41.92	≤-13.15	PASS


Test plot as follows:






Date: 11 APR 2026 18:30:06

BLE 2M Ant1 High 2480





Date: 11 APR 2026 18:34:43

5.7 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass


Test plot as follows:






Date: 11.APR.2026 18:20:56

BLE 1M Ant1 2440_0~Reference




Date: 11.APR.2026 18:21:48

BLE 1M Ant1 2440_30~1000




Date: 11.APR.2026 18:21:52

BLE 1M Ant1 2440 1000~26500




Date: 11.APR.2026 18:22:02

BLE 1M Ant1 2480 0~Reference




Date: 11.APR.2026 18:26:29

BLE 1M Ant1 2480 30~1000




Date: 11 APR 2026 18:26:33

BLE 1M Ant1 2480 1000~26500




Date: 11 APR 2026 18:26:44

BLE 2M Ant1 2402 0~Reference




Date: 11 APR 2026 18:32:22

BLE 2M Ant1 2402 30~1000




Date: 11.APR.2026 18:32:27

BLE 2M Ant1 2402 1000~26500




Date: 11.APR.2026 18:32:37

BLE 2M Ant1 2440 0~Reference




Date: 11.APR.2026 18:33:42

BLE 2M Ant1_2440 30~1000




Date: 11.APR.2026 18:33:46

BLE 2M Ant1_2440 1000~26500




Date: 11.APR.2026 18:33:57

BLE 2M Ant1 2480 0~Reference




Date: 11.APR.2026 18:36:09

BLE 2M Ant1 2480 30~1000



Date: 11.APR.2026 18:36:14

BLE 2M Ant1 2480 1000~26500






Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o), The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.8 Radiated Spurious Emission & Restricted bands

5.8.1 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					



Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both
-----------------	--

	horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with GFSK modulation. Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of data type and GFSK modulation is the worst case. For below 1GHz part, through pre-scan, the worst case is the highest channel. Only the worst case is recorded in the report.
Test Results:	Pass

Radiated Emission below 1GHz

U412C:


1#

30MHz~1GHz

Test mode:

Transmitting

Vertical



		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	32.41	21.43	8.51	29.94	40.00	-10.06	Peak	VERTICAL
2	53.32	18.63	12.74	31.37	40.00	-8.63	Peak	VERTICAL
3	382.59	12.76	17.96	30.72	46.00	-15.28	Peak	VERTICAL
4	605.66	13.96	22.36	36.32	46.00	-9.68	Peak	VERTICAL
5	810.27	10.38	26.76	37.14	46.00	-8.86	Peak	VERTICAL
6 pp	952.09	9.60	28.00	37.60	46.00	-8.40	Peak	VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,


Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	59.44	14.61	12.16	26.77	40.00	-13.23	Peak	HORIZONTAL
2	236.64	20.43	14.87	35.30	46.00	-10.70	Peak	HORIZONTAL
3	254.73	20.61	15.82	36.43	46.00	-9.57	Peak	HORIZONTAL
4	285.98	21.84	16.55	38.39	46.00	-7.61	Peak	HORIZONTAL
5	593.05	17.02	22.13	39.15	46.00	-6.85	Peak	HORIZONTAL
6 pp	810.27	12.57	26.76	39.33	46.00	-6.67	Peak	HORIZONTAL

2#: 30MHz~1GHz		
Test mode:	Transmitting	Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	30.21	26.23	8.15	34.38	40.00	-5.62	Peak	VERTICAL
2	32.41	25.43	8.51	33.94	40.00	-6.06	Peak	VERTICAL
3 pp	58.20	23.53	12.35	35.88	40.00	-4.12	Peak	VERTICAL
4	562.66	14.82	21.91	36.73	46.00	-9.27	Peak	VERTICAL
5	687.15	13.74	23.36	37.10	46.00	-8.90	Peak	VERTICAL
6	857.02	9.15	28.57	37.72	46.00	-8.28	Peak	VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	230.10	19.78	14.17	33.95	46.00	-12.05	Peak	HORIZONTAL
2	261.06	19.06	15.97	35.03	46.00	-10.97	Peak	HORIZONTAL
3	292.06	18.52	16.69	35.21	46.00	-10.79	Peak	HORIZONTAL
4	631.69	16.35	22.63	38.98	46.00	-7.02	Peak	HORIZONTAL
5 pp	704.23	16.42	23.80	40.22	46.00	-5.78	Peak	HORIZONTAL
6	851.04	11.04	28.47	39.51	46.00	-6.49	Peak	HORIZONTAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

U2524		
3#:		
30MHz~1GHz		
Test mode:	Transmitting	Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	33.92	25.53	8.75	34.28	40.00	-5.72	Peak	VERTICAL
2 pp	58.82	22.38	12.26	34.64	40.00	-5.36	Peak	VERTICAL
3	292.06	13.54	16.69	30.23	46.00	-15.77	Peak	VERTICAL
4	355.43	13.09	18.28	31.37	46.00	-14.63	Peak	VERTICAL
5	580.70	13.71	21.84	35.55	46.00	-10.45	Peak	VERTICAL
6	687.15	15.74	23.36	39.10	46.00	-6.90	Peak	VERTICAL


Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.



Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.


4#:

30MHz~1GHz

Test mode:

Transmitting

Vertical



		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	pp	33.33	23.86	8.65	32.51	40.00	-7.49 Peak	VERTICAL
2		53.32	17.63	12.74	30.37	40.00	-9.63 Peak	VERTICAL
3		199.29	11.19	12.25	23.44	43.50	-20.06 Peak	VERTICAL
4		387.99	14.47	18.09	32.56	46.00	-13.44 Peak	VERTICAL
5		699.30	13.10	23.74	36.84	46.00	-9.16 Peak	VERTICAL
6		993.01	8.63	28.26	36.89	54.00	-17.11 Peak	VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Read		Limit	Over			
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	56.39	12.78	12.62	25.40	40.00	-14.60 Peak	HORIZONTAL
2	107.51	14.90	11.85	26.75	43.50	-16.75 Peak	HORIZONTAL
3	254.73	18.61	15.82	34.43	46.00	-11.57 Peak	HORIZONTAL
4	285.98	18.84	16.55	35.39	46.00	-10.61 Peak	HORIZONTAL
5	562.66	16.45	21.91	38.36	46.00	-7.64 Peak	HORIZONTAL
6 pp	810.27	14.57	26.76	41.33	46.00	-4.67 Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Transmitter Emission above 1GHz

Worse case mode:		GFSK(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390	55.53	-9.2	46.33	74	-27.67	Peak	H	1.5	250
2400	56.74	-9.39	47.35	74	-26.65	Peak	H	1.5	138
4804	51.25	-4.33	46.92	74	-27.08	Peak	H	1.5	37
7206	50.54	1.01	51.55	74	-22.45	Peak	H	1.5	139
2390	56.14	-9.2	46.94	74	-27.06	Peak	V	1.5	243
2400	54.48	-9.39	45.09	74	-28.91	Peak	V	1.5	145
4804	53.88	-4.33	49.55	74	-24.45	Peak	V	1.5	307
7206	50.18	1.01	51.19	74	-22.81	Peak	V	1.5	225

Worse case mode:		GFSK(1Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4880	52.04	-4.11	47.93	74	-26.07	peak	H	1.5	67
7320	48.52	1.51	50.03	74	-23.97	peak	H	1.5	49
4880	51.70	-4.11	47.59	74	-26.41	peak	V	1.5	61
7320	48.90	1.51	50.41	74	-23.59	peak	V	1.5	109

Worse case mode:		GFSK(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2483.5	57.16	-9.29	47.87	74	-26.13	Peak	H	1.5	157
4960	51.49	-4.04	47.45	74	-26.55	Peak	H	1.5	143
7440	49.35	1.57	50.92	74	-23.08	Peak	H	1.5	118
2483.5	54.98	-9.29	45.69	74	-28.31	Peak	V	1.5	216
4960	50.95	-4.04	46.91	74	-27.09	Peak	V	1.5	292
7440	48.89	1.57	50.46	74	-23.54	Peak	V	1.5	340

Worse case mode:		GFSK(2Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390	53.94	-9.2	44.74	74	-29.26	Peak	H	1.5	327
2400	55.38	-9.39	45.99	74	-28.01	Peak	H	1.5	331
4804	52.93	-4.33	48.60	74	-25.40	Peak	H	1.5	305
7206	48.39	1.01	49.40	74	-24.60	Peak	H	1.5	172
2390	55.55	-9.2	46.35	74	-27.65	Peak	V	1.5	221
2400	56.49	-9.39	47.10	74	-26.90	Peak	V	1.5	148
4804	54.17	-4.33	49.84	74	-24.16	Peak	V	1.5	343
7206	50.37	1.01	51.38	74	-22.62	Peak	V	1.5	290

Worse case mode:		GFSK(2Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4880	50.54	-4.11	46.43	74	-27.57	peak	H	1.5	347
7320	51.22	1.51	52.73	74	-21.27	peak	H	1.5	60
4880	53.01	-4.11	48.90	74	-25.10	peak	V	1.5	180
7320	49.98	1.51	51.49	74	-22.51	peak	V	1.5	225

Worse case mode:		GFSK(2Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2483.5	54.97	-9.29	45.68	74	-28.32	Peak	H	1.5	353
4960	51.14	-4.04	47.10	74	-26.90	Peak	H	1.5	348
7440	50.67	1.57	52.24	74	-21.76	Peak	H	1.5	290
2483.5	53.25	-9.29	43.96	74	-30.04	Peak	V	1.5	125
4960	50.94	-4.04	46.90	74	-27.10	Peak	V	1.5	352
7440	49.88	1.57	51.45	74	-22.55	Peak	V	1.5	94


Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.


6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emissions Test Setup



6.3 RF Conducted measurement



7 Photographs - EUT Constructional Details

Refer to PHOTOGRAPHS OF EUT for CQASZ20260100274E-01.

*** END OF REPORT **