



Shenzhen Huaxia Testing Technology Co., Ltd.

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD 102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20260100288E-05
Applicant: Ultimea Technology (Shenzhen) Limited
Address of Applicant: 20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Soundbar
Model No.: U622A, U622C, U622D, U622B, U622E, U622F
Test Model No.: U622A
Brand Name: ULTIMEA
FCC ID: 2A9OO-U622AS
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2026-01-30
Date of Test: 2026-01-30 to 2026-03-13
Date of Issue: 2026-4-27
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260100288E-05	Rev.01	Initial report	2026-4-27

Model No.: U622A, U622C, U622D, U622B, U622E, U622F

Their electrical circuit design, layout, components used and internal wiring are identical,

Only the number of subwoofers and AC power cords is different, and the built-in power boards of subwoofers are also different.

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	5
3.4 GENERAL DESCRIPTION OF BLE	5
3.5 GENERAL DESCRIPTION OF 5.8G SRD ANT 0	6
3.6 GENERAL DESCRIPTION OF 5.8G SRD ANT 1	6
4 MPE EVALUATION	7
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
4.1.1 Limits	7
4.1.2 Test Procedure	7
4.1.3 EUT RF Exposure	8

3 General Information

3.1 Client Information

Applicant:	Ultimea Technology (Shenzhen) Limited
Address of Applicant:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Manufacturer:	Ultimea Technology (Shenzhen) Limited
Address of Manufacturer:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Factory:	Zhuhai Fenda Technology Co., Ltd.
Address of Factory:	3/F Building 3, 3/F Building 4, Building 5, 629 Damen Road, Sanzao Town, Jinwan District, Zhuhai City)

3.2 General Description of EUT

Product Name:	Soundbar
Model No.:	U622A, U622C, U622D, U622B, U622E, U622F
Test Model No.:	U622A
Trade Mark:	ULTIMEA
Software Version:	V1.0
Hardware Version:	U622A-MF
EUT Power Supply:	Model:FX96W-180500D1 Input:100-240V~50/60Hz 1.5A Max Output:18V=5A

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.4
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	PCB antenna
Antenna Gain:	1.62dBi

3.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.4
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☒ Mobile ☐ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	1.85dBi

3.5 General Description of 5.8G SRD Ant 0

Operation Frequency:	5725Mhz-5850Mhz
Type of Modulation:	GFSK
Number of Channel:	118 channel
Channel Separation:	5MHz
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna
Antenna Gain:	5dBi

3.6 General Description of 5.8G SRD Ant 1

Operation Frequency:	5725Mhz-5850Mhz
Type of Modulation:	GFSK
Number of Channel:	118 channel
Channel Separation:	1MHz
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna
Antenna Gain:	6.5dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BLE

Antenna Gain: 1.85dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.53 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	9.90	10.0 ± 1	11	12.59
Middle(2440MHz)	10.57	10.5 ± 1	11.5	14.13
Highest(2480MHz)	10.01	10.0 ± 1	11	12.59

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
14.13	1.53	0.004302582	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100288E-02 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (14.13 * 1.53) / (4 * 3.1416 * 20^2) = 0.004302582$

2) For BT

Antenna Gain: 1.62dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.45 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

$\pi/4$ DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	9.86	10.0 ± 1	11.0	12.59
Middle(2440MHz)	10.76	11.0 ± 1	12.0	15.85
Highest(2480MHz)	10.05	10.0 ± 1	11.0	12.59

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
15.85	1.45	0.004578562	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100288E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (15.85 * 1.45) / (4 * 3.1416 * 20^2) = 0.004578562$

3) For 5.8G SRD Ant 0

Output Power Into Antenna & RF Exposure Evaluation Distance:

$\text{dBm} = [20 \cdot \log(3)] - 104.7 + \text{dB } \mu\text{V/m}$

Measurement Data

5.8G SRD mode				
Test channel	Eirp (dB μ V/m)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(5730MHz)	95.5	0.5 $\pm$ 1	1.5	1.41
Middle(5790MHz)	95.91	1.0 $\pm$ 1	2	1.58
Highest(5848MHz)	94.68	0 $\pm$ 1	1	1.26

The worst case:

Maximum tune-up Power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
1.58	0.000622436	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100288E-03 for EUT test Max Conducted Output Power value.

2) $\text{Pd} = (\text{Pout} \cdot \text{G}) / (4 \cdot \text{Pi} \cdot \text{R}^2) = (1.58) / (4 \cdot 3.1416 \cdot 20^2) = 0.000622436$

4) For 5.8G SRD Ant 1

Output Power Into Antenna & RF Exposure Evaluation Distance:

$\text{dBm} = [20 \cdot \log(3)] - 104.7 + \text{dB } \mu\text{V/m}$

Measurement Data

5.8G SRD mode				
Test channel	Eirp (dB μ V/m)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(5730MHz)	95.02	0 $\pm$ 1	1	1.26
Middle(5790MHz)	95.26	1.0 $\pm$ 1	2	1.58
Highest(5848MHz)	96.05	1.0 $\pm$ 1	2	1.58

The worst case:

Maximum tune-up Power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
1.58	0.000622436	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100288E-04 for EUT test Max Conducted Output Power value.

2) $P_d = (P_{\text{out}} \cdot G) / (4 \cdot \pi \cdot R^2) = (1.58) / (4 \cdot 3.1416 \cdot 20^2) = 0.000622436$

Simultaneous transmission:

MPE ratios(BT)+MPE ratios(BLE)+MPE ratios(5.8G SRD Ant 0)

$= 0.004302582/1 + 0.004578562/1 + 0.000622436/1$

$= 0.00950358 \leq 1$

*** END OF REPORT ***