



Shenzhen Huaxia Testing Technology Co., Ltd.

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD 102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03



中国认可
国际互认
检测
TESTING
CNAS L5785

RF Exposure Evaluation Report

Report No.: CQASZ20260500916E-06
Applicant: Ultimea Technology (Shenzhen) Limited
Address of Applicant: 20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Soundbar
Model No.: UC001
Test Model No.: UC001
Brand Name: ULTIMEA
FCC ID: 2A9OO-UC001S
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2026-05-07
Date of Test: 2026-05-07 to 2026-06-04
Date of Issue: 2026-06-18
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260500916E-06	Rev.01	Initial report	2026-06-18

1 Contents

	Page
VERSION	2
1 CONTENTS	3
.....	3
2 GENERAL INFORMATION	4
2.1 CLIENT INFORMATION	4
2.2 GENERAL DESCRIPTION OF EUT	4
2.3 GENERAL DESCRIPTION OF BT CLASSIC	5
2.4 GENERAL DESCRIPTION OF BLE	5
2.5 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
2.6 GENERAL DESCRIPTION OF 5G WIFI CLASSIC	6
2.7 GENERAL DESCRIPTION OF BLE	6
3 MPE EVALUATION	7
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
3.1.1 Limits	7
3.1.2 Test Procedure	7
3.1.3 EUT RF Exposure	8

2 General Information

2.1 Client Information

Applicant:	Ultimea Technology (Shenzhen) Limited
Address of Applicant:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Manufacturer:	Ultimea Technology (Shenzhen) Limited
Address of Manufacturer:	20th Floor, Building 4, Tianan Cloud Park, Bantian St., Longgang District, Shenzhen, China
Factory:	SHENZHEN SOUNDJOYFUL TECHNOLOGY CO., LTD
Address of Factory:	Room 905A, Lingyun Building, Xin'an Street, Bao'an, Shenzhen

2.2 General Description of EUT

Product Name:	Soundbar
Model No.:	UC001
Test Model No.:	UC001
Trade Mark:	ULTIMEA
Software Version:	V023
Hardware Version:	V03
EUT Power Supply:	Power by adapter:GQ36-180200-AU Input:100-240V~50/60Hz 1.0A Max Output:18.0V $\overline{\rule{0.5em}{0.4pt}}$ 2.0A 36.0W

2.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.2
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Module model:	RTL8730ELH
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	ANT1:FPC antenna ANT2:PIFA antenna
Antenna Gain:	ANT1:2.87dBi ANT2:1.86dBi

2.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.2
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Module model:	RTL8730ELH
Sample Type:	☒ Mobile ☐ Portable ☐ Fix Location
Antenna Type:	ANT1:FPC antenna ANT2:PIFA antenna
Antenna Gain:	ANT1:2.87dBi ANT2:1.86dBi

2.5 General Description of 2.4G WIFI Classic

Operation Frequency:	IEEE 802.11b/g/n(HT20)/ax(HE20): 2412MHz to 2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11ax(HE20): OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20/ax HE20: 11 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps

	IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11ax(HE20) : 8.6M/17.2M/25.8M/34.4M/51.6M/68.8M/77.4M/86M/103.2M/114.7M/129M/ 143.4Mbps
Module model:	RTL8730ELH
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	ANT1:FPC antenna ANT2:PIFA antenna
Antenna Gain:	ANT1:2.87dBi ANT2:1.86dBi

2.6 General Description of 5G WIFI Classic

Operation Frequency:	IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850 MHz
Channel Numbers:	IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850MHz/ 5 channel
Type of Modulation:	IEEE for 802.11a/n/ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11ax: OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Module model:	RTL8730ELH
Sample Type:	☒ Mobile ☐ Portable
Test Software of EUT:	Serial
Antenna Type:	ANT1:FPC antenna ANT2:PIFA antenna
Antenna gain:	ANT1:3.23dBi ANT2:0.22dBi
Cable loss:	1.0 dB

2.7 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.2
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Module model:	BT8961B6
Sample Type:	☒ Mobile ☐ Portable ☐ Fix Location
Antenna Type:	FPC antenna
Antenna Gain:	2.97dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

3 MPE Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure

1) For BLE(RTL8730ELH)

Antenna Gain: 2.87dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.94 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	4.00	4.5±1	5.5	3.55
Middle(2440MHz)	3.86	4.0±1	5	3.16
Highest(2480MHz)	3.76	4.0±1	5	3.16

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
3.55	2.87	0.0013668760	1.0	PASS

Note: 1) Refer to report No. CQASZ20260500916E-02 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (3.55 \cdot 2.87) / (4 \cdot 3.1416 \cdot 20^2) = 0.0013668760$

2) For BT(RTL8730ELH)

Antenna Gain: 2.87dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.94 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	6.29	6.5±1	7.5	5.62
Middle(2440MHz)	6.18	6.5±1	7.5	5.62
Highest(2480MHz)	6.31	6.5±1	7.5	5.62

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
5.62	2.87	0.0021663525	1.0	PASS

Note: 1) Refer to report No. CQASZ20260500916E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (5.62 * 1.94) / (4 * 3.1416 * 20^2) = 0.0021663525$

3) For 2.4G WIFI(RTL8730ELH)

Antenna Gain: 2.87dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.94 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

11AX mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	21.86	22.0±1	23	199.53
Middle(2437MHz)	22.14	22.5±1	23.5	223.87
Highest(2462MHz)	21.81	22.0±1	23	199.53

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
223.87	2.87	0.0862440473	1.0	PASS

Note: 1) Refer to report No. CQASZ20260500916E-03 for EUT test Max Conducted AV Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (223.87 * 1.94) / (4 * 3.1416 * 20^2) = 0.0862440473$

4) For 5G WIFI Classic(RTL8730ELH)

Antenna Gain: 3.23dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

11AX mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(5260MHz)	5.68	6.0±1	7.0	5.01
Middle(5280MHz)	5.83	6.0±1	7.0	5.01
Highest(5320MHz)	5.98	6.0±1	7.0	5.01

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
5.01	3.23	0.0020976312	1.0	PASS

Note: 1) Refer to report No. CQASZ20250100185E-04 for EUT test Max Conducted AV Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (5.01 * 2.1) / (4 * 3.1416 * 20^2) = 0.0020976312$

5) For BLE(BT8961B6)

Antenna Gain: 2.97dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.98 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.60	2.0±1	3.0	2.00
Middle(2440MHz)	2.24	2.5±1	3.5	2.24
Highest(2480MHz)	1.58	2.0±1	3.0	2.00

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
2.24	2.97	0.0008825293	1.0	PASS

Note: 1) Refer to report No. CQASZ20260500916E-02 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (2.24 \cdot 1.98) / (4 \cdot 3.1416 \cdot 20^2) = 0.0008825293$

Simultaneous transmission:

MPE ratios(BLE)(BT8961B6)+MPE ratios(2.4G WIFI)(RTL8730ELH)

=0.0008825293/1+0.0862440473/1

=0.087126577 ≤ 1

*** END OF REPORT ***