

FCC RF Exposure

EUT Description: Aroma Diffuser

Model No.: Nevo Scent Diffuser, Decor Collection

FCC ID: 2A9PA-NEVO

Equipment type: mobile device

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (P_{out} * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW; **G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**Test Result of RF Exposure Evaluation****BLE**

Test Model	Conductedpower (dBm)	Max tune-up (mW)	Antenna Gain (dBi)	Min.distance (cm)	Result	Limit
Lowest	0.67	1.1668	-1.08	20	0.0001810	1
Middle	0.78	1.1967	-1.08	20	0.0001857	1
Highest	1.21	1.3213	-1.08	20	0.0002050	1

Conclusion: the max result :0.0002050≤ 1.0 compliance with FCC's RF Exposure.

2.4Gwifi

Test Model	Conductedpower (dBm)	Max tune-up (mW)	Antenna Gain (dBi)	Min.distance (cm)	Result	Limit
802.11b 2412MHz	4.16	2.6062	-1.08	20	0.000404324	1
802.11b 2437MHz	4.26	2.6669	-1.08	20	0.000413742	1
802.11b 2462MHz	4.24	2.6546	-1.08	20	0.000411841	1
802.11g 2412MHz	4.08	2.5586	-1.08	20	0.000396944	1
802.11g 2437MHz	4.95	3.1261	-1.08	20	0.000484986	1
802.11g 2462MHz	4.21	2.6363	-1.08	20	0.000409005	1
802.11n 20 2412MHz	4.08	2.5586	-1.08	20	0.000396944	1
802.11n 20 2437MHz	4.97	3.1405	-1.08	20	0.000487225	1
802.11n 20 2462MHz	4.19	2.6242	-1.08	20	0.000407126	1

Conclusion: the max result :0.000487225≤ 1.0 compliance with FCC's RF Exposure.