

TEST REPORT

Reference No...... : WTH24X07156134W001
FCC ID..... : 2A9QB-KLYDE-1174
Applicant..... : SHENZHEN KLYDE ELECTRONICS CO.,LTD.
Address..... : Building C & D, Zunlong Science Park, Xieping Road, Wulian Village,
Longgang Dist., Shenzhen City, China
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Car Multimedia Player
Model No...... : KD-1174
Standards..... : FCC Part 15.407
Date of Receipt sample..... : 2024-07-03
Date of Test..... : 2024-07-03 to 2024-07-22
Date of Issue..... : 2024-07-22
Test Report Form No...... : WTX_Part 15_407W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen

Approved by:



Jason Su

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	6
1.5 EUT OPERATING DURING TEST	7
1.6 TEST FACILITY	7
1.7 EUT SETUP AND TEST MODE	8
1.8 MEASUREMENT UNCERTAINTY	9
1.9 TEST EQUIPMENT LIST AND DETAILS	10
2. SUMMARY OF TEST RESULTS	13
3. ANTENNA REQUIREMENT	14
3.1 STANDARD APPLICABLE	14
3.2 EVALUATION INFORMATION	14
4. AUTOMATICALLY DISCONTINUE TRANSMISSION	15
4.1 STANDARD APPLICABLE	15
4.2 SUMMARY OF TEST RESULTS	15
5. POWER SPECTRAL DENSITY	16
5.1 STANDARD APPLICABLE	16
5.2 TEST PROCEDURE	16
5.3 SUMMARY OF TEST RESULTS/PLOTS	17
6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	18
6.1 STANDARD APPLICABLE	18
6.2 TEST PROCEDURE	18
6.3 SUMMARY OF TEST RESULTS/PLOTS	20
7. MAXIMUM CONDUCTED OUTPUT POWER	21
7.1 STANDARD APPLICABLE	21
7.2 TEST PROCEDURE	21
7.3 SUMMARY OF TEST RESULTS/PLOTS	22
8. RADIATED SPURIOUS EMISSIONS	23
8.1 STANDARD APPLICABLE	23
8.2 TEST PROCEDURE	23
8.3 TEST RECEIVER SETUP	25
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	25
8.5 SUMMARY OF TEST RESULTS/PLOTS	25
9. FREQUENCY STABILITY	38
9.1 STANDARD APPLICABLE	38
9.2 TEST PROCEDURE	38
9.3 SUMMARY OF TEST RESULTS/PLOTS	38
10. CONDUCTED EMISSIONS	39
10.1 TEST PROCEDURE	39
10.2 BASIC TEST SETUP BLOCK DIAGRAM	39
10.3 TEST RECEIVER SETUP	39
10.4 SUMMARY OF TEST RESULTS/PLOTS	39
APPENDIX SUMMARY	40
APPENDIX A	41
APPENDIX B	45
APPENDIX C	52
APPENDIX D	56

APPENDIX PHOTOGRAPHS 57

Report version

Version No.	Date of issue	Description
Rev.00	2024-07-22	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Car Multimedia Player
Trade Name:	/
Model No.:	KD-1174
Adding Model(s):	/
Rated Voltage:	DC12V
Battery Capacity:	/
Power Adapter:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ac-VHT80
Frequency Range:	5745-5825MHz
Max. RF Output Power:	12.44dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM
Type of Antenna:	Integral Antenna
Antenna Gain:	2.35dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.407: General technical requirements.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

KDB789033 D02 v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB789033 D02 v02r01. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Table for parameters of Test Software setting

Use "SecureCRT.exe" software to set the frequency by firing instructions, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)											
	NCB: 20MHz											
	574 5	578 5	582 5									
802.11a 6Mbps	100	100	100									
802.11n-HT20 MCS0	70	70	70									
Mode	NCB: 40MHz											
	5755	5795										
802.11n-HT40 MCS0	55	55										
Mode	NCB: 80MHz											
	5775											
802.11ac-VHT8 0 MCS0	55											

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

1.6 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5745MHz, 5785MHz, 5825MHz
TM2	802.11n-HT20	5745MHz, 5785MHz, 5825MHz
TM3	802.11n-HT40	5755MHz, 5795MHz
TM4	802.11ac-VHT80	5775MHz
Note: 802.11ac-VHT20, 802.11ac-VHT40 covered by 802.11n-HT20 and 802.11n-HT40.		

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	0.6	Unshielded	With Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.9 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2024-02-24	2025-02-23
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2024-03-19	2025-03-18
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2024-02-24	2025-02-23
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2024-02-27	2025-02-26
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2024-02-24	2025-02-23

WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
☒ Chamber C: Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2024-02-27	2025-02-26
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2023-12-12	2024-12-11
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2024-02-24	2025-02-23

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 1#)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 2#)*	SKET	EMC-I	V2.0

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	N/A
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

4. Automatically Discontinue Transmission

4.1 Standard Applicable

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

4.2 Summary of Test Results

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5. Power Spectral Density

5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11 \text{ dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500kHz, "provided that the measured power is integrated over the full

reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth ($< 1\text{MHz}$, or $< 500\text{kHz}$) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $\text{VBW} \geq 3 \text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500\text{kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 1\text{MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since $\text{RBW}=100\text{kHz}$ is available on nearly all spectrum analyzers.

5.3 Summary of Test Results/Plots

Please refer to Appendix A

6. Emission Bandwidth and Occupied Bandwidth

6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

a) Set RBW = approximately 1% of the emission bandwidth.

b) Set the VBW > RBW.

- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85GHz Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

- 1. Set center frequency to the nominal EUT channel center frequency.
- 2. Set span = 1.5 times to 5.0 times the OBW.
- 3. Set RBW = 1 % to 5 % of the OBW
- 4. Set VBW $\geq 3 \times$ RBW
- 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- 6. Use the 99 % power bandwidth function of the instrument (if available).
- 7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

Reference No.: WTH24X07156134W001

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 Summary of Test Results/Plots

Please refer to Appendix B

7. Maximum Conducted Output Power

7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1MHz.
- (iii) Set VBW $\geq$ 3MHz.
- (iv) Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

7.3 Summary of Test Results/Plots

Please refer to Appendix C

8. Radiated Spurious Emissions

8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85GHz band:
 - (i) All emissions shall be limited to a level of -27dBm/MHz at 75MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E \cdot d)^2) / 30$$

where:


- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

8.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emission From 30MHz to 1GHz
- 5725-5850MHz

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	43.13	-8.69	34.44	40.00	-5.56	-	-	peak
2	86.0796	46.69	-12.53	34.16	40.00	-5.84	-	-	peak
3	110.8581	47.61	-10.98	36.63	43.50	-6.87	-	-	peak
4	183.8660	47.95	-10.16	37.79	43.50	-5.71	-	-	peak
5	208.6580	50.12	-11.58	38.54	43.50	-4.96	-	-	peak
6	368.6682	48.18	-6.71	41.47	46.00	-4.53	-	-	peak

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	36.00	-8.69	27.31	40.00	-12.69	-	-	peak
2	86.0796	46.67	-12.53	34.14	40.00	-5.86	-	-	peak
3	110.8581	40.08	-10.98	29.10	43.50	-14.40	-	-	peak
4	208.6580	49.75	-11.58	38.17	43.50	-5.33	-	-	peak
5	505.7891	45.71	-4.68	41.03	46.00	-4.97	-	-	peak
6	708.6941	41.66	-0.88	40.78	46.00	-5.22	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	40.49	-8.69	31.80	40.00	-8.20	-	-	peak
2	86.0796	46.74	-12.53	34.21	40.00	-5.79	-	-	peak
3	110.8581	47.60	-10.98	36.62	43.50	-6.88	-	-	peak
4	183.8660	47.84	-10.16	37.68	43.50	-5.82	-	-	peak
5	208.6580	49.90	-11.58	38.32	43.50	-5.18	-	-	peak
6	355.9397	48.14	-6.95	41.19	46.00	-4.81	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	36.82	-8.69	28.13	40.00	-11.87	-	-	peak
2	86.0796	46.85	-12.53	34.32	40.00	-5.68	-	-	peak
3	110.8581	40.61	-10.98	29.63	43.50	-13.87	-	-	peak
4	208.6580	49.30	-11.58	37.72	43.50	-5.78	-	-	peak
5	505.7891	45.73	-4.68	41.05	46.00	-4.95	-	-	peak
6	781.9606	38.43	0.70	39.13	46.00	-6.87	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	40.64	-8.69	31.95	40.00	-8.05	-	-	peak
2	86.0796	46.61	-12.53	34.08	40.00	-5.92	-	-	peak
3	110.8581	47.58	-10.98	36.60	43.50	-6.90	-	-	peak
4	183.8660	47.96	-10.16	37.80	43.50	-5.70	-	-	peak
5	208.6580	50.28	-11.58	38.70	43.50	-4.80	-	-	peak
6	368.6682	47.81	-6.71	41.10	46.00	-4.90	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	43.53	-8.69	34.84	40.00	-5.16	-	-	peak
2	86.0796	47.27	-12.53	34.74	40.00	-5.26	-	-	peak
3	110.8581	43.78	-10.98	32.80	43.50	-10.70	-	-	peak
4	208.6580	48.94	-11.58	37.36	43.50	-6.14	-	-	peak
5	498.7303	46.97	-4.81	42.16	46.00	-3.84	-	-	peak
6	578.0359	44.51	-2.78	41.73	46.00	-4.27	-	-	peak

802.11ac-HT80			
Test Channel	5775MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	41.73	-8.69	33.04	40.00	-6.96	-	-	peak
2	86.0796	46.69	-12.53	34.16	40.00	-5.84	-	-	peak
3	110.8581	47.46	-10.98	36.48	43.50	-7.02	-	-	peak
4	183.8660	47.87	-10.16	37.71	43.50	-5.79	-	-	peak
5	208.6580	49.88	-11.58	38.30	43.50	-5.20	-	-	peak
6	368.6682	47.99	-6.71	41.28	46.00	-4.72	-	-	peak


802.11ac-HT80

Test Channel

5775MHz(worst case)

Polarity:

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	61.4343	36.45	-8.69	27.76	40.00	-12.24	-	-	peak
2	86.0796	46.61	-12.53	34.08	40.00	-5.92	-	-	peak
3	110.8581	40.40	-10.98	29.42	43.50	-14.08	-	-	peak
4	208.6580	48.80	-11.58	37.22	43.50	-6.28	-	-	peak
5	427.2920	44.14	-5.68	38.46	46.00	-7.54	-	-	peak
6	505.7891	45.82	-4.68	41.14	46.00	-4.86	-	-	peak

Remark: '-' Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- For the frequency band 5.725-5.850GHz (802.11a)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	55.35	9.45	64.80	74	-9.20	H	PK
11490	38.25	9.45	47.70	54	-6.30	H	AV
11490	57.21	9.45	66.66	74	-7.34	V	PK
11490	38.38	9.45	47.83	54	-6.17	V	AV
Middle Channel (5785MHz)							
11570	58.04	9.62	67.66	74	-6.34	H	PK
11570	39.58	9.62	49.20	54	-4.80	H	AV
11570	55.28	9.62	64.90	74	-9.10	V	PK
11570	40.48	9.62	50.10	54	-3.90	V	AV
High Channel (5825MHz)							
11650	55.77	9.84	65.61	74	-8.39	H	PK
11650	38.53	9.84	48.37	54	-5.63	H	AV
11650	55.95	9.84	65.79	74	-8.21	V	PK
11650	40.08	9.84	49.92	54	-4.08	V	AV

- Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5715	-35.75	-27
	5715 to 5725	-36.32	-17
Highest	5850 to 5860	-27.59	-17
	Above 5860	-29.16	-27

Note: the data just list the worst cases

- For the frequency band 5.725-5.850GHz (802.11n HT20)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	57.45	9.45	66.90	74	-7.10	H	PK
11490	40.27	9.45	49.72	54	-4.28	H	AV
11490	56.32	9.45	65.77	74	-8.23	V	PK
11490	39.42	9.45	48.87	54	-5.13	V	AV
Middle Channel (5785MHz)							
11570	56.80	9.62	66.42	74	-7.58	H	PK
11570	41.81	9.62	51.43	54	-2.57	H	AV
11570	56.54	9.62	66.16	74	-7.84	V	PK
11570	40.05	9.62	49.67	54	-4.33	V	AV
High Channel (5825MHz)							
11650	58.45	9.84	68.29	74	-5.71	H	PK
11650	41.80	9.84	51.64	54	-2.36	H	AV
11650	55.67	9.84	65.51	74	-8.49	V	PK
11650	39.12	9.84	48.96	54	-5.04	V	AV

- Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5715	-38.70	-27
	5715 to 5725	-37.12	-17
Highest	5850 to 5860	-29.34	-17
	Above 5860	-32.59	-27

Note: the data just list the worst cases

Note: this EUT was tested in the low, high channel and the worst case position data was reported.

- For the frequency band 5.725-5.850GHz (802.11n HT40)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5755MHz)							
11510	58.71	9.45	68.16	74	-5.84	H	PK
11510	38.88	9.45	48.33	54	-5.67	H	AV
11510	57.88	9.45	67.33	74	-6.67	V	PK
11510	38.19	9.45	47.64	54	-6.36	V	AV
High Channel (5795MHz)							
11590	58.56	9.27	67.83	74	-6.17	H	PK
11590	40.27	9.27	49.54	54	-4.46	H	AV
11590	55.59	9.27	64.86	74	-9.14	V	PK
11590	40.08	9.27	49.35	54	-4.65	V	AV

- Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5715	-39.77	-27
	5715 to 5725	-36.53	-17
Highest	5850 to 5860	-37.61	-17
	Above 5860	-38.76	-27
Note: the data just list the worst cases			

- For the frequency band 5.725-5.850GHz (802.11ac VH80)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
5775MHz							
11550	57.37	9.93	67.30	74	-6.70	H	PK
11550	39.67	9.93	49.60	54	-4.40	H	AV
11550	55.85	9.93	65.78	74	-8.22	V	PK
11550	40.81	9.93	50.74	54	-3.26	V	AV

- Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5715	-38.81	-27
	5715 to 5725	-37.57	-17
Highest	5850 to 5860	-35.63	-17
	Above 5860	-37.48	-27
Note: the data just list the worst cases			

Note: Testing is carried out with frequency rang 9kHz to 40Ghz, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Frequency Stability

9.1 Standard Applicable

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

9.3 Summary of Test Results/Plots

Please refer to Appendix D


10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

10.2 Basic Test Setup Block Diagram



10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal

10.4 Summary of Test Results/Plots

Not applicable

APPENDIX SUMMARY

Project No.	WTH24X07156134W	Test Engineer	Timi Huang
Start date	2024/7/15	Finish date	2024/7/16
Temperature	23℃	Humidity	55%
RF specifications	U-NII		




APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	Emission Bandwidth and Occupied Bandwidth	Compliant
C	Maximum Conducted Output Power	Compliant
D	Frequency Stability	Compliant




APPENDIX A

U-NII-3: 5725-5850MHz					
Operating mode	Test Channel	Power Spectral Density dBm/300kHz	Factor	Power Spectral Density* dBm/500kHz	Limit dBm/500kHz
802.11a	5745	-4.78	2.22	-2.56	30
	5785	-4.00	2.22	-1.78	30
	5825	-3.36	2.22	-1.14	30
802.11n-HT20	5745	-5.30	2.22	-3.08	30
	5785	-4.00	2.22	-1.78	30
	5825	-3.68	2.22	-1.46	30
802.11n HT40	5755	-10.79	2.22	-8.57	30
	5795	-10.24	2.22	-8.02	30
802.11ac VHT80	5775	-11.89	2.22	-9.67	30
*Note: Maximum PSD=PSD(dBm/300kHz)+10log(500kHz/300kHz)=2.22					


5725-5850MHz




802.11a-Middle	 Ref 20 dBm •Att 30 dB •RBW 300 kHz Marker 1 [T1] -4.00 dBm •VBW 1 MHz •SWT 1 s 5.79680000 GHz 20 Offset 1 dB Center 5.785 GHz 4 MHz/ Span 40 MHz Date: 15.JUL.2024 19:38:08
802.11a-High	 Ref 20 dBm •Att 30 dB •RBW 300 kHz Marker 1 [T1] -3.36 dBm •VBW 1 MHz •SWT 1 s 5.831240000 GHz 20 Offset 1 dB Center 5.825 GHz 4 MHz/ Span 40 MHz Date: 15.JUL.2024 19:40:52
802.11n-HT20-Low	 Ref 20 dBm •Att 30 dB •RBW 300 kHz Marker 1 [T1] -5.30 dBm •VBW 1 MHz •SWT 1 s 5.750280000 GHz 20 Offset 1 dB Center 5.745 GHz 4 MHz/ Span 40 MHz Date: 15.JUL.2024 19:45:27

802.11n-HT20-Middle	 Date: 15.JUL.2024 19:44:06
802.11n-HT20-High	 Date: 15.JUL.2024 19:42:35
802.11n-HT40-Low	 Date: 15.JUL.2024 19:26:02

802.11n-HT40-High



802.11ac-VHT80-Low






APPENDIX B

Emission Bandwidth and Occupied Bandwidth

U-NII-3: 5725-5850MHz				
Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5745	16.48	41.00	≥500
	5785	16.48	41.60	≥500
	5825	16.48	42.00	≥500
802.11n-HT20	5745	17.12	41.80	≥500
	5785	17.12	44.00	≥500
	5825	17.36	42.80	≥500
802.11n-HT40	5755	35.68	66.24	≥500
	5795	36.32	72.64	≥500
802.11ac-VHT80	5775	76.16	138.60	≥500

6 dB BandwidthMHz
5725-5850MHz




802.11a-Low	Date: 15.JUL.2024 20:19:29
802.11a-Middle	Date: 15.JUL.2024 20:22:34
802.11a-High	Date: 15.JUL.2024 20:26:26




802.11n-HT20-Low	 Date: 15.JUL.2024 19:48:23
802.11n-HT20-Middle	 Date: 15.JUL.2024 19:57:07
802.11n-HT20-High	 Date: 15.JUL.2024 20:01:15




Test Case	Measurement Type	Frequency (GHz)	Power (dBm)	Bandwidth (MHz)	Resolution (kHz)	Span (MHz)	Marker 1 (dBm)	Marker 2 (dBm)	Date
802.11n-HT40-Low	Power Spectral Density	5.755	20	80	100	80	-11.51	-4.39	15.JUL.2024 20:05:51
802.11n-HT40-High	Power Spectral Density	5.755	20	80	100	80	-11.56	-3.78	15.JUL.2024 20:09:02
802.11ac-VHT80-Low	Power Spectral Density	5.775	20	160	100	160	-16.17	-5.52	15.JUL.2024 20:14:15

99% BandwidthMHz

5725-5850MHz

802.11a-Low	 Ref 20 dBm *Att 30 dB RBW 1 MHz VSW 3 MHz Marker 1 [T1] 8.25 dBm 5.747800000 GHz OSW 41.000000000 MHz Temp 1 [T1] OSW -10.28 dBm 5.725600000 GHz Temp 2 [T1] OSW -10.17 dBm 5.766600000 GHz Center 5.745 GHz 10 MHz/ Span 100 MHz Date: 15.JUL.2024 20:18:44
802.11a-Middle	 Ref 20 dBm *Att 30 dB RBW 1 MHz VSW 3 MHz Marker 1 [T1] 9.07 dBm 5.780600000 GHz OSW 41.000000000 MHz Temp 1 [T1] OSW -10.41 dBm 5.765400000 GHz Temp 2 [T1] OSW -10.28 dBm 5.807000000 GHz Center 5.785 GHz 10 MHz/ Span 100 MHz Date: 15.JUL.2024 20:23:12
802.11a-High	 Ref 20 dBm *Att 30 dB RBW 1 MHz VSW 3 MHz Marker 1 [T1] 10.09 dBm 5.828400000 GHz OSW 42.000000000 MHz Temp 1 [T1] OSW -10.41 dBm 5.804800000 GHz Temp 2 [T1] OSW -10.28 dBm 5.846800000 GHz Center 5.825 GHz 10 MHz/ Span 100 MHz Date: 15.JUL.2024 20:25:39

802.11n-HT20-Low	 Ref 20 dBm *Att 30 dB SWT 20 ms 5.745200000 GHz OSW 41.800000000 MHz Temp 1 [T1 OBW] -10.15 dBm 5.725600000 GHz Temp 2 [T1 OBW] -11.18 dBm 5.767400000 GHz Center 5.745 GHz 10 MHz/ Span 100 MHz Date: 15.JUL.2024 19:47:02
802.11n-HT20-Middle	 Ref 20 dBm *Att 30 dB SWT 20 ms 5.790200000 GHz OSW 44.000000000 MHz Temp 1 [T1 OBW] -10.18 dBm 5.764400000 GHz Temp 2 [T1 OBW] -11.23 dBm 5.808400000 GHz Center 5.785 GHz 10 MHz/ Span 100 MHz Date: 15.JUL.2024 19:56:08
802.11n-HT20-High	 Ref 20 dBm *Att 30 dB SWT 20 ms 5.830600000 GHz OSW 42.800000000 MHz Temp 1 [T1 OBW] -8.55 dBm 5.804800000 GHz Temp 2 [T1 OBW] -10.42 dBm 5.847600000 GHz Center 5.825 GHz 10 MHz/ Span 100 MHz Date: 15.JUL.2024 20:00:26


802.11n-HT40-Low	 Date: 15.JUL.2024 20:06:35
802.11n-HT40-High	 Date: 15.JUL.2024 20:08:03
802.11ac-VHT80-Low	 Date: 15.JUL.2024 20:15:29




APPENDIX C




Maximum Conducted Output Power

U-NII-3: 5725-5850MHz			
Test mode	Frequency MHz	Output Power dBm	Limit dBm
802.11a	5745	10.73	30.00
	5785	11.69	30.00
	5825	12.44	30.00
802.11n-HT20	5745	10.69	30.00
	5785	11.60	30.00
	5825	12.41	30.00
802.11n-HT40	5755	8.97	30.00
	5795	10.23	30.00
802.11ac-VHT80	5775	9.63	30.00


5725-5850MHz



802.11a-Middle	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.785 GHz 4 MHz/ Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 11.69 dBm Date: 15.JUL.2024 16:43:32
802.11a-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.825 GHz 4 MHz/ Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 12.44 dBm Date: 15.JUL.2024 16:45:59
802.11n-HT20-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.745 GHz 4 MHz/ Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 10.69 dBm Date: 15.JUL.2024 16:57:04


802.11n-HT20-Middle	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.755 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 11.60 dBm Date: 15.JUL.2024 16:58:05
802.11n-HT20-High	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.825 GHz Span: 40 MHz Tx Channel Bandwidth: 20 MHz Power: 12.41 dBm Date: 15.JUL.2024 16:59:00
802.11n-HT40-Low	 Ref: 20 dBm Offset: 1 dB Att: 30 dB RBW: 1 MHz VBW: 3 MHz SWT: 20 ms Center: 5.755 GHz Span: 80 MHz Tx Channel Bandwidth: 40 MHz Power: 8.97 dBm Date: 15.JUL.2024 18:03:27

802.11n-HT40-High



Date: 15.JUL.2024 19:13:59

802.11ac-VHT80-Low



Date: 15.JUL.2024 17:57:00

APPENDIX D

Frequency Stability

U-NII-1:5725-5850MHz worst case at 802.11a middle channel				
Voltage(%)	Power(VDC)	TEMP(°C)	Freq.Dev(Hz)	Deviation
100%	12	-30	534	0.092
100%		-20	468	0.081
100%		-10	512	0.089
100%		0	473	0.082
100%		+10	521	0.090
100%		+20	481	0.083
100%		+30	516	0.089
100%		+40	509	0.088
100%		+50	497	0.086
Low Battery power	13.8	+20	492	0.085
High Battery power	10.2	+20	507	0.088

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****