



REPORT No.: SZ22100161W19

TEST REPORT

APPLICANT : Shenzhen Tengfei Technology Management Ltd.

PRODUCT NAME : 5G Mobile Phone

MODEL NAME : NX729J

BRAND NAME : REDMAGIC

FCC ID : 2A9QD-NX729J

STANDARD(S) : 47 CFR Part 22 Subpart H
47 CFR Part 24 Subpart E

RECEIPT DATE : 2022-11-01

TEST DATE : 2022-11-02 to 2022-12-12

ISSUE DATE : 2022-12-16



Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Fax: 86-755-36698525

Http://www.morlab.cn

E-mail: service@morlab.cn



DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. Maximum E.R.P./E.I.R.P. and Emission Designator	4
1.4. Test Standards and Results	5
1.5. Environmental Conditions	6
2. 47 CFR Part 2, Part 22H Requirements	7
2.1. Conducted RF Output Power	7
2.2. Peak to Average Ratio	9
2.3. Occupied Bandwidth	11
2.4. Frequency Stability	15
2.5. Conducted Out of Band Emissions	17
2.6. Band Edge	20
2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements	22
2.8. Radiated Out of Band Emissions	24
Annex A Test Uncertainty	39
Annex B Testing Laboratory Information	40

Change History		
Version	Date	Reason for change
1.0	2022-12-16	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Shenzhen Tengfei Technology Management Ltd.
Applicant Address:	Room 3101, Building D1, Chuangzhi Yuncheng, Liuxian Avenue, Xili Street, Nanshan, Shenzhen, China
Manufacturer:	Shenzhen Tengfei Technology Management Ltd.
Manufacturer Address:	Room 3101, Building D1, Chuangzhi Yuncheng, Liuxian Avenue, Xili Street, Nanshan, Shenzhen, China

1.2. Equipment Under Test (EUT) Description

Product Name:	5G Mobile Phone	
Sample No.:	3#	
Hardware Version:	NX729J_V1AMB	
Software Version:	NX729J_UNCommon_V3.03	
Modulation Type:	CDMA2000 1xRTT: BPSK,QPSK	
Operating Frequency Range:	CDMA 2000 BC0	Tx: 824MHz-849MHz
		Rx: 869MHz-894MHz
	CDMA 2000 BC1	Tx: 1850MHz-1910MHz
		Rx: 1930MHz-1990MHz
Antenna Type:	PIFA Antenna	
Antenna Gain:	Top Antenna	
	CDMA 2000 BC0	-3.40dBi
	CDMA 2000 BC1	-1.30dBi
	Bottom Antenna	
	CDMA 2000 BC0	-4.50dBi
	CDMA 2000 BC1	-2.10dBi

Accessory Information:	Battery	
	Brand Name:	ATL
	Model No.:	Li3928T89P8h603285
	Serial No.:	N/A
	Capacity:	2860mAh
	Rated Voltage:	7.78V
	Charge Limit:	8.9V
	Manufacturer:	Dongguan Amperex Technology Limited
	AC Adapter	
	Brand Name:	N/A
	Model No.:	STC-A59152050AC-Z
	Serial No.:	N/A
	Rated Output:	5.0V $\Rightarrow$ 3.0A, 9.0V $\Rightarrow$ 3.0A, 15.0V $\Rightarrow$ 3.0A, 20.0V $\Rightarrow$ 3.25A PPS: 5.0V-11.0V $\Rightarrow$ 5.0A, 5.0V-20.0V $\Rightarrow$ 3.25A
	Rated Input:	100-240V $\sim$ 50/60Hz, 1.5A
	Manufacturer:	ShenZhen KunXing Technology Co.,Ltd.

Note 1: SIM 1 and SIM 2 is a chipset unit and tested as a single chipset. The SIM 1 is chosen for test.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

Test Mode	Maximum E.R.P./E.I.R.P. (W)		Emission Designator
	Top Antenna	Bottom Antenna	
CDMA2000 BC0	0.060	0.047	1M28F9W
CDMA2000 BC1	0.157	0.130	1M28F9W

1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 2, Part 22 and Part24 for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-12 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 (10-1-12 Edition)	Public Mobile Services
3	47 CFR Part 24 (10-1-12 Edition)	Personal Communications Services

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination/ Remark
1	2.1046	Conducted RF Output Power	Dec. 12, 2022	Chen Hao	PASS	No deviation
2	24.232(d)	Peak -Average Ratio	Nov. 02, 2022	Li Huaijie	PASS	No deviation
3	2.1049	Occupied Bandwidth	Nov. 02, 2022	Li Huaijie	PASS	No deviation
4	2.1055, 22.355, 24.235	Frequency Stability	Nov. 02, 2022	Li Huaijie	PASS	No deviation
5	2.1051, 22.917(a), 24.238(a)	Conducted Out of Band Emissions	Nov. 02, 2022	Li Huaijie	PASS	No deviation
6	2.1051, 22.917(a), 24.238(a)	Band Edge	Nov. 02, 2022	Li Huaijie	PASS	No deviation
7	22.913(a) 24.232(c)	Transmitter Radiated Power (EIPR/E.R.P.)	Dec. 12, 2022	Li Huaijie	PASS	No deviation
8	2.1053, 22.917(a), 24.238(a)	Radiated Out of Band Emissions	Dec 05, 2022	Su Zhan	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in KDB971168 D01 v03r01 and ANSI/TIA-603-E-2016.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in

the test equipments. The ref offset 24.5dB contains two parts that cable loss 14.5dB and Attenuator 10dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.47 CFR Part 2, Part 22H, Part24E Requirements


2.1. Conducted RF Output Power

2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

2.1.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

**2.1.3. Test Result**

CDMA2000 BC0	Average Power (dBm)		
TX Channel	1013	384	777
Frequency (MHz)	824.7	836.52	848.31
1xRTT RC1 SO55	23.15	23.22	23.21
1xRTT RC3 SO55	23.11	23.15	23.11
1xRTT RC3 SO32 (F+SCH)	23.28	23.34	23.24
1xRTT RC3 SO32 (+SCH)	23.11	23.20	23.19

CDMA2000 BC1	Average Power (dBm)		
TX Channel	25	600	1175
Frequency (MHz)	1851.25	1880	1908.75
1xRTT RC1 SO55	23.19	23.23	23.20
1xRTT RC3 SO55	23.12	23.18	23.16
1xRTT RC3 SO32 (F+SCH)	23.24	23.25	23.22
1xRTT RC3 SO32 (+SCH)	23.19	23.20	23.19


2.2. Peak to Average Ratio

2.2.1. Requirement

According to FCC 24.232(d) the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.


2.2.3. Test Procedure

1. For GSM/EDGE operating mode:
 - a. Set RBW=1MHz, VBW=3MHz, peak detector in spectrum analyzer.
 - b. Set EUT in maximum output power, and triggered the burst signal.
 - c. Measured respectively the peak level and mean level, and the deviation was recorded as Peak to Average ratio.
2. For UMTS operating mode:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1%.



2.2.4. Test Result

CDMA2000 BC1					
Mode	Channel	Frequency (MHz)	Peak to Average ratio (dB)	Limit (dB)	Verdict
1xRTT	25	1851.25	3.78	13	PASS
	600	1880.00	3.74		PASS
	1175	1908.75	3.83		PASS




2.3. Occupied Bandwidth

2.3.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

2.3.2. Test Description

Test Setup:









The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.

**2.3.3. Test Result**

CDMA2000 BC0				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
1xRTT	1013	824.70	1.28	1.43
	384	836.52	1.28	1.43
	777	848.31	1.28	1.43

CDMA2000 BC1				
Mode	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
1xRTT	25	1851.25	1.27	1.42
	600	1880.00	1.27	1.43
	1175	1908.75	1.28	1.43

**CDMA BC0 (1xRTT), CH1013, 824.70MHz****CDMA BC0 (1xRTT), CH384, 836.52MHz****CDMA BC0 (1xRTT), CH777, 848.31MHz**

**CDMA BC1 (1xRTT), CH25, 1851.25MHz****CDMA BC1 (1xRTT), CH600, 1880.00MHz****CDMA BC1 (1xRTT), CH1175, 1908.75MHz**

2.4. Frequency Stability

2.4.1. Requirement


According to FCC section 22.355 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to $+50^{\circ}\text{C}$ at intervals of not more than 10°C .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

Note: The operating temperature of EUT is from 0°C to 40°C , which are specified by the applicant.

2.4.2. Test Description

Test Setup:



The EUT, which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS via a Common Antenna.



2.4.3. Test Result

The nominal, highest and lowest extreme voltages are separately 7.78V, 8.90V and 7.00V, which are specified by the applicant; the normal temperature here used is 20°C.

CDMA2000 BC0 (1xRTT), CH384, 836.52MHz					
Limit =±2.5ppm					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	7.78	+20(Ref)	-52	-0.062	PASS
Normal		0	26	0.031	
Normal		+10	-38	-0.045	
Normal		+20	-47	-0.056	
Normal		+30	24	0.029	
Normal		+40	34	0.041	
High	8.90	+20	25	0.030	
BATT.ENDPOINT	7.00	+20	20	0.024	

CDMA2000 BC1 (1xRTT), Channel 600, Frequency 1880.00MHz					
Limit =Within Authorized Band					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	7.78	+20(Ref)	-51	-0.027	PASS
Normal		0	44	0.023	
Normal		+10	-15	-0.008	
Normal		+20	-42	-0.022	
Normal		+30	-42	-0.022	
Normal		+40	23	0.012	
High	8.90	+20	38	0.020	
BATT.ENDPOINT	7.00	+20	50	0.027	


2.5. Conducted Out of Band Emissions

2.5.1. Requirement

According to FCC section 22.917(a) and 24.238(a) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.5.2. Test Description

Test Setup:




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.




2.5.3. Test Result


CDMA BC0 (1xRTT), CH1013, 824.70MHz



CDMA BC0 (1xRTT), CH384, 836.52MHz




CDMA BC0 (1xRTT), CH777, 848.31MHz







CDMA BC1 (1xRTT), CH25, 1851.25MHz



CDMA BC1 (1xRTT), CH600, 1880.00MHz



CDMA BC1 (1xRTT), CH1175, 1908.75MHz




2.6. Band Edge

2.6.1. Requirement

According to FCC section 22.917(a) and 24.238(a) the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.6.2. Test Description

Test Setup:




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. Power Control Level (PCL) = 5 and Power Class = 4. A call is established between the EUT and the SS.




2.6.3. Test Result

The lowest and highest channels are tested to verify the band edge emissions.


CDMA BC0 (1xRTT), CH1013, 824.70MHz



CDMA BC0 (1xRTT), CH777, 848.31MHz



CDMA BC1 (1xRTT), CH25, 1851.25MHz



CDMA BC1 (1xRTT), CH1175, 1908.75MHz



2.7. Determining E.R.P. and/or E.I.R.P. from conducted RF output power measurements

2.7.1. Requirement

According to FCC section 22.913, the Effective Radiated Power (E.R.P.) of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to FCC section 24.232, the broadband PCS mobile station is limited to 2 Watts e.i.r.p. peak power.

2.7.2. Test Description

The test setups refer to section 2.1.3

A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power (i.e. GSM850MHz band Power Control Level (PCL) = 5/19 and Power Class = 4, GSM1900MHz band Power Control Level (PCL) = 0/15 and Power Class = 1), and only the test result of the maximum output power was recorded. Please refer to section 2.1.3 of this report.

The relevant equation for determining the maximum E.R.P. or E.I.R.P. from the measured RF output power is given in Equation (1) as follows:

$$\text{E.R.P. or E.I.R.P.} = P_{\text{Meas}} + G_T$$

Where:

E.R.P. or E.I.R.P. effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (E.R.P.) or dBi (E.I.R.P.)

For devices utilizing multiple antennas, see ANSI C63.25-2015 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

The following equations demonstrate the mathematical relationship between E.R.P. and E.I.R.P.:

a) $\text{E.R.P.} = \text{E.I.R.P.} - 2.15$, where E.R.P. and E.I.R.P. are expressed in consistent units.

b) $\text{E.I.R.P.} = \text{E.R.P.} + 2.15$, where E.R.P. and E.I.R.P. are expressed in consistent units.



2.7.3. Test Result

Top Antenna

CDMA2000 BC0								
Band	Channel	Frequency (MHz)	PCL	Measured E.R.P.		Limit		Verdict
				dBm	W	dBm	W	
1xRTT	1013	824.70	5	17.73	0.059	38.5	7	PASS
	384	836.52	5	17.79	0.060			PASS
	777	848.31	5	17.69	0.059			PASS
Note 1: Only the worst data were recorded in this report.								

CDMA2000 BC1								
Band	Channel	Frequency (MHz)	PCL	Measured E.R.P.		Limit		Verdict
				dBm	W	dBm	W	
1xRTT	25	1851.25	5	21.94	0.156	33	2	PASS
	600	1880.00	5	21.95	0.157			PASS
	1175	1908.75	5	21.92	0.156			PASS
Note 1: Only the worst data were recorded in this report.								

Bottom Antenna

CDMA2000 BC0								
Band	Channel	Frequency (MHz)	PCL	Measured E.R.P.		Limit		Verdict
				dBm	W	dBm	W	
1xRTT	1013	824.70	5	16.63	0.046	38.5	7	PASS
	384	836.52	5	16.69	0.047			PASS
	777	848.31	5	16.59	0.046			PASS
Note 1: Only the worst data were recorded in this report.								


CDMA2000 BC1								
Band	Channel	Frequency (MHz)	PCL	Measured E.R.P.		Limit		Verdict
				dBm	W	dBm	W	
1xRTT	25	1851.25	5	21.14	0.130	33	2	PASS
	600	1880.00	5	21.13	0.130			PASS
	1175	1908.75	5	21.12	0.129			PASS
Note 1: Only the worst data were recorded in this report.								

2.8. Radiated Out of Band Emissions


2.8.1. Requirement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \cdot \log(P)$ dB. This calculated to be -13dBm. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency.

2.8.2. Test Description



(For the test frequency from 30MHz to 1GHz)



(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power, and only the test result of the maximum output power was recorded.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360° to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

Note: When doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.8.3. Test Procedure

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements.



2.8.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

The substitution corrections are obtained as described below:

$$A_{\text{SUBST}} = P_{\text{SUBST_TX}} - P_{\text{SUBST_RX}} - L_{\text{SUBST_CABLES}} + G_{\text{SUBST_TX_ANT}}$$

$$A_{\text{TOT}} = L_{\text{CABLES}} + A_{\text{SUBST}}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain.

$P_{\text{SUBST_TX}}$ is signal generator level,

$P_{\text{SUBST_RX}}$ is receiver level,

$L_{\text{SUBST_CABLES}}$ is cable losses including TX cable,

$G_{\text{SUBST_TX_ANT}}$ is substitution antenna gain.

A_{TOT} is total correction factor including cable loss and substitution correction

During the test, the data of A_{TOT} was added in the test spectrum analyze, so spectrum analyze reading is the final values which contain the data of A_{TOT} .

Note1: The power of the EUT transmitting frequency should be ignored.

Note2: All test mode and condition mentioned were considered and evaluated respectively by performing full test, only the worst data were recorded and reported.


Note3: All spurious emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note4: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.


Note5: The amplitude of emissions(18GHz to 10th harmonics) which are attenuated more than 20 dB below the limit are not be reported.

Top Antenna

CDMA2000 BC0 (1xRTT), Low Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	824.430	-45.11	-13.00	Horizontal	N/A
2	870.020	-34.26	-13.00	Horizontal	N/A
3	2474.510	-34.18	-13.00	Horizontal	PASS
4	7170.176	-40.33	-13.00	Horizontal	PASS
5	9003.046	-37.40	-13.00	Horizontal	PASS
6	10961.429	-37.21	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	824.430	-50.15	-13.00	Vertical	N/A
2	869.050	-57.77	-13.00	Vertical	N/A
3	2307.403	-39.88	-13.00	Vertical	PASS
4	5150.882	-45.98	-13.00	Vertical	PASS
5	7214.475	-40.54	-13.00	Vertical	PASS
6	9115.639	-37.34	-13.00	Vertical	PASS

CDMA2000 BC0 (1xRTT), Mid Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	836.070	-42.77	-13.00	Horizontal	N/A
2	881.660	-32.60	-13.00	Horizontal	N/A
3	2509.724	-32.51	-13.00	Horizontal	PASS
4	7157.256	-40.87	-13.00	Horizontal	PASS
5	9636.152	-37.04	-13.00	Horizontal	PASS
6	10946.663	-37.32	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	836.070	-47.00	-13.00	Vertical	N/A
2	881.660	-61.32	-13.00	Vertical	N/A
3	2509.724	-37.84	-13.00	Vertical	PASS
4	7120.340	-40.83	-13.00	Vertical	PASS
5	9014.121	-37.73	-13.00	Vertical	PASS
6	11753.273	-37.32	-13.00	Vertical	PASS

CDMA2000 BC0 (1xRTT), High Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	848.680	-37.34	-13.00	Horizontal	N/A
2	893.300	-33.34	-13.00	Horizontal	N/A
3	2545.578	-32.33	-13.00	Horizontal	PASS
4	7173.868	-40.64	-13.00	Horizontal	PASS
5	9135.943	-38.13	-13.00	Horizontal	PASS
6	10878.369	-37.47	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	848.680	-43.91	-13.00	Vertical	N/A
2	893.300	-55.51	-13.00	Vertical	N/A
3	2544.938	-38.42	-13.00	Vertical	PASS
4	6522.304	-41.91	-13.00	Vertical	PASS
5	9003.046	-38.14	-13.00	Vertical	PASS
6	10348.627	-36.74	-13.00	Vertical	PASS

CDMA2000 BC1 (1xRTT), Low Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	97.900	-68.58	-13.00	Horizontal	PASS
2	1851.541	-31.52	-13.00	Horizontal	N/A
3	1930.932	-24.43	-13.00	Horizontal	N/A
4	7229.242	-40.06	-13.00	Horizontal	PASS
5	9646.081	-37.23	-13.00	Horizontal	PASS
6	15009.056	-32.18	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	72.680	-67.53	-13.00	Vertical	PASS
2	1850.900	-39.40	-13.00	Vertical	N/A
3	1931.573	-33.82	-13.00	Vertical	N/A
4	7248.845	-39.65	-13.00	Vertical	PASS
5	9763.702	-37.00	-13.00	Vertical	PASS
6	14869.031	-31.33	-13.00	Vertical	PASS

CDMA2000 BC1 (1xRTT), Mid Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	79.470	-67.93	-13.00	Horizontal	PASS
2	1879.072	-35.79	-13.00	Horizontal	N/A
3	1959.744	-23.19	-13.00	Horizontal	N/A
4	7176.032	-40.24	-13.00	Horizontal	PASS
5	10357.410	-36.66	-13.00	Horizontal	PASS
6	16193.672	-28.84	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	71.710	-67.40	-13.00	Vertical	PASS
2	1270.828	-40.14	-13.00	Vertical	PASS
3	1959.744	-29.97	-13.00	Vertical	N/A
4	7204.037	-40.37	-13.00	Vertical	PASS
5	9755.301	-36.80	-13.00	Vertical	PASS
6	14031.678	-32.67	-13.00	Vertical	PASS

CDMA2000 BC1 (1xRTT), High Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	73.650	-69.56	-13.00	Horizontal	PASS
2	1908.523	-34.17	-13.00	Horizontal	N/A
3	1988.555	-21.09	-13.00	Horizontal	N/A
4	7117.221	-40.66	-13.00	Horizontal	PASS
5	9648.882	-37.56	-13.00	Horizontal	PASS
6	14869.031	-32.59	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	73.650	-67.11	-13.00	Vertical	PASS
2	1279.792	-40.34	-13.00	Vertical	PASS
3	1988.555	-32.51	-13.00	Vertical	N/A
4	7204.037	-40.79	-13.00	Vertical	PASS
5	9099.982	-36.73	-13.00	Vertical	PASS
6	14827.023	-32.23	-13.00	Vertical	PASS

Bottom Antenna

CDMA2000 BC0 (1xRTT), Low Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	824.430	-40.87	-13.00	Horizontal	N/A
2	870.020	-34.95	-13.00	Horizontal	N/A
3	2206.883	-40.04	-13.00	Horizontal	PASS
4	5198.873	-45.34	-13.00	Horizontal	PASS
5	7229.242	-39.30	-13.00	Horizontal	PASS
6	9641.689	-37.13	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	824.430	-58.07	-13.00	Vertical	N/A
2	870.020	-51.96	-13.00	Vertical	N/A
3	2212.645	-39.62	-13.00	Vertical	PASS
4	7175.714	-40.64	-13.00	Vertical	PASS
5	8908.911	-37.75	-13.00	Vertical	PASS
6	11734.815	-37.43	-13.00	Vertical	PASS

CDMA2000 BC0 (1xRTT), Mid Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	836.070	-40.75	-13.00	Horizontal	N/A
2	881.660	-34.12	-13.00	Horizontal	N/A
3	2226.090	-39.53	-13.00	Horizontal	PASS
4	5158.265	-45.25	-13.00	Horizontal	PASS
5	7208.938	-39.66	-13.00	Horizontal	PASS
6	11112.784	-36.06	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	836.070	-51.54	-13.00	Vertical	N/A
2	881.660	-55.02	-13.00	Vertical	N/A
3	2196.639	-39.94	-13.00	Vertical	PASS
4	5195.181	-45.80	-13.00	Vertical	PASS
5	7227.396	-40.54	-13.00	Vertical	PASS
6	10411.384	-35.89	-13.00	Vertical	PASS

CDMA2000 BC0 (1xRTT), High Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	848.680	-34.66	-13.00	Horizontal	N/A
2	893.300	-34.07	-13.00	Horizontal	N/A
3	2304.202	-39.96	-13.00	Horizontal	PASS
4	5158.265	-46.03	-13.00	Horizontal	PASS
5	7592.862	-40.03	-13.00	Horizontal	PASS
6	10880.215	-36.49	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	848.680	-48.22	-13.00	Vertical	N/A
2	893.300	-62.91	-13.00	Vertical	N/A
3	2210.084	-40.59	-13.00	Vertical	PASS
4	5761.839	-42.58	-13.00	Vertical	PASS
5	8381.015	-39.51	-13.00	Vertical	PASS
6	10348.627	-37.30	-13.00	Vertical	PASS

CDMA2000 BC1 (1xRTT), Low Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	98.870	-68.95	-13.00	Horizontal	PASS
2	1851.541	-30.69	-13.00	Horizontal	N/A
3	1930.932	-24.31	-13.00	Horizontal	N/A
4	7240.444	-40.44	-13.00	Horizontal	PASS
5	10886.707	-37.65	-13.00	Horizontal	PASS
6	14012.075	-32.99	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	79.470	-69.17	-13.00	Vertical	PASS
2	1851.541	-37.96	-13.00	Vertical	N/A
3	1930.932	-32.83	-13.00	Vertical	N/A
4	7111.620	-40.49	-13.00	Vertical	PASS
5	10855.901	-37.40	-13.00	Vertical	PASS
6	15014.657	-32.16	-13.00	Vertical	PASS

CDMA2000 BC1 (1xRTT), Mid Channel




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	87.230	-69.11	-13.00	Horizontal	PASS
2	1879.712	-34.29	-13.00	Horizontal	N/A
3	1959.744	-21.83	-13.00	Horizontal	N/A
4	7232.042	-39.71	-13.00	Horizontal	PASS
5	11049.136	-37.20	-13.00	Horizontal	PASS
6	14880.233	-31.63	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	73.650	-68.68	-13.00	Vertical	PASS
2	1879.712	-41.60	-13.00	Vertical	N/A
3	1959.744	-30.84	-13.00	Vertical	N/A
4	7201.237	-40.50	-13.00	Vertical	PASS
5	10349.009	-37.84	-13.00	Vertical	PASS
6	14880.233	-31.77	-13.00	Vertical	PASS

CDMA2000 BC1 (1xRTT), High Channel



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	79.470	-69.22	-13.00	Horizontal	PASS
2	1908.523	-35.18	-13.00	Horizontal	N/A
3	1988.555	-21.86	-13.00	Horizontal	N/A
4	7156.428	-41.22	-13.00	Horizontal	PASS
5	10878.305	-36.60	-13.00	Horizontal	PASS
6	14409.747	-32.93	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	76.560	-68.44	-13.00	Vertical	PASS
2	1908.523	-41.60	-13.00	Vertical	N/A
3	1988.555	-33.20	-13.00	Vertical	N/A
4	7184.434	-40.67	-13.00	Vertical	PASS
5	11732.460	-36.17	-13.00	Vertical	PASS
6	14079.287	-32.85	-13.00	Vertical	PASS

Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Output Power	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Radiated Emission	$\pm 2.95\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2022.07.04	2023.07.03
System Simulator	6200995016	MT8820C	Anritsu	2022.10.10	2023.10.09
Temperature Chamber	20171112102	HZ-2019	Dongguan Lixian Instrument Technology Co., Ltd	2022.10.10	2023.10.09

4.2 List of Software Used

Description	Manufacturer	Software Version
MORLAB EMCR	MORLAB	V1.2

**4.3 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
System Simulator	152038	CMW500	R&S	2022.10.11	2023.10.10
Receiver	MY54130016	N9038A	Agilent	2022.07.07	2023.07.06
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Horn	9120D-963	BBHA 9120D	Schwarzbeck	2022.05.23	2025.05.24
Coaxial cable (N male) (9kHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-40GHz)	CB05	EMC05	Morlab	N/A	N/A
1-18GHz pre-Amplifier	61171/61172	S020180L3203	Tonscend	2022.07.08	2023.07.07
18-26.5GHz pre-Amplifier	46732	S10M100L3802	Tonscend	2022.07.08	2023.07.07
26-40GHz pre-Amplifier	56774	S40M400L4002	Tonscend	2022.07.08	2023.07.07
Notch Filter	N/A	WRCG-CDM A2000 BC0	Wainwright	2022.07.08	2023.07.07
Notch Filter	N/A	WRCG-CDM A2000 BC1	Wainwright	2022.07.08	2023.07.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

_____ END OF REPORT _____