

Standalone SAR test exclusion considerations

RF feature	Mode	Transmitting Frequency(MHz)	Test separation distance (mm)	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) ^{Note1}	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
BLE	1 Mbps	2 480.00	5.0	0.50	0.87	1.221 8	0.38	3.00

Note1. Please refer to the operation description for Max Tune-up power.

KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm

$$\left[\left(\text{max. power of channel, including tune-up tolerance, mW} \right) / \left(\text{min. test separation distance, mm} \right) \right] \cdot \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1g SAR and } \leq 7.5 \text{ for 10g extremity SAR}$$

Sample Calculation

$$= \left[\left(1.2218\text{mW} / 5\text{mm} \right) \right] \times \left[\sqrt{2.48\text{GHz}} \right] = 0.38$$

Note. The calculation result was rounded to two decimal place for comparison.

Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required