

Appendix 5

RF Exposure Information

FCC ID: 2A9TIOHBM

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Output power(mW)
2402	-7.09	0.195
2440	-5.69	0.269
2480	-6.29	0.234

FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$$

for 1-g SAR and ≤7.5 for 10-g extremity SAR₂₄ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(0.195/5) \cdot \sqrt{2.402} = 0.06 < 3.0$$

$$(0.269/5) \cdot \sqrt{2.440} = 0.08 < 3.0$$

$$(0.234/5) \cdot \sqrt{2.480} = 0.07 < 3.0$$

Conclusion:

No SAR is required.